

# Package ‘gotop’

May 27, 2024

**Type** Package

**Title** Scroll Back to Top Icon in Shiny and R Markdown

**Version** 0.1.4

**Description** Add a scroll back to top 'Font Awesome' icon  
<<https://fontawesome.com/>> in 'rmarkdown' documents and 'shiny'  
apps thanks to 'jQuery GoTop' <<https://scottdorman.blog/jquery-gotop/>>.

**License** MIT + file LICENSE

**Imports** jsonlite, htmltools

**URL** <https://felixluginbuhl.com/gotop/>,  
<https://github.com/lgnbhl/gotop/>

**BugReports** <https://github.com/lgnbhl/gotop/issues/>

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**NeedsCompilation** no

**Author** Félix Luginbuhl [aut, cre]

**Maintainer** Félix Luginbuhl <[felix.luginbuhl@protonmail.ch](mailto:felix.luginbuhl@protonmail.ch)>

**Repository** CRAN

**Date/Publication** 2024-05-26 23:00:03 UTC

## R topics documented:

|                                   |   |
|-----------------------------------|---|
| html_dependencies_gotop . . . . . | 2 |
| use_gotop . . . . .               | 2 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>4</b> |
|--------------|----------|

html\_dependencies\_gotop  
*gotop dependencies*

---

### Description

Get gotop html dependencies.

### Usage

```
html_dependencies_gotop(use_cdn = TRUE)
```

### Arguments

|         |   |
|---------|---|
| use_cdn | boolean. TRUE to use a Content Delivery Network (CDN), true by default, or false to use locally stored files. |
|---------|---|

---

use\_gotop *Add scroll up icon*

---

### Description

Add scroll up icon

### Usage

```
use_gotop(  
  src = "fas fa-chevron-up",  
  width = 45,  
  opacity = 0.5,  
  place = "right",  
  color = "",  
  appear = 200,  
  scrolltime = 800,  
  fadein = 500,  
  fadeout = 500,  
  marginX = 2,  
  marginY = 2,  
  container = "",  
  zIndex = 9,  
  use_cdn = TRUE  
)
```

**Arguments**

|            |   |
|------------|---|
| src        | A string. The CSS classes used to display the gotop icon.   |
| width      | An integer. The width of the gotop icon.  |
| opacity    | decimal Sets the transparency level for the gotop icon, where 1 is not transparent at all, 0.5 is 50 percent see-through and 0 is completely transparent. |
| place      | A string. The location where the gotop icon will be shown. Valid values are 'right' or 'left'.  |
| color      | A string. The color of the selected the gotop icon.   |
| appear     | An integer. The amount of pixels the page must be scrolled down before the gotop icon is displayed.   |
| scrolltime | An integer. A number determining how long the animation will run when scrolling to the top of the page.   |
| fadein     | An integer. A number determining how long the animation will run when fading in to opaque.  |
| fadeout    | An integer. A number determining how long the animation will run when fading out to transparent.  |
| marginX    | An integer. The percentage amount indicating how far away the gotop icon is from the bottom, left, or right, depending on the value of place.             |
| marginY    | An integer. The percentage amount indicating how far away the gotop icon is from the top or bottom, depending on the value of place.                      |
| container  | A string. The HTML element to which the scroll function will be attached. If no value is given, then the scroll function will be attached to the window.  |
| zIndex     | An integer. The z-index value.  |
| use_cdn    | boolean. TRUE to use a Content Delivery Network (CDN), true by default, or false to use locally stored files.   |

**Value**

Javascript code initializing GoTop with dependencies

**Examples**

```
use_gotop()
```

# Index

`html_dependencies_gotop`, [2](#)

`use_gotop`, [2](#)