

Package ‘rsdNE’

February 22, 2023

Type Package

Title Response Surface Designs with Neighbour Effects (rsdNE)

Version 1.1.0

Maintainer Ashutosh Dalal <ashutosh.dalal97@gmail.com>

Description Response surface designs with neighbour effects are suitable for experimental situations where it is expected that the treatment combination administered to one experimental unit may affect the response on neighboring units as well as the response on the unit to which it is applied.

Integrating these effects in the response surface model improves the experiment's precision

(Jaggi, S., Sarika and Sharma, V.K. (2010)<<http://krishi.icar.gov.in/jspui/handle/123456789/4364>>;

Verma A., Jaggi S., Varghese, E., Varghese, C., Bhowmik, A., Datta, A. and Hema-

vathi M. (2021)<[DOI:10.1080/03610918.2021.1890123](https://doi.org/10.1080/03610918.2021.1890123)>).

This package includes `sym()`, `asym1()`, `asym2()` functions that generates response surface designs which are rotatable under a

polynomial model of a given order without interaction term incorporating neighbour effects.

License GPL (>= 2)

Encoding UTF-8

Repository CRAN

RoxygenNote 7.2.0

NeedsCompilation no

Author Ashutosh Dalal [aut, cre],

Seema Jaggi [aut, ctb],

Eldho Varghese [aut, ctb],

Subhasish Sarkar [aut],

Arpan Bhowmik [aut],

Cini Varghese [aut],

Anindita Datta [aut],

Soumen Pal [aut]

Date/Publication 2023-02-22 17:40:02 UTC

R topics documented:

asym1	2
asym2	3
sym	4

Index	7
--------------	----------

asym1	<i>This generates a class of asymmetric rotatable response surface designs with neighbour effects under a second order model</i>
-------	--

Description

This function generates asymmetrical rotatable response surface designs in the presence of neighbour effects for $2n$ factors, n factors at 2 levels and another n factors at 3 levels.

Usage

```
asym1(n1, n2, c)
```

Arguments

n1	n1 factors having 2 levels, $1 \leq n1 \leq 5$
n2	n2 factors having 3 levels, $1 \leq n2 \leq 5$
c	Value of alpha (Coefficient of neighbour effects), $0 \leq c \leq 1$

Value

This function generates rotatable designs as well as Z_prime_Z matrix, $inv(Z_primeZ)$ matrix and variance estimated response for the $(2^{n1} * 3^{n2})$ factorial combination.

Note

Here 3 types of cases have been considered: $(2^{n1} * 3^{n2})$, where, $n1=n2=n$; $(2^{n1} * 3)$, where, $n1=n$ and $n2=1$; $(2 * 3^{n2})$, where, $n1=1$ and $n2=n$.

Author(s)

Ashutosh Dalal, Division of Design of Experiments, ICAR-IASRI, New Delhi. Seema Jaggi, Education Division, ICAR, Krishi Anusandhan Bhawan - II, Pusa, New Delhi. Eldho Varghese, Fishery Resources Assessment Division, ICAR-CMFRI, Kochi. Subhasish Sarkar, Division of Computer Application, ICAR-IASRI, New Delhi. Arpan Bhowmik, Division of Design of Experiments, ICAR-IASRI, New Delhi. Cini Varghese, Division of Design of Experiments, ICAR-IASRI, New Delhi. Anindita Datta, Division of Design of Experiments, ICAR-IASRI, New Delhi. Soumen Pal, Division of Computer Application, ICAR-IASRI, New Delhi.

References

Verma et al.2021, Communication in Statistics – Simulation and Computation

Examples

```

library(rsdNE)
asym1(1,1,0.5)
##X matrix
#      [,1] [,2] [,3] [,4]
#[1,]  1  -1  -1   1
#[2,]  1   1   1   1
#[3,]  1   1   0   0
#[4,]  1   1  -1   1
#[5,]  1  -1   1   1
#[6,]  1  -1   0   0
#[7,]  1  -1  -1   1
#[8,]  1   1   1   1
##Z prime Z matrix
#      [,1] [,2] [,3] [,4]
#[1,]  24   0   0  16
#[2,]   0  12   0   0
#[3,]   0   0   1   0
#[4,]  16   0   0  11
##Z prime Z inverse matrix
#      [,1]      [,2]  [,3]  [,4]
#[1,]  1.375 0.00000000  0  -2
#[2,]  0.000 0.08333333  0   0
#[3,]  0.000 0.00000000  1   0
#[4,] -2.000 0.00000000  0   3
#[1] "total number of runs" "6"
#[1] "variance of esitmated response" "1.4583"

```

asym2	<i>This generates a class of asymmetric rotatable response surface designs with neighbour effects under a polynomial model of order $\max(s1,s2)-1$</i>
-------	--

Description

This function generates asymmetrical rotatable response surface designs in the presence of neighbour effects for $(n1 + n2)$ factors, $n1$ factors at $s1$ levels and another $n2$ factors at $s2$ levels.

Usage

```
asym2(s1, n1, s2, n2, c)
```

Arguments

s1	Number of levels of n1 factors, $1 < s1 \leq 8$
n1	Number of factors, $1 \leq n1 \leq 4$
s2	Number of levels of n2 factors, $1 < s2 \leq 8$
n2	Number of factors, $1 \leq n2 \leq 4$
c	Value of alpha (Coefficient of neighbour effects), $0 \leq c \leq 1$

Value

his function generates rotatable designs as well as $Z_{\text{prime}}Z$ matrix, $\text{inv}(Z_{\text{prime}}Z)$ matrix and variance estimated response for the $(s1^{n1} * s2^{n2})$ factorial combination.

Note

Here s1 and s2 both not even at the same time and s1 not equal to s2.

Author(s)

Ashutosh Dalal, Division of Design of Experiments, ICAR-IASRI, New Delhi. Seema Jaggi, Education Division, ICAR, Krishi Anusandhan Bhawan - II, Pusa, New Delhi. Eldho Varghese, Fishery Resources Assessment Division, ICAR-CMFRI, Kochi. Subhasish Sarkar, Division of Computer Application, ICAR-IASRI, New Delhi. Arpan Bhowmik, Division of Design of Experiments, ICAR-IASRI, New Delhi. Cini Varghese, Division of Design of Experiments, ICAR-IASRI, New Delhi. Anindita Datta, Division of Design of Experiments, ICAR-IASRI, New Delhi. Soumen Pal, Division of Computer Application, ICAR-IASRI, New Delhi.

References

Dalal, 2021, Unpublished M.Sc. Thesis, IARI, New Delhi

Examples

```
library(rsdNE)
asym2(2, 2, 5, 2, 0.5)
```

sym	<i>This generates a class of symmetric rotatable response surface designs with neighbour effects under a polynomial model of order (s1-1)</i>
-----	---

Description

This function generates symmetrical rotatable response surface designs in the presence of neighbour effects for n1 factors each at s1 levels.

Usage

```
sym(s1, n1, c)
```

Arguments

s1	Number of levels of n1 factors, $1 < s1 \leq 6$
n1	Number of factors, $1 < n1 \leq 4$
c	Value of alpha (Coefficient of neighbour effects), $0 \leq c \leq 1$

Value

his function generates rotatable designs as well as $Z_{\text{prime}}Z$ matrix, $\text{inv}(Z_{\text{prime}}Z)$ matrix and variance estimated response for the $(s1^{n1})$ factorial combination.

Author(s)

Ashutosh Dalal, Division of Design of Experiments, ICAR-IASRI, New Delhi. Seema Jaggi, Education Division, ICAR, Krishi Anusandhan Bhawan - II, Pusa, New Delhi. Eldho Varghese, Fishery Resources Assessment Division, ICAR-CMFRI, Kochi. Subhasish Sarkar, Division of Computer Application, ICAR-IASRI, New Delhi. Arpan Bhowmik, Division of Design of Experiments, ICAR-IASRI, New Delhi. Cini Varghese, Division of Design of Experiments, ICAR-IASRI, New Delhi. Anindita Datta, Division of Design of Experiments, ICAR-IASRI, New Delhi. Soumen Pal, Division of Computer Application, ICAR-IASRI, New Delhi.

References

Sarika et al.2009, Communications in Statistics-Theory and Methods; Sarika et al.2013, Ars Combinatoria

Examples

```
library(rsdNE)
sym(2,2,0.5)
##output:
## X matrix
#      [,1] [,2] [,3]
# [1,]  1  -1  -1
# [2,]  1   1   1
# [3,]  1   1  -1
# [4,]  1  -1   1
# [5,]  1  -1  -1
# [6,]  1   1   1
# [7,]  1  -1   1
# [8,]  1   1  -1
# [9,]  1  -1  -1
#[10,]  1   1   1
## Z prime Z matrix
#      [,1] [,2] [,3]
#[1,]  32   0   0
#[2,]   0   4   0
#[3,]   0   0   4
## Z prime Z inverse matrix
#      [,1] [,2] [,3]
#[1,] 0.03125 0.00 0.00
```

```
#[2,] 0.00000 0.25 0.00  
#[3,] 0.00000 0.00 0.25  
#[1] "total number of runs" "8"  
#[1] "variance of esitmated response" "0.5312"
```

Index

asym1, [2](#)

asym2, [3](#)

sym, [4](#)