

Package ‘rtson’

October 14, 2022

Type Package

Title Typed JSON

Version 1.3

Date 2015-11-22

Author Alexandre Maurel

Maintainer Alexandre Maurel <alexandre.maurel@gmail.com>

Description TSON, short for Typed JSON, is a binary-encoded serialization of JSON like document that support JavaScript typed data (<https://github.com/tercen/TSON>).

License Apache License Version 2.0

Suggests testthat

Imports R6

URL <https://github.com/tercen/TSON>

BugReports <https://github.com/tercen/TSON/issues>

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2016-08-26 20:35:52

R topics documented:

fromTSON	2
readTSON	3
toTSON	4
tson.character	5
tson.double	5
tson.float32.vec	6
tson.int	6
tson.int16.vec	7
tson.int8.vec	7
tson.map	8

tson.scalar	8
tson.uint16.vec	9
tson.uint32.vec	9
tson.uint8.vec	10
writeTSON	10

Index	12
--------------	-----------

fromTSON	<i>Deserialize a raw vector</i>
----------	---------------------------------

Description

This function convert a raw vector into a list following TSON specification binary-encoded format.

Usage

```
fromTSON(bytes)
```

Arguments

bytes	A raw vector
-------	--------------

Value

A list

Examples

```
## Example

library(rtson)

list = list(integer=42L,
            double=42,
            bool=TRUE,
            uint8=tson.uint8.vec(c(42,0)),
            uint16=tson.uint16.vec(c(42,0)),
            uint32=tson.uint32.vec(c(42,0)),
            int8=tson.int8.vec(c(42,0)),
            int16=tson.int16.vec(c(42,0)),
            int32=as.integer(c(42,0)),
            float32=tson.float32.vec(c(0.0, 42.0)),
            float64=c(42.0,42.0),
            map=list(x=42, y=42, label="42"),
            list=list("42",42)
)

bytes = toTSON(list)
object = fromTSON(bytes)
```

readTSON	<i>Deserialize a connection</i>
----------	---------------------------------

Description

Read TSON specification binary-encoded format from a connection.

Usage

```
readTSON(con)
```

Arguments

con A connection or a raw vector

Value

A list

Examples

```
## Example

library(rtson)

list = list(integer=42L,
            double=42,
            bool=TRUE,
            uint8=tson.uint8.vec(c(42,0)),
            uint16=tson.uint16.vec(c(42,0)),
            uint32=tson.uint32.vec(c(42,0)),
            int8=tson.int8.vec(c(42,0)),
            int16=tson.int16.vec(c(42,0)),
            int32=as.integer(c(42,0)),
            float32=tson.float32.vec(c(0.0, 42.0)),
            float64=c(42.0,42.0),
            map=list(x=42, y=42, label="42"),
            list=list("42",42)
)

con = rawConnection(raw(0), "r+")
writeTSON(list, con)
bytes = rawConnectionValue(con)
close(con)
con = rawConnection(bytes, "r")
object = readTSON(con)
```

toTSON

Serialize a list

Description

This function convert a list into raw following TSON specification binary-encoded format.

Usage

```
toTSON(object)
```

Arguments

object A list

Value

A raw vector

Examples

```
## Example

library(rtson)

list = list(integer=42L,
            double=42,
            bool=TRUE,
            uint8=tson.uint8.vec(c(42,0)),
            uint16=tson.uint16.vec(c(42,0)),
            uint32=tson.uint32.vec(c(42,0)),
            int8=tson.int8.vec(c(42,0)),
            int16=tson.int16.vec(c(42,0)),
            int32=as.integer(c(42,0)),
            float32=tson.float32.vec(c(0.0, 42.0)),
            float64=c(42.0,42.0),
            map=list(x=42, y=42, label="42"),
            list=list("42",42)
)

bytes = toTSON(list)
```

tson.character	<i>Make a tson character</i>
----------------	------------------------------

Description

Make a tson character

Usage

tson.character(object)

Arguments

object A vector or list

Value

A tson character

tson.double	<i>Make a tson double</i>
-------------	---------------------------

Description

Make a tson double

Usage

tson.double(object)

Arguments

object A vector or list

Value

A tson double

tson.float32.vec *Make a tson float32 vector*

Description

Make a tson float32 vector

Usage

tson.float32.vec(object)

Arguments

object A vector or list

Value

A tson float32 vector

tson.int *Make a tson integer*

Description

Make a tson integer

Usage

tson.int(object)

Arguments

object A vector or list

Value

A tson integer

tson.int16.vec *Make a tson int16 vector*

Description

Make a tson int16 vector

Usage

tson.int16.vec(object)

Arguments

object A vector or list

Value

A tson int16 vector

tson.int8.vec *Make a tson int8 vector*

Description

Make a tson int8 vector

Usage

tson.int8.vec(object)

Arguments

object A vector or list

Value

A tson int8 vector

`tson.map`*Make a tson map*

Description

Required to generate empty map.

Usage

```
tson.map(object)
```

Arguments

`object` A vector or list

Value

A tson map

`tson.scalar`*Make a tson scalar (ie: singleton)*

Description

Make a tson scalar (ie: singleton)

Usage

```
tson.scalar(object)
```

Arguments

`object` A vector or list

Value

A tson scalar

tson.uint16.vec	<i>Make a tson uint16 vector</i>
-----------------	----------------------------------

Description

Make a tson uint16 vector

Usage

tson.uint16.vec(object)

Arguments

object A vector or list

Value

A tson uint16 vector

tson.uint32.vec	<i>Make a tson uint32 vector</i>
-----------------	----------------------------------

Description

Make a tson uint32 vector

Usage

tson.uint32.vec(object)

Arguments

object A vector or list

Value

A tson uint32 vector

tson.uint8.vec *Make a tson uint8 vector*

Description

Make a tson uint8 vector

Usage

```
tson.uint8.vec(object)
```

Arguments

object A vector or list

Value

A tson uint8 vector

writeTSON *Serialize a list*

Description

Write TSON specification binary-encoded format to a connection.

Usage

```
writeTSON(object, con)
```

Arguments

object A list
con A connection

Value

invisibly NULL

Examples

```
## Example

library(rtson)

list = list(integer=42L,
            double=42,
            bool=TRUE,
            uint8=tson.uint8.vec(c(42,0)),
            uint16=tson.uint16.vec(c(42,0)),
            uint32=tson.uint32.vec(c(42,0)),
            int8=tson.int8.vec(c(42,0)),
            int16=tson.int16.vec(c(42,0)),
            int32=as.integer(c(42,0)),
            float32=tson.float32.vec(c(0.0, 42.0)),
            float64=c(42.0,42.0),
            map=list(x=42, y=42, label="42"),
            list=list("42",42)
)

con = rawConnection(raw(0), "r+")
writeTSON(list, con)
bytes = rawConnectionValue(con)
close(con)
con = rawConnection(bytes, "r")
object = readTSON(con)
```

Index

[fromTSON](#), [2](#)

[readTSON](#), [3](#)

[toTSON](#), [4](#)

[tson.character](#), [5](#)

[tson.double](#), [5](#)

[tson.float32.vec](#), [6](#)

[tson.int](#), [6](#)

[tson.int16.vec](#), [7](#)

[tson.int8.vec](#), [7](#)

[tson.map](#), [8](#)

[tson.scalar](#), [8](#)

[tson.uint16.vec](#), [9](#)

[tson.uint32.vec](#), [9](#)

[tson.uint8.vec](#), [10](#)

[writeTSON](#), [10](#)