

L^AT_EX Class for the *Association for Computing Machinery**

Boris Veytsman[†]

2023/03/30, v1.90

Abstract

This package provides a class for typesetting publications of the Association for Computing Machinery.

Contents

1	Introduction	3
2	User's guide	3
2.1	Installation	3
2.2	Invocation and options	6
2.3	Top matter	7
2.4	Top matter of ACM Engage materials	19
2.5	ACM cover page	20
2.6	Internationalization	20
2.7	Algorithms	21
2.8	Figures and tables	21
2.9	Descriptions of images	23
2.10	Theorems	23
2.11	Online-only and offline-only material	24
2.12	Note about anonymous mode	24
2.13	Acknowledgments	24
2.14	Bibliography	25
	2.14.1 Processing using Bib _T _E X	25
	2.14.2 Processing using Bib _L _A _T _E X	28
2.15	Colors	29
	2.15.1 Manual bibliography	30
2.16	Other notable packages and typographic remarks	30
2.17	Counting words	30
2.18	Creative Commons licenses for ACM publications	31
2.19	Disabled or forbidden commands	31
2.20	Notes for wizards	31
2.21	Currently supported publications	32
2.22	A note about sigchi-a format	34

*©2016–2023, Association for Computing Machinery

[†]borisv@1k.net, boris@varphi.com

3	Implementation	35
3.1	Identification	35
3.2	Preload hook	35
3.3	Options	35
3.4	Setting switches	39
3.5	Loading the base class and package	40
3.6	Citations	41
3.7	Internationalization	43
3.8	Sectioning	45
3.9	Hyperxmp and hyperref	48
3.10	Other packages	50
3.11	Paper size and paragraphing	50
3.12	Fonts	54
3.13	Image descriptions	55
3.14	Floats	56
3.15	Lists	58
3.16	Top-matter data	59
3.17	Concepts system	76
3.18	Copyright system	76
3.19	Maketitle hook	82
3.20	ACM Engage top matter	83
3.21	Typesetting top matter	83
3.22	Headers and Footers	99
3.23	Sectioning	106
3.24	TOC lists	108
3.25	Theorems	108
3.26	Balancing columns	111
3.27	Acknowledgments	113
3.28	Conditional typesetting	113
3.29	Additional bibliography commands	113
3.30	Index	114
3.31	End of Class	114

1 Introduction

The Association for Computing Machinery¹ is the world’s largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession. It was one of the early adopters of \TeX for its typesetting.

It provided several different classes for a number of journals and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and supporting different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all the different classes and packages and provide an up-to-date \LaTeX package.

This package uses only free \TeX packages and fonts included in \TeX Live, Mik \TeX and other popular \TeX distributions. It is intended to be published in these distributions itself, which minimizes users’ efforts in the installation and support of this package.

I am grateful to Michael D. Adams, Leif Andersen, Lawrence Christopher Angrave, Dirk Beyer, Andrew Black, Joachim Breitner, Yegor Bugayenko, Benjamin Byholm, John Collins, Roberto Di Cosmo, Nils Anders Danielsson, Michael Ekstrand, Matthew Fluet, Paolo G. Giarrusso, Ben Greenman, Enrico Gregorio, Jamie Davis, Ulrike Fischer, Jason Hemann, Peter Kemp, Luis Leiva, Ben Liblit, Rholais Lii, LianTze Lim, Kuldeep S. Meel, Kai Mindermann, Frank Mittelbach, Serguei Mokhov, Ross Moore, John Owens, Joel Nider, Scott Pakin, Tobias Pape, Henning Pohl, Philip Quinn, Mathias Rav, Andreas Reichinger, Matteo Riondato, Craig Rodkin, Bernard Rous, Feras Saad, Kerry A. Seitz, Jr., David Shamma, Gabriel Scherer, Kartik Singhal, Christoph Sommer, Stephen Spencer, Shin Hwei Tan, Daniel Thomas, Shari Trewin, Zack Weinberg, John Wickerson and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User’s guide

This class uses many commands and customization options, so it might appear intimidating for a casual user. Do not panic! Many of these commands and options can be safely left with their default values or the values recommended by your conference or journal editors. If you have problems or questions, do not hesitate to ask me directly or the community at <https://github.com/borisveytsman/acmart>, <https://tex.stackexchange.com> or the closest \TeX Users Group. The world-wide \TeX Users Group is at <https://tug.org/>; please consider joining us if you use \TeX regularly.

2.1 Installation

Most probably, you already have this package installed in your favorite \TeX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since this package uses a number of relatively recent packages, especially the ones related to fonts.

The latest released version of this package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement by making a pull request.

¹<http://www.acm.org/>

Please note that the version on Github is a development (or experimental) version: please download it for testing new features. The production version is the one on CTAN and ACM sites.

Most users should not attempt to install this package themselves but should rather rely on their \TeX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex acmart.ins`. This will produce the file `acmart.cls`
2. Put the files `acmart.cls`, `acm-jdslogo.png`, and `ACM-Reference-Format.bst` in places where \TeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package. (This is probably the file you are reading now.)

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

This class uses a number of other packages. They are included in all major \TeX distributions (\TeX Live, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscs*, <http://www.ctan.org/pkg/amscs>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *balance*, <http://www.ctan.org/pkg/balance>
- *booktabs*, <http://www.ctan.org/pkg/booktabs>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *doclicense*, <http://www.ctan.org/pkg/doclicense>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *etoolbox*, <http://www.ctan.org/pkg/etoolbox>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>
- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>

- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>
- *hyperxmp*, <http://www.ctan.org/pkg/hyperxmp>
- *iftex*, <http://www.ctan.org/pkg/iftex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>
- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *refcount*, <http://www.ctan.org/pkg/refcount>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

2.2 Invocation and options

To use this class, put in the preamble of your document

```
\documentclass[<options>]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example,

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option `format` describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words `format=` can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals, transactions, and course materials, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case, you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

Starting in 2020, ACM retired formats `sigchi` and `sigchi-a`. SIGCHI conferences now use `sigconf` format for their publications. If a file uses `sigchi` format, a warning is issued, and the format is automatically switched to `sigconf`. Format `sigchi-a` can be used for non-ACM documents only (see Section 2.22). The format `acmcp` is used for ACM cover pages discussed in Section 2.5.

There are several Boolean options that can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting a Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option. It provides a version suitable for reviewers and copy editors.

Two samples in the `samples` directory, `manuscript` and `acmsmall-submission`, show manuscripts formatted for submission to ACM.

The default for the option `screen` depends on the publication. At present it is `false` for all publications *but* PACM, since PACM is now electronic-only. Thus PACM titles (see Table 5) set this option to `true`. In the future this option may involve additional features suitable for on-screen versions of articles.

The option `natbib` is used when the corresponding BibTeX style is based on `natbib`. In most cases you do not need to set it. See Section 2.14.

The option `anonymous` is used for anonymous review processes and causes all author information to be obscured.

Table 1: The possible values for the format option

Value	Meaning
manuscript	A manuscript. This is the default.
acmsmall	Small single-column format. Used for ACMJCSS, CIE, CSUR, DLT, FAC, GAMES, JACM, JATS, JDIQ, JDS, JEA, JERIC, JETC, JRC, PACM-CGIT, PACMHCI, PACMMOD, PACMNET, PACMPL, TAAS, TAC-CESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TDS, TEAC, TECS, TELO, THRI, TIIS, TIOT, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPML, TOPS, TORS TOS, TOSEM, TOSN, TQC, TRETTS, TSAS, TSC, TSLP and TWEB, including special issues.
acmlarge	Large single-column format. Used for DTRAP, HEALTH, IMWUT, JOCCH, POMACS and TAP, including special issues.
acmtog	Large double-column format. Used for TOG, including annual conference Technical Papers.
sigconf	Proceedings format for most ACM conferences (with the exception of SIGPLAN) and all ICPS volumes.
sigplan	Proceedings format for SIGPLAN conferences.
acmengage	ACM EngageCSEdu Course materials.
acmcp	ACM cover page.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The footer also includes the page range of the document. This helps detect missing pages in hard copies.

The option `authordraft` is intended for author’s drafts that are not intended for distribution. It typesets a copyright block to give the author an idea of its size and the overall size of the paper but overprints it with the phrase “Unpublished working draft. Not for distribution.”, which is also used as a watermark. This option sets `timestamp` and `review` to `true`, but these can be overridden by setting these options to `false` *after* setting `authordraft` to `true`.

The option `balance` determines whether the last page in the two column mode has balanced columns. By default it is `true`; however, it may lead to problems for some documents. Set it to `false` if you encounter compilation errors. Note that for one page documents `\balance` command might cause problems. An alternative is the (experimental) option `pbalance`, which uses the new package `pbalance` for this end.

The option `urlbreakonhyphens` determines whether URLs can be split between lines after hyphens. By default it is `true`. Set it to `false` to disallow these breaks.

The option `language` is used to define the languages for the multi-language papers. It is discussed in Section 2.6.

2.3 Top matter

A number of commands set up *top matter* or (in computer science jargon) *metadata* for an article. They establish the publication name, article title, authors, DOI and other data. Some of these commands, like `\title` and `\author`, should be put by the authors.

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered and hyperlinks are colored
screen	see text	A screen version: hyperlinks are colored
natbib	true	Whether to use the natbib package (see Section 2.14)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for the authors' personal use or posting (see Section 2.3)
nonacm	false	Use the class typesetting options for a non-ACM document, which will not include the conference/journal header and footers. Currently such documents allow only a Creative Commons license.
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's-draft mode is enabled
acmthm	true	Whether to define theorem-like environments, see Section 2.10
balance	true	Whether to balance the last page in two column mode
pbalance	false	Whether to balance the last page in two column mode using pbalance package
urlbreakonhyphens	true	Whether to break urls on hyphens

Others, like `\acmVolume` and `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be used before `\maketitle`.

This class internally loads the `amsart` class, so many top-matter commands are inherited from `amsart` [2].

`\acmJournal` The macro `\acmJournal{\shortName}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication in *uppercase*, for example,

```
\acmJournal{TOMS}
```

The currently recognized journals are listed in Table 5. Note that conference proceedings published in *book* form do not set this macro.

`\acmConference` The macro `\acmConference[\short name]{\name}{\date}{\venue}` is used for conference proceedings published in the book form. The arguments are the following:

short name: the abbreviated name of the conference (optional).

name: the name of the conference.

date: the date(s) of the conference.

venue: the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November
12--16}{Dallas, TX, USA}
\acmConference[SA'15 Art Papers]{November 02--06, 2015}{Kobe, Japan}
```

`\acmBooktitle` By default we assume that conference proceedings are published in the book named *Proceedings of CONFERENCE*, where CONFERENCE is the name of the conference inferred from the command `\acmConference` above. However, sometimes the book title is different. The command `\acmBooktitle` can be used to set this title, for example,

```
\acmBooktitle{Companion to the first International Conference on the
Art, Science and Engineering of Programming (Programming '17)}
```

An ACM paper should have either `\acmJournal` or `\acmConference` command. If it has both (or more) commands, the last one takes precedence. Note that if you have the command `\acmConference` in a journal format like `acmsmall`, the class will use conference format for bibstrip and reference citation formatting. In the samples directory there is a file `sample-acmsmall-conf.tex` with the example of this usage.

An ACM Engage material should *not* use `\acmJournal` or `\acmConference` command. It may use `\acmBooktitle` to override the default *ACM EngageCSEdu*. It should use `\acmYear` to set the date of the material.

`\editor` In most cases, conference proceedings are edited. You can use the command `\editor{\editor}` to set the editor of the volume. This command can be repeated, for example,

```

\editor{Jennifer B. Sartor}
\editor{Theo D'Hondt}
\editor{Wolfgang De Meuter}

```

`\title` The command `\title`, as in the `amsart` class, has two arguments: one optional, and one mandatory:

```
\title[<ShortTitle>]{<FullTitle>}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

`\subtitle` Besides title, ACM classes allow a subtitle, set with the `\subtitle{<subtitle>}` macro.

The commands for specifying authors are highly structured. The reason is they serve double duty: the authors' information is typeset in the manuscript *and* is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

`\author` The basic commands are `\author`, `\orcid` (for the researchers registered with ORCID, <http://www.orcid.org/>), `\affiliation` and `\email`. In the simplest case, you enter them in this order:

```

\email
\author{...}
\orcid{...}
\affiliation{...}
\email{...}

```

Do *not* use the \LaTeX `\and` macro or commas, or `\\` between the authors! Each author deserves his or her own `\author` command. An attempt to list several authors or their e-mails in one command leads to a warning or an error. This is not a bug, but the expected behavior.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: the metadata tools will get them.

ACM strongly encourages that you include ORCIDs for all authors before compiling or submitting for review and/or production processing.

If you do not have an ORCID, you may get one for free by registering at <http://www.orcid.org/>.

Sometimes an author has several affiliations. In this case, the `\affiliation` command should be repeated:

```

\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}

```

Similarly you can repeat the `\email` command.

You may have several authors with the same affiliation, different affiliations, or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is affiliated with I_2 only, author A_3 is affiliated with I_1 and I_3 , etc.). The recommended

solution is to put the `\affiliation` commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

In some cases, when several authors share the same affiliation, you can try to save space using the format

```
\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}
```

However, this format is not generally recommended.

`\additionalaffiliation` In some cases, too many affiliations can take too much space. The command `\additionalaffiliation{<affiliation>}` creates a footnote after an author's name with the words "Also with {<affiliation>}". You should use this command only as a last resort. An example of usage is:

```
\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
  \institution{The Th{\o}rv{\a}ld Group}
  \streetaddress{1 Th{\o}rv{\a}ld Circle}
  \city{Hekla}
  \country{Iceland}}
\affiliation{%
  \institution{Institute for Clarity in Documentation}
  \streetaddress{P.O. Box 1212}
  \city{Dublin}
  \state{Ohio}
  \postcode{43017-6221}}
```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørvæld Group.

`\position` The `\affiliation` and `\additionalaffiliation` commands are further structured to interact with the metadata extraction tools. Inside these commands you should use the `\position`, `\institution`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode`, `\streetaddress`, `\city`, `\state`, `\postcode`, `\country`

and `\country` macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they *are* necessary since they are used by the XML metadata extraction programs. Do *not* put commas or `\\` between the elements of `\affiliation`. They will be provided automatically.

The fields `\institution`, `\city` and `\country` are mandatory. If they are not provided, an error or a warning is issued. Currently the absence of `\country` produces an error; ACM may change this in the future.

An example of the author block:

```

\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
  \institution{University of New South Wales}
  \department{School of Biomedical Engineering}
  \streetaddress{Samuels Building (F25), Kensington Campus}
  \city{Sidney}
  \state{NSW}
  \postcode{2052}
  \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
  \institution{University of Pennsylvania}
  \city{Philadelphia}
  \state{PA}
  \country{USA}}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}

```

Note that the old ACM conference formats did not allow more than six authors and required some effort from authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same insitution. There could be two situations: the departments are independent, or one department is within another. In the first case, just repeat the command `\department` several times. To handle the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```

\affiliation{%
  \department[0]{Department of Lunar Studies} % 0 is the default
  \department[1]{John Doe Institute} % higher than 0
  \institution{University of San Serriffe}

```

```
\country{San Serriffe}}
```

and

```
\affiliation{%  
  \department{Department of Lunar Studies} % Not in the John Doe Institute!  
  \department{John Doe Institute}  
  \institution{University of San Serriffe}  
  \country{San Serriffe}}
```

The command `\affiliation` formats its output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany, the postcode is put before the city and is not separated by a comma. We can handle this order using

```
\affiliation{%  
  \institution{Fluginstitut}  
  \streetaddress{Sonnenallee 17}  
  \postcode{123456}  
  \city{Helm}  
  \country{Germany}}
```

However, the comma after the postcode is unfortunate: the address will be typeset (in some formats) as

```
Fluginstitut  
Sonnenallee 17  
123456, Helm, Germany
```

To overcome this problem, the command `\affiliation` has an optional parameter `obeypunctuation`, which can be `false` (the default) or `true`. If this parameter is `true`, `\affiliation` obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%  
  \institution{Fluginstitut}\\  
  \streetaddress{Sonnenallee 17}\\  
  \postcode{123456}  
  \city{Helm},  
  \country{Germany}}
```

will be typeset as

```
Fluginstitut  
Sonnenallee 17  
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

`\thanks` Like `amsart` (and unlike standard \LaTeX), we allow `\thanks` only *outside* of the commands `\title` and `\author`. This command is obsolete and should *not* be used in most

cases. Do not list your acknowledgments or grant sponsors here. Put this information in the `acks` environment (see Section 2.13).

`\authorsaddresses` In some formats, addresses are printed as a footnote on the first page. By default \TeX typesets them itself using the information you give it. However, you can override its choice using the command `\authorsaddresses{\langle contact addresses \rangle}`, for example,

```
\authorsaddresses{%
  Authors' addresses: G.~Zhou, Computer Science Department, College of
  William and Mary, 104 Jameson Rd, Williamsburg, PA 23185, US;
  V.~B'eranger, Inria Paris-Rocquencourt, Rocquencourt, France;
  A.~Patel, Rajiv Gandhi University, Rono-Hills, Doimukh, Arunachal
  Pradesh, India; H.~Chan, Tsinghua University, 30 Shuangqing Rd,
  Haidian Qu, Beijing Shi, China; T.~Yan, Eaton Innovation Center,
  Prague, Czech Republic; T.~He, C.~Huang, J.~A.~Stankovic University
  of Virginia, School of Engineering Charlottesville, VA 22903, USA;
  T. F. Abdelzاهر, (Current address) NASA Ames Research Center,
  Moffett Field, California 94035.}
```

You can *suppress* printing authors' addresses by setting them to an empty string: `\authorsaddresses{}`. Please note that authors' addresses are mandatory for journal articles.

`\titlenote` While the command `\thanks` generates a note without a footnote mark, sometimes
`\subtitlenote` the authors might need notes more tightly connected to the title, subtitle or author. The
`\authornote` commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the corresponding
 commands (`\title`, `\subtitle` and `\author`) generate such notes. For example,

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use a `\footnote` inside an `\author` or `\title` command since this confuses the metadata extraction software. (Actually these commands now produce errors.)

`\authornotemark` Sometimes one may need to have the same footnote connected to several authors. The command `\authornotemark[\langle number \rangle]` adds just the footnote mark, for example,

```
\author{A. U. Thor}
\authornote{Both authors contributed equally to the paper}
...
\author{A. N. Other}
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

`\acmVolume` The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are
`\acmNumber` inserted by the editor and set the journal volume, issue, article number, year and month
`\acmArticle` correspondingly. The arguments of all these commands, including `\acmMonth`, is numer-
`\acmYear` ical. For example,

```
\acmMonth
\acmVolume{9}
\acmNumber{4}
\acmArticle{39}
\acmYear{2010}
```

`\acmMonth{3}`

Note that `\acmArticle` is used not only for journals but also for some conference proceedings.

`\acmArticleSeq` The articles in the same issue of a journal have a *sequence number*. It is used to vertically position the black blob on the first page of some formats. By default it is the same as the article number, but the command `\acmArticleSeq{<n>}` can be used to change it:

```
\acmArticle{39} % The sequence number will be 39 by default
\acmArticleSeq{5} % We redefine it to 5
```

Setting this number to zero suppresses the blob.

`\acmSubmissionID` If your paper got a Submission ID from the Conference Management System, put it here:

```
\acmSubmissionID{123-A56-BU3}
```

`\acmPrice` The macro `\acmPrice{<price>}` sets the price for the article, for example,

```
\acmPrice{25.00}
```

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to `usgov`, `rightsretained`, `iw3c2w3`, or `iw3c2w3g`, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN` Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}` sets it. Normally it is set by the typesetter, for example,

```
\acmISBN{978-1-4503-3916-2}
```

Setting it to the empty string, as `\acmISBN{}`, suppresses printing the ISBN.

`\acmDOI` The macro `\acmDOI{<DOI>}` sets the DOI of the article, for example,

```
\acmDOI{10.1145/9999997.9999999}
```

It is normally set by the typesetter. Setting it to the empty string, as `\acmDOI{}`, suppresses the DOI.

`\acmBadge` Some conference articles get special distinctions, for example, the artifact evaluation for PPOPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display special badges supplied by the conference organizers. This class provides command to add these badges: `\acmBadge[<url>]{<graphics>}`. The arguments have the following meaning: [`<url>`], if provided, sets the link to the badge authority in the screen version, while `{<graphics>}` sets the graphics file with the badge image. The file must be a cropped square, which is scaled to a standard size in the output. For example, if the badge image is `ae-logo.pdf`, the command is

```
\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}
```

The command can be repeated, if a paper has several badges.

`\startPage` The macro `\startPage{<page>}` sets the first page of the article in a journal or book. It is used by the typesetter.

`\terms` The command `\keywords{<keyword, keyword,...>}` sets keywords for the article.

`\keywords` They must be separated by commas, for example,

```
\keywords{wireless sensor networks, media access control,  
multi-channel, radio interference, time synchronization}
```

CCSXML (*env.*) ACM publications are classified according to the ACM Computing Classification Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in the metadata in various databases. Therefore you need to provide both \TeX commands and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get results like the following:

```
\begin{CCSXML}  
<ccs2012>  
<concept>  
<concept_id>10010520.10010553.10010562</concept_id>  
<concept_desc>Computer systems organization~Embedded systems</concept_desc>  
<concept_significance>500</concept_significance>  
</concept>  
<concept>  
<concept_id>10010520.10010575.10010755</concept_id>  
<concept_desc>Computer systems organization~Redundancy</concept_desc>  
<concept_significance>300</concept_significance>  
</concept>  
<concept>  
<concept_id>10010520.10010553.10010554</concept_id>  
<concept_desc>Computer systems organization~Robotics</concept_desc>  
<concept_significance>100</concept_significance>  
</concept>  
<concept>  
<concept_id>10003033.10003083.10003095</concept_id>  
<concept_desc>Networks~Network reliability</concept_desc>  
<concept_significance>100</concept_significance>  
</concept>  
</ccs2012>  
\end{CCSXML}  
  
\ccsdesc[500]{Computer systems organization~Embedded systems}  
\ccsdesc[300]{Computer systems organization~Redundancy}  
\ccsdesc{Computer systems organization~Robotics}  
\ccsdesc[100]{Networks~Network reliability}
```

You just need to copy this code and paste it in your paper anywhere before `\maketitle`.

CCS Concepts and user-defined keywords are required for all articles over two pages in length, and are optional for one- and two-page articles (or abstracts).

`\setcopyright` There are several possibilities for the copyright of the papers published by the ACM: the authors may transfer the rights to the ACM, license them to the ACM, some or all

Table 3: Parameters for the `\setcopyright` command

Parameter	Meaning
<code>none</code>	The copyright and permission information is not typeset. (This is the option for some ACM conferences.)
<code>acmcopyright</code>	The authors transfer the copyright to the ACM (the “traditional” choice).
<code>acmlicensed</code>	The authors retain the copyright but license the publication rights to ACM.
<code>rightsretained</code>	The authors retain the copyright and publication rights to themselves or somebody else.
<code>usgov</code>	All the authors are employees of the US government.
<code>usgovmixed</code>	Some authors are employees of the US government.
<code>cagov</code>	All the authors are employees of the Canadian government.
<code>cagovmixed</code>	Some authors are employees of the Canadian government.
<code>licensedusgovmixed</code>	Some authors are employees of the US government, and the publication rights are licensed to ACM.
<code>licensedcagov</code>	All the authors are employees of the Canadian government, and the publication rights are licensed to ACM.
<code>licensedcagovmixed</code>	Some authors are employees of the Canadian government, and the publication rights are licensed to ACM.
<code>othergov</code>	Authors are employees of a government other than the US or Canada.
<code>licensedothergov</code>	Authors are employees of a government other than the US or Canada, and the publication rights are licensed to ACM.
<code>iw3c2w3</code>	Special statement for conferences organized by IW3C2.
<code>iw3c2w3g</code>	Special statement for conferences organized by IW3C2, when some authors are approved Google employees.
<code>cc</code>	Creative Commons license. If this key is set, <i>doclicense</i> images are used to typeset the license. See also <code>\setcctype</code> command. Note that at present this license can be used only for <code>acmengage</code> format or for <code>nonacm</code> publications.

authors might be employees of the US or Canadian governments, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 3. This command must be placed in the preamble, before `\begin{document}`. Additional information about ACM copyright rules is discussed in Section 2.18.

`\setcctype` If Creative Commons license is used, the package by default chooses CC-BY 4.0 Attribution 4.0 International license. You can override this choice by the command `\setcctype[version]{type}`, where [*version*] can be either 3.0 or 4.0 (4.0 by default), and {*type*} can be one of zero, by, by-sa, by-nd, by-nc, by-nc-sa, by-nc-nd (see <https://creativecommons.org/licenses/> for the explanation). This command should be used in the preamble only.

Material published under Creative Commons license should include the corresponding icon. A modern T_EX distribution includes these icons in the package *doclicense*. In case your distribution does not have them, ACM provides a file `cci-cons.zip` with these

icons. Just unzip it in the same directory where your document is.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear` Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this using the macro `\copyrightyear`, e.g.,

```
\acmYear{2016}
\copyrightyear{2015}
```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces a special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell TeX about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version, the page breaks might be different between them.

`abstract (env.)` The environment `abstract` must *precede* the `\maketitle` command. Again, this is different from the standard L^AT_EX. Putting `abstract` after `\maketitle` will trigger an error.

`teaserfigure (env.)` A special kind of figure is used for many two-column conference proceedings. This figure is placed just after the authors but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{This is a teaser}
  \label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You can override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 4. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf`, etc.). The number of boxes per row is determined automatically. If you want to override this, you can do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

However, in most cases you should *not* do this and should use the default settings. Setting `authorsperrow` to 0 will revert it to the default settings.

The parameter `printacmref` specifies whether to print the ACM bibliographic entry (default), or not. Note that this entry is required for all articles over one page in length, and is optional for one-page articles (abstracts).

Table 4: Settings for the `\settopmatter` command

Parameter	Values	Meaning
<code>printccs</code>	true/false	Whether to print CCS categories
<code>printacmref</code>	true/false	Whether to print the ACM bibliographic entry
<code>printfolios</code>	true/false	Whether to print page numbers (folios)
<code>authorsperrow</code>	numeric	Number of authors per row for the title page in conference proceedings formats

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The [*<stage>*] argument is optional; the default is Received for the first date and revised for the subsequent ones. For example,

```
\received{20 February 2007}
\received[revised]{12 March 2009}
\received[accepted]{5 June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top-matter group. That is it must follow the commands defined in this section.

`\shortauthors` *After* the command `\maketitle`, the macro `\shortauthors` stores the names of the authors for the running head. You can redefine it if the list of author's name is too long, e.g.,

```
\maketitle
\renewcommand{\shortauthors}{Zhou et al.}
```

2.4 Top matter of ACM Engage materials

ACM Engage materials resemble conference proceedings, but have some special features. First, as a rule, they are released under a Creative Commons license. By default CC-BY is used. However, if you want to use another variant of CC license, use `\setcctype` command, for example, `\setcctype{by-nc}`. Second, abstract is called *synopsis*. Third, there are special top matter items used for the materials, such as *Course*, *Resource Type*, *Programming Language*, *CS Topics*.

`\setengagemetadata` These items are set with the command `\setengagemetadata{<name>}{<value>}`, for example,

```
\setengagemetadata{Course}{CS1}
\setengagemetadata{Programming Language}{Python}
\setengagemetadata{Knowledge Unit}{Programming Concepts}
\setengagemetadata{CS Topics}{Functions, Data Types, Expressions,
Mathematical Reasoning}
```

Note that the type of Creative Commons license, if such license is used, is automatically added to the metadata.

2.5 ACM cover page

ACM cover pages are forms of extended abstracts that are added to journals at the late stage. Authors prepare them as separate .tex files using acmcp format. At present only JDS uses them, but in the future this may change.

There are several top matter commands specific for this format.

`\acmArticleType` There are five article types accepted by JDS: *Research* (the default), *Review*, *Discussion*, *Invited*, and *Position*. The command `\acmArticleType{<type>}` sets the article type, for example

```
\acmArticleType{Review}
```

`\acmCodeLink` The commands `\acmCodeDataLink{<link>}` and `\acmDataLink{<link>}` set the links
`\acmDataLink` to the data and code accompanying the paper, for example,

```
\acmCodeLink{https://github.com/repository/code}  
\acmDataLink{https://datadryad.org/stash/dataset/doi:DOI}
```

You may repeat these commands if you have several repositories.

ACM cover page should have the following obligatory sections:

- Problem statement,
- Methods,
- Results,
- Significance.

Sometimes the addresses extracted from the authors' data are too long to fit on the page. In this case the command `\authorsaddresses` can be use to override them, for example,

```
\authorsaddresses{Corresponding author: Ben Trovato,  
\href{mailto:trovato@corporation.com}{trovato@corporation.com};  
Institute for Clarity in Documentation, P.O. Box 1212, Dublin,  
Ohio, USA, 43017-6221}
```

The design of the cover page may require additional runs of latex to make the elements of the page align.

2.6 Internationalization

ACM accepts publications in languages other than English, as well as papers in English with translations of titles, subtitles, keywords and abstracts into other languages. Papers in languages other than English usually have titles, subtitles (if applicable), keywords and abstracts in English. Note that CCS concepts are always typeset in English.

To submit these papers you need to set the option `language` in the `\documentclass` command. This option can be repeated, for example,

```
\documentclass[sigconf, language=french, language=english]{acmart}
```

The last language in the list is the main language of the paper, i.e. the one for the main title, abstract, body, etc. The other languages are *secondary*, and used for translated titles, keywords, abstracts. Thus the paper above is written in English, and has a secondary abstract and a secondary title in French. On the other hand, a paper in French with secondary titles and abstracts in English and German should use, for example

```
\documentclass[sigconf,
               language=german,
               language=english,
               language=french]{acmart}
```

This key can use any language defined in *babel* package [3] (currently the package is tested with English, French, German and Spanish languages; other languages may require a translation of `\keywordsname` macro). Actually *acmart* loads *babel* internally, so you can use the facilities provided by this package.

If this key is set, you have access to several additional top matter commands.

`\translatedtitle` The commands `\translatedtitle{<language>}title`, `\translatedsubtitle{<language>}subtitle`
`\translatedsubtitle` and `\translatedkeywordslanguagekeywords` are used to set title, subtitle and key-
`\translatedkeywords` words in the secondary language. For example, a paper in English with French title and abstract may set

```
\title{A note on computational complexity}
\translatedtitle{french}{Remarque sur la complexit'e de calcul}
```

while a paper in French should set

```
\title{Remarque sur la complexit'e de calcul}
\translatedtitle{english}{A note on computational complexity}
```

`translatedabstract (env)` Similarly, `translatedabstract` environment has a mandatory language argument, for example,

```
\begin{translatedabstract}{english}
  This is the English version of the abstract
\end{translatedabstract}
```

You can repeat these commands if a paper has more than one secondary language.

Use the standard commands (`\title`, `\subtitle`, `\keywords`, `abstract`) for the main language of the paper.

2.7 Algorithms

There are now several good packages for typesetting algorithms [4, 5, 6], and the authors are free to choose their favorite one.

2.8 Figures and tables

The new ACM styles use the standard L^AT_EX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies and for tables *before* the table bodies.
2. The ACM uses the standard types for figures and tables and adds several new ones. In total there are the following types:
 - figure, table:** a standard figure or table taking a full text width in one-column formats and one column width in two-column formats.
 - figure***, **table*** in two-column formats, a special figure or table taking a full text width.
 - teaserfigure:** a special figure before `\maketitle`.
3. Accordingly, when scaling images, one should use the following sizes:
 - (a) For `teaserfigure`, `figure` in one-column mode or `figure*` in two-column mode, use `\textwidth`. In one-column mode, you can also use `\columnwidth`, which coincides with `\textwidth` in this case.
 - (b) For `figure` in two-column mode, use `\columnwidth`.

It is strongly recommended to use the package `booktabs` [7] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.
2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in the TeX FAQ [1]. The simplest one is to use a `\minipage` environment:

```

\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a
table footnote. This is a table footnote.} &
(200\,m$\times$200\,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table

```

```
sourcenote. This is a table sourcenote. This is a table
sourcenote.
```

```
\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}
```

Tables and figures are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.9 Descriptions of images

`\Description` Some readers of ACM publications might be visually challenged. These readers might use a voice-over software to read aloud the papers. It is important to provide them a description of each image used in the paper.

The command `\Description[short description]{long description}` should be placed inside every figure, `teaserfigure` or `marginfigure` environment to provide a description of the image(s) used in the figure. Unlike `\caption`, which is used alongside the image, `\Description` is intended to be used instead of the image, for example,

```
\begin{figure}
\centering
\includegraphics{voltage}
\Description{A bell-like histogram centered at  $0.5\text{V}$  with most
measurements between  $0.2\text{V}$  and  $0.8\text{V}$ }
\caption{Histogram of the measurements of voltage}
\label{fig:voltage}
\end{figure}
```

At present the lack of descriptions generates a warning at compilation.

2.10 Theorems

The ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma and corollary, and

acmdefinition: this is the style used for example and definition.

These environments are defined by default. In the unusual circumstance that a user does not wish to have these environments defined, the option `acmthm=false` in the preamble will suppress them.

Sometimes authors want to define new theorem-like constructs that use theorem counters. These constructs must be defined either after `\begin{document}`, or delayed using `\AtEndPreamble` macro, for example,

```
\AtEndPreamble{%
\theoremstyle{acmdefinition}
\newtheorem{remark}[theorem]{Remark}}
```

2.11 Online-only and offline-only material

`printonly` (*env.*) Some supplementary material in ACM publications is put online but not in the printed `screenonly` (*env.*) version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to `true`. Conversely, the text inside the environment `printonly` is typeset only when this option is set to `false`. For example,

```
\section{Supplementary materials}

\begin{printonly}
  Supplementary materials are available in the online version of this paper.
\end{printonly}

\begin{screenonly}
  (The actual supplementary materials.)
\end{screenonly}
```

We use the `comment` package for typesetting this code, so `\begin` and `\end` should start on a line of their own with no leading or trailing spaces.

2.12 Note about anonymous mode

`anonsuppress` (*env.*) When the option `anonymous` is selected, \TeX suppresses author information (including the number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper. For example,

```
\begin{anonsuppress}
  This is the continuation of the previous work by the author
  \cite{prev1, prev2}.
\end{anonsuppress}
```

As for the `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start on a line of their own with no leading or trailing spaces.

`\anon` To suppress short snippets of information, use the command `\anon[<substitute>]{<suppressed-text>}`. By default [*<substitute>*] is the word `ANONYMOUS`. Examples:

```
This work was performed at \anon{NSA}.
This work was performed at \anon[No Such Agency]{NSA}.
```

2.13 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in anonymous mode this section must be omitted: it gives too much information to reviewers. Second, data about grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

`acks` (*env.*) The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for the `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start on a line of their own with no leading or trailing spaces.

`\grantsponsor` All financial support *must* be listed using the commands `\grantsponsor` and `\grantnum`. These commands tell the postprocessing software about the granting organization and grant. The format of these commands is the following:

```
\grantsponsor{\sponsorID}{\name}{\url}
\grantnum[\url]{\sponsorID}{\number}.
```

Here `{\sponsorID}` is the unique ID used to match grants to sponsors, `{\name}` is the name of the sponsor, `{\url}` is its URL, and `{\number}` is the grant number. The `{\sponsorID}` of the `\grantnum` command must correspond to the `{\sponsorID}` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of the `\grantnum` command.

At present `{\sponsorID}` is chosen by the authors and can be an arbitrary key in the same way the label of a `\cite` is arbitrarily chosen. There might be a change to this policy if the ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
The authors would like to thank Dr. Yuhua Li for providing the
matlab code of the \textit{BEPS} method.

The authors would also like to thank the anonymous referees for
their valuable comments and helpful suggestions. This work is
supported by the \grantsponsor{GS501100001809}{National Natural
Science Foundation of
China}{https://doi.org/10.13039/501100001809} under Grant
No.: ~\grantnum{GS501100001809}{61273304}
and ~\grantnum[http://www.nnsf.cn/youngscientists]{GS501100001809}{Young
Scientists' Support Program}.
\end{acks}
```

2.14 Bibliography

The ACM lets you use either `BibTeX` or `BibLaTeX` to process your references: they require slightly different setup of your `LaTeX` file, as detailed in the following subsections.

2.14.1 Processing using `BibTeX`

This uses the `natbib` package for formatting references and the `BibTeX` style file `ACM-Reference-Format.bst` for `BibTeX` processing. You can disable loading of `natbib` using the option `natbib=false` in `\documentclass`. However, it is not recommended, as well as the use of `BibTeX` styles other than `ACM-Reference-Format.bst`, and may delay the processing of the manuscript.

`\citestyle` If you use `natbib`, you can select one of two predefined citation styles using the command `\citestyle`: the author-year format `acmauthoryear` or the numeric format `acmnumeric`. For example,

```
\citestyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

```
\setcitestyle      You can further customize natbib using the \setcitestyle command, for example,  
\setcitestyle{numbers,sort&compress}
```

One of the more common versions is

```
\setcitestyle{nosort}
```

It is useful if you do not like the way natbib sorts citation lists.

If you use natbib, then commands like `\citep` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode and cites the year in author-date mode.

Note that before version 1.48 the command `\citeyear` put the year in parentheses. In version 1.48 and later it produces just the year; the command `\citeyearpar` can be used to emulate its old behavior.

There are several customized \LaTeX entry types and fields in the ACM style file `ACM-Reference-Format.bst` that you may want to be aware of.

The style supports the fields `doi` and `url`, for example,

```
doi =          "10.1145/1188913.1188915",  
url =          "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

Normally the printing of URL is suppressed if DOI is present. However, there is a special field `distinctURL`. If it is present and is not zero, URL is printed even if DOI is present.

The style supports the arXiv-recommended fields `eprint` and (optionally) `primaryclass`, for example,

```
eprint =       "960935712",  
primaryclass = "cs",
```

See the examples at <https://arxiv.org/help/hypertex/bibstyles>.

There are several special entry types. Types `online` and `game` are used for Web pages and games, for example,

```
@online{Thornburg01,  
  author =      "Harry Thornburg",  
  year =       "2001",  
  title =      "Introduction to Bayesian Statistics",  
  url =        "http://ccrma.stanford.edu/~jos/bayes/bayes.html",  
  month =      mar,  
  lastaccessed = "March 2, 2005",  
}
```

Entry types `artifactsoftware`, `artifactdataset` (with synonyms `software` and `dataset`) can be used to cite software artifacts and datasets, for example,

```
@ArtifactSoftware{R,  
  title = {R: A Language and Environment for Statistical Computing},  
  author = {{R Core Team}},  
  organization = {R Foundation for Statistical Computing},
```

```

    address = {Vienna, Austria},
    year = {2019},
    url = {https://www.R-project.org/},
}
@ArtifactDataset{UMassCitations,
author   = {Sam Anzaroot and Andrew McCallum},
title    = {{UMass} Citation Field Extraction Dataset},
year     = 2013,
url      =
    {http://www.iesl.cs.umass.edu/data/data-umasscitationfield},
lastaccessed = {May 27, 2019}
}

```

For these entry types you can use the `lastaccessed` field to add the access date for the URL.

There are two ways to enter video or audio sources in the bibliography corresponding to two different possibilities. For standalone sources available online, you can use an online entry and set its `howpublished` field. For example,

```

@online{Obama08,
author = "Barack Obama",
year = "2008",
title = "A more perfect union",
howpublished = "Video",
day = "5",
url = "http://video.google.com/videoplay?docid=6528042696351994555",
month = mar,
lastaccessed = "March 21, 2008",
}

```

For sources available as attachments to conference proceedings and similar documents, you can use the usual `inproceedings` entry type and set its `howpublished` field:

```

@Inproceedings{Novak03,
author = "Dave Novak",
title = "Solder man",
booktitle = "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
year = "2003",
publisher = "ACM Press",
address = "New York, NY",
pages = "4",
month = "March 21, 2008",
doi = "10.9999/woot07-S422",
howpublished = "Video",
}

```

Sometimes you need to cite a complete issue of a journal. The periodical entry type is intended for this:

```

@periodical{JCohen96,
key = "Cohen",
editor = "Jacques Cohen",

```

```

title = "Special issue: Digital Libraries",
journal = "Communications of the {ACM}",
volume = "39",
number = "11",
month = nov,
year = "1996",
}

```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) to the entry.

If you do not know the author (this is often the case for online entries), use the key field to add a key for sorting and citations, for example,

```

@online{TUGInstmem,
  key = {TUG},
  year = 2017,
  title = "Institutional members of the {\TeX} Users Group",
  url = "http://wwtug.org/instmem.html",
  lastaccessed = "May 27, 2017",
}

```

A note about sorting. The current ACM bibliography styles always sort the entries according to authors names and publication year. There is a controversy about sorting names with “von” or “van” part: should Ludwig van Beethoven be sorted under “V” or under “B”? The American practice is to use “van” in sorting, i.e. to file van Beethoven under “V”. However, some authorities recommend to sort Dutch persons according to their last names (see e.g. <https://www.ifla.org/files/assets/cataloguing/pubs/names-of-persons.1996.pdf>). While I do not want to take a part in this dispute, I would like to point to the old “noopsort” trick by Oren Patashnik. Add to the .bib file the line

```
@PREAMBLE{"\providecommand{\noopsort}[1]{}"}
```

and then encode the author as

```
author = {Ludwig {\noopsort{Beethoven}}van Beethoven},
```

This will make the author to be sorted as “Beethoven” rather than “van Beethoven”.

The current bst style defines a number of macros for common journal names. In particular, all journals listed in Table 5 are included, so you can use strings like `journal = taccess` for *ACM Transactions on Accessible Computing*.

2.14.2 Processing using Bib_{La}T_EX

You will find in this package two sets of style files for Bib_{La}T_EX, `acmnumeric` and `acmauthoryear`, that mimic the behaviour of the `ACM-Reference-Format.bst` Bib_TE_X style. They provide you access to all the power of Bib_{La}T_EX and already include support for advanced citation of software artefact from the `biblatex-software` package, also separately available on CTAN. Look at the `biblatex-software` documentation to learn more about what it offers.

There are a few key differences in how the \LaTeX sources are set up when using $\text{Bib}\LaTeX$ instead of $\text{Bib}\TeX$, that we summarize briefly here (please refer to the official $\text{Bib}\LaTeX$ documentation for more details).

In the preamble of your document you need to load the $\text{Bib}\LaTeX$ package and select the appropriate bibliography style, as follows

```
\RequirePackage[
  datamodel=acmdatamodel,
  style=acmnumeric, % use style=acmauthoryear for publications that require it
]{biblatex}
```

Also in the preamble, you need to declare the bibliography sources files using the \addbibresource directive (one \addbibresource command per source file), e.g.:

```
\addbibresource{software.bib}
\addbibresource{sample-base.bib}
```

At the end of the document, where you want the bibliography to appear, you need to place the command $\text{\printbibliography}$.

Look at the `sample-*-biblatex.tex` files that can be found in the samples directory after running `make` for templates showcasing these $\text{Bib}\LaTeX$ styles.

2.15 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [8]: `ACMBlue`, `ACMYellow`, `ACMOrange`, `ACMRed`, `ACMLightBlue`, `ACMGreen`, `ACMPurple` and `ACMDarkBlue`. You can use them in color assignments.

The ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that differ only in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).
3. Most printing is in black and white.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation) as there is bound to be someone affected!

To ensure that you are using the most accessible colors, the ACM recommends that you choose sets of colors to help ensure suitable variations in when printed in greyscale by using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.15.1 Manual bibliography

Some people create bibliographies manually, writing down `\bibitem` commands explicitly. This approach is *not* recommended for ACM styles. The reason is, ACM submissions, besides being typeset, are also processed by special programs that extract metadata and references. Bibliographies created automatically with ACM styles contain customized macros for these programs, for example,

```
\bibitem[Ablamowicz and Fauser(2007)]%
  {Ablamowicz07}
\bibfield{author}{\bibinfo{person}{Rafal Ablamowicz} {and}
  \bibinfo{person}{Bertfried Fauser}.} \bibinfo{year}{2007}\natexlab{}.
\newblock \bibinfo{booktitle}{\emph{CLIFFORD: a Maple 11 Package for Clifford
  Algebra Computations, version 11}}.
\newblock
\urldef\tempurl%
\url{http://math.tntech.edu/rafal/cliff11/index.html}
\showURL{%
Retrieved February 28, 2008 from \tempurl}
```

Manual bibliographies without these macros may slow down the publication process, and thus are not recommended for ACM submissions.

2.16 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package `subcaption` [9] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages `nomencl` [10] and `glossaries` [11] can be used for the automatic creation of the lists of symbols and concepts used.

By default `acmart` prevents all widows and orphans (i.e., lonely lines at the beginning or end of the page) and hyphenation at the end of the page. This is done by the rather strict settings

```
\widowpenalty=10000
\clubpenalty=10000
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware, the results might be, well, sloppy.

Note that the uppercasing in section titles is done using the `textcase` package [12], so the command `\NoCaseChange` inside the title may help to prevent extraneous uppercasing.

2.17 Counting words

Some ACM conferences use word count limits for papers. The calculation of word number for a paper with math, tables and figures is not a trivial task. Currently the authoritative word count is done by translating the PDF to text and using `wc -w` on the output.

Authors can use the package `texcount` (used by Overleaf) to get an estimate of the word count. To facilitate this one adds to the beginning of the package metacomments

```
%TC:macro \cite [option:text,text]
%TC:macro \citep [option:text,text]
%TC:macro \citet [option:text,text]
%TC:envir table 0 1
%TC:envir table* 0 1
%TC:envir tabular [ignore] word
%TC:envir displaymath 0 word
%TC:envir math 0 word
%TC:envir comment 0 0
```

and uses `\begin{math}... \end{math}` instead of dollar signs for math. Note that the count is in any case approximate, and the final decision of editors is based on PDF count.

The script `texcount` provides a report of word count in the document.

2.18 Creative Commons licenses for ACM publications

At present ACM does not allow the authors to typeset Creative Commons license for most ACM publications. These licenses can be used under an agreement with the ACM publishing office. In this case they are inserted by ACM itself.

The exceptions are ACM Engage format, which allows Creative Commons license, and conferences organized and copyrighted by IW3C2. In these cases the authors should use correspondingly `\setcopyright{cc}`, `\setcopyright{iw3c2w3}`, or `\setcopyright{iw3c2w3g}` (the latter should be used by Google employees).

Yet another case is the typesetting of non-ACM materials, when the option `nonacm` is used. This case is somewhat opposite, because for this case *only* Creative Common licenses are supported.

The command `\setcopyright{cc}` produces an error unless the format is `acmengage` or `nonacm` option is selected. On the other hand, if the option `nonacm` is selected, any argument of `\setcopyright` other than `cc` is treated as `none`.

2.19 Disabled or forbidden commands

The goal of `acmart` package is to provide a uniform look and feel for ACM publications. Accordingly, a number of commands is forbidden or disabled in `acmart`.

You may *not* put several authors or several e-mails into a `\author` or `\email` command. This may lead to errors or warning.

You cannot change `\baselinestretch` in your document: this produces an error.

You should not abuse the command `\vspace`: this command may disturb the typesetting of ACM papers.

You should not load `amssymb` package since the package `acmart` defines the corresponding symbols itself.

2.20 Notes for wizards

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded and certain decisions are made. This presents a number of problems.

For example, one may want to use the `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to a package. Suppose you want to use the `dvipsnames` option of the `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` can be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][\LoadClassOrig[#1]{#2}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

Important note. This hook makes it too easy to create a manuscript that is not acceptable by the ACM. It is even easier to create a file that cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decide to use this hook, you are on your own.

`\AtBeginMaketitle` Another hook is `\AtBeginMaketitle`. The commands in this hook are executed before `\maketitle`, for example,

```
\AtBeginMaketitle{\acmPrice{125.00}}
```

2.21 Currently supported publications

Table 5: ACM publications and arguments of the `\acmJournal` command

Abbreviation	Publication
ACMJCSS	ACM Journal on Computing and Sustainable Societies
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
DLT	Distributed Ledger Technologies: Research and Practice
DGOV	Digital Government: Research and Practice
DTRAP	Digital Threats: Research and Practice
FAC	Formal Aspects of Computing
GAMES	ACM Games: Research and Practice
HEALTH	ACM Transactions on Computing for Healthcare
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JATS	ACM Journal on Autonomous Transportation Systems
JDIQ	ACM Journal of Data and Information Quality

Table 5: ACM publications and arguments of the `\acmJournal` command (continued)

Abbreviation	Publication
JDS	ACM/IMS Journal of Data Science
JEA	ACM Journal of Experimental Algorithmics
JERIC	ACM Journal of Educational Resources in Computing
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCCH	ACM Journal on Computing and Cultural Heritage
JRC	ACM Journal on Responsible Computing
PACMCGIT	Proceedings of the ACM on Computer Graphics and Interactive Techniques
PACMHCI	PACM on Human-Computer Interaction
PACMOD	PACM on Management of Data
PACMNET	PACM on Networking
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TDS	ACM/IMS Transactions on Data Science
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
TELO	ACM Transactions on Evolutionary Learning
THRI	ACM Transactions on Human-Robot Interaction
TIIS	ACM Transactions on Interactive Intelligent Systems
TIOT	ACM Transactions on Internet of Things
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications

Table 5: ACM publications and arguments of the `\acmJournal` command (continued)

Abbreviation	Publication
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPML	ACM Transactions on Probabilistic Machine Learning
TOPS	ACM Transactions on Privacy and Security
TORS	ACM Transactions on Recommender Systems
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TQC	ACM Transactions on Quantum Computing
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

Besides the publications listed in Table 5, there is a special “publication” type FACMP, a forthcoming ACM publication, reserved for new journals which are not assigned an ISSN yet.

2.22 A note about sigchi-a format

Starting in Spring 2020 ACM retired SIGCHI Extended Abstract format (`sigchi-a`). ACM will not, under any circumstances, accept documents in this format for publication and will not offer technical support to the authors who use this template.

You may use this format in the `nonacm` mode only, as in

```
\documentclass[sigchi-a, nonacm]{acmart}
```

`sidebar` (*env.*) This format has large margin uses for special figures and tables. This package provides three environments for this with optional captions:
`marginfigure` (*env.*)
`marginfigure` (*env.*)
`marginfigure` (*env.*)

sidebar: textual information in the margin,

marginfigure: a figure in the margin,

marginfigure: a table in the margin.

The environments `figure` and `table` produce figures and tables with the width of the text column. The environments `figure*` and `table*` produce “wide” figures and tables, which take a large part of the margin.

The horizontal sizes of figures are:

1. `figure`: `\columnwidth`,
2. `marginfigure`: `\marginparwidth`,
3. `figure*`: `\fulltextwidth`.

3 Implementation

3.1 Identification

We start with a declaration of who we are. Most .dtx files put driver code in a separate .drv driver file. We roll this code into the main file and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2023/03/30 v1.90 Typesetting articles for the Association for Computing Machinery]
```

And the driver code:

```
7 <*gobble>
8 \documentclass{ltxdoc}
9 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx, longtable}
10 \usepackage[tt=false, type1=true]{libertine}
11 \usepackage[varqu]{zi4}
12 \usepackage[libertine]{newtxmath}
13 \usepackage[tableposition=top]{caption}
14 \usepackage{hypdoc}
15 \PageIndex
16 \CodelineIndex
17 \RecordChanges
18 \EnableCrossrefs
19 \begin{document}
20   \DocInput{acmart.dtx}
21 \end{document}
22 </gobble>
23 <*class>
24 \def\@classname{acmart}
```

3.2 Preload hook

We preload acmart-preload-hook:

```
25 \InputIfFileExists{acmart-preload-hook.tex}{%
26   \ClassWarning{\@classname}{%
27     I am loading acmart-preload-hook.tex. You are fully responsible
28     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
29 \RequirePackage{xkeyval}
   We use xstring to check whether user input is valid
30 \RequirePackage{xstring}
   We need iftex to check the engine
31 \RequirePackage{iftex}
```

format The possible formats

```
32 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
33 manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
34 sigplan, sigchi, sigchi-a, acmengage, acmcp}[manuscript]{}{%
35 \ClassError{\@classname}{The option format must be manuscript,
36 acmsmall, acmlarge, acmtog, sigconf, siggraph,
37 sigplan, sigchi or sigchi-a}}
38 \def\@DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
39 \@DeclareACMFormat{manuscript}
40 \@DeclareACMFormat{acmsmall}
41 \@DeclareACMFormat{acmlarge}
42 \@DeclareACMFormat{acmtog}
43 \@DeclareACMFormat{sigconf}
44 \@DeclareACMFormat{siggraph}
45 \@DeclareACMFormat{sigplan}
46 \@DeclareACMFormat{sigchi}
47 \@DeclareACMFormat{sigchi-a}
48 \@DeclareACMFormat{acmengage}
49 \@DeclareACMFormat{acmcp}
50 \ExecuteOptionsX{format}
```

\if@ACM@screen Whether we use screen mode

```
51 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
52 \if@ACM@screen
53 \PackageInfo{\@classname}{Using screen mode}%
54 \else
55 \PackageInfo{\@classname}{Not using screen mode}%
56 \fi}{\PackageError{\@classname}{The option screen can be either true or
57 false}}
58 \ExecuteOptionsX{screen=false}
```

\if@ACM@urlbreakonhyphens

```
59 \define@boolkey+{acmart.cls}[@ACM@]{urlbreakonhyphens}[true]{%
60 \if@ACM@urlbreakonhyphens
61 \PackageInfo{\@classname}{Using breaking urls on hyphens}%
62 \else
63 \PackageInfo{\@classname}{Not breaking urls on hyphens}%
64 \fi}{\PackageError{\@classname}{The option urlbreakonhyphens can be either true or
65 false}}
66 \ExecuteOptionsX{urlbreakonhyphens=true}
```

\if@ACM@acmthm Whether we define theorem-like environments.

```
67 \define@boolkey+{acmart.cls}[@ACM@]{acmthm}[true]{%
68 \if@ACM@acmthm
69 \PackageInfo{\@classname}{Requiring acmthm}%
70 \else
71 \PackageInfo{\@classname}{Suppressing acmthm}%
72 \fi}{\PackageError{\@classname}{The option acmthm can be either true or
73 false}}
74 \ExecuteOptionsX{acmthm=true}
```

\if@ACM@review Whether we use review mode

```
75 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
```

```

76 \if@ACM@review
77   \PackageInfo{\@classname}{Using review mode}%
78   \AtBeginDocument{\@ACM@printfoliostrue}%
79 \else
80   \PackageInfo{\@classname}{Not using review mode}%
81 \fi}{\PackageError{\@classname}{The option review can be either true or
82   false}}
83 \ExecuteOptionsX{review=false}

```

`\if@ACM@authorversion` Whether we use author's-version mode

```

84 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
85   \if@ACM@authorversion
86     \PackageInfo{\@classname}{Using authorversion mode}%
87   \else
88     \PackageInfo{\@classname}{Not using authorversion mode}%
89 \fi}{\PackageError{\@classname}{The option authorversion can be either true or
90   false}}
91 \ExecuteOptionsX{authorversion=false}

```

`\if@ACM@nonacm` Special option for non-ACM publications using the ACM typesetting options.

```

92 \define@boolkey+{acmart.cls}[@ACM@]{nonacm}[true]{%
93   \if@ACM@nonacm
94     \PackageInfo{\@classname}{Using nonacm mode}%
95     \AtBeginDocument{\@ACM@printacmreffalse}%
96     % in 'nonacm' mode we disable the "ACM Reference Format"
97     % printing by default, but this can be re-enabled by the
98     % user using \settopmatter{printacmref=true}
99   \else
100     \PackageInfo{\@classname}{Not using nonacm mode}%
101 \fi}{\PackageError{\@classname}{The option nonacm can be either true or
102   false}}
103 \ExecuteOptionsX{nonacm=false}

```

`\if@ACM@balance` Whether to balance the last page

```

104 \define@boolkey+{acmart.cls}[@ACM@]{balance}[true]{}%
105 \PackageError{\@classname}{The option balance can be either true or
106   false}}
107 \ExecuteOptionsX{balance}

```

`\if@ACM@pbalance` Whether to balance the last page

```

108 \define@boolkey+{acmart.cls}[@ACM@]{pbalance}[true]{}%
109 \PackageError{\@classname}{The option pbalance can be either true or
110   false}}
111 \ExecuteOptionsX{pbalance=false}

```

`\if@ACM@natbib@override` This macro is no longer used.

`\if@ACM@natbib` Whether we use natbib mode

```

112 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
113   \if@ACM@natbib
114     \PackageInfo{\@classname}{Explicitly selecting natbib mode}%
115   \else
116     \PackageInfo{\@classname}{Explicitly deselecting natbib mode}%
117 \fi}{\PackageError{\@classname}{The option natbib can be either true or

```

```

118     false}}
119 \ExecuteOptionsX{natbib=true}

\if@ACM@anonymous Whether we use anonymous mode
120 \define@boolkey+{acmart.cls}[@ACM@]{anonymous}[true]{%
121   \if@ACM@anonymous
122     \PackageInfo{\@classname}{Using anonymous mode}%
123   \else
124     \PackageInfo{\@classname}{Not using anonymous mode}%
125   \fi}{\PackageError{\@classname}{The option anonymous can be either true or
126     false}}
127 \ExecuteOptionsX{anonymous=false}

\if@ACM@timestamp Whether we use timestamp mode
128 \define@boolkey+{acmart.cls}[@ACM@]{timestamp}[true]{%
129   \if@ACM@timestamp
130     \PackageInfo{\@classname}{Using timestamp mode}%
131   \else
132     \PackageInfo{\@classname}{Not using timestamp mode}%
133   \fi}{\PackageError{\@classname}{The option timestamp can be either true or
134     false}}
135 \ExecuteOptionsX{timestamp=false}

\if@ACM@authordraft Whether we use author-draft mode
136 \define@boolkey+{acmart.cls}[@ACM@]{authordraft}[true]{%
137   \if@ACM@authordraft
138     \PackageInfo{\@classname}{Using authordraft mode}%
139     \@ACM@timestamptrue
140     \@ACM@reviewtrue
141   \else
142     \PackageInfo{\@classname}{Not using authordraft mode}%
143   \fi}{\PackageError{\@classname}{The option authordraft can be either true or
144     false}}
145 \ExecuteOptionsX{authordraft=false}

\ACM@fontsize The font size to pass to the base class
146 % \changes{v1.87}{2022/08/27}{Added fontsize 8pt}
147 \def\ACM@fontsize{}
148 \DeclareOptionX{8pt}{\edef\ACM@fontsize{\CurrentOption}}
149 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
150 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
151 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
152 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

\ACM@languages The languages of the document
153 \def\ACM@languages{}
154 \DeclareOptionX{language}{%
155   \ifx\ACM@languages\@empty
156     \gdef\ACM@languages{english}\fi
157   \g@addto@macro\ACM@languages{, #1}}

158 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
159 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
160 \ProcessOptionsX
161 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

- `\if@ACM@manuscript` Whether we use manuscript mode
162 `\newif\if@ACM@manuscript`
- `\if@ACM@journal` There are two kinds of publications: journals and books
163 `\newif\if@ACM@journal`
- `\if@ACM@journal@bibstrip` Sometimes ACM wants a journal-like publication to have conference information in the bibstrip and vice versa, so we have an additional switch.
164 `\newif\if@ACM@journal@bibstrip`
- `\if@ACM@sigchiamode` The formatting of SIGCHI extended abstracts is quite unusual. We have a special switch for them.
165 `\newif\if@ACM@sigchiamode`
- `\if@ACM@engage` ACM Engage course materials have special formatting
166 `\newif\if@ACM@engage`
167 `\@ACM@engagefalse`
- `\if@ACM@acmcp` ACM cover page formatting
168 `\newif\if@ACM@acmcp`
169 `\@ACM@acmcpfalse`

Setting up switches

```
170 \ifnum\ACM@format@nr=5\relax % siggraph
171 \ClassWarning{\@classname}{%
172 The format siggraph is now obsolete.\MessageBreak
173 I am switching to sigconf.}
174 \setkeys{acmart.cls}{format=sigconf}
175 \fi
176 \ifnum\ACM@format@nr=7\relax % sigchi
177 \ClassWarning{\@classname}{%
178 The format sigchi is now obsolete.\MessageBreak
179 I am switching to sigconf.}
180 \setkeys{acmart.cls}{format=sigconf}
181 \fi
182 \ifnum\ACM@format@nr=8\relax % sigchi
183 \ClassWarning{\@classname}{%
184 ACM SIGCHI has retired the SIGCHI-A template\MessageBreak
185 effective immediately. ACM is keeping this template\MessageBreak
186 option available to authors who are working on legacy\MessageBreak
187 documents only. ACM will not, under any circumstances,\MessageBreak
188 accept documents in this format for publication and\MessageBreak
189 will not offer technical support to the authors who use\MessageBreak
190 this template.\MessageBreak
191 ACM SIGCHI is directing Conference leaders and\MessageBreak
192 authors to publish their articles using the SIGCONF\MessageBreak
193 template call.}
194 \fi
195 \ifnum\ACM@format@nr=0\relax
196 \@ACM@manuscripttrue
197 \else
```

```

198 \ACM@manuscriptfalse
199 \fi
200 \ACM@sigchiamodeffalse
201 \ifcase\ACM@format@nr
202 \relax % manuscript
203 \ACM@journaltrue
204 \or % acsmall
205 \ACM@journaltrue
206 \or % acmlarge
207 \ACM@journaltrue
208 \or % acmtog
209 \ACM@journaltrue
210 \or % sigconf
211 \ACM@journalfalse
212 \or % siggraph
213 \ACM@journalfalse
214 \or % sigplan
215 \ACM@journalfalse
216 \or % sigchi
217 \ACM@journalfalse
218 \or % sigchi-a
219 \ACM@journalfalse
220 \ACM@sigchiamodetrue
221 \or % acmengage
222 \ACM@journalfalse
223 \ACM@engagetrue
224 \or % acmcp
225 \ACM@journaltrue
226 \ACM@acmcptrue
227 \AtBeginDocument{\ACM@printacmreffalse}%
228 \fi
229 \if\ACM@journal
230 \ACM@journal@bibstriptrue
231 \else
232 \ACM@journal@bibstripfalse
233 \fi

```

3.5 Loading the base class and package

At this point we either have \ACM@fontsize or use defaults

```

234 \ifx\ACM@fontsize\@empty
235 \ifcase\ACM@format@nr
236 \relax % manuscript
237 \def\ACM@fontsize{9pt}%
238 \or % acsmall
239 \def\ACM@fontsize{10pt}%
240 \or % acmlarge
241 \def\ACM@fontsize{10pt}%
242 \or % acmtog
243 \def\ACM@fontsize{9pt}%
244 \or % sigconf
245 \def\ACM@fontsize{9pt}%
246 \or % siggraph
247 \def\ACM@fontsize{9pt}%

```

```

248 \or % sigplan
249 \def\ACM@fontsize{10pt}%
250 \or % sigchi
251 \def\ACM@fontsize{9pt}%
252 \or % sigchi-a
253 \def\ACM@fontsize{10pt}%
254 \or % acmengage
255 \def\ACM@fontsize{10pt}%
256 \or % acmcp
257 \def\ACM@fontsize{9pt}%
258 \fi
259 \fi
260 \ClassInfo{\@classname}{Using fontsize \ACM@fontsize}
261 \LoadClass[\ACM@fontsize, reqno]{amsart}
262 \RequirePackage{microtype}

```

We need etoolbox for delayed code

```
263 \RequirePackage{etoolbox}
```

Booktabs is now the default

```
264 \RequirePackage{booktabs}
```

We need totpages to calculate the number of pages and refcount to use that number

```
265 \RequirePackage{refcount}
```

```
266 \RequirePackage{totpages}
```

The `\collect@body` macro in `amsmath` is defined using `\def`. We load `environ` to access the `\long` version of this command

```
267 \RequirePackage{environ}
```

We use `setspace` for double spacing

```
268 \if@ACM@manuscript
```

```
269 \RequirePackage{setspace}
```

```
270 \onehalfspacing
```

```
271 \fi
```

We need `textcase` for better upcasing

```
272 \RequirePackage{textcase}
```

```
273 \if@ACM@acmcp
```

```
274 \RequirePackage{framed}
```

```
275 \RequirePackage{zref-savepos, zref-user}
```

```
276 \fi
```

`\ACM@acmcp@delta` We need to store the dimen to store the insert length of `acmcp` box

```
277 \newdimen\ACM@acmcp@delta
```

```
278 \ACM@acmcp@delta=0pt\relax
```

3.6 Citations

We patch `\setcitestyle` to allow, for example, `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citestyle` to warn about undefined citation styles.

```
279 \if@ACM@natbib
```

```
280 \RequirePackage{natbib}
```

```
281 \renewcommand{\bibsection}{%
```

```

282     \section*{\refname}%
283     \phantomsection\addcontentsline{toc}{section}{\refname}%
284 }
285 \renewcommand{\bibfont}{\bibliofont}
286 \renewcommand\setcitestyle[1]{
287 \@for\@tempa:=#1\do
288 {\def\@tempb{round}\ifx\@tempa\@tempb
289     \renewcommand\NAT@open{()\renewcommand\NAT@close{}}\fi
290 \def\@tempb{square}\ifx\@tempa\@tempb
291     \renewcommand\NAT@open{[]\renewcommand\NAT@close{[]}\fi
292 \def\@tempb{angle}\ifx\@tempa\@tempb
293     \renewcommand\NAT@open{<}\renewcommand\NAT@close{>}\fi
294 \def\@tempb{curly}\ifx\@tempa\@tempb
295     \renewcommand\NAT@open{\{\}\renewcommand\NAT@close{\}}\fi
296 \def\@tempb{semicolon}\ifx\@tempa\@tempb
297     \renewcommand\NAT@sep{;}\fi
298 \def\@tempb{colon}\ifx\@tempa\@tempb
299     \renewcommand\NAT@sep{:}\fi
300 \def\@tempb{comma}\ifx\@tempa\@tempb
301     \renewcommand\NAT@sep{,}\fi
302 \def\@tempb{authoryear}\ifx\@tempa\@tempb
303     \NAT@numbersfalse\fi
304 \def\@tempb{numbers}\ifx\@tempa\@tempb
305     \NAT@numberstrue\NAT@superfalse\fi
306 \def\@tempb{super}\ifx\@tempa\@tempb
307     \NAT@numberstrue\NAT@supertrue\fi
308 \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
309     \let\bibstyle=\@gobble\fi
310 \def\@tempb{bibstyle}\ifx\@tempa\@tempb
311     \let\bibstyle=\@citestyle\fi
312 \def\@tempb{sort}\ifx\@tempa\@tempb
313     \def\NAT@sort{\@ne}\fi
314 \def\@tempb{nosort}\ifx\@tempa\@tempb
315     \def\NAT@sort{\z@}\fi
316 \def\@tempb{compress}\ifx\@tempa\@tempb
317     \def\NAT@cmprs{\@ne}\fi
318 \def\@tempb{nocompress}\ifx\@tempa\@tempb
319     \def\NAT@cmprs{\z@}\fi
320 \def\@tempb{sort&compress}\ifx\@tempa\@tempb
321     \def\NAT@sort{\@ne}\def\NAT@cmprs{\@ne}\fi
322 \def\@tempb{mcite}\ifx\@tempa\@tempb
323     \let\NAT@merge\@ne\fi
324 \def\@tempb{merge}\ifx\@tempa\@tempb
325     \ifnum\NAT@merge<\tw@\let\NAT@merge\tw@\fi
326 \def\@tempb{elide}\ifx\@tempa\@tempb
327     \ifnum\NAT@merge<\thr@\let\NAT@merge\thr@\fi
328 \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
329     \NAT@longnamestrue\fi
330 \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
331     \def\NAT@nmfmt#1{\mbox{\NAT@up#1}}\fi
332 \expandafter\NAT@find@eq\@tempa=\relax\@nil
333 \if\@tempc\relax\else
334     \expandafter\NAT@rem@eq\@tempc
335     \def\@tempb{open}\ifx\@tempa\@tempb

```

```

336     \xdef\NAT@open{\@tempc}\fi
337     \def\@tempb{close}\ifx\@tempa\@tempb
338     \xdef\NAT@close{\@tempc}\fi
339     \def\@tempb{aysep}\ifx\@tempa\@tempb
340     \xdef\NAT@aysep{\@tempc}\fi
341     \def\@tempb{yysep}\ifx\@tempa\@tempb
342     \xdef\NAT@yrsep{\@tempc}\fi
343     \def\@tempb{notesep}\ifx\@tempa\@tempb
344     \xdef\NAT@cmt{\@tempc}\fi
345     \def\@tempb{citesep}\ifx\@tempa\@tempb
346     \xdef\NAT@sep{\@tempc}\fi
347     \fi
348   }%
349   \NAT@setcites
350 }
351 \renewcommand\citestyle[1]{%
352   \ifcsname bibstyle@#1\endcsname%
353   \csname bibstyle@#1\endcsname\let\bibstyle\@gobble%
354   \else%
355   \@latex@error{Undefined '#1' citestyle}%
356   \fi
357 }%
358 \fi

```

`\bibstyle@acmauthoryear` The default author-year format:

```

359 \newcommand{\bibstyle@acmauthoryear}{%
360   \setcitestyle{%
361     authoryear,%
362     open={[]},close={[]},citesep={;},%
363     aysep={},yysep={},,%
364     notesep={, }}}

```

`\bibstyle@acmnumeric` The default numeric format:

```

365 \newcommand{\bibstyle@acmnumeric}{%
366   \setcitestyle{%
367     numbers,sort&compress,%
368     open={[]},close={[]},citesep={,},%
369     notesep={, }}}

```

The default is numeric:

```

370 \if@ACM@natbib
371 \citestyle{acmnumeric}
372 \fi

```

3.7 Internationalization

```

373 \if@ACM@journal
374   \renewcommand\keywordsname{Additional Key Words and Phrases}%
375 \else
376   \renewcommand\keywordsname{Keywords}%
377 \fi
378 \if@ACM@engage
379   \renewcommand\abstractname{Synopsis}%
380 \fi

```

```

381 \ifx\ACM@languages\@empty
382 \else
383   \RequirePackage[\ACM@languages]{babel}%
384   \addto\captionenglish{%
385     \if@ACM@journal
386       \renewcommand\keywordsname{Additional Key Words and Phrases}%
387     \else
388       \renewcommand\keywordsname{Keywords}%
389     \fi
390   \renewcommand\acksname{Acknowledgements}%
391   \if@ACM@engage
392     \renewcommand\abstractname{Synopsis}%
393   \fi
394 }%
395 \addto\captionfrench{%
396   \if@ACM@journal
397     \renewcommand\keywordsname{Mots Clés et Phrases Supplémentaires}%
398   \else
399     \renewcommand\keywordsname{Mots clés}%
400   \fi
401   \renewcommand\acksname{Remerciements}%
402 }%
403 \addto\captionsgerman{%
404   \if@ACM@journal
405     \renewcommand\keywordsname{Zusätzliche Schlagwörter und Phrasen}%
406   \else
407     \renewcommand\keywordsname{Schlagwörter}%
408   \fi
409   \renewcommand\acksname{Danksagungen}%
410 }%
411 \addto\captionsspanish{%
412   \if@ACM@journal
413     \renewcommand\keywordsname{Palabras y Frases Claves Adicionales}%
414   \else
415     \renewcommand\keywordsname{Palabras claves}%
416   \fi
417   \renewcommand\acksname{Expresiones de gratitud}%
418 }%
419 \fi

```

\ACM@lang@check Some commands should not be used if the document is monlingual

```

420 \newcommand\ACM@lang@check[1]{%
421   \ifx\ACM@languages\@empty\relax
422   \ClassError{\@classname}{%
423     Command \string#1 \MessageBreak is used in monlingual document}{%
424     You used a command (\string#1) \MessageBreak
425     that does not have a meaning \MessageBreak
426     unless are languages are defined. \MessageBreak
427     Please choose the languages in \string\documentclass
428     \MessageBreak
429     (e.g. \string\documentclass[languages={french, english}]{acmart}),
430     \MessageBreak
431     or delete the command.}%
432   \fi}

```

```

\@translatedtitle
433 \def\@translatedtitle{}

\translatedtitle The title of the paper in a different language
434 \newcommand\translatedtitle[2]{\ACM@lang@check{\translatedtitle}%
435 \g@addto@macro\@translatedtitle{\par\foreignlanguage{#1}{#2}}}

\@translatedsubtitle
436 \def\@translatedsubtitle{}

\translatedsubtitle The subtitle of the paper in a different language
437 \newcommand\translatedsubtitle[2]{\ACM@lang@check{\translatedsubtitle}%
438 \g@addto@macro\@translatedsubtitle{\par\foreignlanguage{#1}{#2}}}

\@translatedkeywords
439 \def\@translatedkeywords{}

\translatedkeywords Add keywords to the paper in the language specified
440 \newcommand\translatedkeywords[2]{\ACM@lang@check{\translatedkeywords}%
441 \g@addto@macro\@translatedkeywords{\mktranslatedkeywords{#1}{#2}}}

\@translatedabstracts The container for translated abstracts.
442 \def\@translatedabstracts{}

translatedabstract We save translated abstracts into \@translatedabstracts
443 \newenvironment{translatedabstract}[1]{\Collect@Body
444 \@savetranslatedabstract\@mktranslatedabstract{#1}}{}

\@savetranslatedabstract And saving the abstract
445 \long\def\@savetranslatedabstract#1{\if@ACM@maketitle@typeset
446 \ClassError{\@classname}{Abstract must be defined before maketitle
447 command. Please move it!}\fi
448 \ACM@lang@check{translatedabstract}%
449 \g@addto@macro\@translatedabstracts{\bgroup#1\egroup}}

```

3.8 Sectioning

\@startsection Before we call hyperref, we redefine \@startsection commands to their L^AT_EX defaults since the amsart ones are too AMS-specific. We need to do this early since we want hyperref to have a chance to redefine them again:

```

450 \def\@startsection#1#2#3#4#5#6{%
451 \if@noskipsec \leavevmode \fi
452 \par
453 \@tempskipa #4\relax
454 \@afterindenttrue
455 \ifdim \@tempskipa <\z@
456 \@tempskipa -\@tempskipa \@afterindentfalse
457 \fi
458 \if@nobreak
459 \everypar{}%
460 \else
461 \addpenalty\@secpenalty\addvspace\@tempskipa

```

```

462 \fi
463 \@ifstar
464   {\@ssect{#3}{#4}{#5}{#6}}%
465   {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}%
466 \def\@sect#1#2#3#4#5#6[#7]#8{%
467   \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
468   \ifnum #2>\c@secnumdepth
469     \let\@svsec\@empty
470   \else
471     \refstepcounter{#1}%
472     \protected@edef\@svsec{\@secntformat{#1}\relax}%
473   \fi
474   \@tempskipa #5\relax
475   \ifdim \@tempskipa>\z@
476     \begingroup
477       #6{%
478         \@hangfrom{\hskip #3\relax\@svsec}%
479         \interlinepenalty \@M #8\@par}%
480     \endgroup
481     \csname #1mark\endcsname{#7}%
482     \ifnum #2>\c@secnumdepth \else
483       \@tochangmeasure{\csname the#1\endcsname}%
484     \fi
485     \addcontentsline{toc}{#1}{%
486       \ifnum #2>\c@secnumdepth \else
487         \protect\numberline{\csname the#1\endcsname}%
488       \fi
489       #7}%
490   \else
491     \def\@svsechd{%
492       #6{\hskip #3\relax
493         \@svsec #8}%
494       \csname #1mark\endcsname{#7}%
495       \ifnum #2>\c@secnumdepth \else
496         \@tochangmeasure{\csname the#1\endcsname\space}%
497       \fi
498       \addcontentsline{toc}{#1}{%
499         \ifnum #2>\c@secnumdepth \else
500           \protect\numberline{\csname the#1\endcsname}%
501         \fi
502         #7}}%
503   \fi
504   \@xsect{#5}}
505 \def\@xsect#1{%
506   \@tempskipa #1\relax
507   \ifdim \@tempskipa>\z@
508     \par \nobreak
509     \vskip \@tempskipa
510     \@afterheading
511   \else
512     \@nobreakfalse
513     \global\@noskipsectrue
514     \everypar{%
515       \if@noskipsec

```

```

516     \global\@noskipsecfalse
517     {\setbox\z@\lastbox}%
518     \clubpenalty\@M
519     \begingroup \@svsechd \endgroup
520     \unskip
521     \@tempskipa #1\relax
522     \hskip -\@tempskipa
523     \else
524     \clubpenalty \@clubpenalty
525     \everypar{}%
526     \fi}%
527 \fi
528 \ignorespaces}
529 \def\@secntformat#1{\csname the#1\endcsname\quad}
530 \def\@ssect#1#2#3#4#5{%
531   \@tempskipa #3\relax
532   \ifdim \@tempskipa>\z@
533     \begingroup
534     #4{%
535       \@hangfrom{\hskip #1}%
536       \interlinepenalty \@M #5\@par}%
537     \endgroup
538   \else
539     \def\@svsechd{#4{\hskip #1\relax #5}}%
540   \fi
541   \@xsect{#3}}

```

\@startsection The amsart package redefines \@startsection. Here we redefine it again to make the table of contents work.

```

542 \def\@starttoc#1#2{\begingroup\makeatletter
543   \setTrue{#1}%
544   \par\removelastskip\vskip\z@skip
545   \@startsection{section}\@M\z@{\linespacing\@plus\linespacing}%
546   {.5\linespacing}{\centering\contentsnamefont}{#2}%
547   \@input{\jobname.#1}%
548   \if@filesw
549     \xpnewwrite\csname tf@#1\endcsname
550     \immediate\xpopenout\csname tf@#1\endcsname \jobname.#1\relax
551   \fi
552   \global\@nbreakfalse \endgroup
553   \addvspace{32\p@\@plus14\p@}%
554 }

```

\l@section Section spacing is more generous than for amsart

```
555 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}
```

\l@subsection The spacing in amsart is too large

```
556 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}
```

\l@subsubsection The spacing in amsart is too large

```
557 \def\l@subsubsection{\@tocline{3}{0pt}{1pc}{5pc}{}}
```

We need to define footnote-related stuff before the call to hyperref (Ross Moore)

```
\@makefnmark We do not use indentation for footnotes
558 \def\@makefnmark{\noindent\@makefnmark}
```

```
\@footnotetext In sigchi-a mode our footnotes are in the margin!
559 \if@ACM@sigchiamode
560 \long\def\@footnotetext#1{\marginpar{%
561   \reset@font\small
562   \interlinepenalty\interfootnotelinepenalty
563   \protected@edef\@currentlabel{%
564     \csname p@footnote\endcsname\@thefnmark
565   }}%
566   \color@begingroup
567   \@makefnmark{%
568     \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
569   \color@endgroup}}%
570 \fi
```

```
\@mpfootnotetext We want the footnotes in minipages centered:
571 \long\def\@mpfootnotetext#1{%
572   \global\setbox\@mpfootins\vbox{%
573     \unvbox\@mpfootins
574     \reset@font\footnotesize
575     \hsize\columnwidth
576     \@parboxrestore
577     \protected@edef\@currentlabel
578       {\csname p@mpfootnote\endcsname\@thefnmark}%
579     \color@begingroup\centering
580     \@makefnmark{%
581       \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
582     \color@endgroup}}
```

```
\@makefnmark AMS classes use a buggy definition of \makefnmark. We revert to the standard one.
583 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}
```

3.9 Hyperxmp and hyperref

Adding hyperxmp

```
584 \RequirePackage{hyperxmp}
    And now, hyperref
585 \let\@footnotemark@nolink\@footnotemark
586 \let\@footnotetext@nolink\@footnotetext
587 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
588 \pdfstringdefDisableCommands{%
589   \def\addtocounter#1#2{}%
590   \def\unskip{}%
591   \def\textbullet{- }%
592   \def\textrightarrow{-> }%
593   \def\footnotemark{}%
594 }
595 \urlstyle{rm}
596 \ifcase\ACM@format@nr
597 \relax % manuscript
```

```

598 \or % acmsmall
599 \or % acmlarge
600 \or % acmtog
601 \or % sigconf
602 \or % siggraph
603 \or % sigplan
604 \urlstyle{sf}
605 \or % sigchi
606 \or % sigchi-a
607 \urlstyle{sf}
608 \or % acmengage
609 \or % acmcp
610 \fi
611 \AtEndPreamble{%
612   \if@ACM@urlbreakonhyphens
613     \def\do@url@hyp{\do\~}%
614   \fi
615   \if@ACM@screen
616     \hypersetup{colorlinks,
617       linkcolor=ACMPurple,
618       citecolor=ACMPurple,
619       urlcolor=ACMDarkBlue,
620       filecolor=ACMDarkBlue}
621   \else
622     \hypersetup{hidelinks}
623   \fi
624   \hypersetup{pdflang={en},
625     pdfdisplaydoctitle}}

```

Bibliography mangling.

```

626 \if@ACM@natbib
627   \let\cite\cite
628   \let\cite\citep
629   \let\citeANP\citeauthor
630   \let\citeNN\citeyearpar
631   \let\citeyearNP\citeyear
632   \let\citeNP\citealt
633   \DeclareRobustCommand\citeA
634     {\begingroup\NAT@swafalse
635       \let\NAT@cotype\@ne\NAT@partrue\NAT@fullfalse\NAT@open\NAT@citetp}%
636   \providecommand\newblock{}%
637 \else
638   \AtBeginDocument{%
639     \let\shortcite\cite%
640     \providecommand\citename[1]{#1}}
641 \fi
642 \newcommand\shortcite[2][{}]{%
643   \ifNAT@numbers\cite[#1]{#2}\else\citeyearpar[#1]{#2}\fi}

```

`\bibliographystyle` The `amsart` package redefines `\bibliographystyle` since it prefers the AMS bibliography style. We turn it back to the \LaTeX definition:

```

644 \def\bibliographystyle#1{%
645   \ifx\@begindocumenthook\@undefined\else
646     \expandafter\AtBeginDocument

```

```

647 \fi
648   {\if@filesw
649     \immediate\write\@auxout{\string\bibstyle{#1}}%
650     \fi}}

```

3.10 Other packages

Graphics and color.

```

651 \RequirePackage{graphicx}
652 \RequirePackage[prologue]{xcolor}

```

We define ACM colors according to [8]:

```

653 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
654 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
655 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
656 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
657 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
658 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
659 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
660 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}

```

Author-draft mode or sigchi-a mode

```

661 \if@ACM@authordraft
662   \RequirePackage{draftwatermark}
663   \SetWatermarkFontSize{0.5in}
664   \SetWatermarkColor[gray]{.9}
665   \SetWatermarkText{\parbox{12em}{\centering
666     Unpublished working draft. \\\
667     Not for distribution.}}}
668 \else
669   \if@ACM@sigchiamode
670     \if@ACM@nonacm\else
671       \RequirePackage{draftwatermark}
672       \SetWatermarkFontSize{0.5in}
673       \SetWatermarkColor[gray]{.9}
674       \SetWatermarkText{\parbox{12em}{\centering
675         Legacy document. \\\
676         Not for publication in an ACM venue}}
677     \fi
678   \fi
679 \fi

```

3.11 Paper size and paragraphing

We use geometry for dimensions. Note that the present margins do not depend on the font size option—we might need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```

680 \RequirePackage{geometry}
681 \ifcase\ACM@format@nr
682 \relax % manuscript
683   \geometry{letterpaper,head=13pt,
684     marginparwidth=6pc,heightrounded}%
685 \or % acmsmall
686   \geometry{twoside=true,

```

```

687     includeheadfoot, head=13pt, foot=2pc,
688     paperwidth=6.75in, paperheight=10in,
689     top=58pt, bottom=44pt, inner=46pt, outer=46pt,
690     marginparwidth=2pc,heightrounded
691   }%
692 \or % acmlarge
693   \geometry{twoside=true, head=13pt, foot=2pc,
694     paperwidth=8.5in, paperheight=11in,
695     includeheadfoot,
696     top=78pt, bottom=114pt, inner=81pt, outer=81pt,
697     marginparwidth=4pc,heightrounded
698   }%
699 \or % acmtog
700   \geometry{twoside=true, head=13pt, foot=2pc,
701     paperwidth=8.5in, paperheight=11in,
702     includeheadfoot, columnsep=24pt,
703     top=52pt, bottom=75pt, inner=52pt, outer=52pt,
704     marginparwidth=2pc,heightrounded
705   }%
706 \or % sigconf
707   \geometry{twoside=true, head=13pt,
708     paperwidth=8.5in, paperheight=11in,
709     includeheadfoot, columnsep=2pc,
710     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
711     marginparwidth=2pc,heightrounded
712   }%
713 \or % siggraph
714   \geometry{twoside=true, head=13pt,
715     paperwidth=8.5in, paperheight=11in,
716     includeheadfoot, columnsep=2pc,
717     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
718     marginparwidth=2pc,heightrounded
719   }%
720 \or % sigplan
721   \geometry{twoside=true, head=13pt,
722     paperwidth=8.5in, paperheight=11in,
723     includeheadfoot=false, columnsep=2pc,
724     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
725     marginparwidth=2pc,heightrounded
726   }%
727 \or % sigchi
728   \geometry{twoside=true, head=13pt,
729     paperwidth=8.5in, paperheight=11in,
730     includeheadfoot, columnsep=2pc,
731     top=66pt, bottom=73pt, inner=54pt, outer=54pt,
732     marginparwidth=2pc,heightrounded
733   }%
734 \or % sigchi-a
735   \geometry{twoside=false, head=13pt,
736     paperwidth=11in, paperheight=8.5in,
737     includeheadfoot, marginparsep=72pt,
738     marginparwidth=170pt, columnsep=20pt,
739     top=72pt, bottom=72pt, left=314pt, right=72pt
740   }%

```

```

741 \mparswitchfalse
742 \reversemarginpar
743 \or % acmengage
744 \geometry{twoside=true, head=13pt,
745 paperwidth=8.5in, paperheight=11in,
746 includeheadfoot, columnsep=2pc,
747 top=57pt, bottom=73pt, inner=54pt, outer=54pt,
748 marginparwidth=2pc,heightrounded
749 }%
750 \or % acmcp
751 \geometry{twoside=true,
752 includeheadfoot, head=13pt, foot=2pc,
753 paperwidth=6.75in, paperheight=10in,
754 top=58pt, bottom=44pt, inner=46pt, outer=46pt,
755 marginparwidth=2pc,heightrounded
756 }%
757 \fi

```

\parindent Paragraphing

```

\parskip 758 \setlength\parindent{10\p@}
759 \setlength\parskip{\z@}
760 \ifcase\ACM@format@nr
761 \relax % manuscript
762 \or % acmsmall
763 \or % acmlarge
764 \or % acmtog
765 \setlength\parindent{9\p@}%
766 \or % sigconf
767 \or % siggraph
768 \or % sigplan
769 \or % sigchi
770 \or % sigchi-a
771 \or % acmengage
772 \or % acmcp
773 \fi

```

`\normalparindent` The `amsart` package defines the `\normalparindent` length and initializes it to 12pt (the value of `\parindent` in `amsart`). It is later used to set the `\listparindent` length in the quotation environment and the `\parindent` length in the `\@footnotetext` command. We set `\normalparindent` to the value of `\parindent` as selected by `acmart` for consistent paragraph indents.

```
774 \setlength\normalparindent{\parindent}
```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for the `bibstrip`. In the old ACM classes, the `bibstrip` was a `\@float`. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use `manyfoot` for layered footnotes instead.

`copyrightpermissionfootnoterule` This is the footnote rule that separates the `bibstrip` from the rest of the paper. It is a full width rule.

```

775 \def\copyrightpermissionfootnoterule{\kern-3\p@
776 \hrule \@width \columnwidth \kern 2.6\p@}

```

```

777 \RequirePackage{manyfoot}
778 \SelectFootnoteRule[2]{copyrightpermission}
779 \DeclareNewFootnote{authorsaddresses}
780 \SelectFootnoteRule[2]{copyrightpermission}
781 \DeclareNewFootnote{copyrightpermission}

```

\footnoterule Tschichold's rules:

```

782 \def\footnoterule{\kern-3\p@
783 \hrule \@width 4pc \kern 2.6\p@}

```

\endminipage We do not use footnote rules in minipages

```

784 \def\endminipage{%
785 \par
786 \unskip
787 \ifvoid\@mpfootins\else
788 \vskip\skip\@mpfootins
789 \normalcolor
790 \unvbox\@mpfootins
791 \fi
792 \@minipagefalse
793 \color@endgroup
794 \egroup
795 \expandafter\@iiparbox\@mpargs{\unvbox\@tempboxa}}

```

\@textbottom Add some stretch according to David Carlisle's advice at <http://tex.stackexchange.com/a/62318/5522>

```

796 \def\@textbottom{\vskip \z@ \@plus 1pt}
797 \let\@texttop\relax

```

In two-column layouts, force both columns to be the same height by inserting extra internal vertical space to fill out the page.

```

798 \ifcase\ACM@format@nr
799 \relax % manuscript
800 \or % acsmall
801 \or % acmlarge
802 \or % acmtog
803 \flushbottom
804 \or % sigconf
805 \flushbottom
806 \or % siggraph
807 \flushbottom
808 \or % sigplan
809 \flushbottom
810 \or % sigchi
811 \flushbottom
812 \or % sigchi-a
813 \or % acmengage
814 \flushbottom
815 \or % acmcp
816 \flushbottom
817 \fi

```

3.12 Fonts

Somehow PDFTeX and XeTeX require different incantations to make a PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```
818 \ifPDFTeX
819 \input{glyphtounicode}
820 \pdfglyphtounicode{f_f}{FB00}
821 \pdfglyphtounicode{f_f_i}{FB03}
822 \pdfglyphtounicode{f_f_l}{FB04}
823 \pdfglyphtounicode{f_i}{FB01}
824 \pdfglyphtounicode{t_t}{0074 0074}
825 \pdfglyphtounicode{f_t}{0066 0074}
826 \pdfglyphtounicode{T_h}{0054 0068}
827 \pdfgentounicode=1
828 \RequirePackage{cmap}
829 \fi
```

`\if@ACM@newfonts` Whether we load the new fonts

```
830 \newif\if@ACM@newfonts
831 \@ACM@newfontstrue
832 \IfFileExists{libertine.sty}{\ClassWarning{\@classname}{You do not
833   have the libertine package installed. Please upgrade your
834   TeX}\@ACM@newfontsfalse}
835 \IfFileExists{zi4.sty}{\ClassWarning{\@classname}{You do not
836   have the inconsolata (zi4.sty) package installed. Please upgrade your
837   TeX}\@ACM@newfontsfalse}
838 \IfFileExists{newtxmath.sty}{\ClassWarning{\@classname}{You do not
839   have the newtxmath package installed. Please upgrade your
840   TeX}\@ACM@newfontsfalse}
```

We use Libertine throughout.

```
841 \if@ACM@newfonts
842   \RequirePackage[T1]{fontenc}
843   % Note that the order in which packages are loaded matters,
844   % and the correct order depends on the LaTeX engine used.
845   % See https://github.com/borisveytsman/acmart/issues/402
846   % and https://github.com/borisveytsman/acmart/issues/410
847   \ifxetex
848     \RequirePackage[libertine]{newtxmath}
849     \RequirePackage[tt=false]{libertine}
850     \setmonofont[StylisticSet=3]{inconsolata}
851   \else
852     \ifluatex
853       \RequirePackage[libertine]{newtxmath}
854       \RequirePackage[tt=false]{libertine}
855       \setmonofont[StylisticSet=3]{inconsolata}
856     \else
857       \RequirePackage[tt=false, type1=true]{libertine}
858       \RequirePackage[varqu]{zi4}
859       \RequirePackage[libertine]{newtxmath}
860     \fi
861   \fi
862 \fi
```

`\liningnums` Libertine defines `\liningnums`, which makes `fontspec` unhappy. While we do not use `fontspec`, some users do.

```
863 \let\liningnums\undefined
864 \AtEndPreamble{%
865   \DeclareTextFontCommand{\liningnums}{\libertineLF}}
```

The SIGCHI extended abstracts are sans serif:

```
866 \if@ACM@sigchiamode
867   \renewcommand{\familydefault}{\sfdefault}
868 \fi
```

3.13 Image descriptions

`\if@Description@present` A local switch: whether there is a description in the given figure

```
869 \newif\if@Description@present
870 \@Description@presenttrue
```

`\if@undescribed@images` A global switch whether some images were *not* described

```
871 \newif\if@undescribed@images
872 \@undescribed@imagesfalse
```

`\Description` The `Description` macro right now just sets switches

```
873 \newcommand\Description[2][\global\@Description@presenttrue\ignorespaces}
```

The global warning

```
874 \AtEndDocument{\if@undescribed@images
875   \ClassWarningNoLine{\@classname}{Some images may lack descriptions}\fi}
```

Hooks for figures and tables. We also patch `algorithm` and `algorithm*` in case somebody uses them.

```
876 \AtBeginEnvironment{figure}{\@Description@presentfalse
877   \let\@vspace\@vspace@orig
878   \let\@vspacer\@vspacer@orig}
879 \AtBeginEnvironment{figure*}{\@Description@presentfalse
880   \let\@vspace\@vspace@orig
881   \let\@vspacer\@vspacer@orig}
882 \AtEndEnvironment{figure}{\if@Description@presentfalse
883   \global\@undescribed@imagestrue
884   \ClassWarning{\@classname}{A possible image without description}\fi}
885 \AtEndEnvironment{figure*}{\if@Description@presentfalse
886   \global\@undescribed@imagestrue
887   \ClassWarning{\@classname}{A possible image without description}\fi}
888 \AtBeginEnvironment{table}{\let\@vspace\@vspace@orig
889   \let\@vspacer\@vspacer@orig}
890 \AtBeginEnvironment{table*}{\let\@vspace\@vspace@orig
891   \let\@vspacer\@vspacer@orig}
892 \AtBeginEnvironment{algorithm}{\let\@vspace\@vspace@orig
893   \let\@vspacer\@vspacer@orig}
894 \AtBeginEnvironment{algorithm*}{\let\@vspace\@vspace@orig
895   \let\@vspacer\@vspacer@orig}
896 \AtBeginEnvironment{lstlisting}{\let\@vspace\@vspace@orig
897   \let\@vspacer\@vspacer@orig}
898 \AtBeginEnvironment{lstlisting*}{\let\@vspace\@vspace@orig
```

```

899 \let\@vspacer\@vspacer@orig}
900 \AtBeginEnvironment{minted}{\let\@vspace\@vspace@orig
901 \let\@vspacer\@vspacer@orig}
902 \AtBeginEnvironment{minted*}{\let\@vspace\@vspace@orig
903 \let\@vspacer\@vspacer@orig}
904 \AtBeginEnvironment{listing}{\let\@vspace\@vspace@orig
905 \let\@vspacer\@vspacer@orig}
906 \AtBeginEnvironment{listing*}{\let\@vspace\@vspace@orig
907 \let\@vspacer\@vspacer@orig}
908

```

3.14 Floats

We use the caption package

```

909 \RequirePackage{caption, float}
910 \captionsetup[table]{position=top}
911 \if@ACM@journal
912 \captionsetup{labelfont={sf, small},
913 textfont={sf, small}, margin=\z@}
914 \captionsetup[figure]{name={Fig.}}
915 \else
916 \captionsetup{labelfont={bf},
917 textfont={bf}, labelsep=colon, margin=\z@}
918 \ifcase\ACM@format@nr
919 \relax % manuscript
920 \or % acmsmall
921 \or % acmlarge
922 \or % acmtog
923 \or % sigconf
924 \or % siggraph
925 \captionsetup{textfont={it}}
926 \or % sigplan
927 \captionsetup{labelfont={bf},
928 textfont={normalfont}, labelsep=period, margin=\z@}
929 \or % sigchi
930 \captionsetup[figure]{labelfont={bf, small},
931 textfont={bf, small}}
932 \captionsetup[table]{labelfont={bf, small},
933 textfont={bf, small}}
934 \or % sigchi-a
935 \captionsetup[figure]{labelfont={bf, small},
936 textfont={bf, small}}
937 \captionsetup[table]{labelfont={bf, small},
938 textfont={bf, small}}
939 \or % acmengage
940 \or % acmcp
941 \fi
942 \fi

```

sidebar The sidebar environment:

```

943 \newfloat{sidebar}{s}{sbar}
944 \floatname{sidebar}{Sidebar}
945 \renewenvironment{sidebar}{\Collect@Body\@sidebar}{}

```

```

\@sidebar The processing of the saved text
946 \long\def\@sidebar#1{\bgroup\let\@vspace\@vspace@orig
947 \let\@vspacer\@vspacer@orig\captionsetup{type=sidebar}%
948 \marginpar{\small#1}\egroup}

marginfigure The marginfigure environment:
949 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}

\@marginfigure The processing of the saved text
950 \long\def\@marginfigure#1{\bgroup
951 \let\@vspace\@vspace@orig
952 \let\@vspacer\@vspacer@orig
953 \captionsetup{type=figure}%
954 \marginpar{\@Description@presentfalse\centering
955 \small#1\if@Description@present\else
956 \global\@undescrbed@imagestrue
957 \ClassWarning{\@classname}{A possible image without description}
958 \fi}%
959 \egroup}

marginable The marginable environment:
960 \newenvironment{marginable}{\Collect@Body\@marginable}{}

\@marginable The processing of the saved text
961 \long\def\@marginable#1{\bgroup\let\@vspace\@vspace@orig
962 \let\@vspacer\@vspacer@orig\captionsetup{type=table}%
963 \marginpar{\centering\small#1}\egroup}

SIGCHI extended abstracts provide an interesting possibility to push into the margin.
Here we use figure* and table* for this.

\fulltextwidth We define the width of the boxes as
964 \newdimen\fulltextwidth
965 \fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)

\@dblfloat We redefine the double-float command. First, we make the size bigger. Second, our
default position is going to be tp (to give marginalia a chance)
966 \if@ACM@sigchiamode
967 \def\@dblfloat{\bgroup\let\@vspace\@vspace@orig
968 \let\@vspacer\@vspacer@orig\columnwidth=\fulltextwidth
969 \let\@endfloatbox\@endwidefloatbox
970 \def\@fpsaddddefault{\def\@fps{tp}}%
971 \@float}
972 \fi

\enddblfloat And the end. Just adding a \bgroup.
973 \if@ACM@sigchiamode
974 \def\enddblfloat{%
975 \endfloat\egroup}
976 \fi

```

`\@endwidefloatbox` This is the end of a wide box—we basically move everything to the left

```
977 \def\@endwidefloatbox{%
978   \par\vskip\z@skip
979   \@minipagefalse
980   \outer@nobreak
981   \egroup
982   \color@endbox
983   \global\setbox\@currbox=\vbox{\moveleft
984     \dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%
985   \wd\@currbox=\textwidth
986 }
```

3.15 Lists

```
987 \ifcase\ACM@format@nr
988 \relax % manuscript
989 \or % acsmall
990 \or % acmlarge
991 \or % acmtog
992 \or % sigconf
993 \or % siggraph
994 \or % sigplan
995 \def\labelenumi{\theenumi.}
996 \def\labelenumii{\theenumii.}
997 \def\labelenumiii{\theenumiii.}
998 \def\labelenumiv{\theenumiv.}
999 \or % sigchi
1000 \or % sigchi-a
1001 \or % acmengage
1002 \or % acmcp
1003 \fi
```

The AMS uses generous margins for lists. Note that `amsart` defines `\leftmargin` values for list levels at the beginning of the document, so we must redefine them in the same manner. Also, note that `amsart` redefines the `enumerate` and `itemize` environments with a `\makeLabel` command that uses `\llap`, so the `\labelwidth` value is (effectively) irrelevant; nonetheless, we follow `amsart` and set `\labelwidth` to `\leftmargin` minus `\labelsep`.

```
1004 \newdimen\@ACM@labelwidth
1005 \AtBeginDocument{%
1006   \setlength\labelsep{4pt}
1007   \setlength{\@ACM@labelwidth}{6.5pt}
1008
1009   %% First-level list: when beginning after the first line of an
1010   %% indented paragraph or ending before an indented paragraph, labels
1011   %% should not hang to the left of the preceding/following text.
1012   \setlength\leftmargini{\z@}
1013   \addtolength\leftmargini{\parindent}
1014   \addtolength\leftmargini{2\labelsep}
1015   \addtolength\leftmargini{\@ACM@labelwidth}
1016
1017   %% Second-level and higher lists.
1018   \setlength\leftmarginii{\z@}
1019   \addtolength\leftmarginii{0.5\labelsep}
```

```

1020 \addtolength\leftmarginii{\@ACM@labelwidth}
1021 \setlength\leftmarginiii{\leftmarginii}
1022 \setlength\leftmarginiv{\leftmarginiii}
1023 \setlength\leftmarginv{\leftmarginiv}
1024 \setlength\leftmarginvi{\leftmarginv}
1025 \@listi}
1026 \newskip\listisep
1027 \listisep\smallskipamount
1028 \def\@listI{\leftmargin\leftmargini
1029 \labelwidth\leftmargini \advance\labelwidth-\labelsep
1030 \listparindent\z@
1031 \topsep\listisep}
1032 \let\@listi\@listI
1033 \def\@listii{\leftmargin\leftmarginii
1034 \labelwidth\leftmarginii \advance\labelwidth-\labelsep
1035 \topsep\z@skip}
1036 \def\@listiii{\leftmargin\leftmarginiii
1037 \labelwidth\leftmarginiii \advance\labelwidth-\labelsep}
1038 \def\@listiv{\leftmargin\leftmarginiv
1039 \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
1040 \def\@listv{\leftmargin\leftmarginv
1041 \labelwidth\leftmarginv \advance\labelwidth-\labelsep}
1042 \def\@listvi{\leftmargin\leftmarginvi
1043 \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}
\descriptionlabel We do not use a colon by default like amsart does:
1044 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

\description Make the description environment indentation consistent with that of the itemize
and enumerate environments.
1045 \renewenvironment{description}{\list{}}{%
1046 \labelwidth\@ACM@labelwidth
1047 \let\makelabel\descriptionlabel}%
1048 }{
1049 \endlist
1050 }
1051 \let\enddescription=\endlist % for efficiency

```

3.16 Top-matter data

`\if@ACM@maketitle@typeset` The switch to check whether `\maketitle` is already typeset. It is initially false, and setting top matter when it is true is wrong.

```

1052 \newif\if@ACM@maketitle@typeset
1053 \@ACM@maketitle@typesetfalse

```

We use the `xkeyval` interface to define journal titles and the relevant information

```

1054 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
1055 ACMJCSS,%
1056 CIE,%
1057 CSUR,%
1058 DGOV,%
1059 DLT,%
1060 DTRAP,%
1061 FAC,%

```

1062 GAMES,%
1063 HEALTH,%
1064 IMWUT,%
1065 JACM,%
1066 JATS,%
1067 JDIQ,%
1068 JDS,%
1069 JEA,%
1070 JERIC,%
1071 JETC,%
1072 JOCCH,%
1073 JRC,%
1074 PACMCGIT,%
1075 PACMHCI,%
1076 PACMMOD,%
1077 PACMNET,%
1078 PACMPL,%
1079 POMACS,%
1080 TAAS,%
1081 TACCESS,%
1082 TACO,%
1083 TALG,%
1084 TALLIP,%
1085 TAP,%
1086 TCPS,%
1087 TDS,%
1088 TEAC,%
1089 TECS,%
1090 TELO,%
1091 THRI,%
1092 TIIS,%
1093 TIOT,%
1094 TISSEC,%
1095 TIST,%
1096 TKDD,%
1097 TMIS,%
1098 TOCE,%
1099 TOCHI,%
1100 TOCL,%
1101 TOCS,%
1102 TOCT,%
1103 TODAES,%
1104 TODS,%
1105 TOG,%
1106 TOIS,%
1107 TOIT,%
1108 TOMACS,%
1109 TOMM,%
1110 TOMPECS,%
1111 TOMS,%
1112 TOPC,%
1113 TOPS,%
1114 TOPLAS,%
1115 TOPML,%

```

1116 TORS,%
1117 TOS,%
1118 TOSEM,%
1119 TOSN,%
1120 TQC,%
1121 TRET%
1122 TSAS,%
1123 TSC,%
1124 TSLP,%
1125 TWEB,%
1126 FACMP%
1127 }{%
1128 \ifcase\@journalCode@nr
1129 \relax % ACMJCSS
1130 \def\@journalName{ACM Journal on Computing and Sustainable Societies}%
1131 \def\@journalNameShort{ACM J. Comput. Sustain. Soc.}%
1132 \def\@permissionCodeOne{2834-5533}%
1133 \or % CIE
1134 \def\@journalName{ACM Computers in Entertainment}%
1135 \def\@journalNameShort{ACM Comput. Entertain.}%
1136 \def\@permissionCodeOne{1544-3574}%
1137 \or % CSUR
1138 \def\@journalName{ACM Computing Surveys}%
1139 \def\@journalNameShort{ACM Comput. Surv.}%
1140 \def\@permissionCodeOne{0360-0300}%
1141 \or % DGOV
1142 \def\@journalName{Digital Government: Research and Practice}%
1143 \def\@journalNameShort{Digit. Gov. Res. Pract.}%
1144 \def\@permissionCodeOne{2639-0175}%
1145 \or % DLT
1146 \def\@journalName{Distributed Ledger Technologies: Research and Practice}%
1147 \def\@journalNameShort{Distrib. Ledger Technol.}%
1148 \def\@permissionCodeOne{2769-6472}%
1149 \or % DTRAP
1150 \def\@journalName{Digital Threats: Research and Practice}%
1151 \def\@journalNameShort{Digit. Threat. Res. Pract.}%
1152 \def\@permissionCodeOne{2576-5337}%
1153 \or % FAC
1154 \def\@journalName{Formal Aspects of Computing}%
1155 \def\@journalNameShort{Form. Asp. Comput.}%
1156 \def\@permissionCodeOne{0934-5043}%
1157 \def\@permissionCodeTwo{1433-299X}%
1158 \or % GAMES
1159 \def\@journalName{ACM Games: Research and Practice}%
1160 \def\@journalNameShort{ACM Games}%
1161 \def\@permissionCodeOne{2832-5516}%
1162 \or % HEALTH
1163 \def\@journalName{ACM Transactions on Computing for Healthcare}%
1164 \def\@journalNameShort{ACM Trans. Comput. Healthcare}%
1165 \def\@permissionCodeOne{2637-8051}%
1166 \or % IMWUT
1167 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
1168 Wearable and Ubiquitous Technologies}%
1169 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%

```

```

1170 \def\@permissionCodeOne{2474-9567}%
1171 \@ACM@screentruer
1172 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1173 \or % JACM
1174 \def\@journalName{Journal of the ACM}%
1175 \def\@journalNameShort{J. ACM}%
1176 \def\@permissionCodeOne{0004-5411}%
1177 \or % JATS
1178 \def\@journalName{Journal on Autonomous Transportation Systems}%
1179 \def\@journalNameShort{ACM J. Auton. Transport. Syst.}%
1180 \def\@permissionCodeOne{2833-0528}%
1181 \or % JDIQ
1182 \def\@journalName{ACM Journal of Data and Information Quality}%
1183 \def\@journalNameShort{ACM J. Data Inform. Quality}%
1184 \def\@permissionCodeOne{1936-1955}%
1185 \or % JDS
1186 \def\@journalName{ACM/JMS Journal of Data Science}%
1187 \def\@journalNameShort{ACM/IMS J. Data Sci.}%
1188 \def\@permissionCodeOne{2831-3194}%
1189 \def\@permissionCodeTwo{2831-3194}%
1190 \or % JEA
1191 \def\@journalName{ACM Journal of Experimental Algorithmics}%
1192 \def\@journalNameShort{ACM J. Exp. Algor.}%
1193 \def\@permissionCodeOne{1084-6654}%
1194 \or % JERIC
1195 \def\@journalName{ACM Journal of Educational Resources in Computing}%
1196 \def\@journalNameShort{ACM J. Edu. Resources in Comput.}%
1197 \def\@permissionCodeOne{1073-0516}%
1198 \or % JETC
1199 \def\@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
1200 \def\@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
1201 \def\@permissionCodeOne{1550-4832}%
1202 \or % JOCCH
1203 \def\@journalName{ACM Journal on Computing and Cultural Heritage}%
1204 \def\@journalNameShort{ACM J. Comput. Cult. Herit.}%
1205 \def\@permissionCodeOne{1556-4673}%
1206 \def\@permissionCodeTwo{1556-4711}%
1207 \or % JRC
1208 \def\@journalName{ACM Journal on Responsible Computing}%
1209 \def\@journalNameShort{ACM J. Responsib. Comput.}%
1210 \def\@permissionCodeOne{2832-0565}%
1211 \or % PACMCGIT
1212 \def\@journalName{Proceedings of the ACM on Computer Graphics and Interactive Techniques}%
1213 \def\@journalNameShort{Proc. ACM Comput. Graph. Interact. Tech.}%
1214 \def\@permissionCodeOne{2577-6193}%
1215 \@ACM@screentruer
1216 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1217 \or % PACMHCI
1218 \def\@journalName{Proceedings of the ACM on Human-Computer Interaction}%
1219 \def\@journalNameShort{Proc. ACM Hum.-Comput. Interact.}%
1220 \def\@permissionCodeOne{2573-0142}%
1221 \@ACM@screentruer
1222 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1223 \or % PACMMOD

```

```

1224 \def\@journalName{Proceedings of the ACM on Management of Data}%
1225 \def\@journalNameShort{Proc. ACM Manag. Data}%
1226 \def\@permissionCodeOne{2836-6573}%
1227 \or % PACMNET
1228 \def\@journalName{Proceedings of the ACM on Networkng}%
1229 \def\@journalNameShort{Proc. ACM Netw.}%
1230 \def\@permissionCodeOne{2834-5509}%
1231 \or % PACMPL
1232 \def\@journalName{Proceedings of the ACM on Programming Languages}%
1233 \def\@journalNameShort{Proc. ACM Program. Lang.}%
1234 \def\@permissionCodeOne{2475-1421}%
1235 \@ACM@screentruue
1236 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1237 \or % POMACS
1238 \def\@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
1239 \def\@journalNameShort{Proc. ACM Meas. Anal. Comput. Syst.}%
1240 \def\@permissionCodeOne{2476-1249}%
1241 \@ACM@screentruue
1242 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1243 \or % TAAS
1244 \def\@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
1245 \def\@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
1246 \def\@permissionCodeOne{1556-4665}%
1247 \or % TACCESS
1248 \def\@journalName{ACM Transactions on Accessible Computing}%
1249 \def\@journalNameShort{ACM Trans. Access. Comput.}%
1250 \def\@permissionCodeOne{1936-7228}%
1251 \or % TACO
1252 \def\@journalName{ACM Transactions on Architecture and Code Optimization}%
1253 \def\@journalNameShort{ACM Trans. Arch. Code Optim.}%
1254 \def\@permissionCodeOne{1544-3566}%
1255 \def\@permissionCodeTwo{1544-3973}%
1256 \or % TALG
1257 \def\@journalName{ACM Transactions on Algorithms}%
1258 \def\@journalNameShort{ACM Trans. Algor.}%
1259 \def\@permissionCodeOne{1549-6325}%
1260 \or % TALLIP
1261 \def\@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
1262 \def\@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
1263 \def\@permissionCodeOne{2375-4699}%
1264 \or % TAP
1265 \def\@journalName{ACM Transactions on Applied Perception}%
1266 \def\@journalNameShort{ACM Trans. Appl. Percept.}%
1267 \def\@permissionCodeOne{1544-3558}%
1268 \or % TCPS
1269 \def\@journalName{ACM Transactions on Cyber-Physical Systems}%
1270 \def\@journalNameShort{ACM Trans. Cyber-Phys. Syst.}%
1271 \def\@permissionCodeOne{2378-962X}%
1272 \or % TDS
1273 \def\@journalName{ACM/IMS Transactions on Data Science}%
1274 \def\@journalNameShort{ACM/IMS Trans. Data Sci.}%
1275 \def\@permissionCodeOne{2577-3224}%
1276 \or % TEAC
1277 \def\@journalName{ACM Transactions on Economics and Computation}%

```

1278 \def\@journalNameShort{ACM Trans. Econ. Comput.}%
1279 \def\@permissionCodeOne{2167-8375}%
1280 \or % TECS
1281 \def\@journalName{ACM Transactions on Embedded Computing Systems}%
1282 \def\@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
1283 \def\@permissionCodeOne{1539-9087}%
1284 \or % TELO
1285 \def\@journalName{ACM Transactions on Evolutionary Learning}%
1286 \def\@journalNameShort{ACM Trans. Evol. Learn.}%
1287 \def\@permissionCodeOne{2688-3007}%
1288 \or % THRI
1289 \def\@journalName{ACM Transactions on Human-Robot Interaction}%
1290 \def\@journalNameShort{ACM Trans. Hum.-Robot Interact.}%
1291 \def\@permissionCodeOne{2573-9522}%
1292 \or % TIIS
1293 \def\@journalName{ACM Transactions on Interactive Intelligent Systems}%
1294 \def\@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
1295 \def\@permissionCodeOne{2160-6455}%
1296 \or % TIOT
1297 \def\@journalName{ACM Transactions on Internet of Things}%
1298 \def\@journalNameShort{ACM Trans. Internet Things}%
1299 \def\@permissionCodeOne{2577-6207}%
1300 \or % TISSEC
1301 \def\@journalName{ACM Transactions on Information and System Security}%
1302 \def\@journalNameShort{ACM Trans. Info. Syst. Sec.}%
1303 \def\@permissionCodeOne{1094-9224}%
1304 \or % TIST
1305 \def\@journalName{ACM Transactions on Intelligent Systems and Technology}%
1306 \def\@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
1307 \def\@permissionCodeOne{2157-6904}%
1308 \or % TKDD
1309 \def\@journalName{ACM Transactions on Knowledge Discovery from Data}%
1310 \def\@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
1311 \def\@permissionCodeOne{1556-4681}%
1312 \or % TMIS
1313 \def\@journalName{ACM Transactions on Management Information Systems}%
1314 \def\@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
1315 \def\@permissionCodeOne{2158-656X}%
1316 \or % TOCE
1317 \def\@journalName{ACM Transactions on Computing Education}%
1318 \def\@journalNameShort{ACM Trans. Comput. Educ.}%
1319 \def\@permissionCodeOne{1946-6226}%
1320 \or % TOCHI
1321 \def\@journalName{ACM Transactions on Computer-Human Interaction}%
1322 \def\@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
1323 \def\@permissionCodeOne{1073-0516}%
1324 \or % TOCL
1325 \def\@journalName{ACM Transactions on Computational Logic}%
1326 \def\@journalNameShort{ACM Trans. Comput. Logic}%
1327 \def\@permissionCodeOne{1529-3785}%
1328 \or % TOCS
1329 \def\@journalName{ACM Transactions on Computer Systems}%
1330 \def\@journalNameShort{ACM Trans. Comput. Syst.}%
1331 \def\@permissionCodeOne{0734-2071}%

```

1332 \or % TOCT
1333 \def\@journalName{ACM Transactions on Computation Theory}%
1334 \def\@journalNameShort{ACM Trans. Comput. Theory}%
1335 \def\@permissionCodeOne{1942-3454}%
1336 \or % TODAES
1337 \def\@journalName{ACM Transactions on Design Automation of Electronic Systems}%
1338 \def\@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
1339 \def\@permissionCodeOne{1084-4309}%
1340 \or % TODS
1341 \def\@journalName{ACM Transactions on Database Systems}%
1342 \def\@journalNameShort{ACM Trans. Datab. Syst.}%
1343 \def\@permissionCodeOne{0362-5915}%
1344 \or % TOG
1345 \def\@journalName{ACM Transactions on Graphics}%
1346 \def\@journalNameShort{ACM Trans. Graph.}%
1347 \def\@permissionCodeOne{0730-0301}
1348 \or % TOIS
1349 \def\@journalName{ACM Transactions on Information Systems}%
1350 \def\@journalNameShort{ACM Trans. Inf. Syst.}%
1351 \def\@permissionCodeOne{1046-8188}%
1352 \or % TOIT
1353 \def\@journalName{ACM Transactions on Internet Technology}%
1354 \def\@journalNameShort{ACM Trans. Internet Technol.}%
1355 \def\@permissionCodeOne{1533-5399}%
1356 \or % TOMACS
1357 \def\@journalName{ACM Transactions on Modeling and Computer Simulation}%
1358 \def\@journalNameShort{ACM Trans. Model. Comput. Simul.}%
1359 \def\@permissionCodeOne{1049-3301}%
1360 \def\@permissionCodeTwo{1558-1195}%
1361 \or % TOMM
1362 \def\@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
1363 \def\@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
1364 \def\@permissionCodeOne{1551-6857}%
1365 \def\@permissionCodeTwo{1551-6865}%
1366 \or % TOMPECS
1367 \def\@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
1368 \def\@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
1369 \def\@permissionCodeOne{2376-3639}%
1370 \or % TOMS
1371 \def\@journalName{ACM Transactions on Mathematical Software}%
1372 \def\@journalNameShort{ACM Trans. Math. Softw.}%
1373 \def\@permissionCodeOne{0098-3500}%
1374 \or % TOPC
1375 \def\@journalName{ACM Transactions on Parallel Computing}%
1376 \def\@journalNameShort{ACM Trans. Parallel Comput.}%
1377 \def\@permissionCodeOne{2329-4949}%
1378 \def\@permissionCodeTwo{2329-4957}%
1379 \or % TOPS
1380 \def\@journalName{ACM Transactions on Privacy and Security}%
1381 \def\@journalNameShort{ACM Trans. Priv. Sec.}%
1382 \def\@permissionCodeOne{2471-2566}%
1383 \or % TOPLAS
1384 \def\@journalName{ACM Transactions on Programming Languages and Systems}%
1385 \def\@journalNameShort{ACM Trans. Program. Lang. Syst.}%

```

```

1386 \def\@permissionCodeOne{0164-0925}%
1387 \or % TOPML
1388 \def\@journalName{ACM Transactions on Probabilistic Machine Learning}%
1389 \def\@journalNameShort{ACM Trans. Probab. Mach. Learn.}%
1390 \def\@permissionCodeOne{2836-8924}%
1391 \or % TORS
1392 \def\@journalName{ACM Transactions on Recommender Systems}%
1393 \def\@journalNameShort{ACM Trans. Recomm. Syst.}%
1394 \def\@permissionCodeOne{2770-6699}%
1395 \or % TOS
1396 \def\@journalName{ACM Transactions on Storage}%
1397 \def\@journalNameShort{ACM Trans. Storage}%
1398 \def\@permissionCodeOne{1553-3077}%
1399 \or % TOSEM
1400 \def\@journalName{ACM Transactions on Software Engineering and Methodology}%
1401 \def\@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
1402 \def\@permissionCodeOne{1049-331X}%
1403 \or % TOSN
1404 \def\@journalName{ACM Transactions on Sensor Networks}%
1405 \def\@journalNameShort{ACM Trans. Sensor Netw.}%
1406 \def\@permissionCodeOne{1550-4859}%
1407 \or % TQC
1408 \def\@journalName{ACM Transactions on Quantum Computing}%
1409 \def\@journalNameShort{ACM Trans. Quantum Comput.}%
1410 \def\@permissionCodeOne{2643-6817}%
1411 \or % TRET
1412 \def\@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
1413 \def\@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
1414 \def\@permissionCodeOne{1936-7406}%
1415 \or % TSAS
1416 \def\@journalName{ACM Transactions on Spatial Algorithms and Systems}%
1417 \def\@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
1418 \def\@permissionCodeOne{2374-0353}%
1419 \or % TSC
1420 \def\@journalName{ACM Transactions on Social Computing}%
1421 \def\@journalNameShort{ACM Trans. Soc. Comput.}%
1422 \def\@permissionCodeOne{2469-7818}%
1423 \or % TSLP
1424 \def\@journalName{ACM Transactions on Speech and Language Processing}%
1425 \def\@journalNameShort{ACM Trans. Speech Lang. Process.}%
1426 \def\@permissionCodeOne{1550-4875}%
1427 \or % TWEB
1428 \def\@journalName{ACM Transactions on the Web}%
1429 \def\@journalNameShort{ACM Trans. Web}%
1430 \def\@permissionCodeOne{1559-1131}%
1431 \else % FACMP, a dummy journal
1432 \def\@journalName{ACM Just Accepted}%
1433 \def\@journalNameShort{ACM Accepted}%
1434 \def\@permissionCodeOne{XXXX-XXXX}%
1435 \fi
1436 \ClassInfo{\@classname}{Using journal code \@journalCode}%
1437 }{%
1438 \ClassError{\@classname}{Incorrect journal #1}%
1439 }%

```

`\acmJournal` And the syntactic sugar around it

```
1440 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}%
1441 \global\@ACM@journal@bibstriptrue}
```

The defaults:

```
1442 \def\@journalCode@nr{0}
1443 \def\@journalName{}%
1444 \def\@journalNameShort{\@journalName}%
1445 \def\@permissionCodeOne{XXXX-XXXX}%
1446 \def\@permissionCodeTwo{}%
```

`\acmConference` This is the conference command

```
1447 \newcommand\acmConference[4][{}]{%
1448 \gdef\acmConference@shortname{#1}%
1449 \gdef\acmConference@name{#2}%
1450 \gdef\acmConference@date{#3}%
1451 \gdef\acmConference@venue{#4}%
1452 \ifx\acmConference@shortname\@empty
1453 \gdef\acmConference@shortname{#2}%
1454 \fi
1455 \global\@ACM@journal@bibstripfalse
1456 }
1457 \if@ACM@journal\else
1458 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1459 DC, USA}%
1460 \fi
```

`\acmBooktitle` The book title of the conference:

```
\@acmBooktitle 1461 \def\acmBooktitle#1{\gdef\@acmBooktitle{#1}}
1462 \acmBooktitle{}
1463 \ifx\acmConference@name\@undefined\else
1464 \acmBooktitle{Proceedings of \acmConference@name
1465 \ifx\acmConference@name\acmConference@shortname\else
1466 \ (\acmConference@shortname)\fi}
1467 \fi
```

`\@editorsAbbrev` How to abbreviate editors

```
1468 \def\@editorsAbbrev{(Ed.)}
```

`\@acmEditors` The list of editors

```
1469 \def\@acmEditors{}
```

`\editor` Add a new editor to the list

```
1470 \def\editor#1{\ifx\@acmEditors\@empty
1471 \gdef\@acmEditors{#1}%
1472 \else
1473 \gdef\@editorsAbbrev{(Eds.)}%
1474 \g@addto@macro\@acmEditors{\and#1}%
1475 \fi}
```

`\subtitle` The subtitle macro

```
1476 \def\subtitle#1{\def\@subtitle{#1}}
1477 \subtitle{}
```

`\num@authorgroups` The total number of “groups”. Each group is several authors with the same affiliations(s)
 1478 `\newcount\num@authorgroups`
 1479 `\num@authorgroups=0\relax`

`\num@author` The total number of authors
 1480 `\newcount\num@author`
 1481 `\num@author=0\relax`

`\if@insideauthorgroup` Whether we are continuing an author group
 1482 `\newif\if@insideauthorgroup`
 1483 `\@insideauthorgroupfalse`

`\author` Adding an author to the list of authors and addresses.

Note that we want to typeset the link to the author’s orcid if known. The problem is, we know the orcid only after the author is entered. The trick is based on the idea that `\csname... \endcsname` is `\relax` unless defined. Therefore we typeset authors by the special macro `\csname typeset@author\the\num@author\endcsname`, which is defined by `\orcid` command.

```

1484 \renewcommand\author[2][]{%
1485 \IfSubStr{\detokenize{#2}}{,}{\ClassWarning{\@classname}{Do not put several
1486   authors in the same \string\author\space macro!}}}%
1487 \global\advance\num@author by 1\relax
1488 \if@insideauthorgroup\else
1489   \global\advance\num@authorgroups by 1\relax
1490   \global\@insideauthorgrouptrue
1491 \fi
1492 \ifx\addresses\@empty
1493   \if@ACM@anonymous
1494     \gdef\addresses{\@author{Anonymous Author(s)%
1495       \ifx\@acmSubmissionID\@empty\else\Submission Id:
1496         \@acmSubmissionID\fi}}%
1497     \gdef\authors{Anonymous Author(s)%
1498   \else
1499     \expandafter\gdef\expandafter\addresses\expandafter{%
1500       \expandafter\@author\expandafter{%
1501         \csname typeset@author\the\num@author\endcsname{#2}}}%
1502     \gdef\authors{#2}%
1503   \fi
1504 \else
1505   \if@ACM@anonymous\else
1506     \expandafter\g@addto@macro\expandafter\addresses\expandafter{%
1507       \expandafter\and\expandafter\@author\expandafter{%
1508         \csname typeset@author\the\num@author\endcsname{#2}}}%
1509     \g@addto@macro\authors{\and#2}%
1510   \fi
1511 \fi
1512 \if@ACM@anonymous
1513   \ifx\shortauthors\@empty
1514     \gdef\shortauthors{Anon.
1515       \ifx\@acmSubmissionID\@empty\else Submission Id:
1516         \@acmSubmissionID\fi}%
1517   \fi
1518 \else

```

```

1519 \def\@tempa{#1}%
1520 \ifx\@tempa\@empty
1521 \ifx\shortauthors\@empty
1522 \gdef\shortauthors{#2}%
1523 \else
1524 \g@addto@macro\shortauthors{\and#2}%
1525 \fi
1526 \else
1527 \ifx\shortauthors\@empty
1528 \gdef\shortauthors{#1}%
1529 \else
1530 \g@addto@macro\shortauthors{\and#1}%
1531 \fi
1532 \fi
1533 \fi}

```

`\affiliation` The macro `\affiliation` mimics `\address` from `amsart`. Note that it has an optional argument, which we use differently from `amsart`.

```

1534 \newcommand{\affiliation}[2][{}]{%
1535 \global\@insideauthorgroupfalse
1536 \if@ACM@anonymous\else
1537 \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1538 \fi}

```

`\ACM@affiliation@obeypunctuation` Whether to use the author's punctuation (false by default, which adds American-style address punctuation)

```

1539 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1540 [true]{\ClassError{\@classname}{The option obeypunctuation can be either true or false}}

```

`\additionalaffiliation` Additional affiliations go to footnotes

```

1541 \def\additionalaffiliation#1{\authornote{\@additionalaffiliation{#1}}}

```

`\@additionalaffiliation` Process `\additionalaffiliation` inside `\authornote`

```

1542 \def\@additionalaffiliation#1{\bgroup
1543 \def\position##1{\ignorespaces}%
1544 \def\institution##1{##1\ignorespaces}%
1545 \def\department{\@ifnextchar[{\@department}{\@department[]}}%
1546 \def\@department[##1]##2{\unskip, ##2\ignorespaces}%
1547 \let\streetaddress\position
1548 \let\city\position
1549 \let\state\position
1550 \let\postcode\position
1551 \let\country\position
1552 Also with #1\unskip.\egroup}

```

`\email` The macro `\email` mimics `\email` from `amsart`. Again, it has an optional argument that we do not currently need but keep for possible future use.

```

1553 \renewcommand{\email}[2][{}]{%
1554 \IfSubStr{#2}{,}{\ClassWarning{\@classname}{Do not put several
1555 addresses in the same \string\email\space macro!}}{}%
1556 \if@ACM@anonymous\else
1557 \g@addto@macro\addresses{\email{#1}{#2}}%
1558 \fi}

```

`\orcid` We redefine the command to typeset the current author

```
1559 \def\orcid#1{\unskip\ignorespaces%
1560 \IfBeginWith{#1}{http}{%
1561 \expandafter\gdef\csname
1562 typeset@author\the\num@authors\endcsname##1{%
1563 \href{#1}{##1}}}%
1564 \expandafter\gdef\csname
1565 typeset@author\the\num@authors\endcsname##1{%
1566 \href{https://orcid.org/#1}{##1}}}
```

`\authorsaddresses` Setting up authors' addresses

```
1567 \def\authorsaddresses#1{\def\@authorsaddresses{#1}}
1568 \authorsaddresses{\mkauthorsaddresses}
```

`\@mktranslatedkeywords` We have two argument: the language to typeset keywords and the keywords.

```
1569 \newcommand\@mktranslatedkeywords[2]{\bgroup
1570 \selectlanguage{#1}%
1571 {\@specialsection{keywordsname}%
1572 \noindent#2\par}\egroup}
```

`\@titlenotes` The title notes

```
1573 \def\@titlenotes{}
```

`\titlenote` Adding a note to the title

```
1574 \def\titlenote#1{%
1575 \g@addto@macro\@title{\footnotemark}%
1576 \if@ACM@anonymous
1577 \g@addto@macro\@titlenotes{%
1578 \stepcounter{footnote}\footnotetext{Title note}}%
1579 \else
1580 \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1581 \fi}
```

`\@subtitlenotes` The subtitle notes

```
1582 \def\@subtitlenotes{}
```

`\subtitlenote` Adding a note to the subtitle

```
1583 \def\subtitlenote#1{%
1584 \g@addto@macro\@subtitle{\footnotemark}%
1585 \if@ACM@anonymous
1586 \g@addto@macro\@subtitlenotes{%
1587 \stepcounter{footnote}\footnotetext{Subtitle note}}%
1588 \else
1589 \g@addto@macro\@subtitlenotes{%
1590 \stepcounter{footnote}\footnotetext{#1}}%
1591 \fi}
```

`\@authornotes` The author notes

```
1592 \def\@authornotes{}
```

`\authornote` Adding a note to the author

```
1593 \def\authornote#1{%
1594 \if@ACM@anonymous\else
```

```

1595   \g@addto@macro\addresses{\@authornotemark}%
1596   \g@addto@macro\authornotes{%
1597       \stepcounter{footnote}\footnotetext{#1}}%
1598   \fi}

\authornotemark Adding a footnote mark to the authors
1599 \newcommand\authornotemark[1][\relax]{%
1600   \ifx#1\relax\relax\relax
1601   \g@addto@macro\addresses{\@authornotemark}%
1602   \else
1603   \g@addto@macro\addresses{\@authornotemark{#1}}%
1604   \fi}

\acmVolume The current volume
1605 \def\acmVolume#1{\def\@acmVolume{#1}}
1606 \acmVolume{1}

\acmNumber The current number
1607 \def\acmNumber#1{\def\@acmNumber{#1}}
1608 \acmNumber{1}

\acmArticle The current article
1609 \def\acmArticle#1{\def\@acmArticle{#1}}
1610 \acmArticle{}

\acmArticleSeq The sequence number
1611 \def\acmArticleSeq#1{\def\@acmArticleSeq{#1}}
1612 \acmArticleSeq{\@acmArticle}

\acmYear The current year
1613 \def\acmYear#1{\def\@acmYear{#1}}
1614 \acmYear{\the\year}

\acmMonth The current month
1615 \def\acmMonth#1{\def\@acmMonth{#1}}
1616 \acmMonth{\the\month}

\@acmPubDate The publication date
1617 \def\@acmPubDate{\ifcase\@acmMonth\or
1618   January\or February\or March\or April\or May\or June\or
1619   July\or August\or September\or October\or November\or
1620   December\fi~\@acmYear}

\acmPrice The price
1621 \def\acmPrice#1{\def\@acmPrice{#1}}
1622 \acmPrice{15.00}

\acmSubmissionID The submission ID
1623 \def\acmSubmissionID#1{\def\@acmSubmissionID{#1}}
1624 \acmSubmissionID{}

\acmISBN The book ISBN
1625 \def\acmISBN#1{\def\@acmISBN{#1}}
1626 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}

```

```

\acmDOI The paper DOI
1627 \def\acmDOI#1{\def\@acmDOI{#1}}
1628 \acmDOI{10.1145/nnnnnnn.nnnnnnn}

\if@ACM@badge

\@ACM@badge@width The width of the badge
1629 \newlength\@ACM@badge@width
1630 \setlength\@ACM@badge@width{3pc}

\@ACM@title@width The width of the title
1631 \newlength\@ACM@title@width

\@ACM@badge@skip The spacing between badges
1632 \newlength\@ACM@badge@skip
1633 \setlength\@ACM@badge@skip{1pt}

\@acmBadgeR
1634 \def\@acmBadgeR{}

\@acmBadgeL
1635 \def\@acmBadgeL{}

\acmBadgeR Setting the right badge
1636 \newcommand\acmBadgeR[2][{}]{%
1637 \ifx\@acmBadgeR\@empty
1638 \gdef\@acmBadgeR{%
1639 \smash{%
1640 \raisebox{0.5\height}{%
1641 \href{#1}{\includegraphics[width=\@ACM@badge@width]{#2}}}}}%
1642 \else
1643 \g@addto@macro{\@acmBadgeR}{%
1644 \hspace{\@ACM@badge@skip}%
1645 \smash{%
1646 \raisebox{0.5\height}{%
1647 \href{#1}{\includegraphics[width=\@ACM@badge@width]{#2}}}}}}}%
1648 \fi}

\acmBadgeL Setting the left badge
1649 \newcommand\acmBadgeL[2][{}]{%
1650 \ifx\@acmBadgeL\@empty
1651 \gdef\@acmBadgeL{%
1652 \smash{%
1653 \raisebox{0.5\height}{%
1654 \href{#1}{\includegraphics[width=\@ACM@badge@width]{#2}}}}}}}%
1655 \else
1656 \g@addto@macro{\@acmBadgeL}{%
1657 \hspace{\@ACM@badge@skip}%
1658 \smash{%
1659 \raisebox{0.5\height}{%
1660 \href{#1}{\includegraphics[width=\@ACM@badge@width]{#2}}}}}}}%
1661 \fi}

```

`\acmBadge` Just a syntax sugar for `\acmBadgeR`

```
1662 \let\acmBadge=\acmBadgeR
```

`\startPage` The start page of the paper

```
1663 \def\startPage#1{\def\@startPage{#1}}
1664 \startPage{}
```

`\terms` Terms are obsolete. We use CCS now.

```
1665 \def\terms#1{\ClassWarning{\@classname}{The command \string\terms{} is
1666   obsolete. I am going to ignore it}}
```

`\keywords` Keywords are mostly obsolete. We use CCS now. Still it makes sense to keep them for compatibility.

```
1667 \def\keywords#1{\def\@keywords{#1}}
1668 \let\@keywords\@empty

1669 \AtEndDocument{\if@ACM@nonacm\else\ifx\@keywords\@empty
1670   \ifnum\getrefnumber{TotPages}>2\relax
1671   \ClassWarningNoLine{\@classname}{ACM keywords are mandatory
1672     for papers over two pages}%
1673   \fi\fi\fi}
```

`abstract` The `amsart` package puts `abstract` in a box. Since we do not know whether we will use two-column mode, we prefer to save the text

```
1674 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{}
```

`\@saveabstract` And saving the abstract

```
1675 \long\def\@saveabstract#1{\if@ACM@maketitle@typeset
1676   \ClassError{\@classname}{Abstract must be defined before maketitle
1677     command. Please move it!}\fi
1678   \long\gdef\@abstract{#1}}
1679 \@saveabstract{}
```

`\@empty` The long version of `\@empty` (to compare with `\@abstract`)

```
1680 \long\def\@empty{}
```

`\if@ACM@printccs` Whether to print CCS

```
1681 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printccs}[true]{%
1682   \if@ACM@printccs
1683     \ClassInfo{\@classname}{Printing CCS}%
1684   \else
1685     \ClassInfo{\@classname}{Suppressing CCS}%
1686   \fi}{\ClassError{\@classname}{The option printccs can be either true or false}}
```

`\if@ACM@printacmref` Whether to print the ACM bibstrip

```
1687 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%
1688   \if@ACM@printacmref
1689     \ClassInfo{\@classname}{Printing bibformat}%
1690   \else
1691     \ClassInfo{\@classname}{Suppressing bibformat}%
1692   \fi}{\ClassError{\@classname}{The option printacmref can be either true or false}}
```

```

1693 \AtEndDocument{\if@ACM@nonacm\else\if@ACM@printacmref\else
1694 \ifnum\getrefnumber{TotPages}>1\relax
1695 \ClassWarningNoLine{\@classname}{%
1696   ACM reference format is mandatory \MessageBreak
1697   for papers over one page. \MessageBreak
1698   Please add printacmref=true to the \MessageBreak
1699   \string\settopmatter\space command.}%
1700 \fi\fi\fi}

```

`\if@ACM@printfolios` Whether to print folios

```

1701 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%
1702 \if@ACM@printfolios
1703   \ClassInfo{\@classname}{Printing folios}%
1704 \else
1705   \ClassInfo{\@classname}{Suppressing folios}%
1706 \fi}{\ClassError{\@classname}{The option printfolios can be either true or false}}

```

`\@ACM@authorssperrow` The number of authors per row. 0 means use the default algorithm.

```

1707 \define@cmdkey{@ACM@topmatter@}[@ACM@]{authorssperrow}[0]{%
1708 \IfInteger{#1}{\ClassInfo{\@classname}{Setting authorssperrow to
1709   #1}}{\ClassWarning{\@classname}{The parameter authorssperrow must be
1710   numerical. Ignoring the input #1}\gdef\@ACM@authorssperrow{0}}}

```

`\settopmatter` The usual syntactic sugar

```

1711 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}

```

Now the settings

```

1712 \settopmatter{printccs=true, printacmref=true}
1713 \if@ACM@manuscript
1714   \settopmatter{printfolios=true}
1715 \else
1716   \if@ACM@journal
1717     \settopmatter{printfolios=true}
1718   \else
1719     \settopmatter{printfolios=false}
1720 \fi
1721 \fi
1722 \settopmatter{authorssperrow=0}

```

`\@received` The container for the paper history

```

1723 \def\@received{}

```

`\received` The `\received` command

```

1724 \newcommand\received[2][\def\@tempa{#1}%
1725 \ifx\@tempa\@empty
1726   \ifx\@received\@empty
1727     \gdef\@received{Received #2}%
1728   \else
1729     \g@addto@macro{\@received}{; revised #2}%
1730   \fi
1731 \else
1732   \ifx\@received\@empty
1733     \gdef\@received{#1 #2}%

```

```

1734 \else
1735 \g@addto@macro{\@received}{; #1 #2}%
1736 \fi
1737 \fi}
1738 \AtEndDocument{%
1739 \ifx\@received\@empty\else
1740 \par\bigskip\noindent\small\normalfont\@received\par
1741 \fi}

```

\acmArticleType Article type. We set up the color.

```

1742 \define@choicekey+{ACM}{articletype}[\ACM@ArticleType\ACM@ArticleType@nr]{%
1743 Research,Review,Discussion,Invited,Position}[Review]{%
1744 \ifcase\ACM@ArticleType@nr
1745 \relax % Research
1746 \colorlet{@ACM@Article@color}{ACMBlue}%
1747 \or % Review
1748 \colorlet{@ACM@Article@color}{ACMOrange}%
1749 \or % Discussion
1750 \colorlet{@ACM@Article@color}{ACMGreen}%
1751 \or % Invited
1752 \colorlet{@ACM@Article@color}{ACMPurple}%
1753 \or % Position
1754 \colorlet{@ACM@Article@color}{ACMRed}%
1755 \fi
1756 }{%
1757 \ClassError{\@classname}{Article Type must be Research, Review,\MessageBreak
1758 Discussion, Invited, or Position}}
1759 \def\acmArticleType#1{\setkeys{ACM}{articletype=#1}}
1760 \if@ACM@acmcp
1761 \acmArticleType{Research}%
1762 \fi
1763

```

\@ACM@color@frame The colored frame for the acmcp

```

1764 \newenvironment{@ACM@color@frame}{%
1765 \def\FrameCommand{\hspace*{-6.5pc}}%
1766 \colorbox{@ACM@Article@color!10!white}}%
1767 \MakeFramed {\advance\hsize
1768 -6.5pc\relax\FrameRestore}}{\zsavesposy{@ACM@acmcpframe@y}}%
1769 \endMakeFramed}

```

\acmCodeLink The code link

```

1770 \def\acmCodeLink#1{%
1771 \ifx\@acmCodeDataLink\@empty
1772 \gdef\@acmCodeDataLink{\url{#1}}%
1773 \else
1774 \g@addto@macro{\@acmCodeDataLink}{\ \url{#1}}%
1775 \fi}
1776 \def\@acmCodeDataLink{}

```

\acmDataLink The code link

```

1777 \let\acmDataLink\acmCodeLink

```

3.17 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```
1778 \RequirePackage{comment}
1779 \excludecomment{CCSXML}
```

`\@concepts` This is the storage macro and counter for concepts

```
1780 \let\@concepts\@empty
1781 \newcounter{@concepts}
```

`\ccsdesc` The first argument is the significance, the second is the concept(s)

```
1782 \newcommand\ccsdesc[2][100]{%
1783 \ccsdesc@parse#1~#2~\ccsdesc@parse@end}
```

`\ccsdesc@parse` The parser of the expression Significance~General~Specific (we need `textcomp` for `\textrightarrow`). Note that Specific can be empty!

```
1784 \def\textrightarrow{\rightarrow}
1785 \def\ccsdesc@parse#1~#2~#3~{%
1786 \stepcounter{@concepts}%
1787 \expandafter\ifx\csname CCS@General@#2\endcsname\relax
1788 \expandafter\gdef\csname CCS@General@#2\endcsname{\textbullet\
1789 \textbf{#2}}%
1790 \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{; }%
1791 \expandafter\gdef\csname CCS@Specific@#2\endcsname{}%
1792 \g@addto@macro{\@concepts}{\csname CCS@General@#2\endcsname
1793 \csname CCS@Punctuation@#2\endcsname
1794 \csname CCS@Specific@#2\endcsname}%
1795 \fi
1796 \ifx#3\relax\relax\else
1797 \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{
1798 \textrightarrow\ }%
1799 \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@#2\endcsname}{%
1800 \addtocounter{@concepts}{-1}%
1801 \ifnum#1>499\textbf{#3}\else
1802 \ifnum#1>299\textit{#3}\else
1803 #3\fi\fi\ifnum\value{@concepts}=0.\else; \fi}%
1804 \fi
1805 \ccsdesc@parse@finish}
```

```
1806 \AtEndDocument{\if@ACM@nonacm\else\ifx\@concepts\@empty\relax
1807 \ifnum\getrefnumber{TotPages}>2\relax
1808 \ClassWarningNoLine{\@classname}{CCS concepts are mandatory
1809 for papers over two pages}%
1810 \fi\fi\fi}
```

`\ccsdesc@parse@finish` Gobble everything to `\ccsdesc@parse@end`

```
1811 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}
```

3.18 Copyright system

This is from `acmcopyright.sty`

`\if@printcopyright` Whether to print a copyright symbol

```
1812 \newif\if@printcopyright
1813 \@printcopyrighttrue
```

`\if@printpermission` Whether to print the permission block

```
1814 \newif\if@printpermission
1815 \@printpermissiontrue
```

`\if@acmowned` Whether the ACM owns the rights to the paper

```
1816 \newif\if@acmowned
1817 \@acmownedtrue
```

Keys:

```
1818 \define@choicekey*{ACM@}{acmcopyrightmode}[%
1819 \acm@copyrightinput\acm@copyrightmode]{none,%
1820 acmcopyright,acmlicensed,rightsretained,%
1821 usgov,usgovmixed,cagov,cagovmixed,licensedusgovmixed,%
1822 licensedcagov,licensedcagovmixed,othergov,licensedothergov,%
1823 iw3c2w3,iw3c2w3g,cc}{%
1824 \@printpermissiontrue
1825 \@printcopyrighttrue
1826 \@acmownedtrue
1827 \ifnum\acm@copyrightmode=0\relax % none
1828 \@printpermissionfalse
1829 \@printcopyrightfalse
1830 \@acmownedfalse
1831 \fi
1832 \ifnum\acm@copyrightmode=2\relax % acmlicensed
1833 \@acmownedfalse
1834 \fi
1835 \ifnum\acm@copyrightmode=3\relax % rightsretained
1836 \@acmownedfalse
1837 \AtBeginDocument{\acmPrice{}}%
1838 \fi
1839 \ifnum\acm@copyrightmode=4\relax % usgov
1840 \@printpermissiontrue
1841 \@printcopyrightfalse
1842 \@acmownedfalse
1843 \AtBeginDocument{\acmPrice{}}%
1844 \fi
1845 \ifnum\acm@copyrightmode=6\relax % cagov
1846 \@acmownedfalse
1847 \fi
1848 \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1849 \@acmownedfalse
1850 \fi
1851 \ifnum\acm@copyrightmode=9\relax % licensedcagov
1852 \@acmownedfalse
1853 \fi
1854 \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1855 \@acmownedfalse
1856 \fi
1857 \ifnum\acm@copyrightmode=11\relax % othergov
1858 \@acmownedtrue
1859 \fi
1860 \ifnum\acm@copyrightmode=12\relax % licensedothergov
1861 \@acmownedfalse
1862 \fi
```

```

1863 \ifnum\acm@copyrightmode=13\relax % iw3c2w3
1864 \@acmownedfalse
1865 \AtBeginDocument{\acmPrice{}}%
1866 \fi
1867 \ifnum\acm@copyrightmode=14\relax % iw3c2w3g
1868 \@acmownedfalse
1869 \AtBeginDocument{\acmPrice{}}%
1870 \fi
1871 \ifnum\acm@copyrightmode=15\relax % cc
1872 \@acmownedfalse
1873 \AtBeginDocument{\acmPrice{}}%
1874 \fi}

```

`\setcopyright` This is the syntactic sugar around setting keys.

```

1875 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1876 \setcopyright{acmcopyright}

```

`\setcctype` The type of Creative Commons license used

```

1877 \newcommand\setcctype[2][4.0]{%
1878 \def\ACM@cc@version{#1}%
1879 \def\ACM@cc@type{#2}}
1880 \setcctype{by}

```

`\@copyrightowner` Here is the owner of the copyright

```

1881 \def\@copyrightowner{%
1882 \ifcase\acm@copyrightmode\relax % none
1883 \or % acmcopyright
1884 Association for Computing Machinery.
1885 \or % acmlicensed
1886 Copyright held by the owner/author(s). Publication rights licensed to
1887 ACM\@.
1888 \or % rightsretained
1889 Copyright held by the owner/author(s).
1890 \or % usgov
1891 \or % usgovmixed
1892 Association for Computing Machinery.
1893 \or % cagov
1894 Crown in Right of Canada.
1895 \or %cagovmixed
1896 Association for Computing Machinery.
1897 \or %licensedusgovmixed
1898 Copyright held by the owner/author(s). Publication rights licensed to
1899 ACM\@.
1900 \or % licensedcagov
1901 Crown in Right of Canada. Publication rights licensed to
1902 ACM\@.
1903 \or %licensedcagovmixed
1904 Copyright held by the owner/author(s). Publication rights licensed to
1905 ACM\@.
1906 \or % othergov
1907 Association for Computing Machinery.
1908 \or % licensedothergov
1909 Copyright held by the owner/author(s). Publication rights licensed to
1910 ACM\@.

```

```

1911 \or % ic2w3www
1912 IW3C2 (International World Wide Web Conference Committee), published
1913 under Creative Commons CC-BY~4.0 License.
1914 \or % ic2w3wwwgoogle
1915 IW3C2 (International World Wide Web Conference Committee), published
1916 under Creative Commons CC-BY-NC-ND~4.0 License.
1917 \or % cc
1918 Copyright held by the owner/author(s).
1919 \fi}

```

`\@formatdoi` Print a clickable DOI

```

1920 \def\@formatdoi#1{\url{https://doi.org/#1}}

```

`\@ACM@copyright@check@cc` At present cC licenses can be used only for acmengage format or for non-acm stuff. This macro checks whether the CC license is applicable and generates an error if not.

```

1921 \def\@ACM@copyright@check@cc{%
1922   \if@ACM@nonacm
1923     \ClassInfo{\@classname}{Using CC license with a non-acm
1924       material}%
1925   \else
1926     \if@ACM@engage
1927       \ClassInfo{\@classname}{Using CC license with ACM Enage
1928         material}%
1929     \else
1930       \ClassError{\@classname}{%
1931         Sorry, Creative Commons licenses are\MessageBreak
1932         currently not used with ACM publications\MessageBreak
1933         typeset by the authors}{Please use nonacm
1934         option or ACM Engage class to enable CC licenses}%
1935     \fi
1936 \fi}

```

`\@copyrightpermission` The canned permission block.

```

1937 \def\@copyrightpermission{%
1938   \ifcase\acm@copyrightmode\relax % none
1939   \or % acmcopyright
1940     Permission to make digital or hard copies of all or part of this
1941     work for personal or classroom use is granted without fee provided
1942     that copies are not made or distributed for profit or commercial
1943     advantage and that copies bear this notice and the full citation on
1944     the first page. Copyrights for components of this work owned by
1945     others than ACM must be honored. Abstracting with credit is
1946     permitted. To copy otherwise, or republish, to post on servers or to
1947     redistribute to lists, requires prior specific permission
1948     and\hspace*{.5pt}/or a fee. Request permissions from
1949     permissions@acm.org.
1950   \or % acmlicensed
1951     Permission to make digital or hard copies of all or part of this
1952     work for personal or classroom use is granted without fee provided
1953     that copies are not made or distributed for profit or commercial
1954     advantage and that copies bear this notice and the full citation on
1955     the first page. Copyrights for components of this work owned by
1956     others than the author(s) must be honored. Abstracting with credit
1957     is permitted. To copy otherwise, or republish, to post on servers

```

1958 or to redistribute to lists, requires prior specific permission
1959 and\hspace*{.5pt}/or a fee. Request permissions from
1960 permissions@acm.org.
1961 \or % rightsretained
1962 Permission to make digital or hard copies of part or all of this work
1963 for personal or classroom use is granted without fee provided that
1964 copies are not made or distributed for profit or commercial advantage
1965 and that copies bear this notice and the full citation on the first
1966 page. Copyrights for third-party components of this work must be
1967 honored. For all other uses, contact the
1968 owner\hspace*{.5pt}/author(s).
1969 \or % usgov
1970 This paper is authored by an employee(s) of the United States
1971 Government and is in the public domain. Non-exclusive copying or
1972 redistribution is allowed, provided that the article citation is
1973 given and the authors and agency are clearly identified as its
1974 source.
1975 \or % usgovmixed
1976 ACM acknowledges that this contribution was authored or co-authored
1977 by an employee, contractor, or affiliate of the United States
1978 government. As such, the United States government retains a
1979 nonexclusive, royalty-free right to publish or reproduce this
1980 article, or to allow others to do so, for government purposes only.
1981 \or % cagov
1982 This article was authored by employees of the Government of Canada.
1983 As such, the Canadian government retains all interest in the
1984 copyright to this work and grants to ACM a nonexclusive,
1985 royalty-free right to publish or reproduce this article, or to allow
1986 others to do so, provided that clear attribution is given both to
1987 the authors and the Canadian government agency employing them.
1988 Permission to make digital or hard copies for personal or classroom
1989 use is granted. Copies must bear this notice and the full citation
1990 on the first page. Copyrights for components of this work owned by
1991 others than the Canadian Government must be honored. To copy
1992 otherwise, distribute, republish, or post, requires prior specific
1993 permission and\hspace*{.5pt}/or a fee. Request permissions from
1994 permissions@acm.org.
1995 \or % cagovmixed
1996 ACM acknowledges that this contribution was co-authored by an
1997 affiliate of the national government of Canada. As such, the Crown
1998 in Right of Canada retains an equal interest in the copyright.
1999 Reprints must include clear attribution to ACM and the author's
2000 government agency affiliation. Permission to make digital or hard
2001 copies for personal or classroom use is granted. Copies must bear
2002 this notice and the full citation on the first page. Copyrights for
2003 components of this work owned by others than ACM must be honored.
2004 To copy otherwise, distribute, republish, or post, requires prior
2005 specific permission and\hspace*{.5pt}/or a fee. Request permissions
2006 from permissions@acm.org.
2007 \or % licensedusgovmixed
2008 Publication rights licensed to ACM\@. ACM acknowledges that this
2009 contribution was authored or co-authored by an employee, contractor
2010 or affiliate of the United States government. As such, the
2011 Government retains a nonexclusive, royalty-free right to publish or

2012 reproduce this article, or to allow others to do so, for Government
2013 purposes only.

2014 \or % licensedcagov

2015 This article was authored by employees of the Government of Canada.
2016 As such, the Canadian government retains all interest in the
2017 copyright to this work and grants to ACM a nonexclusive,
2018 royalty-free right to publish or reproduce this article, or to allow
2019 others to do so, provided that clear attribution is given both to
2020 the authors and the Canadian government agency employing them.
2021 Permission to make digital or hard copies for personal or classroom
2022 use is granted. Copies must bear this notice and the full citation
2023 on the first page. Copyrights for components of this work owned by
2024 others than the Canadian Government must be honored. To copy
2025 otherwise, distribute, republish, or post, requires prior specific
2026 permission and\hspace*{.5pt}/or a fee. Request permissions from
2027 permissions@acm.org.

2028 \or % licensedcagovmixed

2029 Publication rights licensed to ACM\@. ACM acknowledges that this
2030 contribution was authored or co-authored by an employee, contractor
2031 or affiliate of the national government of Canada. As such, the
2032 Government retains a nonexclusive, royalty-free right to publish or
2033 reproduce this article, or to allow others to do so, for Government
2034 purposes only.

2035 \or % othergov

2036 ACM acknowledges that this contribution was authored or co-authored
2037 by an employee, contractor or affiliate of a national government. As
2038 such, the Government retains a nonexclusive, royalty-free right to
2039 publish or reproduce this article, or to allow others to do so, for
2040 Government purposes only.

2041 \or % licensedothergov

2042 Publication rights licensed to ACM\@. ACM acknowledges that this
2043 contribution was authored or co-authored by an employee, contractor
2044 or affiliate of a national government. As such, the Government
2045 retains a nonexclusive, royalty-free right to publish or reproduce
2046 this article, or to allow others to do so, for Government purposes
2047 only.

2048 \or % iw3c2w3

2049 This paper is published under the Creative Commons Attribution~4.0
2050 International (CC-BY~4.0) license. Authors reserve their rights to
2051 disseminate the work on their personal and corporate Web sites with
2052 the appropriate attribution.

2053 \or % iw3c2w3g

2054 This paper is published under the Creative Commons
2055 Attribution-NonCommercial-NoDerivs~4.0 International
2056 (CC-BY-NC-ND~4.0) license. Authors reserve their rights to
2057 disseminate the work on their personal and corporate Web sites with
2058 the appropriate attribution.

2059 \or % CC

2060 \@ACM@copyright@check@cc
2061 \IfEq{\ACM@cc@type}{zero}{%
2062 \def\ACM@CC@Url{https://creativecommons.org/publicdomain/zero/1.0/legalcode}}{%
2063 \edef\ACM@CC@Url{https://creativecommons.org/licenses/\ACM@cc@type/\ACM@cc@version/legalcode}}%
2064 \href{\ACM@CC@Url}{\includegraphics[height=5ex]{doclicense-CC-\ACM@cc@type-88x31}}\\
2065 \href{\ACM@CC@Url}{%

```

2066 This work is licensed under a Creative Commons
2067 \IfEq{\ACM@cc@type}{zero}{CC0 1.0 Universal}{%
2068   \IfEq{\ACM@cc@type}{by}{Attribution}{}%
2069   \IfEq{\ACM@cc@type}{by-sa}{Attribution-ShareAlike}{}%
2070   \IfEq{\ACM@cc@type}{by-nd}{Attribution-NoDerivatives}{}%
2071   \IfEq{\ACM@cc@type}{by-nc}{Attribution-NonCommercial}{}%
2072   \IfEq{\ACM@cc@type}{by-nc-sa}{Attribution-NonCommercial-ShareAlike}{}%
2073   \IfEq{\ACM@cc@type}{by-nc-nd}{Attribution-NonCommercial-NoDerivatives}{}%
2074   ~\IfEq{\ACM@cc@version}{4.0}{4.0 International}{3.0 Unported}%
2075 }
2076 License.}%
2077 \fi}

```

`\copyrightyear` By default, the copyright year is the same as `\acmYear`, but one can override this:

```

2078 \def\copyrightyear#1{\def\@copyrightyear{#1}}
2079 \copyrightyear{\@acmYear}

```

`\@teaserfigures` The teaser figures container

```
2080 \def\@teaserfigures{}
```

`teaserfigure` The teaser figure

```
2081 \newenvironment{teaserfigure}{\Collect@Body\@saveteaser}{}

```

`\@saveteaser` Saving the teaser

```
2082 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}
```

`\thanks` We redefine `amsart \thanks` so the anonymous key works

```

2083 \renewcommand{\thanks}[1]{%
2084   \ifnotempty{#1}{%
2085     \if@ACM@anonymous
2086       \g@addto@macro\thankses{\thanks{A note}}%
2087     \else
2088       \g@addto@macro\thankses{\thanks{#1}}%
2089     \fi}}

```

`\anon` We provide `\anon` command, which blinds parts of the text if the package option `anonymous` is set

```

2090 \newcommand{\anon}[2][ANONYMIZED]{%
2091   \if@ACM@anonymous%
2092     {\color{ACMOrange}#1}%
2093   \else%
2094     #2%
2095   \fi}

```

3.19 Maketitle hook

The current \LaTeX provides a nice `lthooks` mechanism. However, since it is relatively new, we will use oldfashioned approach—at least for now.

`\@beginmaketitlehook` The hook

```

2096 \ifx\@beginmaketitlehook\@undefined
2097   \let\@beginmaketitlehook\@empty
2098 \fi

```

`\AtBeginMaketitle` Adding to the hook
2099 `\def\AtBeginMaketitle{\g@addto@macro\@beginmaketitlehook}`

3.20 ACM Engage top matter

`\@acmengagemetadadata` The special metadata for ACM engage course materials
2100 `\def\@acmengagemetadadata{}`

`\setengagemetadadata` Adding topic to engage metadata
2101 `\def\setengagemetadadata#1#2{%`
2102 `\g@addto@macro{\@acmengagemetadadata}{%`
2103 `\setengagemetadadata{#1}{#2}}`

3.21 Typesetting top matter

`\mktitle@bx` Some of our formats use a two-column design. Some use a one-column design. In all cases we use a wide title. Thus we typeset the top matter in a special box to be used in the construction `\@twocolumn[<box>]`.
2104 `\newbox\mktitle@bx`

`\maketitle` The (in)famous `\maketitle`. Note that in sigchi-a mode, authors are *not* in the title box.

Another note: there is a subtle difference between author notes, title notes and thanks. The latter two refer to the paper itself and therefore belong to the copyright/permission block. By the way, this was the default behavior of the old ACM classes.

```
2105 \def\maketitle{\@beginmaketitlehook
2106 \@ACM@maketitle@typesettrue
2107 \if@ACM@anonymous
2108 % Anonymize omission of \author-s
2109 \ifnum\num@authorgroups=0\author{}\fi
2110 \fi
2111 \begingroup
2112 \let\@vspace\@vspace@orig
2113 \let\@vspacer\@vspacer@orig
2114 \let\@footnotemark\@footnotemark@nolink
2115 \let\@footnotetext\@footnotetext@nolink
2116 \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
2117 \hsize=\textwidth
2118 \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
2119 \mktitle\if@ACM@sigchiamode\else\mkauthors\fi\mkteasers
2120 \@printtopmatter
2121 \if@ACM@sigchiamode\mkauthors\fi
2122 \setcounter{footnote}{0}%
2123 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
2124 \@titlenotes
2125 \@subtitlenotes
2126 \@authornotes
2127 \let\@makefnmark\relax
2128 \let\@thefnmark\relax
2129 \let\@makefntext\noindent
2130 \ifx\@empty\thankses\else
2131 \footnotetextauthorsaddresses{%
```

```

2132     \def\par{\let\par\@par}\parindent\z@\@setthanks}%
2133 \fi
2134 \if@ACM@acmcp\else
2135     \ifx\@empty\@authorsaddresses\else
2136         \if@ACM@anonymous\else
2137             \if@ACM@journal@bibstrip
2138                 \footnotetextauthorsaddresses{%
2139                     \def\par{\let\par\@par}\parindent\z@\@setauthorsaddresses}%
2140             \fi
2141         \fi
2142     \fi
2143 \fi
2144 \if@ACM@nonacm
2145     \ifnum\acm@copyrightmode=15\relax % cc
2146         \footnotetextcopyrightpermission{\@copyrightpermission}%
2147     \fi
2148 \else
2149     \if@ACM@acmcp\else
2150         \footnotetextcopyrightpermission{%
2151             \if@ACM@authordraft
2152                 \raisebox{-2ex}[\z@][\z@]{\makebox[0pt][l]{\large\bfseries
2153                     Unpublished working draft. Not for distribution.}}%
2154                 \color[gray]{0.9}%
2155             \fi
2156             \parindent\z@\parskip0.1\baselineskip
2157             \if@ACM@authorversion\else
2158                 \if@printpermission\@copyrightpermission\par\fi
2159             \fi
2160             \if@ACM@manuscript\else
2161                 \if@ACM@journal@bibstrip\else % Print the conference information
2162                     \if@ACM@engage
2163                         {\itshape \@acmBooktitle, \@acmYear.}\par
2164                     \else
2165                         {\itshape \acmConference@shortname, \acmConference@date, \acmConference@venue}\par
2166                     \fi
2167                 \fi
2168             \fi
2169             \if@printcopyright
2170                 \copyright\ \@copyrightyear\ \@copyrightowner\
2171             \else
2172                 \@copyrightyear.\
2173             \fi
2174             \if@ACM@manuscript
2175                 Manuscript submitted to ACM\
2176             \else
2177                 \if@ACM@authorversion
2178                     This is the author's version of the work. It is posted here for
2179                     your personal use. Not for redistribution. The definitive Version
2180                     of Record was published in
2181                     \if@ACM@journal@bibstrip
2182                         \emph{\@journalName}%
2183                     \else
2184                         \emph{\@acmBooktitle}%
2185                     \fi

```

```

2186         \ifx\@acmDOI\@empty
2187         .
2188         \else
2189         , \@formatdoi{\@acmDOI}.
2190         \fi\
2191     \else
2192     \if@ACM@nonacm\else
2193     \if@ACM@journal@bibstrip
2194     \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
2195     \ifx\@acmPrice\@empty\else\ $\@acmPrice\fi\
2196     \@formatdoi{\@acmDOI}%
2197     \else % Conference
2198     \ifx\@acmISBN\@empty\else ACM~ISBN~\@acmISBN
2199     \ifx\@acmPrice\@empty.\else\dots\$\@acmPrice\fi\fi
2200     \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi%
2201     \fi
2202     \fi
2203     \fi
2204     \fi}%
2205     \fi
2206     \fi
2207 \endgroup
2208 \if@ACM@engage\@typesetengagemetadata\fi
2209 \setcounter{footnote}{0}%
2210 \@mkabstract
2211 \ifx\@translatedabstracts\@empty\else
2212 \@translatedabstracts\fi
2213 \if@ACM@printccs
2214 \ifx\@concepts\@empty\else\bgroup
2215     {\@specialsection{CCS Concepts}%
2216     \noindent\@concepts\par}\egroup
2217     \fi
2218     \fi
2219     \if@ACM@acmcp\else
2220     \ifx\@keywords\@empty\else\bgroup
2221     {\@specialsection{\@keywordsname}%
2222     \noindent\@keywords\par}\egroup
2223     \fi
2224     \ifx\@translatedkeywords\@empty\else
2225     \@translatedkeywords
2226     \fi
2227     \fi
2228     \let\metadata@authors=\authors
2229     \nxandlist{, }, }, }metadata@authors
2230     \def\@ACM@checkaffil{}%
2231     \hypersetup{%
2232     pdfauthor={\metadata@authors},
2233     pdftitle={\@title},
2234     pdfsubject={\@concepts},
2235     pdfkeywords={\@keywords},
2236     pdfcreator={LaTeX with acmart
2237     \csname ver@acmart.cls\endcsname\space
2238     and hyperref
2239     \csname ver@hyperref.sty\endcsname}}%

```

```

2240 \andify\authors
2241 \andify\shortauthors
2242 \global\let\authors=\authors
2243 \global\let\shortauthors=\shortauthors
2244 \if@ACM@printacmref
2245   \mkbibcitation
2246 \fi
2247 \global\@topnum\z@ % this prevents floats from falling
2248                   % at the top of page 1
2249 \global\@botnum\z@ % we do not want them to be on the bottom either
2250 \@printendtopmatter
2251 \@afterindentfalse
2252 \@afterheading
2253 \if@ACM@acmcp
2254   \set@ACM@acmcpbox
2255   \AtEndDocument{\end@ACM@color@frame}%
2256   \@ACM@color@frame
2257 \fi
2258 }

```

\set@ACM@acmcpbox Setting infobox for acmcp

```

2259 \newbox\@ACM@acmcpbox
2260 \def\set@ACM@acmcpbox{%
2261   \bgroup
2262   \hsize=5pc
2263   \global\setbox\@ACM@acmcpbox=\vbox{%
2264     \setlength{\parindent}{\z@}%
2265     {\includegraphics[width=\hsize]{acm-jdslogo}\par}%
2266     \scriptsize
2267     \ifnum\getrefnumber{TotPages}>1\else
2268       \zrefused{@ACM@acmcpbox@y}%
2269       \zrefused{@ACM@acmcpframe@y}%
2270       \@tempdima=\dimexpr\zposy{@ACM@acmcpbox@y}sp -
2271       \zposy{@ACM@acmcpframe@y}sp+0.3\FrameSep+
2272       \@ACM@acmcp@delta\relax
2273       \ifdim\@tempdima>0pt\relax
2274         \vspace*{\@tempdima}%
2275         \protected@write\@auxout{%
2276           {\string\global\@ACM@acmcp@delta=\the\@tempdima\relax}%
2277         \fi
2278       \fi
2279       \ifx\@acmCodeDataLink\@empty\else\bigskip
2280       Code and data links:\\ \@acmCodeDataLink\par\bigskip
2281       \fi
2282       \ifx\@keywords\@empty\else\bigskip
2283       Keywords: \@keywords\par
2284       \fi
2285       \ifx\@empty\@authorsaddresses\else\bigskip\setauthorsaddresses\fi
2286       \zsaveposy{@ACM@acmcpbox@y}%
2287   }
2288 \egroup}

```

\@specialsection This macro starts sections for proceedings and uses \small for journals

```

2289 \def\@specialsection#1{%

```

```

2290 \let\@vspace\@vspace@orig
2291 \let\@vspacer\@vspacer@orig
2292 \ifcase\ACM@format@nr
2293 \relax % manuscript
2294 \par\medskip\small\noindent#1: %
2295 \or % acmsmall
2296 \par\medskip\small\noindent#1: %
2297 \or % acmlarge
2298 \par\medskip\small\noindent#1: %
2299 \or % acmtog
2300 \par\medskip\small\noindent#1: %
2301 \or % sigconf
2302 \section*{#1}%
2303 \or % siggraph
2304 \section*{#1}%
2305 \or % sigplan
2306 \noindentparagraph*{#1:~}%
2307 \or % sigchi
2308 \section*{#1}%
2309 \or % sigchi-a
2310 \section*{#1}%
2311 \or % acmengage
2312 \section*{#1}%
2313 \or % acmcp
2314 \section*{#1}%
2315 \fi
2316 \let\@vspace\@vspace@acm
2317 \let\@vspacer\@vspacer@acm
2318 }

```

`\@printtopmatter` The printing of top matter starts a new page and uses the given title box.

Note that if there are too many authors, `\mktitle@bx` might overflow the page. Therefore we start with checking this and if this happens, we split the box and print it page by page.

```

2319 \def\@printtopmatter{%
2320 \ifx\@startPage\@empty
2321 \gdef\@startPage{1}%
2322 \else
2323 \setcounter{page}{\@startPage}%
2324 \fi
2325 \@tempdima=\ht\mktitle@bx
2326 \advance\@tempdima by \dp\mktitle@bx
2327 \ifdim\@tempdima>0.9\textheight
2328 \loop
2329 \setbox\@tempboxa=\vsplit \mktitle@bx to 0.9\textheight
2330 \thispagestyle{firstpagestyle}%
2331 \noindent\unvbox\@tempboxa
2332 \clearpage
2333 \@tempdima=\ht\mktitle@bx
2334 \advance\@tempdima by \dp\mktitle@bx
2335 \ifdim\@tempdima>0.9\textheight\repeat
2336 \fi
2337 \thispagestyle{firstpagestyle}%
2338 \noindent

```

```

2339 \ifcase\ACM@format@nr
2340 \relax % manuscript
2341   \box\mktitle@bx\par
2342 \or % acmsmall
2343   \box\mktitle@bx\par
2344 \or % acmlarge
2345   \box\mktitle@bx\par
2346 \or % acmtog
2347   \twocolumn[\box\mktitle@bx]%
2348 \or % sigconf
2349   \twocolumn[\box\mktitle@bx]%
2350 \or % siggraph
2351   \twocolumn[\box\mktitle@bx]%
2352 \or % sigplan
2353   \twocolumn[\box\mktitle@bx]%
2354 \or % sigchi
2355   \twocolumn[\box\mktitle@bx]%
2356 \or % sigchi-a
2357   \par\box\mktitle@bx\par\bigskip
2358 \or % acmengage
2359   \twocolumn[\box\mktitle@bx]%
2360 \or % acmcp
2361   \box\mktitle@bx\par
2362 \fi
2363 }

```

\@mktitle The title of the article

```

2364 \def\@mktitle{%
2365   \ifcase\ACM@format@nr
2366   \relax % manuscript
2367     \@mktitle@i
2368 \or % acmsmall
2369     \@mktitle@i
2370 \or % acmlarge
2371     \@mktitle@i
2372 \or % acmtog
2373     \@mktitle@i
2374 \or % sigconf
2375     \@mktitle@iii
2376 \or % siggraph
2377     \@mktitle@iii
2378 \or % sigplan
2379     \@mktitle@iii
2380 \or % sigchi
2381     \@mktitle@iii
2382 \or % sigchi-a
2383     \@mktitle@iv
2384 \or % acmengage
2385     \@mktitle@iii
2386 \or % acmcp
2387     \@mktitle@i
2388 \fi
2389 }

```

`\@titlefont` The font to typeset the title

```
2390 \def\@titlefont{%
2391   \ifcase\ACM@format@nr
2392   \relax % manuscript
2393   \LARGE\sffamily\bfseries
2394   \or % acmsmall
2395   \LARGE\sffamily\bfseries
2396   \or % acmlarge
2397   \LARGE\sffamily\bfseries
2398   \or % acmtog
2399   \Huge\sffamily
2400   \or % sigconf
2401   \Huge\sffamily\bfseries
2402   \or % siggraph
2403   \Huge\sffamily\bfseries
2404   \or % sigplan
2405   \Huge\bfseries
2406   \or % sigchi
2407   \Huge\sffamily\bfseries
2408   \or % sigchi-a
2409   \Huge\bfseries
2410   \or % acmengage
2411   \Huge\sffamily\bfseries
2412   \or % acmcp
2413   \LARGE\sffamily\bfseries
2414   \fi}
```

`\@subtitlefont` The font to typeset the subtitle

```
2415 \def\@subtitlefont{\normalsize
2416   \ifcase\ACM@format@nr
2417   \relax % manuscript
2418   \mdseries
2419   \or % acmsmall
2420   \mdseries
2421   \or % acmlarge
2422   \mdseries
2423   \or % acmtog
2424   \LARGE
2425   \or % sigconf
2426   \LARGE\mdseries
2427   \or % siggraph
2428   \LARGE\mdseries
2429   \or % sigplan
2430   \LARGE\mdseries
2431   \or % sigchi
2432   \LARGE\mdseries
2433   \or % sigchi-a
2434   \mdseries
2435   \or % acmengage
2436   \LARGE\mdseries
2437   \or % acmcp
2438   \mdseries
2439   \fi}
```

`\mktitle@i` The version of `\mktitle` for most journals

```
2440 \def\mktitle@i{\hsize=\textwidth
2441 \if@ACM@acmcp
2442 \advance\hsize by -6pc%
2443 \fi
2444 \@ACM@title@width=\hsize
2445 \setbox\mktitle@bx=\vbox{\noindent\@titlefont
2446 \parbox[t]{\@ACM@title@width}{\raggedright
2447 \@titlefont\noindent
2448 \@title\@translatedtitle%
2449 \ifx\@subtitle\@empty\else
2450 \par\noindent{\@subtitlefont\@subtitle\@translatedsubtitle}%
2451 \fi}%
2452 \par\bigskip}}%
```

`\mktitle@ii` The version of `\mktitle` for TOG. Since v1.06, this is subsumed by the `\mktitle@i` macro

`\mktitle@iii` The version of `\mktitle` for SIG proceedings.

```
2453 \def\mktitle@iii{\hsize=\textwidth
2454 \setbox\mktitle@bx=\vbox{\@titlefont\centering
2455 \@ACM@title@width=\hsize
2456 \parbox[t]{\@ACM@title@width}{\centering\@titlefont
2457 \@title\@translatedtitle%
2458 \ifx\@subtitle\@empty\else
2459 \par\noindent{\@subtitlefont\@subtitle\@translatedsubtitle}
2460 \fi
2461 }%
2462 \par\bigskip}}%
```

`\mktitle@iv` The version of `\mktitle` for sigchi-a

```
2463 \def\mktitle@iv{\hsize=\textwidth
2464 \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
2465 \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
2466 \noindent\@title\@translatedtitle%
2467 \ifx\@subtitle\@empty\else
2468 \par\noindent\@subtitlefont\@subtitle\@translatedsubtitle%
2469 \fi
2470 \par\bigskip}}%
```

`\@ACM@addtoaddress` This macro adds an item to the address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted if it is at the end of a line. We use the magic `\cleaders` trick for this.

```
2471 \newbox\@ACM@commabox
2472 \def\@ACM@addtoaddress#1{%
2473 \ifvmode\else
2474 \if@ACM@affiliation@obeypunctuation\else
2475 \setbox\@ACM@commabox=\hbox{, }%
2476 \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
```

```

2477 \fi\fi
2478 #1}

\institution Theoretically we can define the macros for \affiliation inside the \mkauthors-style
\position commands. However, this would lead to a strange error if an author uses them outside
\department \affiliation. Of course we can make them produce an error message, but...
\streetaddress 2479 \def\streetaddress#1{\unskip\ignorespaces}
\city 2480 \def\postcode#1{\unskip\ignorespaces}
\state 2481 \if@ACM@journal
\postcode 2482 \def\position#1{\unskip\ignorespaces}
\country 2483 \def\institution#1{\global\@ACM@instpresenttrue
2484 \unskip~#1\ignorespaces}
2485 \def\city#1{\global\@ACM@citypresenttrue\unskip\ignorespaces}
2486 \def\state#1{\unskip\ignorespaces}
2487 \newcommand\department[2][0]{\unskip\ignorespaces}
2488 \def\country#1{\StrDel{#1}{ }[\@tempa]%
2489 \ifx\@tempa\empty\else
2490 \global\@ACM@countrypresenttrue\fi
2491 \if@ACM@affiliation@obeypunctuation\else, \fi#1\ignorespaces}
2492 \else
2493 \def\position#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
2494 \def\institution#1{\global\@ACM@instpresenttrue
2495 \if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
2496 \newcommand\department[2][0]{\if@ACM@affiliation@obeypunctuation
2497 #2\else#2\par\fi}%
2498 % \def\streetaddress#1{\if@ACM@affiliation@obeypunctuation#1\else#1\par\fi}%
2499 \def\city#1{\global\@ACM@citypresenttrue\@ACM@addtoaddress{#1}}%
2500 \let\state\@ACM@addtoaddress
2501 % \def\postcode#1{\if@ACM@affiliation@obeypunctuation#1\else\unskip\space#1\fi}%
2502 \def\country#1{\global\@ACM@countrypresenttrue\@ACM@addtoaddress{#1}}%
2503 \fi

```

\mkauthors Typesetting the authors

```

2504 \def\mkauthors{\begingroup
2505 \hsize=\textwidth
2506 \ifcase\ACM@format@nr
2507 \relax % manuscript
2508 \mkauthors@i
2509 \or % acsmall
2510 \mkauthors@i
2511 \or % acmlarge
2512 \mkauthors@i
2513 \or % acmtog
2514 \mkauthors@i
2515 \or % sigconf
2516 \mkauthors@iii
2517 \or % siggraph
2518 \mkauthors@iii
2519 \or % sigplan
2520 \mkauthors@iii
2521 \or % sigchi
2522 \mkauthors@iii
2523 \or % sigchi-a
2524 \mkauthors@iv

```

```

2525 \or % acmengage
2526 \mkauthors@iii
2527 \or % acmcp
2528 \mkauthors@i
2529 \fi
2530 \endgroup
2531 }

```

\@authorfont Somehow different conferences use different fonts for author names. Why?

```

2532 \def\@authorfont{\Large\sffamily}

```

\@affiliationfont Font for affiliations

```

2533 \def\@affiliationfont{\normalsize\normalfont}

```

Adjusting fonts for different formats

```

2534 \ifcase\ACM@format@nr
2535 \relax % manuscript
2536 \or % acmsmall
2537 \def\@authorfont{\large\sffamily}
2538 \def\@affiliationfont{\small\normalfont}
2539 \or % acmlarge
2540 \or % acmtog
2541 \def\@authorfont{\LARGE\sffamily}
2542 \def\@affiliationfont{\large}
2543 \or % sigconf
2544 \def\@authorfont{\LARGE}
2545 \def\@affiliationfont{\large}
2546 \or % siggraph
2547 \def\@authorfont{\normalsize\normalfont}
2548 \def\@affiliationfont{\normalsize\normalfont}
2549 \or % sigplan
2550 \def\@authorfont{\Large\normalfont}
2551 \def\@affiliationfont{\normalsize\normalfont}
2552 \or % sigchi
2553 \def\@authorfont{\bfseries}
2554 \def\@affiliationfont{\mdseries}
2555 \or % sigchi-a
2556 \def\@authorfont{\bfseries}
2557 \def\@affiliationfont{\mdseries}
2558 \or % acmengage
2559 \def\@authorfont{\LARGE}
2560 \def\@affiliationfont{\large}
2561 \or % acmcp
2562 \def\@authorfont{\large\sffamily}
2563 \def\@affiliationfont{\small\normalfont}
2564 \fi

```

\@typeset@author@line At this point we have \@currentauthors and \@currentaffiliations. We typeset them in the journal style

```

2565 \def\@typeset@author@line{%
2566 \andify\@currentauthors\par\noindent
2567 \@currentauthors\def\@currentauthors{}%
2568 \ifx\@currentaffiliations\empty\else
2569 \andify\@currentaffiliations

```

```

2570     \unskip, {\@currentaffiliations}\par
2571 \fi
2572 \def\@currentaffiliations{}}

\if@ACM@instpresent Whether the given affiliation has institution
2573 \newif\if@ACM@instpresent
2574 \@ACM@instpresenttrue

\if@ACM@citypresent Whether the given affiliation has city
2575 \newif\if@ACM@citypresent
2576 \@ACM@citypresenttrue

\if@ACM@countrypresent Whether the given affiliation has country
2577 \newif\if@ACM@countrypresent
2578 \@ACM@countrypresenttrue

\@ACM@resetaffil Reset affiliation flags
2579 \def\@ACM@resetaffil{%
2580 \global\@ACM@instpresentfalse
2581 \global\@ACM@citypresentfalse
2582 \global\@ACM@countrypresentfalse
2583 }

\@ACM@checkaffil Check affiliation flags
2584 \def\@ACM@checkaffil{%
2585 \if@ACM@instpresent\else
2586 \ClassWarningNoLine{\@classname}{No institution present for an affiliation}%
2587 \fi
2588 \if@ACM@citypresent\else
2589 \ClassWarningNoLine{\@classname}{No city present for an affiliation}%
2590 \fi
2591 \if@ACM@countrypresent\else
2592 \ClassError{\@classname}{No country present for an affiliation}{ACM
2593 requires each author to indicate their country using country macro.}%
2594 \fi
2595 }

\@mkauthors@i This version is used in most journal formats. Note that \and between authors with the
same affiliation becomes _and_:
2596 \def\@mkauthors@i{%
2597 \def\@currentauthors{}%
2598 \def\@currentaffiliations{}%
2599 \global\let\and\@typeset@author@line
2600 \def\@author##1{%
2601 \ifx\@currentauthors\@empty
2602 \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
2603 \else
2604 \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%
2605 \fi
2606 \gdef\and{}}%
2607 \def\email##1##2{%
2608 \def\affiliation##1##2{%
2609 \def\@tempa{##2}\ifx\@tempa\@empty\else

```

```

2610     \ifx\@currentaffiliations\@empty
2611         \gdef\@currentaffiliations{%
2612             \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2613             \setkeys{@ACM@affiliation@}{##1}%
2614             \@ACM@resetaffil
2615             \@affiliationfont##2\@ACM@checkaffil}%
2616     \else
2617         \g@addto@macro{\@currentaffiliations}{\and
2618             \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2619             \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2620             ##2\@ACM@checkaffil}%
2621     \fi
2622 \fi
2623 \global\let\and\@typeset@author@line}%
2624 \if@ACM@acmcp
2625     \advance\hsize by -6pc%
2626 \fi
2627 \global\setbox\mktitle@bx=\vbox{\noindent\unvbox\mktitle@bx\par\medskip
2628     \noindent\addresses\@typeset@author@line
2629     \par\medskip}%
2630 }

```

`\@mkauthors@ii` The `\@mkauthors@ii` command was the version used in `acmtog`. It is no longer necessary.

`\author@bx` The box to put an individual author in

```
2631 \newbox\author@bx
```

`\author@bx@wd` The width of the author box

```
2632 \newdimen\author@bx@wd
```

`\author@bx@sep` The separation between author boxes

```
2633 \newskip\author@bx@sep
2634 \author@bx@sep=1pc\relax
```

`\@typeset@author@bx` Typesetting the box with authors. Note that in `sigchi-a` the box is not centered.

```

2635 \def\@typeset@author@bx{\bgroup\hsize=\author@bx@wd
2636 \def\and{\par}\normalbaselines
2637 \global\setbox\author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi
2638     \@authorfont\@currentauthors\par\@affiliationfont
2639     \@currentaffiliation}\egroup
2640 \box\author@bx\hspace{\author@bx@sep}%
2641 \gdef\@currentauthors{}}%
2642 \gdef\@currentaffiliation{}}

```

`\@mkauthors@iii` The `sigconf` version. Here we use a centered design with each author in a separate box.

```
2643 \def\@mkauthors@iii{%
```

First, we need to determine the design of the author strip. The boxes are separated by `\author@bx@sep` plus two `\author@bx@sep` margins. This means that each box must be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```

2644 \author@bx@wd=\textwidth\relax
2645 \advance\author@bx@wd by -\author@bx@sep\relax

```

```

2646 \ifnum\@ACM@authorsperrow>0\relax
2647   \divide\author@bx@wd by \@ACM@authorsperrow\relax
2648 \else
2649   \ifcase\num@authorgroups
2650   \relax % 0?
2651   \or % 1=one author per row
2652   \or % 2=two authors per row
2653   \divide\author@bx@wd by \num@authorgroups\relax
2654   \or % 3=three authors per row
2655   \divide\author@bx@wd by \num@authorgroups\relax
2656   \or % 4=two authors per row (!)
2657   \divide\author@bx@wd by 2\relax
2658   \else % three authors per row
2659     \divide\author@bx@wd by 3\relax
2660   \fi
2661 \fi
2662 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

2663 \gdef\@currentauthors{}%
2664 \gdef\@currentaffiliation{}%
2665 \def\@author##1{\ifx\@currentauthors\@empty
2666   \gdef\@currentauthors{\par##1}%
2667 \else
2668   \g@addto@macro\@currentauthors{\par##1}%
2669 \fi
2670 \gdef\and{}}%
2671 \def\@email##1##2{\ifx\@currentaffiliation\@empty
2672   \gdef\@currentaffiliation{\bgroup
2673     \mathchardef\@urlBreakPenalty=10000\nolinkurl{##2}\egroup}%
2674 \else
2675   \g@addto@macro\@currentaffiliation{\par\bgroup
2676     \mathchardef\@urlBreakPenalty=10000\nolinkurl{##2}\egroup}%
2677 \fi}%
2678 \def\@affiliation##1##2{\ifx\@currentaffiliation\@empty
2679   \gdef\@currentaffiliation{%
2680     \setkeys{@ACM@affiliation@}{obypunctuation=false}%
2681     \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2682     ##2\@ACM@checkaffil}%
2683 \else
2684   \g@addto@macro\@currentaffiliation{\par
2685     \setkeys{@ACM@affiliation@}{obypunctuation=false}%
2686     \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2687     ##2\@ACM@checkaffil}%
2688 \fi
2689 \global\let\and\@typeset@author@bx
2690 }%

```

Actual typesetting is done by the \and macro:

```

2691 \hsize=\textwidth
2692 \global\setbox\mktitle@bx=\vbox{\noindent
2693   \unvbox\mktitle@bx\par\medskip\leavevmode
2694   \lineskip=1pc\relax\centering\hspace*{-1em}%
2695   \addresses\let\and\@typeset@author@bx\and\par\bigskip}}

```

\mkauthors@iv The sigchi-a version. We put authors in the main text with no more than 2 authors per line, unless overridden.

```
2696 \def\mkauthors@iv{%
```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{textwidth} - \text{author@bx@sep})/N - \text{author@bx@sep}$, where N is the number of boxes per row.

```
2697 \author@bx@wd=\columnwidth\relax
2698 \advance\author@bx@wd by -\author@bx@sep\relax
2699 \ifnum\@ACM@authorsperrow>0\relax
2700 \divide\author@bx@wd by \@ACM@authorsperrow\relax
2701 \else
2702 \ifcase\num@authorgroups
2703 \relax % 0?
2704 \or % 1=one author per row
2705 \else % 2=two authors per row
2706 \divide\author@bx@wd by 2\relax
2707 \fi
2708 \fi
2709 \advance\author@bx@wd by -\author@bx@sep\relax
```

Now, parsing of \addresses:

```
2710 \gdef\@currentauthors{}%
2711 \gdef\@currentaffiliation{}%
2712 \def\@author##1{\ifx\@currentauthors\@empty
2713 \gdef\@currentauthors{\par##1}%
2714 \else
2715 \g@addto@macro\@currentauthors{\par##1}%
2716 \fi
2717 \gdef\and{}}%
2718 \def\email##1##2{\ifx\@currentaffiliation\@empty
2719 \gdef\@currentaffiliation{\nolinkurl{##2}}%
2720 \else
2721 \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2722 \fi}%
2723 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2724 \gdef\@currentaffiliation{%
2725 \setkeys{@ACM@affiliation@}{obypunctuation=false}%
2726 \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2727 ##2\@ACM@checkaffil}%
2728 \else
2729 \g@addto@macro\@currentaffiliation{\par
2730 \setkeys{@ACM@affiliation@}{obypunctuation=false}%
2731 \setkeys{@ACM@affiliation@}{##1}\@ACM@resetaffil
2732 ##2\@ACM@checkaffil}%
2733 \fi
2734 \global\let\and\@typeset@author@bx}%
2735 %
```

Actual typesetting is done by the \and macro

```
2736 \bgroup\hsize=\columnwidth
2737 \par\raggedright\leftskip=\z@
2738 \lineskip=1pc\noindent
2739 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}
```

`\@mkauthorsaddresses` Typesetting authors' addresses in the footnote style

```
2740 \def\@mkauthorsaddresses{%
2741   \ifnum\@authors>1\relax
2742   Authors' \else Author's \fi
2743   \ifnum\@authorgroups>1\relax
2744   addresses: \else address: \fi
2745   \bgroup
2746   \def\streetaddress##1{\unskip, ##1}%
2747   \def\postcode##1{\unskip, ##1}%
2748   \def\position##1{\unskip\ignorespaces}%
2749   \gdef\@ACM@institution@separator{, }%
2750   \def\institution##1{\unskip\@ACM@institution@separator ##1\gdef\@ACM@institution@separator{ and }}%
2751   \def\city##1{\unskip, ##1}%
2752   \def\state##1{\unskip, ##1}%
2753   \renewcommand\department[2][0]{\unskip\@addpunct, ##2}%
2754   \def\country##1{\unskip, ##1}%
2755   \def\and{\unskip; \gdef\@ACM@institution@separator{, }}%
2756   \def\@author##1{##1}%
2757   \def\email##1##2{\unskip, \nolinkurl{##2}}%
2758   \addresses
2759   \egroup}

2760 \AtEndDocument{\if@ACM@nonacm\else\if@ACM@journal
2761   \ifx\@authorsaddresses\@empty
2762   \ClassWarningNoLine{\@classname}{Authors'
2763     addresses are mandatory for ACM journals}%
2764   \fi\fi\fi}
```

`\@setaddresses` This is an `amsart` macro that we do not need.

```
2765 \def\@setaddresses{}
```

`\@authornotemark` Adding a footnote mark to authors. This version adds a “normal” footnote mark.

```
2766 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}
```

`\@@authornotemark` Adding a footnote mark to authors with a given number

```
2767 \def\@@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}
```

`\@mkteasers` Typesetting the teasers

```
2768 \def\@mkteasers{%
2769   \ifx\@teaserfigures\@empty\else
2770     \def\@teaser##1{\par\bigskip\bgroup
2771       \captionsetup{type=figure}##1\egroup\par}
2772     \global\setbox\mktitle@bx=\vbox{\noindent\unvbox\mktitle@bx\par
2773       \noindent\@Description@presentfalse
2774       \@teaserfigures\par\if@Description@present\else
2775         \global\@undescrbed@imagestrue
2776         \ClassWarning{\@classname}{A possible image without
2777           description}\fi
2778       \medskip}%
2779     \fi}
```

`\@mkabstract` Typesetting the abstract

```
2780 \def\@mkabstract{\bgroup
```

```

2781 \ifx\@abstract\@empty\else
2782 {\phantomsection\addcontentsline{toc}{section}{\abstractname}%
2783 \if@ACM@journal
2784 \everypar{\setbox\z@\lastbox\everypar{}}\small
2785 \else
2786 \section*{\abstractname}%
2787 \fi
2788 \ignorespaces\@abstract\par}%
2789 \fi\egroup}

```

`\@mktranslatedabstract` Typesetting a translated abstract

```

2790 \def\@mktranslatedabstract#1{\selectlanguage{#1}%
2791 \if@ACM@journal
2792 \everypar{\setbox\z@\lastbox\everypar{}}\small
2793 \else
2794 \section*{\abstractname}%
2795 \fi
2796 \ignorespaces}

```

`\@mkbibcitation` Print the bibcitation format

```

2797 \def\@mkbibcitation{\bgroup
2798 \let\@vspace\@vspace@orig
2799 \let\@vspacer\@vspacer@orig
2800 \def\@pages@word{\ifnum\getrefnumber{TotPages}=1\relax page\else pages\fi}%
2801 \def\footnotemark{}%
2802 \def\@unskip{} \ignorespaces}%
2803 \def\footnote{\ClassError{\@classname}{Please do not use footnotes
2804 inside a \string\title{} or \string\author{} command! Use
2805 \string\titlenote{} or \string\authornote{} instead!}}%
2806 \def\@article@string{\ifx\@acmArticle\@empty{\ } \else,
2807 Article~\@acmArticle\ \fi}%
2808 \par\medskip\small\noindent{\bfseries ACM Reference Format:}\par\nobreak
2809 \noindent\bgroup
2810 \def\@unskip{}, \ignorespaces}\authors\egroup. \@acmYear. \@title
2811 \ifx\@subtitle\@empty. \else: \@subtitle. \fi
2812 \if@ACM@nonacm\else
2813 % The 'nonacm' option disables 'printacmref' by default,
2814 % and the present \@mkbibcitation definition is never used
2815 % in this case. The conditional remains useful if the user
2816 % explicitly sets \settopmatter{printacmref=true}.
2817 \if@ACM@journal@bibstrip
2818 \textit{\@journalNameShort}
2819 \@acmVolume, \@acmNumber \@article@string (\@acmPubDate),
2820 \ref{TotPages}~\@pages@word.
2821 \else
2822 In \textit{\@acmBooktitle}%
2823 \ifx\@acmEditors\@empty\textit{.}\else
2824 \andify\@acmEditors\textit{, }\@acmEditors~\@editorsAbbrev.%
2825 \fi\
2826 ACM, New York, NY, USA%
2827 \@article@string\unskip, \ref{TotPages}~\@pages@word.
2828 \fi
2829 \fi
2830 \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi

```

```

2831 \par\egroup}

\@printendtopmatter End the top matter
2832 \def\@printendtopmatter{%
2833 \let\@vspace\@vspace@orig
2834 \let\@vspacer\@vspacer@orig
2835 \par\bigskip
2836 \let\@vspace\@vspace@acm
2837 \let\@vspacer\@vspacer@acm
2838 }

\@setthanks We redefine \setthanks using \long
2839 \def\@setthanks{\long\def\thanks##1{\par##1\@addpunct.}\thankses}

\@setauthorsaddresses
2840 \def\@setauthorsaddresses{\@authorsaddresses\unskip\@addpunct.}

\@typesetengagemetadata Typesetting special metadata for ACM Engage
2841 \def\@typesetengagemetadata{%
2842 \def\@setengagemetadata##1##2{\par\noindent\textbf{##1} ##2\par}%
2843 \@acmengagemetadata}

```

3.22 Headers and Footers

We use fancyhdr for our headers and footers:

```
2844 \RequirePackage{fancyhdr}
```

\ACM@restore@pagestyle The following code by Ross Moore protects against changes by the totpages package:

```

2845 \let\ACM@ps@plain\ps@plain
2846 \let\ACM@ps@myheadings\ps@myheadings
2847 \let\ACM@ps@headings\ps@headings
2848 \def\ACM@restore@pagestyle{%
2849 \let\ps@plain\ACM@ps@plain
2850 \let\ps@myheadings\ACM@ps@myheadings
2851 \let\ps@headings\ACM@ps@headings}
2852 \AtBeginDocument{\ACM@restore@pagestyle}

```

\ACM@linecount@bx This is the box displayed in review mode

```

2853 \if@ACM@review
2854 \newsavebox{\ACM@linecount@bx}
2855 \newlength\ACM@linecount@bxht
2856 \newcount\ACM@linecount
2857 \ACM@linecount\@ne\relax
2858 \def\ACM@mk@linecount{%
2859 \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{\normalfont
2860 \normalfont
2861 \setlength{\ACM@linecount@bxht}{0pt}%
2862 \loop{\color{red}\scriptsize\the\ACM@linecount}\@
2863 \global\advance\ACM@linecount by \@ne
2864 \addtolength{\ACM@linecount@bxht}{\baselineskip}%
2865 \ifdim\ACM@linecount@bxht<\textheight\repeat
2866 {\color{red}\scriptsize\the\ACM@linecount}\hfill
2867 \global\advance\ACM@linecount by \@ne}}}
2868 \fi

```

`\ACM@linecountL` How to display the box on the left

```
2869 \def\ACM@linecountL{%
2870   \if@ACM@review
2871   \ACM@mk@linecount
2872   \begin{picture}(0,0)%
2873     \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2874   \end{picture}%
2875   \fi}
```

`\ACM@linecountR` How to display the box on the right. In one column formats we do not step the numbers.

```
2876 \def\ACM@linecountR{%
2877   \if@ACM@review
2878   \ifcase\ACM@format@nr
2879     \relax % manuscript
2880     \relax
2881     \or % acmsmall
2882     \relax
2883     \or % acmlarge
2884     \relax
2885     \or % acmtog
2886     \ACM@mk@linecount
2887     \or % sigconf
2888     \ACM@mk@linecount
2889     \or % siggraph
2890     \ACM@mk@linecount
2891     \or % sigplan
2892     \ACM@mk@linecount
2893     \or % sigchi
2894     \ACM@mk@linecount
2895     \or % sigchi-a
2896     \ACM@mk@linecount
2897     \or % acmengage
2898     \ACM@mk@linecount
2899     \or % acmcp
2900     \relax
2901   \fi
2902   \begin{picture}(0,0)%
2903     \put(20,-22){\usebox{\ACM@linecount@bx}}%
2904   \end{picture}%
2905   \fi}
```

`\ACM@timestamp` The timestamp system

```
2906 \if@ACM@timestamp
2907 % Subtracting 30 from \time gives us the effect of rounding down despite
2908 % \numexpr rounding to nearest
2909 \newcounter{ACM@time@hours}
2910 \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2911 \newcounter{ACM@time@minutes}
2912 \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2913 \newcommand\ACM@timestamp{%
2914   \footnotesize%
2915   \ifx\@acmSubmissionID\empty\relax\else
2916     Submission ID: \@acmSubmissionID.{ }%
2917   \fi}
```

```

2918 \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2919 \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{. }%
2920 Page \thepage\ of \@startPage--\pageref*{TotPages}.%
2921 }
2922 \fi

```

\@shortauthors Even if the author redefined \@shortauthors, we do not print it in the headers when in anonymous mode:

```

2923 \def\@shortauthors{%
2924 \if@ACM@anonymous
2925 Anon.
2926 \ifx\@acmSubmissionID\@empty\else Submission Id: \@acmSubmissionID\fi
2927 \else\@shortauthors\fi}

```

\@headfootfont The font to typeset header and footer text.

```

2928 \def\@headfootfont{\sffamily\footnotesize}

```

standardpagestyle The page style for all pages but the first one The page style for all pages but the first one

```

2929 \AtBeginDocument{%
2930 \fancypagestyle{standardpagestyle}{%
2931 \fancyhf{}%
2932 \renewcommand{\headrulewidth}{\z@}%
2933 \renewcommand{\footrulewidth}{\z@}%
2934 \def\@acmArticlePage{%
2935 \ifx\@acmArticle\@empty%
2936 \if@ACM@printfolios\thepage\fi%
2937 \else%
2938 \@acmArticle\if@ACM@printfolios:\thepage\fi%
2939 \fi%
2940 }%
2941 \if@ACM@journal@bibstrip
2942 \ifcase\ACM@format@nr
2943 \relax % manuscript
2944 \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2945 \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2946 \fancyhead[RE]{\@shortauthors}%
2947 \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2948 \if@ACM@nonacm\else%
2949 \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}
2950 \fi%
2951 \or % acmsmall
2952 \fancyhead[LE]{\ACM@linecountL\@headfootfont\@acmArticlePage}%
2953 \fancyhead[RO]{\@headfootfont\@acmArticlePage}%
2954 \fancyhead[RE]{\@headfootfont\@shortauthors}%
2955 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2956 \if@ACM@nonacm\else%
2957 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2958 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2959 \fi
2960 \or % acmlarge
2961 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2962 \@acmArticlePage\quad\textbullet\quad\@shortauthors}%
2963 \fancyhead[LO]{\ACM@linecountL}%

```

```

2964 \fancyhead[RO]{\@headfont
2965 \shorttitle\quad\textbullet\quad\@acmArticlePage}%
2966 \if@ACM@nonacm\else%
2967 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2968 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2969 \fi
2970 \or % acmtog
2971 \fancyhead[LE]{\ACM@linecountL\@headfont
2972 \@acmArticlePage\quad\textbullet\quad\@shortauthors}%
2973 \fancyhead[LO]{\ACM@linecountL}%
2974 \fancyhead[RE]{\ACM@linecountR}%
2975 \fancyhead[RO]{\@headfont
2976 \shorttitle\quad\textbullet\quad\@acmArticlePage\ACM@linecountR}%
2977 \if@ACM@nonacm\else%
2978 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2979 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2980 \fi
2981 \else % Proceedings
2982 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2983 \fancyhead[LO]{\ACM@linecountL\@headfont\shorttitle}%
2984 \fancyhead[RE]{\@headfont\@shortauthors\ACM@linecountR}%
2985 \if@ACM@nonacm
2986 \fancyhead[LE]{\ACM@linecountL}%
2987 \fancyhead[RO]{\ACM@linecountR}%
2988 \else%
2989 \if@ACM@engage
2990 \fancyhead[LE]{\ACM@linecountL\@headfont\footnotesize
2991 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi}%
2992 \fancyhead[RO]{\@headfont
2993 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2994 \ACM@linecountR}%
2995 \else
2996 \fancyhead[LE]{\ACM@linecountL\@headfont\footnotesize
2997 \acmConference@shortname,
2998 \acmConference@date, \acmConference@venue}%
2999 \fancyhead[RO]{\@headfont
3000 \acmConference@shortname,
3001 \acmConference@date, \acmConference@venue\ACM@linecountR}%
3002 \fi
3003 \fi
3004 \fi
3005 \else % Proceedings
3006 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
3007 \fancyhead[LO]{\ACM@linecountL\@headfont\shorttitle}%
3008 \fancyhead[RE]{\@headfont\@shortauthors\ACM@linecountR}%
3009 \if@ACM@nonacm
3010 \fancyhead[LE]{\ACM@linecountL}%
3011 \fancyhead[RO]{\ACM@linecountR}%
3012 \else%
3013 \if@ACM@engage
3014 \fancyhead[LE]{\ACM@linecountL\@headfont
3015 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi}%
3016 \fancyhead[RO]{\@headfont
3017 EngageCSEdu. \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi

```

```

3018         \ACM@linecountR}%
3019     \else
3020         \fancyhead[LE]{\ACM@linecountL\@headfootfont
3021             \acmConference@shortname,
3022             \acmConference@date, \acmConference@venue}%
3023         \fancyhead[RO]{\@headfootfont
3024             \acmConference@shortname,
3025             \acmConference@date, \acmConference@venue\ACM@linecountR}%
3026     \fi
3027 \fi
3028 \fi
3029 \if@ACM@sigchiamode
3030     \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
3031 \fi
3032 \if@ACM@timestamp
3033     \fancyfoot[LO,RE]{\ACM@timestamp}
3034 \fi
3035 \if@ACM@acmcp
3036     \renewcommand{\footrulewidth}{0.1\p@}%
3037     \fancyheadoffset[L]{46pt}%
3038     \fancyhead[L]{\makebox[\z@][l]{%
3039         \raisebox{-\dimexpr(0.25\textheight*\ACM@ArticleType@nr)}{%
3040             \rotatebox{90}{\colorbox{@ACM@Article@color}{\color{white}%
3041                 \strut\ACM@ArticleType~Article}}}%
3042         \ACM@linecountL}%
3043     \fancyhead[R]{\makebox[\z@][r]{\box\@ACM@acmcpbox}}%
3044     \fancyfoot[L,C]{%
3045     \fancyfoot[R]{\footnotesize
3046         \@journalName, Volume~\@acmVolume, Issue~\@acmNumber,
3047         \ifx\@acmArticle\@empty\else Article~\@acmArticle\fi\space
3048         (\@acmPubDate)\ifx\@acmDOI\@empty\else\\@formatdoi{\@acmDOI}\fi}
3049 \fi
3050 }%
3051 \pagestyle{standardpagestyle}
3052 }

```

\@folio@wd Folio blob width, height, offsets and max number

```

\@folio@ht 3053 \newdimen\@folio@wd
\@folio@voffset 3054 \@folio@wd=\z@
\@folio@max 3055 \newdimen\@folio@ht
3056 \@folio@ht=\z@
3057 \newdimen\@folio@voffset
3058 \@folio@voffset=\z@
3059 \def\@folio@max{1}
3060 \ifcase\ACM@format@nr
3061 \relax % manuscript
3062 \or % acmsmall
3063 \@folio@wd=45.75pt\relax
3064 \@folio@ht=1.25in\relax
3065 \@folio@voffset=.2in\relax
3066 \def\@folio@max{8}
3067 \or % acmlarge
3068 \@folio@wd=43.25pt\relax
3069 \@folio@ht=79pt\relax

```

```

3070 \@folio@voffset=.55in\relax
3071 \def\@folio@max{10}
3072 \fi

```

`\@folioblob` The macro to typeset the folio blob.

```

3073 \def\@folioblob{\@tempcnta=0\@acmArticleSeq\relax
3074 \ifnum\@tempcnta=0\relax\else
First, we calculate \@acmArticleSeq modulo \@folio@max
3075 \loop
3076 \ifnum\@tempcnta>\@folio@max\relax
3077 \advance\@tempcnta by - \@folio@max
3078 \repeat
3079 \advance\@tempcnta by -1\relax
3080 \@tempdima=\@folio@ht\relax
3081 \multiply\@tempdima by \the\@tempcnta\relax
3082 \advance\@tempdima by -\@folio@voffset\relax
3083 \begin{picture}(0,0)
3084 \makebox[\z@]{\raisebox{-\@tempdima}{%
3085 \rlap{%
3086 \raisebox{-0.45\@folio@ht}[\z@][\z@]{%
3087 \rule{\@folio@wd}{\@folio@ht}}}%
3088 \parbox{\@folio@wd}{%
3089 \centering
3090 \textcolor{white}{\LARGE\sffamily\bfseries\@acmArticle}}}}
3091 \end{picture}\fi}
3092

```

`firstpagestyle` The page style for the first page only.

```

3093 \AtBeginDocument{%
3094 \fancypagestyle{firstpagestyle}{%
3095 \fancyhf{}%
3096 \renewcommand{\headrulewidth}{\z@}%
3097 \renewcommand{\footrulewidth}{\z@}%
3098 \if@ACM@journal@bibstrip
3099 \ifcase\ACM@format@nr
3100 \relax % manuscript
3101 \fancyhead[L]{\ACM@linecountL\@acmBadgel}%
3102 \fancyhead[R]{\@acmBadger}%
3103 \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
3104 \if@ACM@nonacm\else%
3105 \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
3106 \fi%
3107 \or % acmsmall
3108 \if@ACM@nonacm\else%
3109 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
3110 \@acmNumber, Article \@acmArticle. Publication date:
3111 \@acmPubDate.}%
3112 \fi%
3113 \fancyhead[LE]{\ACM@linecountL\@folioblob\@acmBadgel}%
3114 \fancyhead[LO]{\ACM@linecountL\@acmBadgel}%
3115 \fancyhead[RO]{\@acmBadger\@folioblob}%
3116 \fancyhead[RE]{\@acmBadger}%
3117 \fancyheadoffset[RO,LE]{0.6\@folio@wd}%

```

```

3118 \or % acmlarge
3119 \if@ACM@nonacm\else%
3120 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
3121 \@acmNumber, Article \@acmArticle. Publication date:
3122 \@acmPubDate.}%
3123 \fi%
3124 \fancyhead[RO]{\@acmBadgeR\@folioblob}%
3125 \fancyhead[RE]{\@acmBadgeR}%
3126 \fancyhead[LE]{\ACM@linecountL\@folioblob\@acmBadgeL}%
3127 \fancyhead[LO]{\ACM@linecountL\@acmBadgeL}%
3128 \fancyheadoffset[RO,LE]{1.4\@folio@wd}%
3129 \or % acmtog
3130 \if@ACM@nonacm\else%
3131 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
3132 \@acmNumber, Article \@acmArticle. Publication date:
3133 \@acmPubDate.}%
3134 \fi%
3135 \fancyhead[L]{\ACM@linecountL\@acmBadgeL}%
3136 \fancyhead[R]{\@acmBadgeR\ACM@linecountR}%
3137 \else % Conference proceedings
3138 \fancyhead[L]{\ACM@linecountL\@acmBadgeL}%
3139 \fancyhead[R]{\@acmBadgeR\ACM@linecountR}%
3140 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
3141 \fi
3142 \else
3143 \fancyhead[L]{\ACM@linecountL\@acmBadgeL}%
3144 \fancyhead[R]{\@acmBadgeR\ACM@linecountR}%
3145 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
3146 \fi
3147 \if@ACM@timestamp
3148 \ifnum\ACM@format@nr=0\relax % Manuscript
3149 \fancyfoot[LO,RE]{\ACM@timestamp\quad
3150 \if@ACM@nonacm\else
3151 \footnotesize Manuscript submitted to ACM
3152 \fi}
3153 \else
3154 \fancyfoot[LO,RE]{\ACM@timestamp}
3155 \fi
3156 \fi
3157 \if@ACM@acmcp
3158 \renewcommand{\footrulewidth}{0.1\p@}%
3159 \fancyheadoffset[L]{46pt}%
3160 \fancyhead[L]{\makebox[\z@][l]{%
3161 \raisebox{-\dimexpr(0.25\textheight*\ACM@ArticleType@nr)}{%
3162 \rotatebox{90}{\colorbox{@ACM@Article@color}{\color{white}%
3163 \strut\ACM@ArticleType~Article}}}%
3164 \ACM@linecountL\@acmBadgeL}%
3165 \fancyhead[R]{\@acmBadgeR\makebox[\z@][r]{\box\@ACM@acmcpbox}}%
3166 \fancyfoot[L,C]}%
3167 \fancyfoot[R]{\footnotesize
3168 \@journalName, Volume~\@acmVolume, Issue~\@acmNumber,
3169 \ifx\@acmArticle\@empty\else Article~\@acmArticle\fi\space
3170 (\@acmPubDate)\ifx\@acmDOI\@empty\else\\@formatdoi{\@acmDOI}\fi}
3171 \fi

```

```
3172 }}}
```

3.23 Sectioning

`\ACM@NRadjust` Ross Moore's macro.

Initially `\ACM@sect@format@` just passes through its #1 argument unchanged. When a sectioning macro such as `\section` occurs, the `\ACM@NRadjust` redefines `\ACM@sect@format@` to expand into the styling commands; e.g., `\@secfont`. Then `\Sectionformat` is temporarily redefined to produce `\realSectionformat{\ACM@sect@format{#1}}{#2}`, which ultimately becomes `\Sectionformat{\@secfont{#1}}{#2}`. This is done to allow `\Sectionformat` to be variable, as may be needed in particular circumstances. Its current expansion is saved as `\realSectionformat` which is used with the modified 1st argument, then `\Sectionformat` is reverted to its former expansion.

To style the section-number, the line `#1{}` is used at the end of `\ACM@NRadjust`. This imposes style-changing commands for fonts and sizes, but any `\MakeUppercase` acts on just the `{}`. It's a bit hacky, by essentially assuming that only numbers occur here, not letters to be case-changed. (This should be acceptable in a class-file, as it ought to be possible to change the case elsewhere, if that was ever desired.) Also, it can result in `\@adddotafter` being called too soon, so a slight adjustment is made, via `\ACM@adddotafter`, which now tests whether its argument is empty. But the coding has to allow for other packages to have also patched `\@adddotafter`.

```
3173 \def\ACM@NRadjust#1{%
3174   \begingroup
3175   \expandafter\ifx\csname Sectionformat\endcsname\relax
3176   % do nothing when \Sectionformat is unknown
3177   \def\next{\endgroup #1}%
3178   \else
3179   \def\next{\endgroup
3180     \let\realSectionformat\Sectionformat
3181     \def\ACM@sect@format@{#1}%
3182     \let\Sectionformat\ACM@NR@adjustedSectionformat
3183     %% next lines added 2018-06-17 to ensure section number is styled
3184     \let\real@adddotafter\@adddotafter
3185     \let\@adddotafter\ACM@adddotafter
3186     #1{ }% imposes the styles, but nullifies \MakeUppercase
3187     \let\@adddotafter\real@adddotafter
3188   }%
3189   \fi \next
3190 }
```

`\ACM@NR@adjustedSectionformat`

```
3191 \def\ACM@NR@adjustedSectionformat#1#2{%
3192   \realSectionformat{\ACM@sect@format{#1}}{#2}%
3193   \let\Sectionformat\realSectionformat}
3194 \DeclareRobustCommand{\ACM@sect@format@}{\ACM@sect@format@}
3195 \def\ACM@sect@format@null#1{#1}
3196 \let\ACM@sect@format@\ACM@sect@format@null
3197 \AtBeginDocument{%
3198   \expandafter\ifx\csname LTX@adddotafter\endcsname\relax
```

```

3199 \let\LTX@adddotafter\@adddotafter
3200 \fi
3201 }

```

\ACM@adddotafter

```

3202 \def\ACM@adddotafter#1{\ifx\relax#1\relax\else\LTX@adddotafter{#1}\fi}

```

Sectioning is different for different levels

```

3203 \renewcommand\section{\@startsection{section}{1}{\z@}%
3204 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3205 {.25\baselineskip}%
3206 {\ACM@NRadjust\@secfont}}
3207 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
3208 {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3209 {.25\baselineskip}%
3210 {\ACM@NRadjust\@subsecfont}}
3211 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
3212 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3213 {-3.5\p@}%
3214 {\ACM@NRadjust{\@subsubsecfont\@adddotafter}}}}
3215 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
3216 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3217 {-3.5\p@}%
3218 {\ACM@NRadjust{\@parfont\@adddotafter}}}}
3219 \newcommand\noindentparagraph{\@startsection{paragraph}{4}{\z@}%
3220 {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
3221 {-3.5\p@}%
3222 {\ACM@NRadjust{\@parfont}}}}
3223
3224 \renewcommand\part{\@startsection{part}{9}{\z@}%
3225 {-1\p@ \@plus -4\p@ \@minus -2\p@}%
3226 {4\p@}%
3227 {\ACM@NRadjust{\@parfont}}}

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase

```

3228 \def\section@raggedright{\@rightskip\@flushglue
3229 \rightskip\@rightskip
3230 \leftskip\z@skip
3231 \parindent\z@}

```

\@secfont Fonts for sections etc. are different for different formats.

```

\@subsecfont 3232 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
\@subsubsecfont 3233 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
\@parfont 3234 \def\@subsubsecfont{\sffamily\itshape}
3235 \def\@parfont{\itshape}
3236 \setcounter{secnumdepth}{3}
3237 \ifcase\ACM@format@nr
3238 \relax % manuscript
3239 \or % acmsmall
3240 \or % acmlarge
3241 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
3242 \def\@subsecfont{\sffamily\large\section@raggedright}
3243 \or % acmtog
3244 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}

```

```

3245 \def\@subsecfont{\sffamily\large\section@raggedright}
3246 \or % sigconf
3247 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
3248 \def\@subsecfont{\bfseries\Large\section@raggedright}
3249 \or % siggraph
3250 \def\@secfont{\sffamily\bfseries\Large\section@raggedright\MakeTextUppercase}
3251 \def\@subsecfont{\sffamily\bfseries\Large\section@raggedright}
3252 \or % sigplan
3253 \def\@secfont{\bfseries\Large\section@raggedright}
3254 \def\@subsecfont{\bfseries\section@raggedright}
3255 \def\@subsubsecfont{\bfseries\section@raggedright}
3256 \def\@parfont{\bfseries\itshape}
3257 \def\@subparfont{\itshape}
3258 \or % sigchi
3259 \setcounter{secnumdepth}{1}
3260 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
3261 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
3262 \or % sigchi-a
3263 \setcounter{secnumdepth}{0}
3264 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
3265 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
3266 \or % acmengage
3267 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
3268 \def\@subsecfont{\bfseries\Large\section@raggedright}
3269 \or %acmcp
3270 \fi

```

`\@adddotafter` Add punctuation after a sectioning command

```
3271 \def\@adddotafter#1{#1\@addpunct{.}}
```

`\@addspaceafter` Add space after a sectioning command

```
3272 \def\@addspaceafter#1{#1\@addpunct{\enspace}}
```

```
3273 \if@ACM@acmcp
```

```
3274 \setcounter{secnumdepth}{-1}%
```

```
3275 \fi
```

3.24 TOC lists

`\@dotsep` Related to the `\tableofcontents` are all the horizontal fillers. Base \LaTeX defines `\@dottedtocline`, which we should not disable. Yet, this command expects `\@dotsep` to be defined but leaves this to the class implementation. Since `amsart` does not provide this, we copy the standard variant from `article` here.

```
3276 \providecommand*\@dotsep{4.5}
```

3.25 Theorems

`\@acmplainbodyfont` The font to typeset the body of the `acmplain` theorem style.

```
3277 \def\@acmplainbodyfont{\itshape}
```

`\@acmplainindent` The amount to indent the `acmplain` theorem style.

```
3278 \def\@acmplainindent{\parindent}
```

`\@acmplainheadfont` The font to typeset the head of the acmplain theorem style.

```
3279 \def\@acmplainheadfont{\scshape}
```

`\@acmplainnotefont` The font to typeset the note of the acmplain theorem style.

```
3280 \def\@acmplainnotefont{\@empty}
```

Customization of the acmplain theorem style:

```
3281 \ifcase\ACM@format@nr
3282 \relax % manuscript
3283 \or % acmsmall
3284 \or % acmlarge
3285 \or % acmtog
3286 \or % sigconf
3287 \or % siggraph
3288 \or % sigplan
3289 \def\@acmplainbodyfont{\itshape}
3290 \def\@acmplainindent{\z@}
3291 \def\@acmplainheadfont{\bfseries}
3292 \def\@acmplainnotefont{\normalfont}
3293 \or % sigchi
3294 \or % sigchi-a
3295 \or % acmengage
3296 \or % acmcp
3297 \fi
```

`acmplain` The acmplain theorem style

```
3298 \newtheoremstyle{acmplain}%
3299   {.5\baselineskip\@plus.2\baselineskip
3300    \@minus.2\baselineskip}% space above
3301   {.5\baselineskip\@plus.2\baselineskip
3302    \@minus.2\baselineskip}% space below
3303   {\@acmplainbodyfont}% body font
3304   {\@acmplainindent}% indent amount
3305   {\@acmplainheadfont}% head font
3306   {.%} punctuation after head
3307   {.5em}% spacing after head
3308   {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmplainnotefont(#3)}}}% head spec
```

`\@acmdefinitionbodyfont` The font to typeset the body of the acmdefinition theorem style.

```
3309 \def\@acmdefinitionbodyfont{\normalfont}
```

`\@acmdefinitionindent` The amount to indent the acmdefinition theorem style.

```
3310 \def\@acmdefinitionindent{\parindent}
```

`\@acmdefinitionheadfont` The font to typeset the head of the acmdefinition theorem style.

```
3311 \def\@acmdefinitionheadfont{\itshape}
```

`\@acmdefinitionnotefont` The font to typeset the note of the acmdefinition theorem style.

```
3312 \def\@acmdefinitionnotefont{\@empty}
```

Customization of the acmdefinition theorem style:

```
3313 \ifcase\ACM@format@nr
3314 \relax % manuscript
```

```

3315 \or % acmsmall
3316 \or % acmlarge
3317 \or % acmtog
3318 \or % sigconf
3319 \or % siggraph
3320 \or % sigplan
3321 \def\@acmdefinitionbodyfont{\normalfont}
3322 \def\@acmdefinitionindent{\z@}
3323 \def\@acmdefinitionheadfont{\bfseries}
3324 \def\@acmdefinitionnotefont{\normalfont}
3325 \or % sigchi
3326 \or % sigchi-a
3327 \or % acmengage
3328 \or % acmcp
3329 \fi

```

acmdefinition The acmdefinition theorem style

```

3330 \newtheoremstyle{acmdefinition}%
3331  {.5\baselineskip\@plus.2\baselineskip
3332   \@minus.2\baselineskip}% space above
3333  {.5\baselineskip\@plus.2\baselineskip
3334   \@minus.2\baselineskip}% space below
3335  {\@acmdefinitionbodyfont}% body font
3336  {\@acmdefinitionindent}% indent amount
3337  {\@acmdefinitionheadfont}% head font
3338  {.%} punctuation after head
3339  {.5em}% spacing after head
3340  {\thmname{#1}\thmnumber{ #2}\thmnote{ {\@acmdefinitionnotefont{#3}}}}% head spec

```

Make acmplain the default theorem style.

```

3341 \theoremstyle{acmplain}

```

Delay defining the theorem environments until after other packages have been loaded. In particular, the `cleveref` package must be loaded before the theorem environments are defined in order to show the correct environment name (see <https://github.com/borisveytsman/acmart/issues/138>). The `acmthm` option is used to suppress the definition of any theorem environments. Also, to avoid obscure errors arising from these environment definitions conflicting with environments defined by the user or by user-loaded packages, we only define environments that have not yet been defined.

```

3342 \AtEndPreamble{%
3343   \if@ACM@acmthm
3344   \theoremstyle{acmplain}
3345   \@ifundefined{theorem}{%
3346     \newtheorem{theorem}{Theorem}[section]
3347   }{}
3348   \@ifundefined{conjecture}{%
3349     \newtheorem{conjecture}[theorem]{Conjecture}
3350   }{}
3351   \@ifundefined{proposition}{%
3352     \newtheorem{proposition}[theorem]{Proposition}
3353   }{}
3354   \@ifundefined{lemma}{%
3355     \newtheorem{lemma}[theorem]{Lemma}

```

```

3356   }{}
3357   \ifundefined{corollary}{%
3358   \newtheorem{corollary}[theorem]{Corollary}
3359   }{}
3360   \theoremstyle{acmdefinition}
3361   \ifundefined{example}{%
3362   \newtheorem{example}[theorem]{Example}
3363   }{}
3364   \ifundefined{definition}{%
3365   \newtheorem{definition}[theorem]{Definition}
3366   }{}
3367   \fi
3368   \theoremstyle{acmplain}
3369 }

```

`\@proofnamefont` The font to typeset the proof name.

```
3370 \def\@proofnamefont{\scshape}
```

`\@proofindent` Whether or not to indent proofs.

```
3371 \def\@proofindent{\indent}
```

Customization of the proof environment.

```

3372 \ifcase\ACM@format@nr
3373 \relax % manuscript
3374 \or % acmsmall
3375 \or % acmlarge
3376 \or % acmtog
3377 \or % sigconf
3378 \or % siggraph
3379 \or % sigplan
3380 \def\@proofnamefont{\itshape}
3381 \def\@proofindent{\noindent}
3382 \or % sigchi
3383 \or % sigchi-a
3384 \or % acmengage
3385 \or % acmcp
3386 \fi

```

`proof` We want some customization of the proof environment.

```

3387 \renewenvironment{proof}[1][\proofname]{\par
3388   \pushQED{\qed}%
3389   \normalfont \topsep6\p@\@plus6\p@\relax
3390   \trivlist
3391     \item[\@proofindent\hskip\labelsep
3392       {\@proofnamefont #1\@addpunct{.}}]\ignorespaces
3393 }{%
3394   \popQED\endtrivlist\endpfalse
3395 }

```

3.26 Balancing columns

We need balancing only if the user did not disable it, and we use a two column format. Note that `pbalance` uses a different mechanism.

```

3396 \AtEndPreamble{%
3397   \if@ACM@pbalance
3398     \global\@ACM@balancefalse
3399     \ifcase\ACM@format@nr
3400     \relax % manuscript
3401       \or % acsmall
3402       \or % acmlarge
3403       \or % acmtog
3404         \RequirePackage{pbalance}%
3405       \or % sigconf
3406         \RequirePackage{pbalance}%
3407       \or % siggraph
3408         \RequirePackage{pbalance}%
3409       \or % sigplan
3410         \RequirePackage{pbalance}%
3411       \or % sigchi
3412         \RequirePackage{pbalance}%
3413       \or % sigchi-a
3414       \or % acmengage
3415         \RequirePackage{pbalance}%
3416       \or % acmcp
3417     \fi
3418   \fi
3419   \if@ACM@balance
3420     \ifcase\ACM@format@nr
3421     \relax % manuscript
3422     \global\@ACM@balancefalse
3423     \or % acsmall
3424     \global\@ACM@balancefalse
3425     \or % acmlarge
3426     \global\@ACM@balancefalse
3427     \or % acmtog
3428     \RequirePackage{balance}%
3429     \or % sigconf
3430     \RequirePackage{balance}%
3431     \or % siggraph
3432     \RequirePackage{balance}%
3433     \or % sigplan
3434     \RequirePackage{balance}%
3435     \or % sigchi
3436     \RequirePackage{balance}%
3437     \or % sigchi-a
3438     \global\@ACM@balancefalse
3439     \or % acmengage
3440     \RequirePackage{balance}%
3441     \or % acmcp
3442     \global\@ACM@balancefalse
3443     \fi
3444   \fi
3445 }
3446 \AtEndDocument{%
3447   \if@ACM@balance
3448   \if@twocolumn
3449   \balance

```

```
3450 \fi\fi}
```

3.27 Acknowledgments

`\acksname`

```
3451 \newcommand\acksname{Acknowledgments}
```

`\acks` This is a comment-like structure

```
3452 \specialcomment{acks}{%
3453 \begingroup
3454 \section*\acksname}
3455 \phantomsection\addcontentsline{toc}{section}{\acksname}
3456 }{%
3457 \endgroup
3458 }
```

`\grantsponsor` We just typeset the name of the sponsor

```
3459 \def\grantsponsor#1#2#3{#2}
```

`\grantnum`

```
3460 \newcommand\grantnum[3][]{#3%
3461 \def\@tempa{#1}\ifx\@tempa\@empty\else\space(\url{#1})\fi}
```

3.28 Conditional typesetting

We use the comment package for conditional typesetting:

```
3462 \AtEndPreamble{%
3463 \if@ACM@screen
3464 \includecomment{screenonly}
3465 \excludecomment{printonly}
3466 \else
3467 \excludecomment{screenonly}
3468 \includecomment{printonly}
3469 \fi
3470 \if@ACM@anonymous
3471 \excludecomment{anonsuppress}
3472 \excludecomment{acks}
3473 \else
3474 \includecomment{anonsuppress}
3475 \fi}
```

3.29 Additional bibliography commands

`\showeprint` The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’.

```
3476 \newcommand\showeprint[2][arxiv]{%
3477 \def\@tempa{#1}%
3478 \ifx\@tempa\@empty\def\@tempa{arxiv}\fi
3479 \def\@tempb{arxiv}%
3480 \ifx\@tempa\@tempb\relax
3481 arXiv:\href{https://arxiv.org/abs/#2}{#2}%
3482 \else
```

```

3483 \def\@tempb{arXiv}%
3484 \ifx\@tempa\@tempb\relax
3485   arXiv:\href{https://arxiv.org/abs/#2}{#2}%
3486 \else
3487   #1:#2%
3488 \fi
3489 \fi}

```

3.30 Index

`\theindex` Standard amsart uses plain page style in index pages. This clashes with line numbering for review option, so we redefine it.

```

3490 \def\theindex{\@restonecoltrue\if@twocolumn\@restonecolfalse\fi
3491 \columnseprule\z@ \columnsep 35\p@
3492 \@indextitlestyle
3493 \let\item\@idxitem
3494 \parindent\z@ \parskip\z@\@plus.3\p@\relax
3495 \raggedright
3496 \hyphenpenalty\@M
3497 \footnotesize}

```

3.31 End of Class

`\vspace` We do not disable `\vspace`, but add warning to it

```

3498 \let\@vspace@orig=\@vspace
3499 \let\@vspacer@orig=\@vspacer
3500 \apptocmd{\@vspace}{\ClassWarning{\@classname}{\string\vspace\space should
3501   only be used to provide space above/below surrounding
3502   objects}}{}{}
3503 \apptocmd{\@vspacer}{\ClassWarning{\@classname}{\string\vspace\space should
3504   only be used to provide space above/below surrounding
3505   objects}}{}{}
3506 \let\@vspace@acm=\@vspace
3507 \let\@vspacer@acm=\@vspacer

```

`\ACM@origbaselinestretch` We produce an error if the user tries to change `\baselinestretch`

```

3508 \let\ACM@origbaselinestretch\baselinestretch
3509 \AtEndDocument{\ifx\baselinestretch\ACM@origbaselinestretch\else
3510   \ClassError{\@classname}{An attempt to redefine
3511     \string\baselinestretch\space detected. Please do not do this for
3512     ACM submissions!}\fi}

3513 \normalfont\normalfont\normalfont\normalfont\normalfont\normalfont
3514 </class>

```

References

- [1] UK TeX Users Group. UK list of TeX frequently asked questions. <https://texfaq.org>, 2019.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Johannes L. Braams and Javier Bezos. *Babel*, 2022. <http://www.ctan.org/pkg/babel>.
- [4] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [5] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [6] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [7] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [8] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [9] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [10] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomencl>.
- [11] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.44*, December 2019. <http://www.ctan.org/pkg/glossaries>.
- [12] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

Change History

1.48	General: Added prologue option to xcolor	50	\ccsdesc@parse: Added warning for missing concepts	76
	Bib code cleanup (Zack Weinberg)	35	\if@ACM@printacmref: Added warning for longer papers	74
	Documentation update (siggraph)	35	\keywords: Added warning for missing keywords	73
1.49	General: New journal: DTRAP	35	1.69	\vspace: Added the changed command to avoid grouping
1.53	General: New journals: PACMCGIT, TIOT, TDSCI	35	1.70	General: Name change for TDS
	Rearranged docs	35	1.71	General: Bibliography change: volume for @inproceedings is now in brackets together with series
1.54	General: Moved footnote stuff before hyperref call (Ross Moore)	35	1.75	General: Documentation update
1.56	General: Documented \Description	35	1.78	General: Documentation update: Word count
1.57	General: Booktabs package is now the default	35	1.79	General: Updated indormation for TAP, TCPS, TEAC
1.58	General: Changes in samples (Enrico Gregorio)	35	1.80	General: Added DLT and FAC
	New journal: HEALTH. TDS is renamed to TDSCI	35	1.82	General: Updated abbreviations and codes for several journals
1.60	General: New option: urlbreakonhyphens	35	1.84	General: New journals: JDS, GAMES
	\if@ACM@urlbreakonhyphens: introduced macro	36	1.85	General: Added CC licenses
1.62	General: New journal: TELO	35		Added: acmengage
1.63	General: New journal: FACMP	35		New journal: JRC
	New journal: TQUANT	35		\@mkauthors: Added: acmengage
1.63a	General: Move: TQUANT to TQC	35		\@mktitle: Added: acmengage
1.64	General: Putting abstract after \maketitle now causes an error	35		\@parfont: Added: acmengage
1.65	General: New journal: DGOV	35		\@printtopmatter: Added: acmengage
1.66	General: ACM reference format is now mandatory for papers over one page; CCS concepts and keywords are now mandatory for papers over two pages	35		\@specialsection: Added: acmengage
	Authors' addresses are mandatory for journal articles	35		\@subtitlefont: Added: acmengage
	\@mkauthorsaddresses: Added warning for missing addresses	97		\@titlefont: Added: acmengage
				\ACM@linecountR: Added: acmengage
				format: New format: acmengage
				\parskip: Added: acmengage

1.87	General: New journals: ACMJCSS, JATS, TORS	59	v1.04	General: Updated bibliography for siggraph	35
	format: New format: acmcp	36		\acmArticleSeq: Name change by Matthew Fluet	71
1.88	General: Added ISSN for ACMJCSS	59		\acmDOI: Name change by Matthew Fluet	72
	Added ISSN for GAMES	59		\acmISBN: Name change by Matthew Fluet	71
	Added PACMNET	59			
1.89	General: Added PACMMOD	59	v1.05	General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib	35
	Added TOPML	59		Patched \setcitestyle command; closes https: //github.com/borisveytsman/ acmart/issues/19	35
	\@printtopmatter: Moved badges to top header	87			
1.90	General: Added TOPML eISSN	59	v1.06	\@ACM@badge@skip: Added macro	72
v1.00	General: First released version	35		\@ACM@badge@width: Added macro	72
v1.01	General: Changed hyperref colors in screen mode (closes https: //github.com/borisveytsman/ acmart/issues/1)	35		\@ACM@title@width: Added macro	72
	Defined ACM colors	35		\@mktitle@i: Added processing badges	89
	Explicitly put draft option (closes https: //github.com/borisveytsman/ acmart/issues/4)	38		Made generic	89
	Set headheight to 1pc for all formats (closes https: //github.com/borisveytsman/ acmart/issues/5)	35		\@mktitle@ii: Now this macro is obsolete	90
v1.02	General: Added TOPS and TSC (closes https: //github.com/borisveytsman/ acmart/issues/12)	35		\@mktitle@iii: Added processing badges	90
	Documentation changes (closes https: //github.com/borisveytsman/ acmart/issues/13)	35		Made more generic	90
v1.03	General: Added anonsuppress environment	35		\@mktitle@iv: Made more generic	90
	Added authorversion option (closes https: //github.com/borisveytsman/ acmart/issues/9)	35		\@printtopmatter: Added processing badges	87
	\@formatdoi: Added macro	79		\@subtitlefont: Added macro	89
	\if@ACM@authorversion: Added macro	37		\@titlefont: Added macro	88
	\maketitle: Added special case of authorversion	83		\acmBadgeL: Added macro	72
				\acmBadgeR: Added macro	72
				\if@ACM@badge: Added macro	72
			v1.07	\maketitle: Corrected a bug with abstract footnotes	83
				Corrected a bug with permssion and footnotes order	83
			v1.08	General: SIGPLAN reformatting by Matthew Fluet	35
				Typos corrected (Tobias Pape)	35
			v1.09	General: Revert SIGPLAN caption rules	35
			v1.10	General: Changes of 'licensedothergov' wording	77
				\maketitle: Corrected a bug with doi in manuscript and author vertesion,	

	https://github.com/borisveytsman/acmart/issues/36	83		<code>\bibstyle@acmauthoryear</code> : Moved def of <code>\bibstyle@acmauthoryear</code> before use	43
	<code>standardpagestyle</code> : Reversed folios location	101		<code>\bibstyle@acmnumeric</code> : Moved def of <code>\bibstyle@numeric</code> before use	43
v1.11	General: Customization of ACM theorem styles and proof environment by Matthew Fluet	35	v1.15	<code>\@ACM@addtoaddress</code> : Added macro	90
v1.12	General: Added graceful behavior when libertine fonts are absent	54		<code>\@mkauthors@iii</code> : New authors system	94
	Documentation updates	35		<code>\@shortauthors</code> : Introduced macro	101
	<code>\@marginfigure</code> : Now centering by default	57		<code>\@typeset@author@bx</code> : Moved to separate macro	94
	<code>\@marginable</code> : Now centering by default	57		<code>\acks</code> : Added macro	113
	<code>\@parfont</code> : Moved to <code>\section@raggedright</code>	107		<code>\affiliation</code> : Added code for author groups	69
	<code>\copyrightpermissionfootnoterule</code> : Added macro	52		<code>\author</code> : Added code for author groups	68
	<code>\descriptionlabel</code> : Redefined	59		<code>\city</code> : Added macro	91
	<code>\footnoterule</code> : Made shorter	53		<code>\country</code> : Added macro	91
	<code>\if@ACM@natbib@override</code> : Added macro	37		<code>\department</code> : Added macro	91
	<code>\if@ACM@newfonts</code> : Added macro	54		<code>\grantnum</code> : Added macro	113
	<code>\maketitle</code> : Moved thankses to <code>copyrightpermission</code> box	83		<code>\grantsponsor</code> : Added macro	113
	<code>\section@raggedright</code> : Introduced macro	107		<code>\if@insideauthorgroup</code> : Introduced macro	68
v1.13	General: Font adjustments for <code>acmsmall</code>	92		<code>\institution</code> : Added macro	91
	Increased font size for ACM Large Print bibliographic information by default for the proceedings	74		<code>\num@authorgroups</code> : Renamed	68
	<code>\@mpfootnotetext</code> : Made minipage footnotes centered	48		<code>\orcid</code> : Introduced macro	70
	<code>\bibliographystyle</code> : Redefined macro	49		<code>\position</code> : Added macro	91
	<code>\bibstyle@acmauthoryear</code> : Added macro	43		<code>\postcode</code> : Added macro	91
	<code>\bibstyle@acmnumeric</code> : Added macro	43		<code>\state</code> : Added macro	91
	<code>\if@ACM@printfolios</code> : Added macro	74		<code>\streetaddress</code> : Added macro	91
	<code>standardpagestyle</code> : Added headers for sigs	101		<code>standardpagestyle</code> : Better handling of anonymous mode	101
	Expanded headers for sigchi-a	101	v1.16	General: Formatting header/footer (Matthew Fluet)	35
	Suppressed folios if sig	101		<code>\@headfootfont</code> : Added macro	101
v1.14	General: <code>\citestyle</code> updates (Matthew Fluet)	35		<code>standardpagestyle</code> : Customize header/footer text font	101
	Patched <code>\citestyle</code>	41	v1.17	General: Slightly decreased margins for sigs	50
				<code>\@makefnmark</code> : Redefined	48
				<code>\@mkauthors</code> : TOG now uses the same authors block as other journals	91
				<code>\@mkauthors@ii</code> : Deleted	94
				<code>\@mkbibcitation</code> : Added <code>\nobreak</code> Changed format for sigs	98
				<code>\acmArticle</code> : The default is now numerical	71
				<code>\acmMonth</code> : The default must be numerical. Closes #50.	71
				<code>\acmNumber</code> : The default is now numerical	71

\acmVolume: The default is now numerical	71	\ccsdesc@parse: Change from \to to \textrightarrow (Matteo Riondato)	76
\acmYear: The default is now numerical	71	v1.29	
\description: Decreased indent	59	General: Increased head to 13pt	50
\grantnum: Added url	113	\@mkabstract: Removed spurious indentation (John Wickerson)	97
\grantsponsor: Renamed	113	\ccsdesc@parse: Add spacing after bullet and around rightharrow; semicolon separators no longer in bold/italic (John Wickerson)	76
\if@ACM@printacmref: Renamed from \if@ACM@printbib	73	standardpagestyle: Corrected printfolios (Matthew Fluet)	101
standardpagestyle: Added paper title to sigs	101	v1.30	
v1.18		General: Added \frenchspacing	114
General: Natbib is now the default for all formats	35	Bibtex style now recognizes https:// in doi	35
\@mkauthors@i: Now we andify affiliations	93	Switched to T1: looks like libertine has problems with \l in OT1	54
\@typeset@author@line: Added macro	92	Updated IMWUT and PACMPL	59
v1.19		\department: Added optional parameter	91
General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	35	v1.31	
Include 'References' in PDF bookmarks (Matthew Fluet)	41	General: Documentation changes	35
\@mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet)	97	\@additionalaffiliation: Added macro	69
\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet)	113	\@mkbibcitation: Disabled linebreak	98
v1.20		\@startsection: Added \tochangmeasure	45
General: Bug fixes for bst	35	Redefined macro	47
\@mkabstract: Deleted spurious space	97	\@textbottom: Redefined	53
v1.21		\acmMonth: The default now is the current month (Matteo Riondato)	71
\showeprint: Added macro	113	\acmYear: The default now is the current year (Matteo Riondato)	71
v1.22		\additionalaffiliation: Added macro	69
General: More bibliography changes for Aptara	35	\l@section: Redefined macro	47
v1.23		\l@subsubsection: Redefined macro	47
General: Add PACMPL journal option	35	v1.32	
v1.24		General: Added POMACS journal option	35
General: Add IMWUT journal option	59	Format siggraph is now obsolete	35
v1.25		\@formatdoi: New doi format	79
General: Updated PACMPL	59	v1.33	
v1.26		General: Added acmart-preload-hook	35
General: Corrected \shortcite bug	35	Added cmap and glyphtounicode	54
Documentation typos fixed (thanks to Stephen Spencer)	35	BibTeX comma before articleno bug corrected	35
v1.27		BibTeX crossref bug corrected	35
\if@ACM@printccs: Typo corrected	73	BibTeX numpages bug corrected	35
v1.28		Documentation updates	35
General: Corrected option natbib behavior	43		
Got rid of warnings in pdf keywords	48		

Moved <code>\citename</code> definition for non-natbib bibliography, so a package may redefine it	49	v1.34	Added timestamp (Michael D. Adams)	101
Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann) .	54		<code>\@mkbibcitation</code> : Deleted DOI from doi numbers	98
<code>\@ACM@addtoaddress</code> : Added obexpunctuation code	90		<code>\ACM@linecount@bx</code> : Rulers now are continuous	99
<code>\@mkauthors@i</code> : Added obexpunctuation code	93		<code>\ACM@linecountL</code> : Rulers now are continuous	100
<code>\@mkauthors@iii</code> : Added obexpunctuation code	94		<code>\ACM@linecountR</code> : Rulers now are continuous	100
<code>\@mkauthors@iv</code> : Added obexpunctuation code	95		<code>\maketitle</code> : Added date to the bibstrip in conf proceedings	83
<code>\@subtitlefont</code> : Added <code>\normalsize</code>	89		Deleted 'DOI' from doi numbers . .	83
<code>\ACM@linecountL</code> : Renamed macro .	100		Rearranged bibstrip	83
<code>\ACM@linecountR</code> : Added macro . .	100		The <code>\terms</code> command is now obsolete	83
<code>\ACM@timestamp</code> : Added current page number	100	v1.35	<code>\terms</code> : The <code>\terms</code> command now just produces a warning	73
Added macro (Michael D. Adams) .	100		General: BibTeX bug fixed: et al. . . .	35
Added submission id	100		If the copyright is set to usgov or rigtsretained, the price is suppressed	77
<code>\acmSubmissionID</code> : Added macro . .	71		<code>\bibstyle@acmauthoryear</code> : Square brackets for author-year style . . .	43
<code>\city</code> : Added obexpunctuation code	91			
<code>\country</code> : Added obexpunctuation code	91	v1.36	General: Added PACMHCI journal options	59
<code>\department</code> : Added obexpunctuation code	91		Added the possibility to adjust number of author boxes per row in conference formats	35
<code>\if@ACM@affiliation@obexpunctuation</code> : Added macro	69		<code>\@ACM@authorsperrow</code> : Added macro	74
<code>\if@ACM@authordraft</code> : Added macro	38		<code>\@mkauthors@iii</code> : Added authorsperrow override	94
<code>\if@ACM@natbib@override</code> : Deleted macro	37		<code>\@mkauthors@iv</code> : Added authorsperrow override	95
<code>\if@ACM@timestamp</code> : Added macro (Michael D. Adams)	38		<code>\if@ACM@authordraft</code> : Corrected typo, thanks to bargteil	38
<code>\institution</code> : Added obexpunctuation code	91	v1.37	General: Reduce list indentation (Matthew Fluet)	58
<code>firstpagestyle</code> : Added right linecount for two-column formats	104		Set <code>\normalparindent</code> ; Reduce list indentation (Matthew Fluet)	35
Added timestamp (Michael D. Adams)	104		<code>\description</code> : Reduce list indentation (Matthew Fluet)	59
<code>\maketitle</code> : Fixed the bug with figures on top and bottom of the title page, thanks to David Epstein	83		<code>\descriptionlabel</code> : Reduce list indentation (Matthew Fluet)	59
<code>\position</code> : Added obexpunctuation code	91		<code>\normalparindent</code> : Set <code>\normalparindent</code> (Matthew Fluet)	52
<code>\postcode</code> : Added obexpunctuation code	91	v1.38	General: Increase default font size for SIGPLAN	35, 40
<code>\state</code> : Added obexpunctuation code	91			
<code>\streetaddress</code> : Added obexpunctuation code	91			
<code>standardpagestyle</code> : Added right linecount for two-column formats	101			

v1.39			
	\@authornotemark: Added macro	97	
	\authornotemark: Added macro	71	
v1.40			
	General: Added 'textcase' package	41	
	Added heightrounded to geometry	50	
	Added new copyright version:		
	licensedcagov	35	
	Added package cleveref	35	
	Added Ross Moore code for		
	glyphtounicode	54	
	Bibliography changes	35	
	\@copyrightowner: Added new		
	copyright version: licensedcagov	78	
	\@copyrightpermission: Added new		
	copyright version: licensedcagov	79	
	\@mkauthors@i: Switched to		
	MakeTextUppercase	93	
	\@parfont: Switched to		
	MakeTextUppercase	107	
	\ACM@linecount@bx: Work around a		
	bug in xcolor: looks like cmyk		
	colors in boxes do not work	99	
	\ccd@parse@finish: Added		
	macro	76	
	\@city: We now do not print this even		
	in SIG	91	
	\@country: Fixed bugs with extra		
	spaces	91	
	\@l@section: Redefined macro	47	
	\@postcode: We now do not print this		
	even in SIG	91	
	\@state: We now do not print this even		
	in SIG	91	
	\@streetaddress: We now do not		
	print this even in SIG	91	
v1.41			
	General: Added new badges	35	
v1.42			
	General: Deleted ACM badges	35	
v1.43			
	\@startsection: Added		
	\makeatletter	47	
	\@country: Added comma before		
	country for journals	91	
v1.44			
	General: Added package refcount	35	
	Deleted package cleveref	35	
	Put theorem defs in a separate style	35	
	\@acmBooktitle: Added macro	67	
	\@acmEditors: Added macro	67	
	\@editorsAbbrev: Added macro	67	
	\@folioblob: Suppress the blob if		
	acmArticleSeq is empty	104	
	\@mkbibcitation: If the paper has		
	just one page, use 'page' instead of		
	'pages'	98	
	\ACM@restore@pagestyle: Added		
	macro	99	
	\acmArticle: The default is now		
	empty	71	
	\acmArticleSeq: Now acmArticle		
	might be empty	71	
	\acmBooktitle: Added macro	67	
	\@editor: Added macro	67	
	\if@ACM@acmthm: Added macro	36	
	\@maketitle: Empty DOI or ISBN are		
	not printed (by Michael Ekstrand)	83	
v1.45			
	\@folioblob: Switched		
	\bfeseries\sffamily to		
	\sffamily\bfseries	104	
	\@parfont: Switched		
	\bfeseries\sffamily to		
	\sffamily\bfseries	107	
	\@titlefont: Switched		
	\bfeseries\sffamily to		
	\sffamily\bfseries	88	
v1.46			
	General: Added etoolbox	35	
	Bst file bug fixes: label width is		
	calculated correctly	35	
	Delayed hypersetup since journal		
	options may change screen mode	48	
	PACM now set screen to true	59	
	Restore theorem defs to class file	35	
	\@mkauthorsaddresses: Introduced		
	macro	97	
	\@mkbibcitation: Added subtitle	98	
	\@printendtopmatter: Made it		
	\par\bigskip uniformly	99	
	\@printtopmatter: Deleted rule	87	
	\@setauthorsaddresses: Introduced		
	macro	99	
	\ACM@linecount@bx: Rearranged the		
	code to get rid of spurious		
	underfull messages (Benjamin		
	Byholm)	99	
	\@author: Started counting authors	68	
	\@authorsaddresses: Introduced		
	macro	70	
	\@country: Corrected spacing for		
	institution	91	
	\if@ACM@acmthm: Modified		
	description	36	
	\@liningnums: Workaround for		
	compatibility with fontspec	55	
	\@maketitle: Added authors' addresses	83	

Thankses go before authors' addresses	83	v1.53	General: Added PACMCGIT, TIOT, TDSCI	59
v1.47				
\num@author: Introduced macro	68	v1.54	General: Added Ross's patch for sectioning	107
v1.48			Deleted indent for subsection	107
General: New journal: THRI	35		XeTeX now uses T1 encoding	54
General: \citeyear no longer behaves like \citeyearpar	49		\@mkbibcitation: Bug corrected (Ross Moore)	98
Code prettying (Michael D. Adams)	35		\@shortauthors: Added submission id in anonymous mode	101
Initial support for Biblalex (Daniel Thomas)	35		\ACM@adddotafter: Added macro	107
Misc entries in the bibliography no longer produce a separate date	35		\ACM@NR@adjustedSectionformat: Added macro	106
Typos fixed (Jamie Davis)	35		\ACM@NRadjust: Added macro	106
\@headfootfont: Deleted unnecessary switch (Michael D. Adams)	101		\author: Added submission id in anonymous mode	68
\@mkabstract: Removed spurious indentation if abstract is followed by an empty line	97		\if@ACM@nonacm: Added macro	37
\ACM@timestamp: Fromatting change (Michael D. Adams)	100	v1.55	General: Now we use purple color for links	48
\if@ACM@review: Review mode now switches on folios	36		Table captions for SIGCHI now use the same font size as figure captions (Luis Leiva)	56
\maketitle: Added acmart and version info to pdfcreator tag	83		Typo corrected (Zack Weinberg)	41
Added language and doctitle attributes to PDF (Andreas Reichinger)	83		\@mkbibcitation: Bug corrected	98
Supressed empty DOI (Serguei Mokhov)	83	v1.56	\maketitle: Fixes topnum	83
v1.50			General: Looks like XeTeX requires explicit monotype font declaration	54
\@copyrightpermission: New copyright statements for iw3c2w3[g]	79		Make two-column layouts flush (Philip Quinn)	50
v1.51			\@marginfigure: Added checking for description	57
General: Corrected the bug with price suppression	77		\@mkteasers: Added check for description	97
Suppress price if the copyright is set to iw3c2w3 or iw3c2w3g	77		\acksname: Added macro (Philip Quinn)	113
XeTeX now uses OTF fonts (Joachim Breitner)	54		\ccsdesc@parse: End the concepts list with a period (Philip Quinn)	76
firstpagestyle: We now use journal abbreviation for footers	104		\Description: Added macro	55
standardpagestyle: We now use journal abbreviation for footers	101		\if@Description@present: Added macro	55
v1.52			\if@undescribed@images: Added macro	55
\@copyrightowner: Rewording of licenses	78	v1.57	\ACM@origbaselinestretch: Added check whether the user changed \baselinestretch	114
\@copyrightpermission: Another rewording of copyright statements for iw3c2w3[g]	79		\author: Added warning if \author has comma	68
			\email: Added warning if \author has comma	69

	\if@ACM@balance: Added macro . . .	37		\maketitle: Added a switch setting to show that \maketitle is typeset .	83
	\vspace: Added warning	114			
v1.58	General: Added HEALTH. TDS CI is renamed to TDS	59	v1.65	\@mkauthorsaddresses: Deleted cs@addpunct	97
	Suppressed \addtocounter in pdf subject	48	v1.66	General: Patching algorithm and algorithm* to prevent spurious space warnings	55
	\@dblfloat: Deleted spurious \vspace warning	57		\@specialsection: Suppress warnings about \vspace	86
	\@marginfigure: Deleted spurious \vspace warning	57	v1.67	General: Patching lstlisting and lstlisting* to prevent spurious space warnings	55
	\@margintable: Deleted spurious \vspace warning	57		\@parfont: Deleted redefinitions of sections	107
	\@mkbibcitation: Deleted spurious \vspace warning	98		\@specialsection: Paragraph inside group does not print its argument. Added a bugfix	86
	\@printendtopmatter: Deleted spurious \vspace warning	99	v1.68	General: New command for unindent paras	107
	\@sidebar: Deleted spurious \vspace warning	57		\@specialsection: Deleted grouping altogether	86
	\maketitle: Original \vspace inside \maketitle	83	v1.69	General: No dots for unindented paragraphs	107
	\vspace: Preserved old versions as \@vspace@orig and \@vspace@orig	114		\@printendtopmatter: Deleted grouping	99
v1.59	\acmConference: Setting \@ACM@journal@bibstrip	67		\@specialsection: Changed dot to colon for sigplan	86
	\acmJournal: Setting \@ACM@journal@bibstrip	67		\ACM@linecountR: Do not increase numbers in one column format	100
	\if@ACM@journal@bibstrip: Introduced macro	39		\ccsdesc@parse: Use math right arrow in text	76
	firstpagestyle: Added logic for conference papers using journal format	104	v1.71	\@subsubsection: Bug fixed (thanks to Andrew Black)	47
	Moved page styles to \@AtBeginDocument	104	v1.72	General: Added hyperxmp	48
	standardpagestyle: Added logic for conference papers using journal format	101		\author: Added \detokenize (Kuldeep S. Meel)	68
	Moved page styles to \@AtBeginDocument	101		\maketitle: Do not andify authors for pdf metadata (Scott Pakin)	83
v1.60	\@headfootfont: Moved to footnotesize	101	v1.73	General: Patching minted and minted* to prevent spurious space warnings	55
v1.61	\@typeset@author@bx: Added \normalbaselines	94		\@ACM@checkaffil: Added macro	93
v1.64	\ACM@linecount@bx: Bug fix: made the spacing on the left and the right size equal	99		\@ACM@resetaffil: Added macro	93
	\if@ACM@maketitle@typeset: Introduced macro	59		\@mkauthors@ei: Check the presence of required elements for affiliations	93

\@mkauthors@iii: Check the presence of required elements for affiliations	94	v1.82	\anon: Introduced macro	82
\@mkauthors@iv: Check the presence of required elements for affiliations	95	v1.83	General: Use babel for multilanguage papers	43
\city: Check the presence in affil	91		\@mkabstract:I13n	97
\country: Check the presence in affil	91		\@mktitle@i: Added	
\if@ACM@citypresent: Added macro	93		\translatedtitle and	
\if@ACM@countrypresent: Added macro	93		\translatedsubtitle	89
\if@ACM@instpresent: Added macro	93		\@mktitle@iii: Added	
\institution: Check the presence in affil	91		\translatedtitle and	
\maketitle: Do not check again the presence of address fields	83		\translatedsubtitle	90
v1.74			\@mktitle@iv: Added	
General: Changed the order of font loading	54		\translatedtitle and	
v1.75			\translatedsubtitle	90
\@ACM@checkaffil: Changed warning to error for country	93		\@mktranslatedabstract: Added macro	98
\@beginmaketitlehook: Introduced macro	82		\@mktranslatedkeywords: Added macro	70
\@AtBeginMaketitle: Introduced macro	83		\@translatedabstracts: Added macro	45
\maketitle: Added			\@translatedkeywords: Added macro	45
\@beginmaketitlehook	83		\@translatedsubtitle: Added macro	45
v1.76			\@translatedtitle: Added macro	44
General: Moved hyperxmp before hyperref, see https://github.com/borisveytsman/acmart/issues/425	48		\ACM@lang@check: Added macro	44
\author: Added code for orcid links	68		\ACM@languages: Introduced macro	38
\if@ACM@pbalance: Added macro	37		\maketitle:I13n	83
\maketitle: Put \par inside group for keywords	83		translatedabstract: Added macro	45
\orcid: Added code for orcid links	70		\translatedkeywords: Added macro	45
standardpagestyle: Fixed bug with no line numbers for nonacm	101		\translatedsubtitle: Added macro	45
v1.77			\translatedtitle: Added macro	45
\@mkauthorsaddresses: New separator of institutions	97		v1.85	
v1.78			General: Added CC licenses	77
\@mkauthors@i: Unboxing			\@acmengagemetadata: Introduced macro	83
\mktitle@bx	93		\@copyrightowner: Added CC licenses	78
\@mkauthors@iii: Unboxing			\@copyrightpermission: Added CC licenses	79
\mktitle@bx	94		\@typesetengagemetadata: Introduced macro	99
\@mkteasers: Unboxing \mktitle@bx	97		\if@ACM@engage: Introduced macro	39
\@printtopmatter: Added processing the overflowing title box	87		\maketitle: acmengage	83
\@specialsection: Again suppressed \vspace warning	86		\setcctype: Added macro	78
			\setengagemetadata: Introduced macro	83
			v1.86	
			\country: Error if country is empty	91
			standardpagestyle: Special treatment of ACM Engage materials	101

v1.87			
General: Added 'framed' package for		standardpagestyle: Special	
acmcp	41	treatment of ACMCP	101
No numbering sections for ACMCP	108		
\@ACM@color@frame: Introduced		\@mktitle@i: Moved down title for	
macro	75	acmcp	89
\@ACM@copyright@check@cc: Added		v1.89	
macro	79	General: Added 'zref-savepos' package	
\@copyrightpermission: CC licenses		for acmcp	41
now are allowed only for non-acm		\@ACM@acmcp@delta: Added dimen	41
or ACM engage publications	79	\@ACM@badge@skip: Redefined macro	72
\@mkauthors@i: Special treatment for		\@ACM@color@frame: Added saving	
acmcp	93	the position of the bottom	75
\@mktitle@i: Special treatment for		\@acmBadgeL: Introduced macro	72
acmcp	89	\@acmBadgeR: Introduced macro	72
\acmArticleType: Introduced macro	75	\@mktitle@i: Moved badges to top	
\acmCodeLink: Added possibility to		header	89
have several links	75	Moved up acmcp title	89
Introduced macro	75	\@mktitle@iii: Moved badges to top	
\acmDataLink: Introduced macro	75	header	90
Now this is the same as the code link	75	\acmBadge: Added macro	73
\if@ACM@acmcp: Introduced macro	39	\acmBadgeL: Redefined macro	72
firstpagestyle: Special treatment		\acmBadgeR: Redefined macro	72
for acmcp	104	\if@ACM@badge: Deleted macro	72
\maketitle: CC license are allowed		firstpagestyle: Moved badges here	104
for non-acm publications	83	\set@ACM@acmcpbox: Added logo	86
\set@ACM@acmcpbox: Added macro	86	Added zref position of the bottom	86

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\backslash \$ 2195, 2199	\backslash ACM@instpresentfalse
\backslash - 613 2580
\backslash @	1887, 1899, 1902, 1905, 1910, 2008, 2029, 2042	\backslash ACM@instpresenttrue
\backslash @authornotemark 2483, 2494, 2574
.....	1603, <u>2767</u>	\backslash ACM@journal@bibstripfalse
\backslash @par 479, 536 232, 1455
\backslash ACM@acmcp@delta	..	\backslash ACM@journal@bibstriptrue
.....	<u>277</u> , 2272, 2276 230, 1441
\backslash ACM@acmcp@box	\backslash ACM@journalfalse
.....	2259, 2263, 3043, 3165 211,
\backslash ACM@acmcpfalse	... 169	213, 215, 217, 219, 222
\backslash ACM@acmcptrue	... 226	\backslash ACM@journaltrue
\backslash ACM@addtoaddress 203, 205, 207, 209, 225
.....	2471, 2499, 2500, 2502	\backslash ACM@labelwidth
\backslash ACM@author@sperrrow	1007, 1015, 1020, 1046
.....	1707,	\backslash ACM@maketitle@typesetfalse
2646, 2647, 2699, 2700	 1053
\backslash ACM@badge@skip	...	\backslash ACM@maketitle@typesettrue
...	1632, 1644, 1657 2106
\backslash ACM@badge@width	..	\backslash ACM@manuscriptfalse
.....	<u>1629</u> ,	198
1641, 1647, 1654, 1660		\backslash ACM@manuscripttrue
\backslash ACM@balancefalse	..	196
.....	3398, 3422,	\backslash ACM@newfontfalse
3424, 3426, 3438, 3442	 834, 837, 840
\backslash ACM@check@affil	2230,	\backslash ACM@newfonttrue
<u>2584</u> , 2615, 2620,		.. 831
2682, 2687, 2727, 2732		\backslash ACM@printacmreffalse
\backslash ACM@city@presentfalse 95, 227
.....	2581	\backslash ACM@print@foliostrue
\backslash ACM@city@presenttrue	...	78
...	2485, 2499, 2576	\backslash ACM@reset@affil
\backslash ACM@color@frame 2579, 2614, 2619,
.....	1764, 2256	2681, 2686, 2726, 2731
\backslash ACM@comm@box	\backslash ACM@reviewtrue
...	2471, 2475, 2476	... 140
\backslash ACM@copyright@check@cc	\backslash ACM@screentrue
.....	1921, 2060	1171,
\backslash ACM@country@presentfalse	1215, 1221, 1235, 1241
.....	2582	\backslash ACM@sigchiamodeffalse
\backslash ACM@country@presenttrue 200
...	2490, 2502, 2578	\backslash ACM@sigchiamodetrue
\backslash ACM@engagefalse	.. 167	220
\backslash ACM@engagetrue	... 223	\backslash ACM@timestamptrue
\backslash ACM@institution@separator	139
...	2749, 2750, 2755	\backslash ACM@title@width
	
		1631,
		2444, 2446, 2455, 2456
		\backslash DeclareACMFormat
		38,
		39, 40, 41, 42, 43,
		44, 45, 46, 47, 48, 49
		\backslash Description@presentfalse
		.. 876, 879, 954, 2773
		\backslash Description@presenttrue
	 870, 873
		\backslash EM
		479, 518, 536, 545, 3496
		\backslash @abstract
		1678, 2781, 2788
		\backslash @acmArticle
	
		1609, 1612, 2194,
		2806, 2807, 2935,
		2938, 2958, 2968,
		2979, 3047, 3090,
		3110, 3121, 3132, 3169
		\backslash @acmArticlePage
		...
		2934, 2952, 2953,
		2962, 2965, 2972, 2976
		\backslash @acmArticleSeq
		1611, 3073
		\backslash @acmBadgeL
	
		<u>1635</u> , 1650, 1651,
		1656, 3101, 3113,
		3114, 3126, 3127,
		3135, 3138, 3143, 3164
		\backslash @acmBadgeR
	
		<u>1634</u> , 1637, 1638,
		1643, 3102, 3115,
		3116, 3124, 3125,
		3136, 3139, 3144, 3165
		\backslash @acmBooktitle
	
		<u>1461</u> , 2163, 2184, 2822
		\backslash @acmCodeDataLink
		..
	 1771, 1772,
		1774, 1776, 2279, 2280
		\backslash @acmDOI
		.. 1627, 2186,
		2189, 2196, 2200,
		2830, 2991, 2993,
		3015, 3017, 3048, 3170
		\backslash @acmEditors
		<u>1469</u> , 1470,
		1471, 1474, 2823, 2824
		\backslash @acmISBN
	 1625, 2198
		\backslash @acmMonth
		1615, 1617, 2194
		\backslash @acmNumber
	
		1607, 2819, 2958,
		2968, 2979, 3046,
		3110, 3121, 3132, 3168
		\backslash @acmPrice
		1621, 2195, 2199
		\backslash @acmPubDate
	
		<u>1617</u> , 2819, 2958,
		2968, 2979, 3048,
		3111, 3122, 3133, 3170
		\backslash @acmSubmissionID
		..
	 1495,
		1496, 1515, 1516,
		1623, 2915, 2916, 2926

<code>\@acmVolume</code>	<code>\@authorfont</code> 2532 , 2537 ,	2671 , 2672 , 2675 ,
1605 , 2819 , 2957 ,	2541 , 2544 , 2547 ,	2678 , 2679 , 2684 ,
2967 , 2978 , 3046 ,	2550 , 2553 , 2556 ,	2711 , 2718 , 2719 ,
3109 , 3120 , 3131 , 3168	2559 , 2562 , 2602 , 2638	2721 , 2723 , 2724 , 2729
<code>\@acmYear</code>	<code>\@authornotemark</code> . . .	<code>\@currentaffiliations</code>
1613 , 1620 ,	. . . 1595 , 1601 , 2766 2568 ,
2079 , 2163 , 2194 , 2810	<code>\@authornotes</code>	2569 , 2570 , 2572 ,
<code>\@acmdefinitionbodyfont</code>	. . . 1592 , 1596 , 2126	2598 , 2610 , 2611 , 2617
. . . 3309 , 3321 , 3335	<code>\@authorsaddresses</code> .	<code>\@currentauthors</code> . . .
<code>\@acmdefinitionheadfont</code> 1567 , 2566 , 2567 ,
. . . 3311 , 3323 , 3337	2135 , 2285 , 2761 , 2840	2597 , 2601 , 2602 ,
<code>\@acmdefinitionindent</code>	<code>\@auxout</code> 649 , 2275	2604 , 2638 , 2641 ,
. . . 3310 , 3322 , 3336	<code>\@begindocumenthook</code> 645	2663 , 2665 , 2666 ,
<code>\@acmdefinitionnotefont</code>	<code>\@beginmaketitlehook</code>	2668 , 2710 , 2712 ,
. . . 3312 , 3324 , 3340	. . . 2096 , 2099 , 2105	2713 , 2715 , 2766 , 2767
<code>\@acmengagemetadata</code>	<code>\@botnum</code> 2249	<code>\@currentlabel</code> . . . 563 , 577
. . . 2100 , 2102 , 2843	<code>\@citestyle</code> 311	<code>\@dblalg</code> 465
<code>\@acmownedfalse</code>	<code>\@classname</code>	<code>\@dblfloat</code> 966
. 1830 , 1833 ,	24 , 26 , 35 , 53 , 55 ,	<code>\@department</code> . . . 1545 , 1546
1836 , 1842 , 1846 ,	56 , 61 , 63 , 64 , 69 ,	<code>\@dotsep</code> 3276
1849 , 1852 , 1855 ,	71 , 72 , 77 , 80 , 81 ,	<code>\@editorsAbbrev</code>
1861 , 1864 , 1868 , 1872	86 , 88 , 89 , 94 , 100 , 1468 , 1473 , 2824
<code>\@acmownedtrue</code>	101 , 105 , 109 , 114 ,	<code>\@empty</code> 155 ,
. 1817 , 1826 , 1858	116 , 117 , 122 , 124 ,	234 , 381 , 421 , 469 ,
<code>\@acmplainbodyfont</code> .	125 , 130 , 132 , 133 ,	1452 , 1470 , 1492 ,
. . . 3277 , 3289 , 3303	138 , 142 , 143 , 161 ,	1495 , 1513 , 1515 ,
<code>\@acmplainheadfont</code> .	171 , 177 , 183 , 260 ,	1520 , 1521 , 1527 ,
. . . 3279 , 3291 , 3305	422 , 446 , 832 , 835 ,	1637 , 1650 , 1668 ,
<code>\@acmplainindent</code> . . .	838 , 875 , 884 , 887 ,	1669 , 1725 , 1726 ,
. . . 3278 , 3290 , 3304	957 , 1172 , 1216 ,	1732 , 1739 , 1771 ,
<code>\@acmplainnotefont</code> .	1222 , 1236 , 1242 ,	1780 , 1806 , 2097 ,
. . . 3280 , 3292 , 3308	1436 , 1438 , 1485 ,	2130 , 2135 , 2186 ,
<code>\@adddotafter</code>	1540 , 1554 , 1665 ,	2195 , 2198 , 2199 ,
. 3184 , 3185 , 3187 ,	1671 , 1676 , 1683 ,	2200 , 2211 , 2214 ,
3199 , 3214 , 3218 , 3271	1685 , 1686 , 1689 ,	2220 , 2224 , 2279 ,
<code>\@additionalaffiliation</code>	1691 , 1692 , 1695 ,	2282 , 2285 , 2320 ,
. 1541 , 1542	1703 , 1705 , 1706 ,	2449 , 2458 , 2467 ,
<code>\@addpunct</code>	1708 , 1709 , 1757 ,	2489 , 2568 , 2601 ,
2753 , 2839 ,	1808 , 1923 , 1927 ,	2609 , 2610 , 2665 ,
2840 , 3271 , 3272 , 3392	1930 , 2586 , 2589 ,	2671 , 2678 , 2712 ,
<code>\@addspaceafter</code>	2592 , 2762 , 2776 ,	2718 , 2723 , 2761 ,
3272	2803 , 3500 , 3503 , 3510	2769 , 2806 , 2811 ,
<code>\@affiliationfont</code> . .	<code>\@clubpenalty</code> 524	2823 , 2830 , 2915 ,
. 2533 , 2538 ,	<code>\@concepts</code> 1780 , 1792 ,	2926 , 2991 , 2993 ,
2542 , 2545 , 2548 ,	1806 , 2214 , 2216 , 2234	3015 , 3017 , 3047 ,
2551 , 2554 , 2557 ,	<code>\@copyrightowner</code> . . .	3048 , 3169 , 3170 ,
2560 , 2563 , 2615 , 2638 1881 , 2170	3280 , 3312 , 3461 , 3478
<code>\@afterheading</code>	<code>\@copyrightpermission</code>	<code>\@endfloatbox</code> 969
510 , 2252 1937 , 2146 , 2158	<code>\@endpfalse</code> 3394
<code>\@afterindentfalse</code> .	<code>\@copyrightyear</code>	<code>\@endwdefloatbox</code> 969 , 977
. 456 , 2251 2078 , 2170 , 2172	<code>\@finalstrut</code> 568 , 581
<code>\@afterindenttrue</code>	<code>\@currbox</code> 983 , 984 , 985	<code>\@float</code> 971
454	<code>\@currentaffiliation</code>	<code>\@flushglue</code> 3228
<code>\@article@string</code>	2639 , 2642 , 2664 ,	<code>\@fnsymbol</code> 2116
. 2806 , 2819 , 2827		
<code>\@author</code>		
1494 , 1500 , 1507 ,		
2600 , 2665 , 2712 , 2756		

<code>\@folioeht</code>	1146, 1150, 1154,	2222, 2235, 2282, 2283
3053, 3080, 3086, 3087	1159, 1163, 1167,	<code>\@latex@error</code>
<code>\@folio@max</code> 3053, 3076, 3077	1174, 1178, 1182,	355
<code>\@folio@voffset</code> 3053, 3082	1186, 1191, 1195,	<code>\@empty</code>
<code>\@folio@wd</code>	1199, 1203, 1208,	1680, 2781
3087, 3088, 3117, 3128	1212, 1218, 1224,	<code>\@listI</code>
<code>\@folioblob</code>	1228, 1232, 1238,	1028, 1032
3113, 3115, 3124, 3126	1244, 1248, 1252,	<code>\@listi</code>
<code>\@footnotemark</code> .	1257, 1261, 1265,	1025, 1032
585, 2114	1269, 1273, 1277,	<code>\@listii</code>
<code>\@footnotemark@nolink</code>	1281, 1285, 1289,	1033
.....	1293, 1297, 1301,	<code>\@listiii</code>
585, 2114	1305, 1309, 1313,	1036
<code>\@footnotetext</code>	1317, 1321, 1325,	<code>\@listiv</code>
.....	1329, 1333, 1337,	1038
559, 586, 2115	1341, 1345, 1349,	<code>\@listv</code>
<code>\@footnotetext@nolink</code>	1353, 1357, 1362,	1040
.....	1367, 1371, 1375,	<code>\@listvi</code>
586, 2115	1380, 1384, 1388,	1042
<code>\@for</code>	1392, 1396, 1400,	<code>\@m</code>
287	1404, 1408, 1412,	467
<code>\@formatdoi</code>	1416, 1420, 1424,	<code>\@makefnmark</code> ...
1920,	1428, 1432, 1443,	558,
2189, 2196, 2200,	1444, 2182, 3046, 3168	583, 2118, 2123, 2127
2830, 2991, 2993,		<code>\@makefntext</code>
3015, 3017, 3048, 3170		.. 558, 567, 580, 2129
<code>\@fps</code>		<code>\@marginfigure</code> .
970		949, 950
<code>\@fpsadddfault</code>		<code>\@marginable</code> ..
970		960, 961
<code>\@gobble</code>		<code>\@minipagefalse</code> .
309, 353		792, 979
<code>\@hangfrom</code>		<code>\@minus</code> 3204, 3208, 3212,
478, 535		3216, 3220, 3225,
<code>\@headfootfont</code>		3300, 3302, 3332, 3334
.....		<code>\@mkabstract</code> ..
2928, 2952,		2210, 2780
2953, 2954, 2955,		<code>\@mkauthors</code> 2119, 2121, 2504
2961, 2964, 2971,		<code>\@mkauthors@i</code>
2975, 2983, 2984,	
2990, 2992, 2996,		2508, 2510,
2999, 3007, 3008,		2512, 2514, 2528, 2596
3014, 3016, 3020, 3023		<code>\@mkauthors@ii</code>
<code>\@idxitem</code>		2631
3493		<code>\@mkauthors@iii</code>
<code>\@ifnextchar</code>
1545		2516, 2518,
<code>\@ifnotempty</code>		2520, 2522, 2526, 2643
2084		<code>\@mkauthors@iv</code> 2524, 2696
<code>\@ifnum</code>		<code>\@mkauthorsaddresses</code>
325, 327	
<code>\@ifstar</code>		1568, 2740
463		<code>\@mkbibcitation</code> 2245, 2797
<code>\@ifundefined</code>		<code>\@mkteasers</code> ...
.....		2119, 2768
3345, 3348, 3351,		<code>\@mkttitle</code>
3354, 3357, 3361, 3364		2119, 2364
<code>\@iiiparbox</code>		<code>\@mkttitle@i</code> 2367, 2369,
795		2371, 2373, 2387, 2440
<code>\@indextitlestyle</code> ..		<code>\@mkttitle@ii</code>
3492		2453
<code>\@input</code>		<code>\@mkttitle@iii</code>
547	
<code>\@insideauthorgroupfalse</code>		2375, 2377,
.....		2379, 2381, 2385, 2453
1483, 1535		<code>\@mkttitle@iv</code> ..
<code>\@insideauthorgrouptrue</code>		2383, 2463
.....		<code>\@mktranslatedabstract</code>
1490	
<code>\@journalCode</code>		444, 2790
.....		<code>\@mktranslatedkeywords</code>
1054, 1172, 1216,	
1222, 1236, 1242, 1436		441, 1569
<code>\@journalCode@nr</code> ...		<code>\@mpargs</code>
.....		795
1054, 1128, 1442		<code>\@mparswitchfalse</code> ..
<code>\@journalName</code> ..		741
1130,		<code>\@mpfootins</code>
1134, 1138, 1142,	
1167, 1174, 1178, 1182,		572, 573, 787, 788, 790
1186, 1191, 1195,		<code>\@mpfootnotetext</code> ...
1199, 1203, 1208,		571
1212, 1218, 1224,		<code>\@one</code> .
1228, 1232, 1238,		313, 317, 321, 323,
1244, 1248, 1252,		635, 2857, 2863, 2867
1257, 1261, 1265,		
1269, 1273, 1277,		
1281, 1285, 1289,		
1293, 1297, 1301,		
1305, 1309, 1313,		
1317, 1321, 1325,		
1329, 1333, 1337,		
1341, 1345, 1349,		
1353, 1357, 1362,		
1367, 1371, 1375,		
1380, 1384, 1388,		
1392, 1396, 1400,		
1404, 1408, 1412,		
1416, 1420, 1424,		
1428, 1432, 1443,		
1444, 2182, 3046, 3168		
<code>\@journalNameShort</code> .		
.....		
1131,		
1135, 1139, 1143,		
1147, 1151, 1155,		
1160, 1164, 1169,		
1175, 1179, 1183,		
1187, 1192, 1196,		
1200, 1204, 1209,		
1213, 1219, 1225,		
1229, 1233, 1239,		
1245, 1249, 1253,		
1258, 1262, 1266,		
1270, 1274, 1278,		
1282, 1286, 1290,		
1294, 1298, 1302,		
1306, 1310, 1314,		
1318, 1322, 1326,		
1330, 1334, 1338,		
1342, 1346, 1350,		
1354, 1358, 1363,		
1368, 1372, 1376,		
1381, 1385, 1389,		
1393, 1397, 1401,		
1405, 1409, 1413,		
1417, 1421, 1425,		
1429, 1433, 1444,		
2818, 2957, 2967,		
2978, 3109, 3120, 3131		
<code>\@keywords</code>		
1667,		
1668, 1669, 2220,		

<code>\@nil</code>	332	<code>\@printpermissiontrue</code>		<code>\@teaserfigures</code>	
<code>\@nobreakfalse</code> .	512, 552	. . .	1815, 1824, 1840		2080, 2082, 2769, 2774
<code>\@noskipsecfalse</code> . . .	516	<code>\@printtopmatter</code> . . .		<code>\@tempa</code>	287,
<code>\@noskipsectrue</code>	513	2120, 2319		288, 290, 292, 294,
<code>\@pages@word</code>		<code>\@proofindent</code>			296, 298, 300, 302,
.	2800, 2820, 2827	3371, 3381, 3391		304, 306, 308, 310,
<code>\@par</code>	2132, 2139	<code>\@proofnamefont</code>			312, 314, 316, 318,
<code>\@parboxrestore</code>	576	3370, 3380, 3392		320, 322, 324, 326,
<code>\@parfont</code>		<code>\@received</code> .	1723, 1726,		328, 330, 332, 335,
.	3218, 3222, 3227, 3232	1727, 1729, 1732,		337, 339, 341, 343,
		1733, 1735, 1739, 1740		345, 1519, 1520,
<code>\@permissionCodeOne</code>		<code>\@restonecolfalse</code> . .	3490		1724, 1725, 2488,
.	1132,	<code>\@restonecoltrue</code> . . .	3490		2489, 2609, 3461,
	1136, 1140, 1144,	<code>\@rightskip</code> . . .	3228, 3229		3477, 3478, 3480, 3484
	1148, 1152, 1156,	<code>\@saveabstract</code> .	1674, 1675	<code>\@tempb</code>	
	1161, 1165, 1170,	<code>\@saveteaser</code> . .	2081, 2082		288, 290, 292, 294,
	1176, 1180, 1184,	<code>\@savetranslatedabstract</code>			296, 298, 300, 302,
	1188, 1193, 1197,	444, 445		304, 306, 308, 310,
	1201, 1205, 1210,	<code>\@secntformat</code> .	472, 529		312, 314, 316, 318,
	1214, 1220, 1226,	<code>\@secfont</code>	3206, 3232		320, 322, 324, 326,
	1230, 1234, 1240,	<code>\@secpenalty</code>	461		328, 330, 335, 337,
	1246, 1250, 1254,	<code>\@sect</code>	465, 466		339, 341, 343, 345,
	1259, 1263, 1267,	<code>\@setaddresses</code>	2765		3479, 3480, 3483, 3484
	1271, 1275, 1279,	<code>\@setauthorsaddresses</code>		<code>\@tempboxa</code> .	795, 2329, 2331
	1283, 1287, 1291,	2139, 2285, 2840	<code>\@tempc</code> .	333, 334, 336,
	1295, 1299, 1303,	<code>\@setengagemetadata</code>			338, 340, 342, 344, 346
	1307, 1311, 1315,	2103, 2842	<code>\@tempcnta</code> .	3073, 3074,
	1319, 1323, 1327,	<code>\@setthanks</code> . . .	2132, 2839		3076, 3077, 3079, 3081
	1331, 1335, 1339,	<code>\@shortauthors</code>		<code>\@tempdima</code>	2270,
	1343, 1347, 1351,	2923, 2946, 2954,		2273, 2274, 2276,
	1355, 1359, 1364,		2962, 2972, 2984, 3008		2325, 2326, 2327,
	1369, 1373, 1377,	<code>\@sidebar</code>	945, 946		2333, 2334, 2335,
	1382, 1386, 1390,	<code>\@specialsection</code> . . .			3080, 3081, 3082, 3084
	1394, 1398, 1402,	1571, 2215, 2221, 2289	<code>\@tempskipa</code>	
	1406, 1410, 1414,	<code>\@ssect</code>	464, 530		453, 455, 456, 461,
	1418, 1422, 1426,	<code>\@startPage</code>	1663,		474, 475, 506, 507,
	1430, 1434, 1445, 2194	2320, 2321, 2323, 2920		509, 521, 522, 531, 532
<code>\@permissionCodeTwo</code>		<code>\@startsection</code> .	450,	<code>\@textbottom</code>	796
.	1157,	542, 3203, 3207,		
	1189, 1206, 1255,		3211, 3215, 3219, 3224	<code>\@textsuperscript</code> . .	
	1360, 1365, 1378, 1446	<code>\@starttoc</code>	542	583, 2118, 2123
<code>\@plus</code>	545, 553,	<code>\@subparfont</code>	3257	<code>\@texttop</code>	797
	796, 3204, 3208,	<code>\@subsecfont</code> . .	3210, 3232		
	3212, 3216, 3220,	<code>\@subsubsecfont</code>	3214, 3232	<code>\@thefnmark</code> .	564, 578,
	3225, 3299, 3301,	1476, 1584,		583, 2118, 2123, 2128
	3331, 3333, 3389, 3494	<code>\@subtitle</code> .	2449, 2450, 2458,	<code>\@title</code> . . .	1575, 2233,
<code>\@printcopyrightfalse</code>		2459, 2467, 2468, 2811		2448, 2457, 2466, 2810
.	1829, 1841	<code>\@subtitlefont</code>		<code>\@titlefont</code> .	2390, 2445,
<code>\@printcopyrighttrue</code>		2415, 2450, 2459, 2468		2447, 2454, 2456, 2464
.	1813, 1825	<code>\@subtitlenotes</code>		<code>\@titlenotes</code>	
<code>\@printendtopmatter</code>		1582, 1586, 1589, 2125		1573, 1577, 1580, 2124
.	2250, 2832	<code>\@svsec</code> .	469, 472, 478, 493	<code>\@tochangmeasure</code>	483, 496
<code>\@printpermissionfalse</code>		<code>\@svsechd</code> . . .	491, 519, 539	<code>\@toclevel</code>	467
.	1828	<code>\@teaser</code>	2082, 2770	<code>\@tocline</code> . . .	555, 556, 557
				<code>\@topnum</code>	2247

<code>\ACM@sect@format@null</code>	<code>\advance</code>	<code>\authors</code>
..... 3195, 3196	1029, 1034, 1037,	1497, 1502, 1509,
<code>\ACM@timestamp</code>	1039, 1041, 1043,	2228, 2240, 2242, 2810
..... 2906, 3033, 3149, 3154	1487, 1489, 1767,	<code>\authorsaddresses</code> 14, 1567
<code>\acmArticle</code>	2326, 2334, 2442,	
..... 14, 1609	2625, 2645, 2662,	B
<code>\acmArticleSeq</code>	2698, 2709, 2863,	<code>\balance</code>
..... 15, 1611	2867, 3077, 3079, 3082 3449
<code>\acmArticleType</code>	<code>\affiliation</code>	<code>\baselineskip</code>
..... 20, 1742 10,	.. 2156,
<code>\acmBadge</code>	1534, 2608, 2678, 2723	2864, 3204, 3205,
..... 15, 1662	<code>\and</code>	3208, 3209, 3212,
<code>\acmBadgeL</code> 1474, 1507,	3216, 3220, 3299,
..... 1649	1509, 1524, 1530,	3300, 3301, 3302,
<code>\acmBadgeR</code>	2599, 2604, 2606,	3331, 3332, 3333, 3334
..... 1636, 1662	2617, 2623, 2636,	<code>\baselinestretch</code>
<code>\acmBooktitle</code>	2670, 2689, 2695,	... 3508, 3509, 3511
..... 9, 1461	2717, 2734, 2739, 2755	<code>\begin</code>
<code>\acmCodeLink</code>	<code>\andify</code>	.. 19, 2872, 2902, 3083
20, 1770, 1777 2240,	<code>\beginingroup</code>
<code>\acmConference</code>	2241, 2566, 2569, 2824 476,
.. 9, 1447	<code>\anon</code>	519, 533, 542, 634,
<code>\acmConference@date</code> 24, 2090	2111, 2504, 3174, 3453
..... 1450, 2165,	<code>\anonsuppress (env.)</code>	<code>\bfseries</code>
2998, 3001, 3022, 3025	... 24
<code>\acmConference@name</code>	<code>\apptocmd</code>	1044, 2152, 2393,
1449, 1463, 1464, 1465 3500, 3503	2395, 2397, 2401,
<code>\acmConference@shortname</code>	<code>\AtBeginDocument</code>	2403, 2405, 2407,
1448, 1452, 1453,	.. 78,	2409, 2411, 2413,
1465, 1466, 2165,	95, 227, 638, 646,	2553, 2556, 2808,
2997, 3000, 3021, 3024	1005, 1837, 1843,	3090, 3232, 3233,
<code>\acmConference@venue</code>	1865, 1869, 1873,	3247, 3248, 3250,
..... 1451, 2165,	2852, 2929, 3093, 3197	3251, 3253, 3254,
2998, 3001, 3022, 3025	<code>\AtBeginEnvironment</code>	3255, 3256, 3260,
<code>\acmDataLink</code>	... 876, 879, 888,	3261, 3264, 3265,
... 20, 1777	890, 892, 894, 896,	3267, 3268, 3291, 3323
<code>\acmdefinition</code>	898, 900, 902, 904, 906	<code>\bgroup</code>
..... 3330	<code>\AtBeginMaketitle</code>	.. 449, 946, 950,
<code>\acmDOI</code>	32, 2099	961, 967, 1542,
..... 15, 1627	<code>\AtEndDocument</code>	1569, 2214, 2220,
<code>\acmISBN</code>	2261, 2635, 2672,
..... 15, 1625 874, 1669,	2675, 2736, 2745,
<code>\acmJournal</code>	1693, 1738, 1806,	2770, 2780, 2797, 2809
..... 9, 1440	2255, 2760, 3446, 3509	<code>\bibfont</code>
<code>\acmMonth</code>	<code>\AtEndEnvironment</code> 285
..... 14, 1615	882, 885	<code>\bibfont</code>
<code>\acmNumber</code>	<code>\AtEndPreamble</code> 285
..... 14, 1607	.. 611,	<code>\bibliographystyle</code>
<code>\acmplain</code>	864, 3342, 3396, 3462	.. 644
..... 3298	<code>\author</code>	<code>\bibsection</code>
<code>\acmPrice</code> 10, 281
15, 1621, 1837,	1484, 2108, 2109, 2804	<code>\bibstyle</code>
1843, 1865, 1869, 1873	<code>\author@bx</code>	309, 311, 353, 649
<code>\acmSubmissionID</code>	2631, 2637, 2640	<code>\bibstyle@acmauthoryear</code>
15, 1623	<code>\author@bx@sep</code> 359
<code>\acmVolume</code> 2633, 2640,	<code>\bibstyle@acmnumeric</code>
..... 14, 1605	2645, 2662, 2698, 2709	365
<code>\acmYear</code>	<code>\author@bx@wd</code>	<code>\bigskip</code>
..... 14, 1613	1740, 2279, 2280,
<code>\addcontentsline</code> 2632, 2635,	2282, 2285, 2357,
283,	2644, 2645, 2647,	2452, 2462, 2470,
485, 498, 2782, 3455	2653, 2655, 2657,	2695, 2739, 2770, 2835
<code>\additionalaffiliation</code>	2659, 2662, 2697,	<code>\box</code>
..... 11, 1541	2698, 2700, 2706, 2709 984, 2341,
<code>\addpenalty</code>	<code>\authornote</code>	2343, 2345, 2347,
..... 461	2349, 2351, 2353,
<code>\addresses</code>	.. 14, 1541, 1593, 2805	
1492, 1494, 1499,	<code>\authornotemark</code>	
1506, 1537, 1557,	.. 14, 1599	
1595, 1601, 1603,		
2628, 2695, 2739, 2758		
<code>\addto</code>		
.. 384, 395, 403, 411		
<code>\addtocounter</code>		
.. 589, 1800		
<code>\addtolength</code>		
1013, 1014,		
1015, 1019, 1020, 2864		
<code>\addvspace</code>		
..... 461, 553		

	2355, 2357, 2359, 2361, 2640, 3043, 3165		
C			
\c@footnote	2116		
\c@secnumdepth	468, 482, 486, 495, 499		
\captionenglish	384		
\captionsetup	910, 912, 914, 916, 925, 927, 930, 932, 935, 937, 947, 953, 962, 2771		
\captionsfrench	395		
\captionsgerman	403		
\captionsspanish	411		
\ccdesc@parse@finish	1811		
\ccsdesc	16, 1782		
\ccsdesc@parse	1783, 1784		
\ccsdesc@parse@end	1783, 1811		
\ccsdesc@parse@finish	1805, 1811		
CCSXML (env.)	16		
\centering	546, 579, 665, 674, 954, 963, 2454, 2456, 2637, 2694, 3089		
\changes	146		
\cite	627, 628, 639, 643		
\citeA	633		
\citealt	632		
\citeANP	629		
\citeauthor	629		
\citeN	627		
\citename	640		
\citeNN	630		
\citeNP	632		
\citete	628		
\citestyle	25, 351, 371		
\citeyear	631		
\citeyearNP	631		
\citeyearpar	630, 643		
\city	11, 1548, 2479, 2751		
\ClassError	35, 422, 446, 1438, 1540, 1676, 1686, 1692, 1706, 1757, 1930, 2592, 2803, 3510		
\ClassInfo	161, 260, 1436, 1683, 1685, 1689, 1691, 1703, 1705, 1708, 1923, 1927		
\ClassWarning	26, 171, 177, 183, 832, 835,		
	838, 884, 887, 957, 1485, 1554, 1665, 1709, 2776, 3500, 3503		
\ClassWarningNoLine	875, 1671, 1695, 1808, 2586, 2589, 2762		
\cleaders	2476		
\clearpage	2332		
\clubpenalty	518, 524		
\CodelineIndex	16		
\Collect@Body	443, 945, 949, 960, 1674, 2081		
\color	2092, 2154, 2862, 2866, 3040, 3162		
\color@begingroup	566, 579		
\color@endbox	982		
\color@endgroup	569, 582, 793		
\colorbox	1766, 3040, 3162		
\colorlet	1746, 1748, 1750, 1752, 1754		
\columnsep	3491		
\columnseprule	3491		
\columnwidth	575, 776, 968, 2697, 2736		
\contentsnamefont	546		
\copy	2476		
\copyright	2170		
\copyrightpermissionfootnoterule	775		
\copyrightyear	18, 2078		
\country	11, 1551, 2479, 2754		
\csname	353, 481, 483, 487, 494, 496, 500, 529, 549, 550, 564, 578, 1501, 1508, 1561, 1564, 1787, 1788, 1790, 1791, 1792, 1793, 1794, 1797, 1799, 2237, 2239, 3175, 3198		
\CurrentOption	148, 149, 150, 151, 152, 158, 159		
D			
\day	2918		
\DeclareNewFootnote	779, 781		
\DeclareOptionX	38, 148, 149, 150, 151, 152, 154, 158, 159		
\DeclareRobustCommand	633, 3194		
\DeclareTextFontCommand	865		
\def	24, 38, 147, 153, 237, 239, 241, 243, 245, 247, 249, 251, 253, 255, 257, 288, 290, 292, 294, 296, 298, 300, 302, 304, 306, 308, 310, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 324, 326, 328, 330, 331, 335, 337, 339, 341, 343, 345, 433, 436, 439, 442, 445, 450, 466, 491, 505, 529, 530, 539, 542, 555, 556, 557, 558, 560, 571, 583, 589, 590, 591, 592, 593, 613, 644, 775, 782, 784, 796, 946, 950, 961, 967, 970, 974, 977, 995, 996, 997, 998, 1028, 1033, 1036, 1038, 1040, 1042, 1130, 1131, 1132, 1134, 1135, 1136, 1138, 1139, 1140, 1142, 1143, 1144, 1146, 1147, 1148, 1150, 1151, 1152, 1154, 1155, 1156, 1157, 1159, 1160, 1161, 1163, 1164, 1165, 1167, 1169, 1170, 1174, 1175, 1176, 1178, 1179, 1180, 1182, 1183, 1184, 1186, 1187, 1188, 1189, 1191, 1192, 1193, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1212, 1213, 1214, 1218, 1219, 1220, 1224, 1225, 1226, 1228, 1229, 1230, 1232, 1233, 1234, 1238, 1239, 1240, 1244, 1245, 1246, 1248,		

1249, 1250, 1252,	1574, 1582, 1583,	3179, 3181, 3191,
1253, 1254, 1255,	1592, 1593, 1605,	3195, 3202, 3228,
1257, 1258, 1259,	1607, 1609, 1611,	3232, 3233, 3234,
1261, 1262, 1263,	1613, 1615, 1617,	3235, 3241, 3242,
1265, 1266, 1267,	1621, 1623, 1625,	3244, 3245, 3247,
1269, 1270, 1271,	1627, 1634, 1635,	3248, 3250, 3251,
1273, 1274, 1275,	1663, 1665, 1667,	3253, 3254, 3255,
1277, 1278, 1279,	1675, 1680, 1711,	3256, 3257, 3260,
1281, 1282, 1283,	1723, 1724, 1759,	3261, 3264, 3265,
1285, 1286, 1287,	1765, 1770, 1776,	3267, 3268, 3271,
1289, 1290, 1291,	1784, 1785, 1811,	3272, 3277, 3278,
1293, 1294, 1295,	1875, 1878, 1879,	3279, 3280, 3289,
1297, 1298, 1299,	1881, 1920, 1921,	3290, 3291, 3292,
1301, 1302, 1303,	1937, 2062, 2078,	3309, 3310, 3311,
1305, 1306, 1307,	2080, 2082, 2099,	3312, 3321, 3322,
1309, 1310, 1311,	2100, 2101, 2105,	3323, 3324, 3370,
1313, 1314, 1315,	2118, 2123, 2132,	3371, 3380, 3381,
1317, 1318, 1319,	2139, 2230, 2260,	3459, 3461, 3477,
1321, 1322, 1323,	2289, 2319, 2364,	3478, 3479, 3483, 3490
1325, 1326, 1327,	2390, 2415, 2440,	<code>\define@boolkey</code>
1329, 1330, 1331,	2453, 2463, 2472,	. . . 51, 59, 67, 75,
1333, 1334, 1335,	2479, 2480, 2482,	84, 92, 104, 108,
1337, 1338, 1339,	2483, 2485, 2486,	112, 120, 128, 136,
1341, 1342, 1343,	2488, 2493, 2494,	1539, 1681, 1687, 1701
1345, 1346, 1347,	2498, 2499, 2501,	<code>\define@choicekey</code> . .
1349, 1350, 1351,	2502, 2504, 2532,	. 32, 1054, 1742, 1818
1353, 1354, 1355,	2533, 2537, 2538,	<code>\define@cmdkey</code> 1707
1357, 1358, 1359,	2541, 2542, 2544,	<code>\definecolor</code>
1360, 1362, 1363,	2545, 2547, 2548,	. . . 653, 654, 655,
1364, 1365, 1367,	2550, 2551, 2553,	656, 657, 658, 659, 660
1368, 1369, 1371,	2554, 2556, 2557,	<code>\department</code>
1372, 1373, 1375,	2559, 2560, 2562,	. 11, 1545, 2479, 2753
1376, 1377, 1378,	2563, 2565, 2567,	<code>\Description</code> 23, 873
1380, 1381, 1382,	2572, 2579, 2584,	<code>\description</code> 1045
1384, 1385, 1386,	2596, 2597, 2598,	<code>\descriptionlabel</code> . .
1388, 1389, 1390,	2600, 2607, 2608, 1044, 1047
1392, 1393, 1394,	2609, 2635, 2636,	<code>\detokenize</code> 1485
1396, 1397, 1398,	2643, 2665, 2671,	<code>\dimexpr</code> . . . 965, 984,
1400, 1401, 1402,	2678, 2696, 2712,	2270, 3030, 3039, 3161
1404, 1405, 1406,	2718, 2723, 2740,	<code>\divide</code> 2647, 2653, 2655,
1408, 1409, 1410,	2746, 2747, 2748,	2657, 2659, 2700, 2706
1412, 1413, 1414,	2750, 2751, 2752,	<code>\do</code> 287, 613
1416, 1417, 1418,	2754, 2755, 2756,	<code>\do@url@hyp</code> 613
1420, 1421, 1422,	2757, 2765, 2766,	<code>\DocInput</code> 20
1424, 1425, 1426,	2767, 2768, 2770,	<code>\documentclass</code> 8, 427, 429
1428, 1429, 1430,	2780, 2790, 2797,	<code>\dots</code> 2199
1432, 1433, 1434,	2800, 2801, 2802,	<code>\dp</code> 2326, 2334
1440, 1442, 1443,	2803, 2806, 2810,	
1444, 1445, 1446,	2832, 2839, 2840,	
1461, 1468, 1469,	2841, 2842, 2848,	E
1470, 1476, 1519,	2858, 2869, 2876,	<code>\edef</code> 148, 149,
1541, 1542, 1543,	2923, 2928, 2934,	150, 151, 152, 467, 2063
1544, 1545, 1546,	3059, 3066, 3071,	<code>\editor</code> 9, 1470
1559, 1567, 1573,	3073, 3173, 3177,	<code>\egroup</code> 449,
		794, 948, 959, 963,

975, 981, 1552,	2781, 2785, 2793,	translatedabstract
1572, 2216, 2222,	2800, 2806, 2811, 21
2288, 2639, 2673,	2812, 2821, 2823,	\everypar 459,
2676, 2739, 2759,	2830, 2915, 2926,	514, 525, 2784, 2792
2771, 2789, 2810, 2831	2927, 2937, 2948,	\excludacomment . 1779,
	2956, 2966, 2977,	3465, 3467, 3471, 3472
\else 54,	2981, 2988, 2991,	\ExecuteOptionsX ...
62, 70, 79, 87, 99,	2993, 2995, 3005,	... 50, 58, 66, 74,
115, 123, 131, 141,	3012, 3015, 3017,	83, 91, 103, 107,
197, 231, 333, 354,	3019, 3047, 3048,	111, 119, 127, 135, 145
375, 382, 387, 398,	3074, 3104, 3108,	\expandafter 332, 334,
406, 414, 460, 467,	3119, 3130, 3137,	646, 795, 1499,
470, 482, 486, 490,	3142, 3150, 3153,	1500, 1506, 1507,
495, 499, 511, 523,	3169, 3170, 3178,	1561, 1564, 1787,
538, 621, 637, 643,	3202, 3461, 3466,	1788, 1790, 1791,
645, 668, 670, 787,	3473, 3482, 3486, 3509	1797, 1799, 3175, 3198
851, 856, 882, 885,	\email 10, 1553,	
915, 955, 1431,	2607, 2671, 2718, 2757	F
1457, 1463, 1465,	\emph 2182, 2184	\familydefault 867
1472, 1488, 1495,	\empty 2935	\fancyfoot 2949,
1498, 1504, 1505,	\EnableCrossrefs 18	2957, 2967, 2978,
1515, 1518, 1523,	\end ... 21, 2874, 2904, 3091	2982, 3006, 3033,
1526, 1529, 1536,	\end@ACM@color@frame 2255	3044, 3045, 3103,
1556, 1579, 1588,	\end@dblfloat 973	3105, 3109, 3120,
1594, 1602, 1642,	\end@float 975	3131, 3140, 3145,
1655, 1669, 1684,	\endcsname 352, 353, 481,	3149, 3154, 3166, 3167
1690, 1693, 1704,	483, 487, 494, 496,	\fancyhead . 2944, 2945,
1715, 1718, 1728,	500, 529, 549, 550,	2946, 2947, 2952,
1731, 1734, 1739,	564, 578, 1501,	2953, 2954, 2955,
1773, 1796, 1801,	1508, 1562, 1565,	2961, 2963, 2964,
1802, 1803, 1806,	1787, 1788, 1790,	2971, 2973, 2974,
1925, 1929, 2087,	1791, 1792, 1793,	2975, 2983, 2984,
2093, 2119, 2130,	1794, 1797, 1799,	2986, 2987, 2990,
2134, 2135, 2136,	2237, 2239, 3175, 3198	2992, 2996, 2999,
2148, 2149, 2157,	\enddescription 1051	3007, 3008, 3010,
2160, 2161, 2164,	\endgroup ... 480, 519,	3011, 3014, 3016,
2171, 2176, 2183,	537, 552, 2207,	3020, 3023, 3038,
2188, 2191, 2192,	2530, 3177, 3179, 3457	3043, 3101, 3102,
2195, 2197, 2198,	\endlist 1049, 1051	3113, 3114, 3115,
2199, 2200, 2211,	\endMakeFramed 1769	3116, 3124, 3125,
2214, 2219, 2220,	\endminipage 784	3126, 3127, 3135,
2224, 2267, 2279,	\endtrivlist 3394	3136, 3138, 3139,
2282, 2285, 2322,	\enspace 3272	3143, 3144, 3160, 3165
2449, 2458, 2467,	environments:	\fancyheadoffset 3030,
2473, 2474, 2489,	abstract 18	3037, 3117, 3128, 3159
2491, 2492, 2493,	acks 24	\fancyhf 2931, 3095
2495, 2497, 2498,	anonsuppress 24	\fancypagestyle 2930, 3094
2501, 2568, 2585,	CCSXML 16	\fi 56, 64, 72, 81,
2588, 2591, 2603,	marginfigure 34	89, 101, 117, 125,
2609, 2616, 2637,	marginable 34	133, 143, 156, 175,
2648, 2658, 2667,	printonly 24	181, 194, 199, 228,
2674, 2683, 2701,	screenonly 24	233, 258, 259, 271,
2705, 2714, 2720,	sidebar 34	276, 289, 291, 293,
2728, 2742, 2744,	teaserfigure 18	295, 297, 299, 301,
2760, 2769, 2774,		

303, 305, 307, 309,
311, 313, 315, 317,
319, 321, 323, 325,
327, 329, 331, 336,
338, 340, 342, 344,
346, 347, 356, 358,
372, 377, 380, 389,
393, 400, 408, 416,
419, 432, 447, 451,
457, 462, 467, 473,
484, 488, 497, 501,
503, 526, 527, 540,
551, 570, 610, 614,
623, 641, 643, 647,
650, 677, 678, 679,
757, 773, 791, 817,
829, 860, 861, 862,
868, 875, 884, 887,
941, 942, 958, 972,
976, 1003, 1435,
1454, 1460, 1466,
1467, 1475, 1491,
1496, 1503, 1510,
1511, 1516, 1517,
1525, 1531, 1532,
1533, 1538, 1558,
1581, 1591, 1598,
1604, 1620, 1648,
1661, 1673, 1677,
1686, 1692, 1700,
1706, 1720, 1721,
1730, 1736, 1737,
1741, 1755, 1762,
1775, 1795, 1803,
1804, 1810, 1831,
1834, 1838, 1844,
1847, 1850, 1853,
1856, 1859, 1862,
1866, 1870, 1874,
1919, 1935, 1936,
2077, 2089, 2095,
2098, 2109, 2110,
2119, 2121, 2133,
2140, 2141, 2142,
2143, 2147, 2155,
2158, 2159, 2166,
2167, 2168, 2173,
2185, 2190, 2195,
2199, 2200, 2201,
2202, 2203, 2204,
2205, 2206, 2208,
2212, 2217, 2218,
2223, 2226, 2227,
2246, 2257, 2277,
2278, 2281, 2284,
2285, 2315, 2324,
2336, 2362, 2388,
2414, 2439, 2443,
2451, 2460, 2469,
2477, 2490, 2491,
2493, 2495, 2497,
2498, 2501, 2503,
2529, 2564, 2571,
2587, 2590, 2594,
2605, 2621, 2622,
2626, 2637, 2660,
2661, 2669, 2677,
2688, 2707, 2708,
2716, 2722, 2733,
2742, 2744, 2764,
2777, 2779, 2787,
2789, 2795, 2800,
2807, 2811, 2825,
2828, 2829, 2830,
2868, 2875, 2901,
2905, 2917, 2922,
2926, 2927, 2936,
2938, 2939, 2944,
2945, 2950, 2959,
2969, 2980, 2982,
2991, 2993, 3002,
3003, 3004, 3006,
3015, 3017, 3026,
3027, 3028, 3031,
3034, 3047, 3048,
3049, 3072, 3091,
3103, 3106, 3112,
3123, 3134, 3140,
3141, 3145, 3146,
3152, 3155, 3156,
3169, 3170, 3171,
3189, 3200, 3202,
3270, 3275, 3297,
3329, 3367, 3386,
3417, 3418, 3443,
3444, 3450, 3461,
3469, 3475, 3478,
3488, 3489, 3490, 3512
\firstpagestyle 3093
\floatname 944
\flushbottom 803, 805,
807, 809, 811, 814, 816
\footnote 2803
\footnotemark 593, 1575,
1584, 2766, 2767, 2801
\footnoterule 782
\footnotesep 568, 581
\footnotesize 574, 2914,
2928, 2949, 2957,
2967, 2978, 2982,
2990, 2996, 3006,
3045, 3105, 3109,
3120, 3131, 3140,
3145, 3151, 3167, 3497
\footnotetext . . 1578,
1580, 1587, 1590, 1597
\footnotetextauthorsaddresses
. 2131, 2138
\footnotetextcopyrightpermission
. 2146, 2150
\footrulewidth
2933, 3036, 3097, 3158
\foreignlanguage 435, 438
\format 32
\FrameCommand 1765
\FrameRestore 1768
\FrameSep 2271
\frenchspacing 3513
\fulltextwidth
. 964, 968, 984

G
\g@addto@macro
157, 435, 438, 441,
449, 1474, 1506,
1509, 1524, 1530,
1537, 1557, 1575,
1577, 1580, 1584,
1586, 1589, 1595,
1596, 1601, 1603,
1643, 1656, 1729,
1735, 1774, 1792,
1799, 2082, 2086,
2088, 2099, 2102,
2604, 2617, 2668,
2675, 2684, 2715,
2721, 2729, 2766, 2767
\gdef 156,
1448, 1449, 1450,
1451, 1453, 1461,
1471, 1473, 1494,
1497, 1499, 1502,
1514, 1522, 1528,
1561, 1564, 1638,
1651, 1678, 1710,
1727, 1733, 1772,
1788, 1790, 1791,
1797, 2321, 2602,
2606, 2611, 2641,
2642, 2663, 2664,
2666, 2670, 2672,
2679, 2710, 2711,

	2713, 2717, 2719,	\if@ACM@acmcp	168, 273,	2956, 2966, 2977,
	2724, 2749, 2750, 2755		1760, 2134, 2149,	2985, 3009, 3104,
\geometry . . .	683, 686,		2219, 2253, 2441,	3108, 3119, 3130, 3150
	693, 700, 707, 714,		2624, 3035, 3157, 3273	\if@ACM@pbalance
	721, 728, 735, 744, 751	\if@ACM@acmthm .	67, 3343	108, 3397
\getrefnumber . .	1670,	\if@ACM@affiliation@obeypunctuation	1687, 2244	
	1694, 1807, 2267, 2800		1539,	\if@ACM@printacmref
\global .	513, 516, 552,		2474, 2491, 2493,	\if@ACM@printccs
	572, 873, 883, 886,		2495, 2496, 2498, 2501	1681, 2213
	956, 983, 1441,	\if@ACM@anonymous . .		\if@ACM@printfolios
	1455, 1487, 1489,		120, 1493,	1701, 2936, 2938,
	1490, 1535, 2242,		1505, 1512, 1536,	2944, 2945, 2982,
	2243, 2247, 2249,		1556, 1576, 1585,	3006, 3103, 3140, 3145
	2263, 2276, 2483,		1594, 2085, 2091,	\if@ACM@review
	2485, 2490, 2494,		2107, 2136, 2924, 3470	75, 2853, 2870, 2877
	2499, 2502, 2580,	\if@ACM@authordraft		\if@ACM@screen
	2581, 2582, 2599,		136, 661, 2151	51, 615, 3463
	2623, 2627, 2637,	\if@ACM@authorversion		\if@ACM@sigchiamode
	2689, 2692, 2734,		84, 2157, 2177	165, 559,
	2772, 2775, 2863,	\if@ACM@badge	1629	669, 866, 966, 973,
	2867, 3398, 3422,	\if@ACM@balance		2119, 2121, 2637, 3029
	3424, 3426, 3438, 3442		104, 3419, 3447	\if@ACM@timestamp
\grantnum	25, 3460	\if@ACM@citypresent		128, 2906, 3032, 3147
\grantsponsor . .	25, 3459		2575, 2588	\if@ACM@urlobonhyphens
		\if@ACM@countrypresent		59, 612
			2577, 2591	\if@acmowned
		\if@ACM@engage .	166,	1816
			378, 391, 1926,	\if@Description@present
			2162, 2208, 2989, 3013	869,
		\if@ACM@instpresent		882, 885, 955, 2774
			2573, 2585	\if@filesw
		\if@ACM@journal		548, 648
			163, 229, 373,	\if@insideauthorgroup
			385, 396, 404, 412,	1482, 1488
			911, 1457, 1716,	\if@nobreak
			2481, 2760, 2783, 2791	458
		\if@ACM@journal@bibstrip		\if@noskipsec . .
			164,	451, 515
			2137, 2161, 2181,	\if@printcopyright
			2193, 2817, 2941, 3098	1812, 2169
\hskip . .	478, 492, 522,	\if@ACM@journal@bibstrip		\if@printpermission
	535, 539, 2476, 3391		164,	1814, 2158
\hspace	1644,	\if@ACM@maketitle@typeset		\if@twocolumn .
	1657, 1765, 1948,		445, 1052, 1675	3448, 3490
	1959, 1968, 1993,	\if@ACM@manuscript .		\if@undescrbed@images
	2005, 2026, 2640, 2694		162,	871, 874
\ht	2325, 2333		268, 1713, 2160, 2174	\IfBeginWith
\Huge .	2399, 2401, 2403,	\if@ACM@natbib		1560
	2405, 2407, 2409, 2411		112, 279, 370, 626	\ifcase .
\hypersetup		\if@ACM@natbib@override		201, 235, 596,
	616, 622, 624, 2231		112	681, 760, 798, 918,
\hyphenpenalty	3496	\if@ACM@newfonts	830, 841	987, 1128, 1617,
			92, 670,	1744, 1882, 1938,
			1669, 1693, 1806,	2292, 2339, 2365,
			1922, 2144, 2192,	2391, 2416, 2506,
			2760, 2812, 2948,	2534, 2649, 2702,
				2878, 2942, 3060,
				3099, 3237, 3281,
				3313, 3372, 3399, 3420
				\ifcscname
				352
				\ifdim
				455, 475, 507, 532,
				2273, 2327, 2335, 2865

I

<code>\IfEq</code>	2061, 2067, 2068, 2069, 2070, 2071, 2072, 2073, 2074	2991, 2993, 3015, 3017, 3047, 3048, 3169, 3170, 3175,	<code>\labelsep</code>	1006, 1014, 1019, 1029, 1034, 1037, 1039, 1041, 1043, 3391	
<code>\IfFileExists</code>	832, 835, 838	3198, 3202, 3461, 3478, 3480, 3484, 3509	<code>\labelwidth</code>	1029, 1034, 1037, 1039, 1041, 1043, 1046	
<code>\IfInteger</code>	1708		<code>\LARGE</code>	2393, 2395, 2397, 2413, 2424, 2426, 2428, 2430, 2432, 2436, 2541, 2544, 2559, 3090	
<code>\ifluatex</code>	852	<code>\ifxetex</code>	847		
<code>\ifNAT@numbers</code>	643	<code>\ignorespaces</code>		528, 568, 581, 873, 1543, 1544, 1546, 1559, 2479, 2480, 2482, 2484, 2485, 2486, 2487, 2491, 2748, 2788, 2796, 2802, 2810, 3392	
<code>\ifnum</code>	170, 176, 182, 195, 467, 468, 482, 486, 495, 499, 1670, 1694, 1801, 1802, 1803, 1807, 1827, 1832, 1835, 1839, 1845, 1848, 1851, 1854, 1857, 1860, 1863, 1867, 1871, 2109, 2145, 2267, 2646, 2699, 2741, 2743, 2800, 3074, 3076, 3148	<code>\immediate</code>	550, 649	<code>\Large</code>	2532, 2550, 3247, 3248, 3250, 3251, 3253, 3267, 3268
<code>\ifPDFTeX</code>	818	<code>\includecomment</code>		<code>\large</code>	2152, 2537, 2542, 2545, 2560, 2562, 3241, 3242, 3244, 3245
<code>\IfSubStr</code>	1485, 1554	<code>\includegraphics</code>		<code>\lastbox</code>	517, 2784, 2792
<code>\ifvmode</code>	2473		1641, 1647, 1654, 1660, 2064, 2265	<code>\leaders</code>	2465
<code>\ifvoid</code>	787	<code>\indent</code>	3371	<code>\leavevmode</code>	451, 2465, 2693
<code>\ifx</code>	155, 234, 288, 290, 292, 294, 296, 298, 300, 302, 304, 306, 308, 310, 312, 314, 316, 318, 320, 322, 324, 326, 328, 330, 335, 337, 339, 341, 343, 345, 381, 421, 645, 1452, 1463, 1465, 1470, 1492, 1495, 1513, 1515, 1520, 1521, 1527, 1600, 1637, 1650, 1669, 1725, 1726, 1732, 1739, 1771, 1787, 1796, 1806, 2096, 2130, 2135, 2186, 2195, 2198, 2199, 2200, 2211, 2214, 2220, 2224, 2279, 2282, 2285, 2320, 2449, 2458, 2467, 2489, 2568, 2601, 2609, 2610, 2665, 2671, 2678, 2712, 2718, 2723, 2761, 2769, 2781, 2806, 2811, 2823, 2830, 2915, 2926, 2935,	<code>\input</code>	819	<code>\leftmargin</code>	1028, 1033, 1036, 1038, 1040, 1042
		<code>\InputIfFileExists</code> . . .	25	<code>\leftmargini</code>	1012, 1013, 1014, 1015, 1028, 1029
		<code>\institution</code>		<code>\leftmarginii</code>	1018, 1019, 1020, 1021, 1033, 1034
		<code>\interfootnotelinepenalty</code>		<code>\leftmarginiii</code>	1021, 1022, 1036, 1037
			562	<code>\leftmarginiv</code>	1022, 1023, 1038, 1039
		<code>\interlinepenalty</code>		<code>\leftmarginv</code>	1023, 1024, 1040, 1041
			479, 536, 562	<code>\leftmarginvi</code>	1024, 1042, 1043
		<code>\item</code>	3391, 3493	<code>\leftskip</code>	2464, 2737, 3230
		<code>\itshape</code>		<code>\let</code>	309, 311, 323, 325, 327, 353, 469, 585, 586, 627, 628, 629, 630, 631, 632, 635, 639, 797, 863, 877, 878, 880, 881, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 901, 902, 903, 904, 905, 906, 907, 946, 947, 951, 952, 961, 962, 967, 968, 969, 1032, 1047, 1051, 1547, 1548, 1549, 1550, 1551, 1662, 1668,
			2163, 2165, 3234, 3235, 3256, 3257, 3277, 3289, 3311, 3380		
		J			
		<code>\jobname</code>	547, 550		
		K			
		<code>\kern</code>	775, 776, 782, 783, 2465		
		<code>\keywords</code>	16, 1667		
		<code>\keywordsname</code>			
			374, 376, 386, 388, 397, 399, 405, 407, 413, 415, 1571, 2221		
		L			
		<code>\l@section</code>	555		
		<code>\l@subsection</code>	555, 556		
		<code>\l@subsubsection</code>	557		
		<code>\labelenumi</code>	995		
		<code>\labelenumii</code>	996		
		<code>\labelenumiii</code>	997		
		<code>\labelenumiv</code>	998		

1777, 1780, 2097,		
2112, 2113, 2114,		
2115, 2127, 2128,		
2129, 2132, 2139,		
2228, 2242, 2243,		
2290, 2291, 2316,		
2317, 2500, 2599,		
2623, 2689, 2695,		
2734, 2739, 2798,		
2799, 2833, 2834,		
2836, 2837, 2845,		
2846, 2847, 2849,		
2850, 2851, 3180,		
3182, 3184, 3185,		
3187, 3193, 3196,		
3199, 3493, 3498,		
3499, 3506, 3507, 3508		
\libertineLF	865	
\lineskip	2694, 2738	
\linespacing	545, 546	
\liningnums	863	
\list	1045	
\listisep	1026, 1027, 1031	
\listparindent	1030	
\LoadClass	261	
\long 445, 560, 571, 946,		
950, 961, 1675,		
1678, 1680, 2082, 2839		
\loop	2328, 2862, 3075	
\LTX@adddotafter	3199, 3202	
M		
\makeatletter	542	
\makebox	2152, 3038,	
3043, 3084, 3160, 3165		
\MakeFramed	1767	
\makelabel	1047	
\MakeTextUppercase	2602, 2604, 3232,	
3241, 3244, 3247,		
3250, 3260, 3264, 3267		
\maketitle	19, 2105	
\MakeUppercase	3186	
\marginfigure	949	
marginfigure (env.)	34	
\marginpar 560, 948, 954, 963		
\marginparsep	965, 3030	
\marginparwidth	965, 3030	
\margintable	960	
margintable (env.)	34	
\mathchardef	2673, 2676	
\mbox	331	
\mdseries	2418, 2420,	
2422, 2426, 2428,		
2430, 2432, 2434,		
2436, 2438, 2554, 2557		
\medskip	2294, 2296,	
2298, 2300, 2627,		
2629, 2693, 2778, 2808		
\MessageBreak	172, 178, 184, 185,	
186, 187, 188, 189,		
190, 191, 192, 423,		
424, 425, 426, 428,		
430, 1696, 1697,		
1698, 1757, 1931, 1932		
\metadata@authors	2228, 2229, 2232	
\mktitle@bx 2104, 2325,		
2326, 2329, 2333,		
2334, 2341, 2343,		
2345, 2347, 2349,		
2351, 2353, 2355,		
2357, 2359, 2361,		
2445, 2454, 2464,		
2627, 2692, 2693, 2772		
\month	1616, 2918	
\moveleft	983	
\multiply	3081	
N		
\NAT@setcites	349	
\NAT@aysep	340	
\NAT@citetp	635	
\NAT@close	289, 291, 293, 295, 338	
\NAT@cmprs	317, 319, 321	
\NAT@cmt	344	
\NAT@ctype	635	
\NAT@find@eq	332	
\NAT@fullfalse	635	
\NAT@longnamestrue	329	
\NAT@merge	323, 325, 327	
\NAT@nmfmt	331	
\NAT@numbersfalse	303	
\NAT@numberstrue 305, 307		
\NAT@open	289,	
291, 293, 295, 336, 635		
\NAT@partrue	635	
\NAT@rem@eq	334	
\NAT@sep 297, 299, 301, 346		
\NAT@sort	313, 315, 321	
\NAT@superfalse	305	
\NAT@supertrue	307	
\NAT@swafalse	634	
\NAT@up	331	
\NAT@yrsep	342	
\NeedsTeXFormat	1	
\newblock	636	
\newbox	2104, 2259, 2471, 2631	
\newcommand	359, 365,	
420, 434, 437, 440,		
642, 873, 1447,		
1534, 1569, 1599,		
1636, 1649, 1724,		
1782, 1877, 2090,		
2487, 2496, 2913,		
3219, 3451, 3460, 3476		
\newcount	1478, 1480, 2856	
\newcounter 1781, 2909, 2911		
\newdimen 277, 964, 1004,		
2632, 3053, 3055, 3057		
\newenvironment	443,	
949, 960, 1764, 2081		
\newfloat	943	
\newif	162, 163, 164,	
165, 166, 168, 830,		
869, 871, 1052,		
1482, 1812, 1814,		
1816, 2573, 2575, 2577		
\newlength	1629, 1631, 1632, 2855	
\newsavebox	2854	
\newskip	1026, 2633	
\newtheorem	3346, 3349, 3352,	
3355, 3358, 3362, 3365		
\newtheoremstyle	3298, 3330	
\newwrite	549	
\next	3177, 3179, 3189	
\nobreak	508, 2808	
\noindent	558, 1572,	
1740, 2129, 2216,		
2222, 2294, 2296,		
2298, 2300, 2331,		
2338, 2445, 2447,		
2450, 2459, 2465,		
2466, 2468, 2566,		
2627, 2628, 2692,		
2738, 2772, 2773,		
2808, 2809, 2842, 3381		
\noindentparagraph	2306, 3219	
\nolinkurl	2673,	
2676, 2719, 2721, 2757		
\normalbaselines	2636	
\normalcolor	789	

<code>\normalfont</code>	583,	1247, 1251, 1256,	2891, 2893, 2895,
	1740, 2123, 2533,	1260, 1264, 1268,	2897, 2899, 2951,
	2538, 2547, 2548,	1272, 1276, 1280,	2960, 2970, 3062,
	2550, 2551, 2563,	1284, 1288, 1292,	3067, 3107, 3118,
	2859, 3292, 3309,	1296, 1300, 1304,	3129, 3239, 3240,
	3321, 3324, 3389, 3513	1308, 1312, 1316,	3243, 3246, 3249,
<code>\normalparindent</code> . . .	<u>774</u>	1320, 1324, 1328,	3252, 3258, 3262,
<code>\normalsize</code>		1332, 1336, 1340,	3266, 3269, 3283,
	2415, 2533, 2547,	1344, 1348, 1352,	3284, 3285, 3286,
	2548, 2551, 2860, 3513	1356, 1361, 1366,	3287, 3288, 3293,
<code>\num@authorgroups</code> . .		1370, 1374, 1379,	3294, 3295, 3296,
 <u>1478</u> ,	1383, 1387, 1391,	3315, 3316, 3317,
	1489, 2109, 2649,	1395, 1399, 1403,	3318, 3319, 3320,
	2653, 2655, 2702, 2743	1407, 1411, 1415,	3325, 3326, 3327,
<code>\num@authors</code>		1419, 1423, 1427,	3328, 3374, 3375,
	<u>1480</u> , 1487, 1501,	1617, 1618, 1619,	3376, 3377, 3378,
	1508, 1562, 1565, 2741	1747, 1749, 1751,	3379, 3382, 3383,
<code>\number</code>	467	1753, 1883, 1885,	3384, 3385, 3401,
<code>\numberline</code>	487, 500	1888, 1890, 1891,	3402, 3403, 3405,
<code>\numexpr</code> .	2908, 2910, 2912	1893, 1895, 1897,	3407, 3409, 3411,
<code>\xandlist</code>	2229	1900, 1903, 1906,	3413, 3414, 3416,
		1908, 1911, 1914,	3423, 3425, 3427,
		1917, 1939, 1950,	3429, 3431, 3433,
		1961, 1969, 1975,	3435, 3437, 3439, 3441
		1981, 1995, 2007,	<code>\orcid</code> <u>10, 1559</u>
<code>\onehalfspacing</code>	270	2014, 2028, 2035,	<code>\outer@nobreak</code>
<code>\openout</code>	550	2041, 2048, 2053,	980
<code>\or</code>	204, 206, 208,	2059, 2295, 2297,	
	210, 212, 214, 216,	2299, 2301, 2303,	P
	218, 221, 224, 238,	2305, 2307, 2309,	<code>\pe</code>
	240, 242, 244, 246,	2311, 2313, 2342,	553, 758,
	248, 250, 252, 254,	2344, 2346, 2348,	765, 775, 776, 782,
	256, 598, 599, 600,	2350, 2352, 2354,	783, 3036, 3158,
	601, 602, 603, 605,	2356, 2358, 2360,	3204, 3208, 3212,
	606, 608, 609, 685,	2368, 2370, 2372,	3213, 3216, 3217,
	692, 699, 706, 713,	2374, 2376, 2378,	3220, 3221, 3225,
	720, 727, 734, 743,	2380, 2382, 2384,	3226, 3389, 3491, 3494
	750, 762, 763, 764,	2386, 2394, 2396,	<code>\PackageError</code> 56, 64, 72,
	766, 767, 768, 769,	2398, 2400, 2402,	81, 89, 101, 105,
	770, 771, 772, 800,	2404, 2406, 2408,	109, 117, 125, 133, 143
	801, 802, 804, 806,	2410, 2412, 2419,	<code>\PackageInfo</code>
	808, 810, 812, 813,	2421, 2423, 2425,	53,
	815, 920, 921, 922,	2427, 2429, 2431,	55, 61, 63, 69,
	923, 924, 926, 929,	2433, 2435, 2437,	71, 77, 80, 86, 88,
	934, 939, 940, 989,	2509, 2511, 2513,	94, 100, 114, 116,
	990, 991, 992, 993,	2515, 2517, 2519,	122, 124, 130, 132,
	994, 999, 1000,	2521, 2523, 2525,	138, 142, 1172,
	1001, 1002, 1133,	2527, 2536, 2539,	1216, 1222, 1236, 1242
	1137, 1141, 1145,	2540, 2543, 2546,	<code>\PageIndex</code>
	1149, 1153, 1158,	2549, 2552, 2555,	15
	1162, 1166, 1173,	2558, 2561, 2651,	<code>\pageref</code>
	1177, 1181, 1185,	2652, 2654, 2656,	2920
	1190, 1194, 1198,	2704, 2881, 2883,	<code>\pagestyle</code>
	1202, 1207, 1211,	2885, 2887, 2889,	3051
	1217, 1223, 1227,		<code>\par</code>
	1231, 1237, 1243,		435, 438, 452,
			508, 544, 785, 978,
			1572, 1740, 2132,
			2139, 2158, 2163,
			2165, 2216, 2222,
			2265, 2280, 2283,

screenonly (env.)	24	\SetWatermarkColor	664, 673	\subsection	3207
\scriptsize	2266, 2862, 2866	\SetWatermarkFontSize	663, 672	\subsubsection	3211
\scshape	3279, 3370	\SetWatermarkText	665, 674	\subtitle	10, 1476
\section	282, 2302, 2304, 2308, 2310, 2312, 2314, 2786, 2794, 3203, 3454	\sfdefault	867	\subtitlenote	14, 1583
\section@raggedright	3228, 3232, 3233, 3241, 3242, 3244, 3245, 3247, 3248, 3250, 3251, 3253, 3254, 3255, 3260, 3261, 3264, 3265, 3267, 3268	\sffamily	2393, 2395, 2397, 2399, 2401, 2403, 2407, 2411, 2413, 2532, 2537, 2541, 2562, 2928, 3090, 3232, 3233, 3234, 3241, 3242, 3244, 3245, 3250, 3251, 3260, 3261, 3264, 3265	T	
\Sectionformat	3176, 3180, 3182, 3193	\shortauthors	19, 1513, 1514, 1521, 1522, 1524, 1527, 1528, 1530, 2241, 2243, 2927	\teaserfigure	2081
\SelectFootnoteRule	778, 780	\shortcite	639, 642	teaserfigure (env.)	18
\selectlanguage	1570, 2790	\shorttitle	2947, 2955, 2965, 2976, 2983, 3007	\terms	16, 1665
\set@ACM@acmcpbox	2254, 2259	\showeprint	3476	\textbf	1789, 1801, 2842
\setbox	517, 572, 983, 2263, 2329, 2445, 2454, 2464, 2475, 2627, 2637, 2692, 2772, 2784, 2792	\sidebar	943	\textbullet	591, 1788, 2962, 2965, 2972, 2976
\setcctype	17, 1877	sidebar (env.)	34	\textcolor	3090
\setcitestyle	26, 286, 360, 366	\skip	788	\textheight	2327, 2329, 2335, 2865, 3039, 3161
\setcopyright	16, 1875	\small	561, 948, 955, 963, 1740, 2294, 2296, 2298, 2300, 2538, 2563, 2784, 2792, 2808, 3103	\textit	1802, 2818, 2822, 2823, 2824
\setcounter	2122, 2209, 2323, 2910, 2912, 3236, 3259, 3263, 3274	\smallskipamount	1027	\textrightarrow	592, 1784, 1798
\setengagemetadata	19, 2101	\smash	1639, 1645, 1652, 1658	\textwidth	965, 984, 985, 2117, 2440, 2453, 2463, 2505, 2644, 2691
\setkeys	38, 174, 180, 1440, 1711, 1759, 1875, 2612, 2613, 2618, 2619, 2680, 2681, 2685, 2686, 2725, 2726, 2730, 2731	\space	496, 1486, 1555, 1699, 2237, 2501, 3047, 3169, 3461, 3500, 3503, 3511	\thanks	13, 2083, 2839
\setlength	758, 759, 765, 774, 1006, 1007, 1012, 1018, 1021, 1022, 1023, 1024, 1630, 1633, 2264, 2861	\specialcomment	3452	\thankses	2086, 2088, 2130, 2839
\setmonofont	850, 855	\standardpagestyle	2929	\the	1501, 1508, 1562, 1565, 1614, 1616, 2276, 2862, 2866, 2918, 3081
\settopmatter	18, 98, 1699, 1711, 1712, 1714, 1717, 1719, 1722, 2816	\startPage	16, 1663	\theACM@time@hours	2912, 2919
\setTrue	543	\state	11, 1549, 2479, 2752	\theACM@time@minutes	2919
		\stepcounter	1578, 1580, 1587, 1590, 1597, 1786	\theenumi	995
		\StrDel	2488	\theenumii	996
		\streetaddress	11, 1547, 2479, 2746	\theenumiii	997
		\string	423, 424, 427, 429, 649, 1486, 1555, 1665, 1699, 2276, 2804, 2805, 3500, 3503, 3511	\theenumiv	998
		\strut	3041, 3163	\thefootnote	2116
		\strutbox	568, 581	\theindex	3490
				\theoremstyle	3341, 3344, 3360, 3368
				\thepage	2920, 2936, 2938, 2944, 2945, 2982, 3006, 3103, 3140, 3145
				\thispagestyle	2330, 2337
				\thmname	3308, 3340
				\thmnote	3308, 3340
				\thmnumber	3308, 3340
				\thr@@	327
				\time	2907, 2910, 2912
				\title	10, 2804
				\titlenote	14, 1574, 2805
				\topsep	1031, 1035, 3389
				\translatedabstract	443

translatedabstract	\upshape 1044	Y
(env.) 21	\url . 1772, 1774, 1920, 3461	\year 1614, 2918
\translatedkeywords	\UrlBreakPenalty 2673, 2676	
. 21, 440	\urlstyle 595, 604, 607	Z
\translatedsubtitle	\usebox 2873, 2903	\z@ 315, 319,
. 21, 437	\usepackage	455, 475, 507, 517,
\translatedtitle . 21, 434 9, 10, 11, 12, 13, 14	532, 545, 568, 581,
\trivlist 3390		759, 796, 913, 917,
\tw@ 325	V	928, 1012, 1018,
\tw@digits 2918, 2919	\value 1803	1030, 2132, 2139,
\twocolumn . 2347, 2349,	\vbox 572, 983,	2152, 2156, 2247,
2351, 2353, 2355, 2359	2263, 2445, 2454,	2249, 2264, 2737,
	2464, 2627, 2692, 2772	2784, 2792, 2932,
U	\vskip 509, 544, 788, 796, 978	2933, 3038, 3043,
\unskip 520, 590,	\vspace 2274, 3498	3054, 3056, 3058,
786, 1546, 1552,	\vsplit 2329	3084, 3086, 3096,
1559, 2476, 2479,	\vtop 2637	3097, 3160, 3165,
2480, 2482, 2484,		3203, 3207, 3211,
2485, 2486, 2487,	W	3219, 3224, 3231,
2501, 2570, 2746,	\wd 985, 2476	3290, 3322, 3491, 3494
2747, 2748, 2750,	\write 649	\z@skip 544, 978, 1035, 3230
2751, 2752, 2753,		\zposy 2270, 2271
2754, 2755, 2757,	X	\zrefused 2268, 2269
2802, 2810, 2827, 2840	\xdef 336,	\zsaveposy 1768, 2286
\unvbox . 573, 790, 795,	338, 340, 342, 344, 346	
2331, 2627, 2693, 2772		