

# The `minted` package: Highlighted source code in L<sup>A</sup>T<sub>E</sub>X

Geoffrey M. Poore  
`gpoore@gmail.com`  
`github.com/gpoore/minted`

Originally created and maintained (2009–2013) by  
Konrad Rudolph

v2.6 from 2021/12/24

## **Abstract**

`minted` is a package that facilitates expressive syntax highlighting using the powerful `Pygments` library. The package also provides options to customize the highlighted source code output.

## **License**

LaTeX Project Public License (LPPL) version 1.3.

Additionally, the project may be distributed under the terms of the 3-Clause (“New”) BSD license: <http://opensource.org/licenses/BSD-3-Clause>.

# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
<b>2</b>	<b>Installation</b>	<b>4</b>
2.1	Prerequisites . . . . .	4
2.2	Required packages . . . . .	5
2.3	Installing minted . . . . .	5
<b>3</b>	<b>Basic usage</b>	<b>6</b>
3.1	Preliminary . . . . .	6
3.2	A minimal complete example . . . . .	6
3.3	Formatting source code . . . . .	7
3.4	Using different styles . . . . .	8
3.5	Supported languages . . . . .	9
<b>4</b>	<b>Floating listings</b>	<b>9</b>
<b>5</b>	<b>Options</b>	<b>11</b>
5.1	Package options . . . . .	11
5.2	Macro option usage . . . . .	15
5.3	Available options . . . . .	16
<b>6</b>	<b>Defining shortcuts</b>	<b>29</b>
<b>7</b>	<b>FAQ and Troubleshooting</b>	<b>31</b>
	<b>Acknowledgements</b>	<b>34</b>
	<b>Version History</b>	<b>35</b>
<b>8</b>	<b>Implementation</b>	<b>43</b>
8.1	Required packages . . . . .	43
8.2	Package options . . . . .	44
8.3	Input, caching, and temp files . . . . .	46

8.4	OS interaction . . . . .	49
8.5	Option processing . . . . .	50
8.6	Internal helpers . . . . .	66
8.7	Public API . . . . .	74
8.8	Command shortcuts . . . . .	79
8.9	Float support . . . . .	81
8.10	Epilogue . . . . .	82
8.11	Final cleanup . . . . .	82
<b>9</b>	<b>Implementation of compatibility package</b>	<b>83</b>

# 1 Introduction

minted is a package that allows formatting source code in L<sup>A</sup>T<sub>E</sub>X. For example:

---

```
\begin{minted}{<language>}
<code>
\end{minted}
```

---

will highlight a piece of code in a chosen language. The appearance can be customized with a number of options and color schemes.

Unlike some other packages, most notably `listings`, `minted` requires the installation of additional software, `Pygments`. This may seem like a disadvantage, but there are also significant advantages.

`Pygments` provides superior syntax highlighting compared to conventional packages. For example, `listings` basically only highlights strings, comments and keywords. `Pygments`, on the other hand, can be completely customized to highlight any kind of token the source language might support. This might include special formatting sequences inside strings, numbers, different kinds of identifiers and exotic constructs such as HTML tags.

Some languages make this especially desirable. Consider the following Ruby code as an extreme, but at the same time typical, example:

```
class Foo
  def init
    pi = Math::PI
    @var = "Pi is approx. #{pi}"
  end
end
```

Here we have four different colors for identifiers (five, if you count keywords) and escapes from inside strings, none of which pose a problem for `Pygments`.

Additionally, installing `Pygments` is actually incredibly easy (see the next section).

## 2 Installation

### 2.1 Prerequisites

`Pygments` is written in Python, so make sure that you have Python 2.6 or later installed on your system. This may be easily checked from the command line:

```
$ python --version
Python 2.7.5
```

If you don't have Python installed, you can download it from the [Python website](#) or use your operating system's package manager.

Some Python distributions include `Pygments` (see some of the options under “Alternative Implementations” on the Python site). Otherwise, you will need to install `Pygments` manually. This may be done by installing `setuptools`, which facilitates the distribution of Python applications. You can then install `Pygments` using the following command:

```
$ sudo easy_install Pygments
```

Under Windows, you will not need the `sudo`, but may need to run the command prompt as administrator. `Pygments` may also be installed with `pip`:

```
$ pip install Pygments
```

If you already have `Pygments` installed, be aware that the latest version is recommended (at least 1.4 or later). Some features, such as `escapeinside`, will only work with 2.0+. `minted` may work with versions as early as 1.2, but there are no guarantees.

## 2.2 Required packages

`minted` requires that the following packages be available and reasonably up to date on your system. All of these ship with recent  $\text{T}_{\text{E}}\text{X}$  distributions.

- `keyval`
- `ifthen`
- `xcolor`
- `kvoptions`
- `calc`
- `lineno`
- `fancyvrb`
- `ifplatform`
- `framed`
- `fvextra`
- `pdftexcmds`
- `shellesc` (for `luatex 0.87+`)
- `upquote`
- `etoolbox`
- `catchfile`
- `float`
- `xstring`

## 2.3 Installing `minted`

You can probably install `minted` with your  $\text{T}_{\text{E}}\text{X}$  distribution's package manager. Otherwise, or if you want the absolute latest version, you can install it manually by following the directions below.

You may download `minted.sty` from the [project's homepage](#). We have to install the file so that  $\text{\TeX}$  is able to find it. In order to do that, please refer to the  [\$\text{\TeX}\$  FAQ](#). If you just want to experiment with the latest version, you could locate your current `minted.sty` in your  $\text{\TeX}$  installation and replace it with the latest version. Or you could just put the latest `minted.sty` in the same directory as the file you wish to use it with.

## 3 Basic usage

### 3.1 Preliminary

Since `minted` makes calls to the outside world (that is, `Pygments`), you need to tell the  $\text{\LaTeX}$  processor about this by passing it the `-shell-escape` option or it won't allow such calls. In effect, instead of calling the processor like this:

```
$ latex input
```

you need to call it like this:

```
$ latex -shell-escape input
```

The same holds for other processors, such as `pdflatex` or `xelatex`.

You should be aware that using `-shell-escape` allows  $\text{\LaTeX}$  to run potentially arbitrary commands on your system. It is probably best to use `-shell-escape` only when you need it, and to use it only with documents from trusted sources.

### Working with OS X

If you are using `minted` with some versions/configurations of OS X, and are using caching with a large number of code blocks ( $> 256$ ), you may receive an error like

```
OSError: [Errno 24] Too many open files:
```

This is due to the way files are handled by the operating system, combined with the way that caching works. To resolve this, you may use the OS X commands `launchctl limit maxfiles` or `ulimit -n` to increase the number of files that may be used.

### 3.2 A minimal complete example

The following file `minimal.tex` shows the basic usage of `minted`.

---

```

\documentclass{article}

\usepackage{minted}

\begin{document}
\begin{minted}{c}
int main() {
    printf("hello, world");
    return 0;
}
\end{minted}
\end{document}

```

---

By compiling the source file like this:

```
$ pdflatex -shell-escape minimal
```

we end up with the following output in `minimal.pdf`:

```

int main() {
    printf("hello, world");
    return 0;
}

```

### 3.3 Formatting source code

`minted` Using `minted` is straightforward. For example, to highlight some Python source code we might use the following code snippet (result on the right):

```

\begin{minted}{python}
def boring(args = None):
    pass
\end{minted}
def boring(args = None):
    pass

```

Optionally, the environment accepts a number of options in `key=value` notation, which are described in more detail below.

`\mint` For a single line of source code, you can alternatively use a shorthand notation:

```

\mint{python}|import this|
import this

```

This typesets a single line of code using a command rather than an environment, so it saves a little typing, but its output is equivalent to that of the `minted` environment.

The code is delimited by a pair of identical characters, similar to how `\verb` works. The complete syntax is `\mint[⟨options⟩]{⟨language⟩}⟨delim⟩⟨code⟩⟨delim⟩`, where the code delimiter can be almost any punctuation character. The `⟨code⟩` may also be delimited with matched curly braces `{}`, so long as `⟨code⟩` itself does not contain unmatched curly braces. Again, this command supports a number of options described below.

Note that the `\mint` command is **not for inline use**. Rather, it is a shortcut for `\minted` when only a single line of code is present. The `\mintinline` command is provided for inline use.

`\mintinline` Code can be typeset inline:

```
X\mintinline{python}{print(x**2)}X   Xprint(x**2)X
```

The syntax is `\mintinline[⟨options⟩]{⟨language⟩}⟨delim⟩⟨code⟩⟨delim⟩`. The delimiters can be a pair of characters, as for `\mint`. They can also be a matched pair of curly braces, `{}`.

The command has been carefully crafted so that in most cases it will function correctly when used inside other commands.<sup>1</sup>

`\inputminted` Finally, there's the `\inputminted` command to read and format whole files. Its syntax is `\inputminted[⟨options⟩]{⟨language⟩}{⟨filename⟩}`.

### 3.4 Using different styles

`\usemintedstyle` Instead of using the default style you may choose another stylesheet provided by Pygments. This may be done via the following:

---

```
\usemintedstyle{name}
```

---

The full syntax is `\usemintedstyle[⟨language⟩]{⟨style⟩}`. The style may be set for the document as a whole (no language specified), or only for a particular language. Note that the style may also be set via `\setminted` and via the optional argument for each command and environment.<sup>2</sup>

To get a list of all available stylesheets, see the online demo at the [Pygments website](#) or execute the following command on the command line:

```
$ pygmentize -L styles
```

---

<sup>1</sup>For example, `\mintinline` works in footnotes! The main exception is when the code contains the percent `%` or hash `#` characters, or unmatched curly braces.

<sup>2</sup>Version 2.0 added the optional language argument and removed the restriction that the command be used in the preamble.



Creating your own styles is also easy. Just follow the instructions provided on the [Pygments website](#).

### 3.5 Supported languages

Pygments supports over 300 different programming languages, template languages, and other markup languages. To see an exhaustive list of the currently supported languages, use the command

```
$ pygmentize -L lexers
```

## 4 Floating listings

`listing` `minted` provides the `listing` environment to wrap around a source code block. This puts the code into a floating box, with the default placement `tbp` like figures and tables. You can also provide a `\caption` and a `\label` for such a listing in the usual way (that is, as for the `figure` and `table` environments):

---

```
\begin{listing}[H]
  \mint{cl}/(car (cons 1 '(2)))/
  \caption{Example of a listing.}
  \label{lst:example}
\end{listing}
```

Listing `\ref{lst:example}` contains an example of a listing.

---

will yield:

```
(car (cons 1 '(2)))
```

Listing 1: Example of a listing.

Listing 1 contains an example of a listing.

The default `listing` placement can be modified easily. When the package option `newfloat=false` (default), the `float` package is used to create the `listing` environment. Placement can be modified by redefining `\fps@listing`. For example,

```
\makeatletter
\renewcommand{\fps@listing}{htp}
\makeatother
```

When `newfloat=true`, the more powerful `newfloat` package is used to create the `listing` environment. In that case, `newfloat` commands are available to customize `listing`:

```
\SetupFloatingEnvironment{listing}{placement=htp}
```

`\listoflistings` The `\listoflistings` macro will insert a list of all (floated) listings in the document:

<b>List of Listings</b>		
<code>\listoflistings</code>	1	Example of a listing. 9

## Customizing the `listing` environment

By default, the `listing` environment is created using the `float` package. In that case, the `\listingscaption` and `\listoflistingscaption` macros described below may be used to customize the caption and list of listings. If `minted` is loaded with the `newfloat` option, then the `listing` environment will be created with the more powerful `newfloat` package instead. `newfloat` is part of `caption`, which provides many options for customizing captions.

When `newfloat` is used to create the `listing` environment, customization should be achieved using `newfloat`'s `\SetupFloatingEnvironment` command. For example, the string “Listing” in the caption could be changed to “Program code” using

```
\SetupFloatingEnvironment{listing}{name=Program code}
```

And “List of Listings” could be changed to “List of Program Code” with

```
\SetupFloatingEnvironment{listing}{listname=List of Program Code}
```

Refer to the `newfloat` and `caption` documentation for additional information.

`\listingscaption` (Only applies when package option `newfloat` is not used.) The string “Listing” in a listing’s caption can be changed. To do this, simply redefine the macro `\listingscaption`, for example:

---

```
\renewcommand{\listingscaption}{Program code}
```

---

`\listoflistingscaption` (Only applies when package option `newfloat` is not used.) Likewise, the caption of the listings list, “List of Listings,” can be changed by redefining `\listoflistingscaption`:

---

```
\renewcommand{\listoflistingscaption}{List of Program Code}
```

---

## 5 Options

### 5.1 Package options

`chapter` To control how L<sup>A</sup>T<sub>E</sub>X counts the `listing` floats, you can pass either the `section` or `chapter` option when loading the `minted` package. For example, the following will cause listings to be counted by chapter:

---

```
\usepackage[chapter]{minted}
```

---

`cache=boolean`  
(`default: true`) `minted` works by saving code to a temporary file, highlighting the code via Pygments and saving the output to another temporary file, and inputting the output into the L<sup>A</sup>T<sub>E</sub>X document. This process can become quite slow if there are several chunks of code to highlight. To avoid this, the package provides a `cache` option. This is on by default.

The `cache` option creates a directory `_minted-jobname` in the document's root directory (this may be customized with the `cachedir` option).<sup>3</sup> Files of highlighted code are stored in this directory, so that the code will not have to be highlighted again in the future. In most cases, caching will significantly speed up document compilation.

Cached files that are no longer in use are automatically deleted.<sup>4</sup>

`cachedir=directory`  
(`def: _minted-jobname`) This allows the directory in which cached files are stored to be specified. Paths should use forward slashes, even under Windows.

Special characters must be escaped. For example, `cachedir=~/.mintedcache` would not work because the tilde `~` would be converted into the L<sup>A</sup>T<sub>E</sub>X commands for a non-breaking space, rather than being treated literally. Instead, use `\string~/.mintedcache`, `\detokenize{~/.mintedcache}`, or an equivalent solution.

Paths may contain spaces, but only if the entire `directory` is wrapped in curly braces `{}`, and only if the spaces are quoted. For example,

---

<sup>3</sup>The directory is actually named using a “sanitized” copy of `jobname`, in which spaces and asterisks have been replaced by underscores, and double quotation marks have been stripped. If the file name contains spaces, `\jobname` will contain a quote-wrapped name, except under older versions of MiKTeX which used the name with spaces replaced by asterisks. Using a “sanitized” `jobname` is simpler than accommodating the various escaping conventions.

<sup>4</sup>This depends on the main auxiliary file not being deleted or becoming corrupted. If that happens, you could simply delete the cache directory and start over.

```
cachedir = {\detokenize{-/"minted cache"/"with spaces"}}
```

Note that the cache directory is relative to the `outputdir`, if an `outputdir` is specified.

```
finalizcache={boolean}  
(default: false)
```

In some cases, it may be desirable to use `minted` in an environment in which `-shell-escape` is not allowed. A document might be submitted to a publisher or preprint server or used with an online service that does not support `-shell-escape`. This is possible as long as `minted` content does not need to be modified.

Compiling with the `finalizcache` option prepares the cache for use in an environment without `-shell-escape`.<sup>5</sup> Once this has been done, the `finalizcache` option may be swapped for the `frozenscache` option, which will then use the frozen (static) cache in the future, without needing `-shell-escape`.

```
fontencoding={encoding}  
(default: {doc encoding})
```

Set font encoding used for typesetting code.

For example, `fontencoding=T1`.

```
frozenscache={boolean}  
(default: false)
```

Use a frozen (static) cache created with the `finalizcache` option. When `frozenscache` is on, `-shell-escape` is not needed, and Python and Pygments are not required. In addition, any external files accessed through `\inputminted` are no longer necessary.

**This option must be used with care. A document *must* be in final form, as far as `minted` is concerned, *before* `frozenscache` is turned on, and the document *must* have been compiled with `finalizcache`. When this option is on, `minted` content cannot be modified, except by editing the cache files directly. Changing any `minted` settings that require Pygments or Python is not possible. If `minted` content is incorrectly modified after `frozenscache` is turned on, `minted` *cannot* detect the modification.**

If you are using `frozenscache`, and want to verify that `minted` settings or content have not been modified in an invalid fashion, you can test the cache using the following procedure.

1. Obtain a copy of the cache used with `frozenscache`.
2. Compile the document in an environment that supports `-shell-escape`, with `finalizcache=true` and `frozenscache=false`. This essentially regenerates the frozen (static) cache.
3. Compare the original cache with the newly generated cache. Under Linux and OS X, you could use `diff`; under Windows, you probably want `fc`. If `minted` content and settings have not been modified in an invalid fashion, all

---

<sup>5</sup>Ordinarily, cache files are named using an MD5 hash of highlighting settings and highlighted text. `finalizcache` renames cache files using a `listing<number>.pygtex` scheme. This makes it simpler to match up document content and cache files, and is also necessary for the XeTeX engine since prior to TeX Live 2016 it lacked the built-in MD5 capabilities that pdfTeX and LuaTeX have.

files will be identical (assuming that compatible versions of Pygments are used for both caches).

`draft={boolean}`  
(default: false) This uses `fancyvrb` alone for all typesetting; `Pygments` is not used. This trades syntax highlighting and some other `minted` features for faster compiling. Performance should be essentially the same as using `fancyvrb` directly; no external temporary files are used. Note that if you are not changing much code between compiles, the difference in performance between caching and draft mode may be minimal. Also note that `draft` settings are typically inherited from the document class.

Draft mode does not support `autogobble`. Regular `gobble`, `linenos`, and most other options not related to syntax highlighting will still function in draft mode.

Documents can usually be compiled without shell escape in draft mode. The `ifplatform` package may issue a warning about limited functionality due to shell escape being disabled, but this may be ignored in almost all cases. (Shell escape is only really required if you have an unusual system configuration such that the `\ifwindows` macro must fall back to using shell escape to determine the system. See the `ifplatform` documentation for more details: <http://www.ctan.org/pkg/ifplatform>.)

If the `cache` option is set, then all existing cache files will be kept while draft mode is on. This allows caching to be used intermitently with draft mode without requiring that the cache be completely recreated each time. Automatic cleanup of cached files will resume as soon as draft mode is turned off. (This assumes that the auxiliary file has not been deleted in the meantime; it contains the cache history and allows automatic cleanup of unused files.)

`final={boolean}`  
(default: true) This is the opposite of `draft`; it is equivalent to `draft=false`. Again, note that `draft` and `final` settings are typically inherited from the document class.

`kpsewhich={boolean}`  
(default: false) This option uses `kpsewhich` to locate files that are to be highlighted. Some build tools such as `texi2pdf` function by modifying `TEXINPUTS`; in some cases, users may customize `TEXINPUTS` as well. The `kpsewhich` option allows `minted` to work with such configurations.

This option may add a noticeable amount of overhead on some systems, or with some system configurations.

This option does *not* make `minted` work with the `-output-directory` and `-aux-directory` command-line options for `LATEX`. For those, see the `outputdir` package option.

`langlinenos={boolean}`  
(default: false) `minted` uses the `fancyvrb` package behind the scenes for the code typesetting. `fancyvrb` provides an option `firstnumber` that allows the starting line number of an environment to be specified. For convenience, there is an option `firstnumber=last` that allows line numbering to pick up where it left off. The `langlinenos` option makes `firstnumber` work for each language individually with all `minted` and `\mint` usages. For example, consider the code and output below.

```

\begin{minted}[linenos]{python}
def f(x):
    return x**2
\end{minted}

\begin{minted}[linenos]{ruby}
def func
  puts "message"
end
\end{minted}

\begin{minted}[linenos, firstnumber=last]{python}
def g(x):
    return 2*x
\end{minted}

```

```

1  def f(x):
2  return x**2

1  def func
2  puts "message"
3  end

3  def g(x):
4  return 2*x

```

Without the `langlinenos` option, the line numbering in the second Python environment would not pick up where the first Python environment left off. Rather, it would pick up with the Ruby line numbering.

```

newfloat=boolean
(default: false)

```

By default, the `listing` environment is created using the `float` package. The `newfloat` option creates the environment using `newfloat` instead. This provides better integration with the `caption` package.

```

outputdir=directory
(default: none)

```

The `-output-directory` and `-aux-directory` (MiKTeX) command-line options for  $\LaTeX$  cause problems for `minted`, because the `minted` temporary files are saved in `<outputdir>`, but `minted` still looks for them in the document root directory. There is no way to access the value of the command-line option so that `minted` can automatically look in the right place. But it is possible to allow the output directory to be specified manually as a package option.

The output directory should be specified using an absolute path or a path relative to the document root directory. Paths should use forward slashes, even under Windows. Special characters must be escaped, while spaces require quoting and need the entire `<directory>` to be wrapped in curly braces `{}`. See `cachedir` above for examples of escaping and quoting.

**section** To control how L<sup>A</sup>T<sub>E</sub>X counts the `listing` floats, you can pass either the `section` or `chapter` option when loading the `minted` package.

## 5.2 Macro option usage

All `minted` highlighting commands accept the same set of options. Options are specified as a comma-separated list of `key=value` pairs. For example, we can specify that the lines should be numbered:

```
\begin{minted}[linenos=true]{c++}
#include <iostream>
int main() {
    std::cout << "Hello "
               << "world"
               << std::endl;
}
\end{minted}
1 #include <iostream>
2 int main() {
3     std::cout << "Hello "
4               << "world"
5               << std::endl;
6 }
```

An option value of `true` may also be omitted entirely (including the “=”). To customize the display of the line numbers further, override the `\theFancyVerbLine` command. Consult the `fancyvrb` documentation for details.

`\mint` accepts the same options:

```
\mint[linenos]{perl}|$x=~ /foo/| 1 $x=~ /foo/
```

Here’s another example: we want to use the L<sup>A</sup>T<sub>E</sub>X math mode inside comments:

```
\begin{minted}[mathescape]{python}
# Returns  $\sum_{i=1}^n i$ 
def sum_from_one_to(n):
    r = range(1, n + 1)
    return sum(r)
\end{minted}
# Returns  $\sum_{i=1}^n i$ 
def sum_from_one_to(n):
    r = range(1, n + 1)
    return sum(r)
```

To make your L<sup>A</sup>T<sub>E</sub>X code more readable you might want to indent the code inside a `minted` environment. The option `gobble` removes these unnecessary whitespace characters from the output. There is also an `autogobble` option that detects the length of this whitespace automatically.

<pre> \begin{minted}[gobble=2,   showspaces]{python} def boring(args = None):     pass \end{minted} </pre>	<pre> def boring(args=None):     pass </pre>
versus	versus
<pre> \begin{minted}[showspaces]{python} def boring(args = None):     pass \end{minted} </pre>	<pre> def boring(args=None):     pass </pre>

`\setminted` You may wish to set options for the document as a whole, or for an entire language. This is possible via `\setminted[⟨language⟩]{⟨key=value,...⟩}`. Language-specific options override document-wide options. Individual command and environment options override language-specific options.

`\setmintedinline` You may wish to set separate options for `\mintinline`, either for the document as a whole or for a specific language. This is possible via `\setmintedinline[⟨language⟩]{⟨key=value,...⟩}`. Language-specific options override document-wide options. Individual command options override language-specific options. All settings specified with `\setmintedinline` override those set with `\setminted`. That is, inline settings always have a higher precedence than general settings.

### 5.3 Available options

Following is a full list of available options. For more detailed option descriptions please refer to the `fancyvrb` and `Pygments` documentation.

`autogobble` (boolean) (default: `false`)  
 Remove (gobble) all common leading whitespace from code. Essentially a version of `gobble` that automatically determines what should be removed. Good for code that originally is not indented, but is manually indented after being pasted into a `LATEX` document.

<pre> ...text. \begin{minted}[autogobble]{python}   def f(x):     return x**2 \end{minted} </pre>	<pre> ...text. def f(x):     return x**2 </pre>
---	---

`baselinestretch` (dimension) (default: `⟨document default⟩`)  
 Value to use as for `baselinestretch` inside the listing.



`beameroverlays` (boolean) (default: `false`)  
Give the `<` and `>` characters their normal text meanings when used with `escapeinside` and `texcomments`, so that `beamer` overlays of the form `\only<1>{...}` will work.

`breakafter` (string) (default: `none`)  
Break lines after specified characters, not just at spaces, when `breaklines=true`. Does not apply to `\mintinline`.

For example, `breakafter=-/` would allow breaks after any hyphens or slashes. Special characters given to `breakafter` should be backslash-escaped (usually `#`, `{`, `}`, `%`, `[`, `]`; the backslash `\` may be obtained via `\\`).

For an alternative, see `breakbefore`. When `breakbefore` and `breakafter` are used for the same character, `breakbeforegroup` and `breakaftergroup` must both have the same setting.

```
\begin{minted}[breaklines, breakafter=d]{python}
some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeverFitOnOneLine'
\end{minted}

_____

some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCould
→ NeverFitOnOneLine'
```

`breakaftergroup` (boolean) (default: `true`)  
When `breakafter` is used, group all adjacent identical characters together, and only allow a break after the last character. When `breakbefore` and `breakafter` are used for the same character, `breakbeforegroup` and `breakaftergroup` must both have the same setting.

`breakaftersymbolpre` (string) (default: `\,\footnotesize\ensuremath{\_rflfloor}, \_j`)  
The symbol inserted pre-break for breaks inserted by `breakafter`.

`breakaftersymbolpost` (string) (default: `none`)  
The symbol inserted post-break for breaks inserted by `breakafter`.

`breakanywhere` (boolean) (default: `false`)  
Break lines anywhere, not just at spaces, when `breaklines=true`. Does not apply to `\mintinline`.

```

\begin{minted}[breaklines, breakanywhere]{python}
some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeverFitOnOneLine'
\end{minted}

_____

some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeve
→ rFitOnOneLine'

```

**breakanywheresymbolpre** (string) (default: `\, \footnotesize\ensuremath{\_ \rfloor}`, `_]`)  
The symbol inserted pre-break for breaks inserted by `breakanywhere`.

**breakanywheresymbolpost** (string) (default: `(none)`)  
The symbol inserted post-break for breaks inserted by `breakanywhere`.

**breakautoindent** (boolean) (default: `true`)  
When a line is broken, automatically indent the continuation lines to the indentation level of the first line. When `breakautoindent` and `breakindent` are used together, the indentations add. This indentation is combined with `breaksymbolindentleft` to give the total actual left indentation. Does not apply to `\mintinline`.

**breakbefore** (string) (default: `(none)`)  
Break lines before specified characters, not just at spaces, when `breaklines=true`. Does not apply to `\mintinline`.

For example, `breakbefore=A` would allow breaks before capital A's. Special characters given to `breakbefore` should be backslash-escaped (usually `#`, `{`, `}`, `%`, `[`, `]`; the backslash `\` may be obtained via `\\`).

For an alternative, see `breakafter`. When `breakbefore` and `breakafter` are used for the same character, `breakbeforegroup` and `breakaftergroup` must both have the same setting.

```

\begin{minted}[breaklines, breakbefore=A]{python}
some_string = 'SomeTextThatGoesOnAndOnForSoLongThatItCouldNeverFitOnOneLine'
\end{minted}

_____

some_string = 'SomeTextThatGoesOn
→ AndOnForSoLongThatItCouldNeverFitOnOneLine'

```

**breakbeforegroup** (boolean) (default: `true`)  
When `breakbefore` is used, group all adjacent identical characters together, and only allow a break before the first character. When `breakbefore` and `breakafter` are used for the same character, `breakbeforegroup` and `breakaftergroup` must

both have the same setting.

`breakbeforesymbolpre` (string) (default: `\,\footnotesize\ensuremath{\_}\rfloor`)  
The symbol inserted pre-break for breaks inserted by `breakbefore`.

`breakbeforesymbolpost` (string) (default: `\none`)  
The symbol inserted post-break for breaks inserted by `breakbefore`.

`breakbytoken` (boolean) (default: `false`)  
Only break lines at locations that are not within tokens; prevent tokens from being split by line breaks. By default, `breaklines` causes line breaking at the space nearest the margin. While this minimizes the number of line breaks that are necessary, it can be inconvenient if a break occurs in the middle of a string or similar token.

This is not compatible with `draft` mode. A complete list of Pygments tokens is available at <http://pygments.org/docs/tokens/>. If the breaks provided by `breakbytoken` occur in unexpected locations, it may indicate a bug or shortcoming in the Pygments lexer for the language.

`breakbytokenanywhere` (boolean) (default: `false`)  
Like `breakbytoken`, but also allows line breaks between immediately adjacent tokens, not just between tokens that are separated by spaces. Using `breakbytokenanywhere` with `breakanywhere` is redundant.

`breakindent` (dimension) (default: `\breakindentnchars`)  
When a line is broken, indent the continuation lines by this amount. When `breakautoindent` and `breakindent` are used together, the indentations add. This indentation is combined with `breaksymbolindentleft` to give the total actual left indentation.

Does not apply to `\mintinline`.

`breakindentnchars` (integer) (default: 0)  
This allows `breakindent` to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).

`breaklines` (boolean) (default: `false`)  
Automatically break long lines in `minted` environments and `\mint` commands, and wrap longer lines in `\mintinline`.

By default, automatic breaks occur at space characters. Use `breakanywhere` to enable breaking anywhere; use `breakbytoken`, `breakbytokenanywhere`, `breakbefore`, and `breakafter` for more fine-tuned breaking. Currently, only `breakbytoken` and `breakbytokenanywhere` work with `\mintinline`. Using `escapeinside` to escape to  $\LaTeX$  and then insert a manual break is also an option. For example,

use `escapeinside=`, and then insert `\\` at the appropriate point. (Note that `escapeinside` does not work within strings.)

<pre>...text. \begin{minted}[breaklines]{python} def f(x):     return 'Some text ' + str(x) \end{minted}</pre>	<pre>...text. def f(x):     return 'Some text ' +     ↪ str(x)</pre>
--	--

Breaking in `minted` and `\mint` may be customized in several ways. To customize the indentation of broken lines, see `breakindent` and `breakautoindent`. To customize the line continuation symbols, use `breaksymbolleft` and `breaksymbolright`. To customize the separation between the continuation symbols and the code, use `breaksymbolsepleft` and `breaksymbolsepright`. To customize the extra indentation that is supplied to make room for the break symbols, use `breaksymbolindentleft` and `breaksymbolindentright`. Since only the left-hand symbol is used by default, it may also be modified using the alias options `breaksymbol`, `breaksymbolsep`, and `breaksymbolindent`. Note than none of these options applies to `\mintinline`, since they are not relevant in the inline context.

An example using these options to customize the `minted` environment is shown below. This uses the `\carriagereturn` symbol from the `dingbat` package.

<pre>\begin{minted}[breaklines,                 breakautoindent=false,                 breaksymbolleft=\raisebox{0.8ex}{                     \small\reflectbox{\carriagereturn}},                 breaksymbolindentleft=0pt,                 breaksymbolsepleft=0pt,                 breaksymbolright=\small\carriagereturn,                 breaksymbolindentright=0pt,                 breaksymbolsepright=0pt]{python} def f(x):     return 'Some text ' + str(x) + ' some more text ' +     ↪ str(x) + ' even more text that goes on for a     ↪ while' \end{minted}</pre>	<pre>def f(x):     return 'Some text ' + str(x) + ' some more text ' +     ↪ str(x) + ' even more text that goes on for a while'</pre>
--	--

Automatic line breaks are limited with `Pygments` styles that use a colored background behind large chunks of text. This coloring is accomplished with `\colorbox`,

which cannot break across lines. It may be possible to create an alternative to `\colorbox` that supports line breaks, perhaps with TikZ, but the author is unaware of a satisfactory solution. The only current alternative is to redefine `\colorbox` so that it does nothing. For example,

```
\AtBeginEnvironment{minted}{\renewcommand{\colorbox}[3] [] {#3}}
```

uses the `etoolbox` package to redefine `\colorbox` within all `minted` environments. Automatic line breaks will not work with `showspaces=true` unless you use `breakanywhere` or `breakafter=\space`.

`breaksymbol` (string) (default: `breaksymbolleft`)  
Alias for `breaksymbolleft`.

`breaksymbolleft` (string) (default: `\tiny\ensuremath{\hookrightarrow}`,  $\leftrightarrow$ )  
The symbol used at the beginning (left) of continuation lines when `breaklines=true`. To have no symbol, simply set `breaksymbolleft` to an empty string (“=,” or “={}”). The symbol is wrapped within curly braces `{}` when used, so there is no danger of formatting commands such as `\tiny` “escaping.”

The `\hookrightarrow` and `\hookleftarrow` may be further customized by the use of the `\rotatebox` command provided by `graphicx`. Additional arrow-type symbols that may be useful are available in the `dingbat` (`\carriagereturn`) and `mnsymbol` (hook and curve arrows) packages, among others.

Does not apply to `\mintinline`.

`breaksymbolright` (string) (default: `none`)  
The symbol used at breaks (right) when `breaklines=true`. Does not appear at the end of the very last segment of a broken line.

`breaksymbolindent` (dimension) (default: `breaksymbolindentleftnchars`)  
Alias for `breaksymbolindentleft`.

`breaksymbolindentnchars` (integer) (default: `breaksymbolindentleftnchars`)  
Alias for `breaksymbolindentleftnchars`.

`breaksymbolindentleft` (dimension) (default: `breaksymbolindentleftnchars`)  
The extra left indentation that is provided to make room for `breaksymbolleft`. This indentation is only applied when there is a `breaksymbolleft`.

Does not apply to `\mintinline`.

`breaksymbolindentleftnchars` (integer) (default: 4)  
This allows `breaksymbolindentleft` to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).

<code>breaksymbolindentright</code>	(dimension)	(default: <code>&lt;breaksymbolindentrightnchars&gt;</code> )
	The extra right indentation that is provided to make room for <code>breaksymbolright</code> . This indentation is only applied when there is a <code>breaksymbolright</code> .	
<code>breaksymbolindentrightnchars</code>	(integer)	(default: 4)
	This allows <code>breaksymbolindentright</code> to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).	
<code>breaksymbolsep</code>	(dimension)	(default: <code>&lt;breaksymbolsepleftnchars&gt;</code> )
	Alias for <code>breaksymbolsepleft</code> .	
<code>breaksymbolsepnchars</code>	(integer)	(default: <code>&lt;breaksymbolsepleftnchars&gt;</code> )
	Alias for <code>breaksymbolsepleftnchars</code> .	
<code>breaksymbolsepleft</code>	(dimension)	(default: <code>&lt;breaksymbolsepleftnchars&gt;</code> )
	The separation between the <code>breaksymbolleft</code> and the adjacent text.	
<code>breaksymbolsepleftnchars</code>	(integer)	(default: 2)
	Allows <code>breaksymbolsepleft</code> to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).	
<code>breaksymbolsepright</code>	(dimension)	(default: <code>&lt;breaksymbolseprightnchars&gt;</code> )
	The <i>minimum</i> separation between the <code>breaksymbolright</code> and the adjacent text. This is the separation between <code>breaksymbolright</code> and the furthest extent to which adjacent text could reach. In practice, <code>\linewidth</code> will typically not be an exact integer multiple of the character width (assuming a fixed-width font), so the actual separation between the <code>breaksymbolright</code> and adjacent text will generally be larger than <code>breaksymbolsepright</code> . This ensures that break symbols have the same spacing from the margins on both left and right. If the same spacing from text is desired instead, <code>breaksymbolsepright</code> may be adjusted. (See the definition of <code>\FV@makeLineNumber</code> in <code>fvextra</code> for implementation details.)	
<code>breaksymbolseprightnchars</code>	(integer)	(default: 2)
	Allows <code>breaksymbolsepright</code> to be specified as an integer number of characters rather than as a dimension (assumes a fixed-width font).	
<code>bgcolor</code>	(string)	(default: <code>&lt;none&gt;</code> )
	Background color of the listing. Be aware that this option has several limitations (described below); see “Framing alternatives” below for more powerful alternatives.	
	The value of this option must <i>not</i> be a color command. Instead, it must be a color <i>name</i> , given as a string, of a previously-defined color:	

```

\definecolor{bg}{rgb}{0.95,0.95,0.95}
\begin{minted}[bgcolor=bg]{php}
<?php
  echo "Hello, $x";
?>
\end{minted}

```

```

<?php
  echo "Hello, $x";
?>

```

This option puts `minted` environments and `\mint` commands in a `snugshade*` environment from the `framed` package, which supports breaks across pages. (Prior to `minted` 2.2, a `minipage` was used, which prevented page breaks and gave undesirable spacing from surrounding text.) Be aware that if `bgcolor` is used with `breaklines=true`, and a line break occurs just before a page break, then text may extend below the colored background in some instances. It is best to use a more advanced framing package in those cases; see “Framing alternatives” below.

This option puts `\mintinline` inside a `\colorbox`, which **does not allow line breaks**. If you want to use `\setminted` to set background colors, and only want background colors on `minted` and `\mint`, you may use `\setmintedinline{bgcolor={}}` to turn off the coloring for inline commands.

### Framing alternatives

If you want more reliable and advanced options for background colors and framing, you should consider a more advanced framing package such as `mdframed` or `tcolorbox`. It is easy to add framing to `minted` commands and environments using the `etoolbox` package, which is automatically loaded by `minted`. For example, using `mdframed`:

```

\BeforeBeginEnvironment{minted}{\begin{mdframed}}
\AfterEndEnvironment{minted}{\end{mdframed}}

```

Some framing packages also provide built-in commands for such purposes. For example, `mdframed` provides a `\surroundwithmdframed` command, which could be used to add a frame to all `minted` environments:

```

\surroundwithmdframed{minted}

```

`tcolorbox` even provides a built-in framing environment with `minted` support. Simply use `\tcboxlibrary{minted}` in the preamble, and then put code within a `tcblisting` environment:

```

\begin{tcblisting}{<tcb options>,
  minted language=<language>,
  minted style=<style>,
  minted options={<option list>} }
<code>
\end{tcblisting}

```

`tcolorbox` provides other commands and environments for fine-tuning listing appearance and for working with external code files.

- `codetagify` (list of strings) (default: highlight XXX, TODO, BUG, and NOTE)  
Highlight special code tags in comments and docstrings.
- `curlyquotes` (boolean) (default: false)  
By default, the backtick ``` and typewriter single quotation mark `'` always appear literally, instead of becoming the left and right curly single quotation marks `‘` and `’`. This option allows these characters to be replaced by the curly quotation marks when that is desirable.
- `encoding` (string) (default: `<system-specific>`)  
Sets the file encoding that Pygments expects. See also `outencoding`.
- `escapeinside` (string) (default: `<none>`)  
Escape to L<sup>A</sup>T<sub>E</sub>X between the two characters specified in `(string)`. All code between the two characters will be interpreted as L<sup>A</sup>T<sub>E</sub>X and typeset accordingly. This allows for additional formatting. The escape characters need not be identical. Special L<sup>A</sup>T<sub>E</sub>X characters must be escaped when they are used as the escape characters (for example, `escapeinside=\#\%`). Requires Pygments 2.0+.

**Escaping does not work inside strings and comments (for comments, there is `texcomments`). As of Pygments 2.0.2, this means that escaping is “fragile” with some lexers.** Due to the way that Pygments implements `escapeinside`, any “escaped” L<sup>A</sup>T<sub>E</sub>X code that resembles a string or comment for the current lexer may break `escapeinside`. There is a [Pygments issue](#) for this case. Additional details and a limited workaround for some scenarios are available on the [minted GitHub site](#).

```
\begin{minted}[escapeinside=||]{py}
def f(x):
    y = x|\colorbox{green}{**}|2
    return y
\end{minted}
def f(x):
    y = x ** 2
    return y
```

**Note that when math is used inside escapes, any active characters beyond those that are normally active in verbatim can cause problems.** Any package that relies on special active characters in math mode (for example, `icomma`) will produce errors along the lines of TeX capacity exceeded and `\leavevmode\kern\z@`. This may be fixed by modifying `\@noligs`, as described at <http://tex.stackexchange.com/questions/223876>.

- `firstline` (integer) (default: 1)  
The first line to be shown. All lines before that line are ignored and do not appear in the output.



<code>firstnumber</code>	(auto   last   integer) Line number of the first line.	(default: auto = 1)
<code>fontfamily</code>	(family name) The font family to use. <code>tt</code> , <code>courier</code> and <code>helvetica</code> are pre-defined.	(default: <code>tt</code> )
<code>fontseries</code>	(series name) The font series to use.	(default: auto – the same as the current font)
<code>fontsize</code>	(font size) The size of the font to use, as a size command, e.g. <code>\footnotesize</code> .	(default: auto – the same as the current font)
<code>fontshape</code>	(font shape) The font shape to use.	(default: auto – the same as the current font)
<code>formatcom</code>	(command) A format to execute before printing verbatim text.	(default: <code>&lt;none&gt;</code> )
<code>frame</code>	(none   leftline   topline   bottomline   lines   single) The type of frame to put around the source code listing.	(default: none)
<code>framerule</code>	(dimension) Width of the frame.	(default: 0.4pt)
<code>framesep</code>	(dimension) Distance between frame and content.	(default: <code>\fboxsep</code> )
<code>funcnamehighlighting</code>	(boolean) [For PHP only] If <code>true</code> , highlights built-in function names.	(default: <code>true</code> )
<code>gobble</code>	(integer) Remove the first <i>n</i> characters from each input line.	(default: 0)
<code>highlightcolor</code>	(string) Set the color used for <code>highlightlines</code> , using a predefined color name from <code>color</code> or <code>xcolor</code> , or a color defined via <code>\definecolor</code> .	(default: <code>LightCyan</code> )
<code>highlightlines</code>	(string) This highlights a single line or a range of lines based on line numbers. For example, <code>highlightlines={1, 3-4}</code> . The line numbers refer to the line numbers that would appear if <code>linenos=true</code> , etc. They do not refer to original or actual line numbers before adjustment by <code>firstnumber</code> .  The highlighting color can be customized with <code>highlightcolor</code> .	(default: <code>&lt;none&gt;</code> )

<code>keywordcase</code>	(string) (default: <code>lower</code> ) Changes capitalization of keywords. Takes <code>lower</code> , <code>upper</code> , or <code>capitalize</code> .
<code>label</code>	(string) (default: <code>empty</code> ) Add a label to the top, the bottom or both of the frames around the code. See the <code>fancyvrb</code> documentation for more information and examples. <i>Note:</i> This does <i>not</i> add a <code>\label</code> to the current listing. To achieve that, use a floating environment (section 4) instead.
<code>labelposition</code>	( <code>none</code>   <code>topline</code>   <code>bottomline</code>   <code>all</code> ) (default: <code>topline</code> , <code>all</code> , or <code>none</code> ) Position where to print the label (see above; default: <code>topline</code> if one label is defined, <code>all</code> if two are defined, <code>none</code> else). See the <code>fancyvrb</code> documentation for more information.
<code>lastline</code>	(integer) (default: <code>&lt;last line of input&gt;</code> ) The last line to be shown.
<code>linenos</code>	(boolean) (default: <code>false</code> ) Enables line numbers. In order to customize the display style of line numbers, you need to redefine the <code>\theFancyVerbLine</code> macro:
<pre> \renewcommand{\theFancyVerbLine}{\sffamily   \textcolor[rgb]{0.5,0.5,1.0}{\scriptsize     \oldstylenums{\arabic{FancyVerbLine}}}}  \begin{minted}[linenos,   firstnumber=11]{python} def all(iterable):     for i in iterable:         if not i:             return False     return True \end{minted} 11 def all(iterable): 12     for i in iterable: 13         if not i: 14             return False 15     return True </pre>	
<code>numberfirstline</code>	(boolean) (default: <code>false</code> ) Always number the first line, regardless of <code>stepnumber</code> .
<code>numbers</code>	( <code>left</code>   <code>right</code>   <code>both</code>   <code>none</code> ) (default: <code>none</code> ) Essentially the same as <code>linenos</code> , except the side on which the numbers appear may be specified.
<code>mathescape</code>	(boolean) (default: <code>false</code> ) Enable L <sup>A</sup> T <sub>E</sub> X math mode inside comments. Usage as in package <code>listings</code> . See the note under <code>escapeinside</code> regarding math and ligatures.

<code>numberblanklines</code>	(boolean) Enables or disables numbering of blank lines.	(default: <code>true</code> )
<code>numbersep</code>	(dimension) Gap between numbers and start of line.	(default: <code>12pt</code> )
<code>obeytabs</code>	(boolean) Treat tabs as tabs instead of converting them to spaces—that is, expand them to tab stops determined by <code>tabsize</code> . <b>While this will correctly expand tabs within leading indentation, usually it will not correctly expand tabs that are preceded by anything other than spaces or other tabs. It should be avoided in those case.</b>	(default: <code>false</code> )
<code>outencoding</code>	(string) Sets the file encoding that Pygments uses for highlighted output. Overrides any encoding previously set via <code>encoding</code> .	(default: <code>&lt;system-specific&gt;</code> )
<code>python3</code>	(boolean) [For <code>PythonConsoleLexer</code> only] Specifies whether Python 3 highlighting is applied.	(default: <code>false</code> )
<code>resetmargins</code>	(boolean) Resets the left margin inside other environments.	(default: <code>false</code> )
<code>rulecolor</code>	(color command) The color of the frame.	(default: <code>black</code> )
<code>samepage</code>	(boolean) Forces the whole listing to appear on the same page, even if it doesn't fit.	(default: <code>false</code> )
<code>showspaces</code>	(boolean) Enables visible spaces: <code>visible_spaces</code> .	(default: <code>false</code> )
<code>showtabs</code>	(boolean) Enables visible tabs—only works in combination with <code>obeytabs</code> .	(default: <code>false</code> )
<code>space</code>	(macro) Redefine the visible space character. Note that this is only used if <code>showspaces=true</code> .	(default: <code>\textvisiblespace</code> , <code>␣</code> )
<code>spacecolor</code>	(string) Set the color of visible spaces. By default ( <code>none</code> ), they take the color of their surroundings.	(default: <code>none</code> )
<code>startinline</code>	(boolean) [For PHP only] Specifies that the code starts in PHP mode, i.e., leading <code>&lt;?php</code> is	(default: <code>false</code> )

omitted.

<code>style</code>	(string) (default: <code>&lt;default&gt;</code> ) Sets the stylesheet used by Pygments.
<code>stepnumber</code>	(integer) (default: 1) Interval at which line numbers appear.
<code>stepnumberfromfirst</code>	(boolean) (default: <code>false</code> ) By default, when line numbering is used with <code>stepnumber</code> $\neq$ 1, only line numbers that are a multiple of <code>stepnumber</code> are included. This offsets the line numbering from the first line, so that the first line, and all lines separated from it by a multiple of <code>stepnumber</code> , are numbered.
<code>stepnumberoffsetvalues</code>	(boolean) (default: <code>false</code> ) By default, when line numbering is used with <code>stepnumber</code> $\neq$ 1, only line numbers that are a multiple of <code>stepnumber</code> are included. Using <code>firstnumber</code> to offset the numbering will change which lines are numbered and which line gets which number, but will not change which <i>numbers</i> appear. This option causes <code>firstnumber</code> to be ignored in determining which line numbers are a multiple of <code>stepnumber</code> . <code>firstnumber</code> is still used in calculating the actual numbers that appear. As a result, the line numbers that appear will be a multiple of <code>stepnumber</code> , plus <code>firstnumber</code> minus 1.
<code>stripall</code>	(boolean) (default: <code>false</code> ) Strip all leading and trailing whitespace from the input.
<code>stripnl</code>	(boolean) (default: <code>false</code> ) Strip leading and trailing newlines from the input.
<code>tab</code>	(macro) (default: fancyvrb's <code>\FancyVerbTab</code> , ↯) Redefine the visible tab character. Note that this is only used if <code>showtabs=true</code> . <code>\rightarrowfill</code> , <code>—&gt;</code> , may be a nice alternative.
<code>tabcolor</code>	(string) (default: <code>black</code> ) Set the color of visible tabs. If <code>tabcolor=none</code> , tabs take the color of their surroundings. This is typically undesirable for tabs that indent multiline comments or strings.
<code>tabsize</code>	(integer) (default: 8) The number of spaces a tab is equivalent to. If <code>obeytabs</code> is <i>not</i> active, tabs will be converted into this number of spaces. If <code>obeytabs</code> is active, tab stops will be set this number of space characters apart.

<code>texcl</code>	(boolean)	(default: <code>false</code> )
	Enables $\LaTeX$ code inside comments. Usage as in package <code>listings</code> . See the note under <code>escapeinside</code> regarding math and ligatures.	
<code>texcomments</code>	(boolean)	(default: <code>false</code> )
	Enables $\LaTeX$ code inside comments. The newer name for <code>texcl</code> . See the note under <code>escapeinside</code> regarding math and ligatures.	
	As of Pygments 2.0.2, <code>texcomments</code> fails with multiline C/C++ preprocessor directives, and may fail in some other circumstances. This is because preprocessor directives are <code>tokenized as Comment.Preproc</code> , so <code>texcomments</code> causes preprocessor directives to be treated as literal $\LaTeX$ code. <a href="#">An issue has been opened at the Pygments site</a> ; additional details are also available on the <a href="#">minted GitHub site</a> .	
<code>xleftmargin</code>	(dimension)	(default: 0)
	Indentation to add before the listing.	
<code>xrightmargin</code>	(dimension)	(default: 0)
	Indentation to add after the listing.	

## 6 Defining shortcuts

Large documents with a lot of listings will nonetheless use the same source language and the same set of options for most listings. Always specifying all options is redundant, a lot to type and makes performing changes hard.

One option is to use `\setminted`, but even then you must still specify the language each time.

`minted` therefore defines a set of commands that lets you define shortcuts for the highlighting commands. Each shortcut is specific for one programming language.

`\newminted` `\newminted` defines a new alias for the `minted` environment:

```
\newminted{cpp}{gobble=2,linenos}

\begin{cppcode}
  template <typename T>
  T id(T value) {
    return value;
  }
\end{cppcode}
1 template <typename T>
2 T id(T value) {
3     return value;
4 }
```

If you want to provide extra options on the fly, or override existing default options, you can do that, too:

```
\newminted{cpp}{gobble=2,linenos}
```

```
\begin{cppcode*}{linenos=false,  
                frame=single}  
  int const answer = 42;  
\end{cppcode*}
```

```
int const answer = 42;
```

Notice the star “\*” behind the environment name—due to restrictions in `fancyvrb`’s handling of options, it is necessary to provide a *separate* environment that accepts options, and the options are *not* optional on the starred version of the environment.

The default name of the environment is `<language>code`. If this name clashes with another environment or if you want to choose an own name for another reason, you may do so by specifying it as the first argument: `\newminted[<environment name>]{<language>}{<options>}`.

Like normal minted environments, environments created with `\newminted` may be used within other environment definitions. Since the minted environments use `fancyvrb` internally, any environment based on them must include the `fancyvrb` command `\VerbatimEnvironment`. This allows `fancyvrb` to determine the name of the environment that is being defined, and correctly find its end. It is best to include this command at the beginning of the definition. For example,

```
\newminted{cpp}{gobble=2,linenos}  
\newenvironment{env}{\VerbatimEnvironment\begin{cppcode}}{\end{cppcode}}
```

`\newmint`

The above macro only defines shortcuts for the `minted` environment. The main reason is that the short command form `\mint` often needs different options—at the very least, it will generally not use the `gobble` option. A shortcut for `\mint` is defined using `\newmint[<macro name>]{<language>}{<options>}`. The arguments and usage are identical to `\newminted`. If no `<macro name>` is specified, `<language>` is used.

```
\newmint{perl}{showspaces}
```

```
my_ $foo = _ $bar;
```

```
\perl/my $foo = $bar;/
```

`\newmintinline`

This creates custom versions of `\mintinline`. The syntax is the same as that for `\newmint`: `\newmintinline[<macro name>]{<language>}{<options>}`. If a `<macro name>` is not specified, then the created macro is called `\<language>inline`.

```
\newmintinline{perl}{showspaces}
```

```
Xmy_ $foo = _ $bar;X
```

```
X\perlinline/my $foo = $bar;/X
```

`\newmintedfile`

This creates custom versions of `\inputminted`. The syntax is

```
\newmintedfile[<macro name>]{<language>}{<options>}
```

If no  $\langle macro\ name \rangle$  is given, then the macro is called  $\langle language \rangle file$ .

## 7 FAQ and Troubleshooting

In some cases, `minted` may not give the desired result due to other document settings that it cannot control. Common issues are described below, with workarounds or solutions. You may also wish to search [tex.stackexchange.com](https://tex.stackexchange.com) or ask a question there, if you are working with `minted` in a non-typical context.

- **There are intermittent “I can’t write on file” errors.** This can be caused by using `minted` in a directory that is synchronized with Dropbox or a similar file syncing program. These programs can try to sync `minted`’s temporary files while it still needs to be able to modify them. The solution is to turn off file syncing or use a directory that is not synced.
- **I receive a “Font Warning: Some font shapes were not available” message, or bold or italic seem to be missing.** This is due to a limitation in the font that is currently in use for typesetting code. In some cases, the default font shapes that L<sup>A</sup>T<sub>E</sub>X substitutes are perfectly adequate, and the warning may be ignored. In other cases, the font substitutions may not clearly indicate bold or italic text, and you will want to switch to a different font. See The L<sup>A</sup>T<sub>E</sub>X Font Catalogue’s section on [Typewriter Fonts](#) for alternatives. If you like the default L<sup>A</sup>T<sub>E</sub>X fonts, the `lmodern` package is a good place to start. The `beramono` and `courier` packages may also be good options.
- **I receive a “Too many open files” error under OS X when using caching.** See the note on OS X under Section 3.1.
- **TeXShop can’t find pygmentize.** You may need to create a symlink. See <https://tex.stackexchange.com/questions/279214>.
- **Weird things happen when I use the fancybox package.** `fancybox` conflicts with `fancyvrb`, which `minted` uses internally. When using `fancybox`, make sure that it is loaded before `minted` (or before `fancyvrb`, if `fancyvrb` is not loaded by `minted`).
- **When I use minted with KOMA-Script document classes, I get warnings about \float@addtolists.** `minted` uses the `float` package to produce floated listings, but this conflicts with the way KOMA-Script does floats. Load the package `scrhack` to resolve the conflict. Or use `minted`’s `newfloat` package option.
- **Tilde characters ~ are raised, almost like superscripts.** This is a font issue. You need a different font encoding, possibly with a different font. Try `\usepackage[T1]{fontenc}`, perhaps with `\usepackage{lmodern}`, or something similar.

- **I'm getting errors with math, something like TeX capacity exceeded and \leavevmode\kern\z@.** This is due to ligatures being disabled within verbatim content. See the note under `escapeinside`.
- **With mathescape and the breqn package (or another special math package), the document never finishes compiling or there are other unexpected results.** Some math packages like `breqn` give certain characters like the comma special meanings in math mode. These can conflict with `minted`. In the `breqn` and comma case, this can be fixed by redefining the comma within `minted` environments:

```
\AtBeginEnvironment{minted}{\catcode`\,=12\mathcode`\,="613B}
```

Other packages/special characters may need their own modifications.

- **I'm getting errors with Beamer.** Due to how Beamer treats verbatim content, you may need to use either the `fragile` or `fragile=singleslide` options for frames that contain `minted` commands and environments. `fragile=singleslide` works best, but it disables overlays. `fragile` works by saving the contents of each frame to a temp file and then reusing them. This approach allows overlays, but will break if you have the string `\end{frame}` at the beginning of a line (for example, in a `minted` environment). To work around that, you can indent the content of the environment (so that the `\end{frame}` is preceded by one or more spaces) and then use the `gobble` or `autogobble` options to remove the indentation.
- **Tabs are eaten by Beamer.** This is due to a [bug in Beamer's treatment of verbatim content](#). Upgrade Beamer or use the linked patch. Otherwise, try `fragile=singleslide` if you don't need overlays, or consider using `\inputminted` or converting the tabs into spaces.
- **I'm trying to create several new minted commands/environments, and want them all to have the same settings. I'm saving the settings in a macro and then using the macro when defining the commands/environments. But it's failing.** This is due to the way that `keyval` works (`minted` uses it to manage options). Arguments are not expanded. See [this](#) and [this](#) for more information. It is still possible to do what you want; you just need to expand the options macro before passing it to the commands that create the new commands/environments. An example is shown below. The `\expandafter` is the vital part.

```
\def\args{linenos,frame=single,fontsize=\footnotesize,style=bw}

\newcommand{\makenewmintedfiles}[1]{%
  \newmintedfile[inputlatex]{latex}{#1}%
  \newmintedfile[inputc]{c}{#1}%
}

\expandafter\makenewmintedfiles\expandafter{\args}
```



- **I want to use `\mintinline` in a context that normally doesn't allow verbatim content.** The `\mintinline` command will already work in many places that do not allow normal verbatim commands like `\verb`, so make sure to try it first. If it doesn't work, one of the simplest alternatives is to save your code in a box, and then use it later. For example,

```
\newsavebox\mybox
\begin{lrbox}{\mybox}
\mintinline{cpp}{std::cout}
\end{lrbox}

\commandthatdoesnotlikeverbatim{Text \usebox{\mybox}}
```

- **Extended characters do not work inside `minted` commands and environments, even when the `inputenc` package is used.** Version 2.0 adds support for extended characters under the pdfTeX engine. But if you need characters that are not supported by `inputenc`, you should use the XeTeX or LuaTeX engines instead.
- **The `polyglossia` package is doing undesirable things to code. (For example, adding extra space around colons in French.)** You may need to put your code within `\begin{english}...\end{english}`. This may be done for all `minted` environments using `etoolbox` in the preamble:

```
\usepackage{etoolbox}
\BeforeBeginEnvironment{minted}{\begin{english}}
\AfterEndEnvironment{minted}{\end{english}}
```

- **Tabs are being turned into the character sequence `^^I`.** This happens when you use XeLaTeX. You need to use the `-8bit` command-line option so that tabs may be written correctly to temporary files. See <http://tex.stackexchange.com/questions/58732/how-to-output-a-tabulation-into-a-file> for more on XeLaTeX's handling of tab characters.
- **The `caption` package produces an error when `\captionof` and other commands are used in combination with `minted`.** Load the `caption` package with the option `compatibility=false`. Or better yet, use `minted`'s `newfloat` package option, which provides better caption compatibility.
- **I need a listing environment that supports page breaks.** The built-in listing environment is a standard float; it doesn't support page breaks. You will probably want to define a new environment for long floats. For example,

```
\usepackage{caption}
\newenvironment{longlisting}{\captionsetup{type=listing}}{}
```

With the caption package, it is best to use minted’s newfloat package option. See <http://tex.stackexchange.com/a/53540/10742> for more on listing environments with page breaks.

- **I want to use a custom script/executable to access Pygments, rather than pygmentize.** Redefine \MintedPygmentize:

```
\renewcommand{\MintedPygmentize}{...}
```

- **I want to use the command-line option -output-directory, or MiKTeX’s -aux-directory, but am getting errors.** Use the package option outputdir to specify the location of the output directory. Unfortunately, there is no way for minted to detect the output directory automatically.
- **I want extended characters in frame labels, but am getting errors.** This can happen with minted <2.0 and Python 2.7, due to a [terminal encoding issue with Pygments](#). It should work with any version of Python with minted 2.0+, which processes labels internally and does not send them to Python.
- **minted environments have extra vertical space inside tabular.** It is possible to [create a custom environment](#) that eliminates the extra space. However, a general solution that behaves as expected in the presence of adjacent text remains to be found.
- **I’m receiving a warning from lineno.sty that “Command \@parboxrestore has changed.”** This can happen when minted is loaded after csquotes. Try loading minted first. If you receive this message when you are not using csquotes, you may want to experiment with the order of loading packages and might also open an issue.
- **I’m using texi2pdf, and getting “Cannot stat” errors from tar:** This is due to the way that texi2pdf handles temporary files. minted automatically cleans up its temporary files, but texi2pdf assumes that any temporary file that is ever created will still exist at the end of the run, so it tries to access the files that minted has deleted. It’s possible to disable minted’s temp file cleanup by adding \renewcommand{\DeleteFile}[2][{} after the \usepackage{minted}.

## Acknowledgements

**Konrad Rudolph:** Special thanks to Philipp Stephani and the rest of the guys from `comp.text.tex` and `tex.stackexchange.com`.

**Geoffrey Poore:**

- Thanks to Marco Daniel for the code on [tex.stackexchange.com](http://tex.stackexchange.com) that inspired automatic line breaking.

- Thanks to Patrick Vogt for improving TikZ externalization compatibility.
- Thanks to @muzimuzhi for assistance with GitHub issues.
- Thanks to @jfbu for suggestions and discussion regarding support for arbitrary Pygments style names (#210, #294, #299, #317), and for debugging assistance.

## Version History

### v2.6 (2021/12/24)

- `autogobble` automatically uses `python` or `python3` executables, depending on availability, instead of requiring `python`. A custom executable can be specified by redefining `\MintedPython` (#277, #287).
- Fixed `autogobble` compatibility with `fancyvrb` 4.0+ (#315, #316).
- Pygments style names may now contain arbitrary non-whitespace characters. Previously, style names containing digits and some punctuation characters were incompatible (#210, #294, #299, #317). Pygments macros are now only defined just before use locally within `minted` commands and environments, rather than globally. Pygments macros now always use a `\PYG` prefix regardless of style, rather than a prefix of the form `\PYG<style>` (for example, what was previously `\PYGdefault` is now simply `\PYG`).
- Removed Python-based MD5 hashing for XeTeX, which was necessary before XeTeX added `\mdfivesum` in 2017.
- The default for `stripnl` is now `false`, so that original code is preserved exactly by default (#198).
- Added support for `fontencoding` option from `fvextra` (#208).
- Added note to FAQ about getting `texi2pdf` to work with `minted` given `texi2pdf`'s assumptions about temp files (#186).
- Reimplemented `bgcolor` option to be compatible with `color` package.

### v2.5 (2017/07/19)

- The default placement for the `listing` float is now `tbp` instead of `h`, to parallel `figure` and `table` and also avoid warnings caused by `h` (#165). The documentation now contains information about changing default placement. The `float` package is no longer loaded when the `newfloat` package option is used.
- Added support for `*nchars` options from `fvextra` v1.3 that allow setting `breaklines`-related indentation in terms of a number of characters, rather than as a fixed dimension.

- Fixed incompatibility with `babel magyar` (#158).
- Added support for `beamer` overlays with `beameroverlays` option (#155).
- Comments in the Pygments  $\LaTeX$  style files no longer appear as literal text when `minted` is used in `.dtx` files (#161).
- `autogobble` now works with package option `kpsewhich` (#151). Under Windows, the `kpsewhich` option no longer requires PowerShell.
- Fixed a bug that prevented `finalizcache` from working with `outputdir` (#149).
- Fixed a bug with `firstline` and `lastline` that prevented them from working with the `minted` environment (#145).
- Added note on `breqn` conflicts to FAQ (#163).

#### v2.4.1 (2016/10/31)

- Single quotation marks in `\jobname` are now replaced with underscores in `\minted@jobname` to prevent quoting errors (#137).
- The `autogobble` option now takes `firstline` and `lastline` into account (#130).
- Fixed `numberblanklines`, which had been lost in the transition to v2.0+ (#135).

#### v2.4 (2016/07/20)

- Line breaking and all associated options are now completely delegated to `fvextra`.
- Fixed a bug from v2.2 that could cause the first command or environment to vanish when `cache=false` (related to work on `\MintedPygmentize`).

#### v2.3 (2016/07/14)

- The `fvextra` package is now required. `fvextra` extends and patches `fancyvrb`, and includes improved versions of `fancyvrb` extensions that were formerly in `minted`.
- As part of `fvextra`, the `upquote` package is always loaded. `fvextra` brings the new option `curlyquotes`, which allows curly single quotation marks instead of the literal backtick and typewriter single quotation mark produced by `upquote`. This allows the default `upquote` behavior to be disabled when desired.
- Thanks to `fvextra`, the options `breakbefore`, `breakafter`, and `breakanywhere` are now compatible with non-ASCII characters under pdfTeX (#123).

- Thanks to `fvextra`, `obeytabs` no longer causes lines in multi-line comments or strings to vanish (#88), and is now compatible with `breaklines` (#99). `obeytabs` will now always give correct results with tabs used for indentation. However, tab stops are not guaranteed to be correct for tabs in the midst of text.
- `fvextra` brings the new options `space`, `spacecolor`, `tab`, and `tabcolor` that allow these characters and their colors to be redefined (#98). The tab may now be redefined to a flexible-width character such as `\rightarrowfill`. The visible tab will now always be black by default, instead of changing colors depending on whether it is part of indentation for a multiline string or comment.
- `fvextra` brings the new options `highlightcolor` and `highlightlines`, which allow single lines or ranges of lines to be highlighted based on line number (#124).
- `fvextra` brings the new options `numberfirstline`, `stepnumberfromfirst`, and `stepnumberoffsetvalues` that provide better control over line numbering when `stepnumber` is not 1.
- Fixed a bug from v2.2.2 that prevented `upquote` from working.

#### v2.2.2 (2016/06/21)

- Fixed a bug introduced in v2.2 that prevented setting the Pygments style in the preamble. Style definitions are now more compatible with using `\MintedPygmentize` to call a custom `pygmentize`.

#### v2.2.1 (2016/06/15)

- The `shellesc` package is loaded before `ifplatform` and other packages that might invoke `\write18` (#112).
- When caching is enabled, XeTeX uses the new `\mdfivesum` macro from TeX Live 2016 to hash cache content, rather than using `\ShellEscape` with Python to perform hashing.

#### v2.2 (2016/06/08)

- All uses of `\ShellEscape` (`\write18`) no longer wrap file names and paths with double quotes. This allows a cache directory to be specified relative to a user's home directory, for example, `~/minted_cache`. `cachedir` and `outputdir` paths containing spaces will now require explicit quoting of the parts of the paths that contain spaces, since `minted` no longer supplies quoting. See the updated documentation for examples (#89).
- Added `breakbefore`, `breakbeforegroup`, `breakbeforesymbolpre`, and `breakbeforesymbolpost`. These parallel `breakafter*`. It is possible to use `breakbefore` and `breakafter` for the same character, so long as `breakbeforegroup` and `breakaftergroup` have the same setting (#117).

- Added package options `finalizcache` and `frozencache`. These allow the cache to be prepared for (`finalizcache`) and then used (`frozencache`) in an environment in which `-shell-escape`, Python, and/or Pygments are not available. Note that this only works if `minted` content does not need to be modified, and if no settings that depend on Pygments or Python need to be changed (#113).
- Style names containing hyphens and underscores (`paraiso-light`, `paraiso-dark`, `algot_nu`) now work (#111).
- The `shellesc` package is now loaded, when available, for compatibility with LuaTeX 0.87+ (TeX Live 2016+, etc.). `\ShellEscape` is now used everywhere instead of `\immediate\write18`. If `shellesc` is not available, then a `\ShellEscape` macro is created. When `shellesc` is loaded, there is a check for versions before v0.01c to patch a bug in v0.01b (present in TeX Live 2015) (#112).
- The `bgcolor` option now uses the `snugshade*` environment from the `framed` package, so `bgcolor` is now compatible with page breaks. When `bgcolor` is in use, immediately preceding text will no longer push the `minted` environment into the margin, and there is now adequate spacing from surrounding text (#121).
- Added missing support for `fancyvrb`'s `labelposition` (#102).
- Improved fix for TikZ externalization, thanks to Patrick Vogt (#73).
- Fixed `breakautoindent`; it was disabled in version 2.1 due to a bug in `breakanywhere`.
- Properly fixed handling of `\MintedPygmentize` (#62).
- Added note on incompatibility of `breaklines` and `obeytabs` options. Trying to use these together will now result in a package error (#99). Added note on issues with `obeytabs` and multiline comments (#88). Due to the various `obeytabs` issues, the docs now discourage using `obeytabs`.
- Added note to FAQ on `fancybox` and `fancyvrb` conflict (#87).
- Added note to docs on the need for `\VerbatimEnvironment` in environment definitions based on `minted` environments.

### v2.1 (2015/09/09)

- Changing the highlighting style now no longer involves re-highlighting code. Style may be changed with almost no overhead.
- Improved control of automatic line breaks. New option `breakanywhere` allows line breaks anywhere when `breaklines=true`. The pre-break and post-break symbols for these types of breaks may be set with `breakanywheresymbolpre` and `breakanywheresymbolpost` (#79). New option `breakafter` allows specifying characters after which line breaks are allowed. Breaks between adjacent, identical characters may

be controlled with `breakaftergroup`. The pre-break and post-break symbols for these types of breaks may be set with `breakaftersymbolpre` and `breakaftersymbolpost`.

- `breakbytoken` now only breaks lines between tokens that are separated by spaces, matching the documentation. The new option `breakbytokenanywhere` allows for breaking between tokens that are immediately adjacent. Fixed a bug in `\mintinline` that produced a following linebreak when `\mintinline` was the first thing in a paragraph and `breakbytoken` was true (#77).
- Fixed a bug in draft mode option handling for `\inputminted` (#75).
- Fixed a bug with `\MintedPygmentize` when a custom `pygmentize` was specified and there was no `pygmentize` on the default path (#62).
- Added note to docs on caching large numbers of code blocks under OS X (#78).
- Added discussion of current limitations of `texcomments` (#66) and `escapeinside` (#70).
- PGF/TikZ externalization is automatically detected and supported (#73).
- The package is now compatible with L<sup>A</sup>T<sub>E</sub>X files whose names contain spaces (#85).

#### v2.0 (2015/01/31)

- Added the compatibility package `minted1`, which provides the `minted 1.7` code. This may be loaded when 1.7 compatibility is required. This package works with other packages that `\RequirePackage{minted}`, so long as it is loaded first.
- Moved all old `\changes` into `changelog`.

#### Development releases for 2.0 (2014–January 2015)

- Caching is now on by default.
- Fixed a bug that prevented compiling under Windows when file names contained commas.
- Added `breaksymbolleft`, `breaksymbolsepleft`, `breaksymbolindentleft`, `breaksymbolright`, `breaksymbolsepright`, and `breaksymbolindentright` options. `breaksymbol`, `breaksymbolsep`, and `breaksymbolindent` are now aliases for the correspondent `*left` options.
- Added `kpsewhich` package option. This uses `kpsewhich` to locate the files that are to be highlighted. This provides compatibility with build tools like `texi2pdf` that function by modifying `TEXINPUTS` (#25).
- Fixed a bug that prevented `\inputminted` from working with `outputdir`.
- Added informative error messages when Pygments output is missing.

- Added `final` package option (opposite of `draft`).
- Renamed the default cache directory to `_minted-<jobname>` (replaced leading period with underscore). The leading period caused the cache directory to be hidden on many systems, which was a potential source of confusion.
- `breaklines` and `breakbytoken` now work with `\mintinline` (#31).
- `bgcolor` may now be set through `\setminted` and `\setmintedinline`.
- When math is enabled via `texcomments`, `mathescape`, or `escapeinside`, space characters now behave as in normal math by vanishing, instead of appearing as literal spaces. Math need no longer be specially formatted to avoid undesired spaces.
- In default value of `\listoflistingscaption`, capitalized “Listings” so that capitalization is consistent with default values for other lists (figures, tables, algorithms, etc.).
- Added `newfloat` package option that creates the `listing` environment using `newfloat` rather than `float`, thus providing better compatibility with the `caption` package (#12).
- Added support for Pygments option `stripall`.
- Added `breakbytoken` option that prevents `breaklines` from breaking lines within Pygments tokens.
- `\mintinline` uses a `\colorbox` when `bgcolor` is set, to give more reasonable behavior (#57).
- For PHP, `\mintinline` automatically begins with `startinline=true` (#23).
- Fixed a bug that threw off line numbering in `minted` when `langlinenos=false` and `firstnumber=last`. Fixed a bug in `\mintinline` that threw off subsequent line numbering when `langlinenos=false` and `firstnumber=last`.
- Improved behavior of `\mint` and `\mintinline` in `draft` mode.
- The `\mint` command now has the additional capability to take code delimited by paired curly braces `{}`.
- It is now possible to set options only for `\mintinline` using the new `\setmintedinline` command. Inline options override options specified via `\setminted`.
- Completely rewrote option handling. `fancyvrb` options are now handled on the  $\LaTeX$  side directly, rather than being passed to Pygments and then returned. This makes caching more efficient, since code is no longer rehighlighted just because `fancyvrb` options changed.
- Fixed buffer size error caused by using `cache` with a very large number of files (#61).
- Fixed `autogobble` bug that caused failure under some operating systems.



- Added support for `escapeinside` (requires Pygments 2.0+; #38).
- Fixed issues with XeTeX and caching (#40).
- The `upquote` package now works correctly with single quotes when using Pygments 1.6+ (#34).
- Fixed caching incompatibility with Linux and OS X under xelatex (#18 and #42).
- Fixed `autogobble` incompatibility with Linux and OS X.
- `\mintinline` and derived commands are now robust, via `\newrobustcmd` from `etoolbox`.
- Unused styles are now cleaned up when caching.
- Fixed a bug that could interfere with caching (#24).
- Added `draft` package option (#39). This typesets all code using `fancyvrb`; Pygments is not used. This trades syntax highlighting for maximum speed in compiling.
- Added automatic line breaking with `breaklines` and related options (#1).
- Fixed a bug with boolean options that needed a `False` argument to cooperate with `\setminted` (#48).

#### **v2.0-alpha3** (2013/12/21)

- Added `autogobble` option. This sends code through Python's `textwrap.dedent()` to remove common leading whitespace.
- Added package option `cachedir`. This allows the directory in which cached content is saved to be specified.
- Added package option `outputdir`. This allows an output directory for temporary files to be specified, so that the package can work with LaTeX's `-output-directory` command-line option.
- The `kvoptions` package is now required. It is needed to process key-value package options, such as the new `cachedir` option.
- Many small improvements, including better handling of paths under Windows and improved key system.

#### **v2.0-alpha2** (2013/08/21)

- `\DeleteFile` now only deletes files if they do indeed exist. This eliminates warning messages due to missing files.
- Fixed a bug in the definition of `\DeleteFile` for non-Windows systems.
- Added support for Pygments option `stripnl`.
- Settings macros that were previously defined globally are now defined locally, so that `\setminted` may be confined by `\begingroup... \endgroup` as expected.

- Macro definitions for a given style are now loaded only once per document, rather than once per command/environment. This works even without caching.
- A custom script/executable may now be substituted for `pygmentize` by redefining `\MintedPygmentize`.

### **v2.0alpha** (2013/07/30)

- Added the package option `cache`. This significantly increases compilation speed by caching old output. For example, compiling the documentation is around 5x faster.
- New inline command `\mintinline`. Custom versions can be created via `\newmintinline`. The command works inside other commands (for example, footnotes) in most situations, so long as the percent and hash characters are avoided.
- The new `\setminted` command allows options to be specified at the document and language levels.
- All extended characters (Unicode, etc.) supported by `inputenc` now work under the pdfTeX engine. This involved using `\detokenize` on everything prior to saving.
- New package option `langlinenos` allows line numbering to pick up where it left off for a given language when `firstnumber=last`.
- New options, including `style`, `encoding`, `outencoding`, `codetagify`, `keywordcase`, `texcomments` (same as `texcl`), `python3` (for the `PythonConsoleLexer`), and `numbers`.
- `\usemintedstyle` now takes an optional argument to specify the style for a particular language, and works anywhere in the document.
- `xcolor` is only loaded if `color` isn't, preventing potential package clashes.

### **1.7** (2011/09/17)

- Options for float placement added [2011/09/12]
- Fixed `tabsize` option [2011/08/30]
- More robust detection of the `-shell-escape` option [2011/01/21]
- Added the `label` option [2011/01/04]
- Installation instructions added [2010/03/16]
- Minimal working example added [2010/03/16]
- Added PHP-specific options [2010/03/14]
- Removed unportable flag from Unix shell command [2010/02/16]

### **1.6** (2010/01/31)

- Added font-related options [2010/01/27]
- Windows support added [2010/01/27]
- Added command shortcuts [2010/01/22]
- Simpler versioning scheme [2010/01/22]

#### 0.1.5 (2010/01/13)

- Added `fillcolor` option [2010/01/10]
- Added float support [2010/01/10]
- Fixed `firstnumber` option [2010/01/10]
- Removed `caption` option [2010/01/10]

#### 0.0.4 (2010/01/08)

- Initial version [2010/01/08]

## 8 Implementation

### 8.1 Required packages

Load required packages. For compatibility reasons, most old functionality should be supported with the original set of packages. More recently added packages, such as `etoolbox` and `xstring`, should only be used for new features when possible. `shellesc` must be loaded before any packages that invoke `\write18`, since it is possible that they haven't yet been patched to work with LuaTeX 0.87+.

```

1 \RequirePackage{keyval}
2 \RequirePackage{kvoptions}
3 \RequirePackage{fvextra}
4 \RequirePackage{ifthen}
5 \RequirePackage{calc}
6 \IfFileExists{shellesc.sty}
7   {\RequirePackage{shellesc}
8    \ifpackagelater{shellesc}{2016/04/29}
9     {}
10    {\protected\def\ShellEscape{\immediate\write18 }}}
11  {\protected\def\ShellEscape{\immediate\write18 }}
12 \RequirePackage{ifplatform}
13 \RequirePackage{pdftexcmds}
14 \RequirePackage{etoolbox}
15 \RequirePackage{xstring}
16 \RequirePackage{lineno}
17 \RequirePackage{framed}
18 \RequirePackage{catchfile}

```

Make sure that either `color` or `xcolor` is loaded by the beginning of the document.

```
19 \AtEndPreamble{%
20   \ifpackageloaded{color}{}{}%
21   \ifpackageloaded{xcolor}{}{\RequirePackage{xcolor}}}%
22 }
```

## 8.2 Package options

`\minted@float@within` Define an option that controls the section numbering of the `listing` float.

```
23 \DeclareVoidOption{chapter}{\def\minted@float@within{chapter}}
24 \DeclareVoidOption{section}{\def\minted@float@within{section}}
```

`newfloat` Define an option to use `newfloat` rather than `float` to create a floated `listing` environment.

```
25 \DeclareBoolOption{newfloat}
```

`cache` Define an option that determines whether highlighted content is cached. We use a boolean to keep track of its state.

```
26 \DeclareBoolOption[true]{cache}
```

`\minted@jobname` At various points, temporary files and directories will need to be named after the main `.tex` file. The typical way to do this is to use `\jobname`. However, if the file name contains spaces, then `\jobname` will contain the name wrapped in quotes (older versions of MiKTeX replace spaces with asterisks instead, and XeTeX apparently allows double quotes within file names, in which case names are wrapped in single quotes). While that is perfectly fine for working with L<sup>A</sup>T<sub>E</sub>X internally, it causes problems with `\write18`, since quotes will end up in unwanted locations in shell commands. It would be possible to strip the wrapping quotation marks when they are present, and maintain any spaces in the file name. But it is simplest to create a “sanitized” version of `\jobname` in which spaces and asterisks are replaced by underscores, and double quotes are stripped. Single quotes are also replaced, since they can cause quoted string errors, or become double quotes in the process of being passed to the system through `\write18`.

```
27 \StrSubstitute{\jobname}{ }{_[\minted@jobname]
28 \StrSubstitute{\minted@jobname}{*}{_[\minted@jobname]
29 \StrSubstitute{\minted@jobname}{"}{'}[\minted@jobname]
30 \StrSubstitute{\minted@jobname}{'}{_[\minted@jobname]
```

`\minted@cachedir` Set the directory in which cached content is saved. The default uses a `minted-` prefix followed by the sanitized `\minted@jobname`.

```

31 \newcommand{\minted@cachedir}{\detokenize{_\minted-\minted@jobname}}
32 \let\minted@cachedir@windows\minted@cachedir
33 \define@key{minted}{cachedir}{%
34   \@namedef{minted@cachedir}{#1}%
35   \StrSubstitute{\minted@cachedir}{/}{\@backslashchar}[\minted@cachedir@windows]}

```

**finalizcache** Define an option that switches the naming of cache files from an MD5-based system to a `listing<number>` scheme. Compiling with this option is a prerequisite to turning on `frozenscache`.

```
36 \DeclareBoolOption{finalizcache}
```

**frozenscache** Define an option that uses a fixed set of cache files, using `listing<number>` file naming with `\write18` disabled. This is convenient for working with a document in an environment in which `\write18` support is disabled and `minted` content does not need to be modified.

```
37 \DeclareBoolOption{frozenscache}
```

**\minted@outputdir** The `-output-directory` command-line option for  $\LaTeX$  causes problems for `minted`, because the `minted` temporary files are saved in the output directory, but `minted` still looks for them in the document root directory. There is no way to access the value of the command-line option. But it is possible to allow the output directory to be specified manually as a package option. A trailing slash is automatically appended to the `outputdir`, so that it may be directly joined to `cachedir`. This may be redundant if the user-supplied value already ends with a slash, but doubled slashes are ignored under `*nix` and Windows, so it isn't a problem.

```

38 \let\minted@outputdir\@empty
39 \let\minted@outputdir@windows\@empty
40 \define@key{minted}{outputdir}{%
41   \@namedef{minted@outputdir}{#1/}%
42   \StrSubstitute{\minted@outputdir}{/}{%
43     {\@backslashchar}[\minted@outputdir@windows]}

```

**kpsewhich** Define an option that invokes `kpsewhich` to locate the files that are to be `pygmentized`. This isn't done by default to avoid the extra overhead, but can be useful with some build tools such as `texi2pdf` that rely on modifying `TEXINPUTS`.

```
44 \DeclareBoolOption{kpsewhich}
```

**langlinenos** Define an option that makes all `minted` environments and `\mint` commands for a given language share cumulative line numbering (if `firstnumber=last`).

```
45 \DeclareBoolOption{langlinenos}
```

`draft` Define an option that allows `fancyvrb` to do all typesetting directly, without using `Pygments`. This trades syntax highlighting for speed. Note that in many cases, the difference in performance between caching and draft mode will be minimal. Also note that draft settings may be inherited from the document class.

```
46 \DeclareBoolOption{draft}
```

`final` Define a `final` option that is the opposite of `draft`, since many packages do this.

```
47 \DeclareComplementaryOption{final}{draft}
```

Process package options. Proceed with everything that immediately relies upon them. If PGF/TikZ externalization is in use, switch on `draft` mode and turn off `cache`. Externalization involves compiling the *entire* document; all parts not related to the current image are “silently thrown away.” `minted` needs to cooperate with that by not writing any temp files or creating any directories. Two checks are done for externalization. The first, using `\tikzifexternalizing`, works if externalization is set before `minted` is loaded. The second, using `\tikzexternalrealjob`, works if externalization is set after `minted` is loaded.

```
48 \ProcessKeyvalOptions*
49 \ifthenelse{\boolean{minted@newfloat}}{\RequirePackage{newfloat}}{\RequirePackage{float}}
50 \ifcsname tikzifexternalizing\endcsname
51   \tikzifexternalizing{\minted@drafttrue\minted@cachefalse}{}
52 \else
53   \ifcsname tikzexternalrealjob\endcsname
54     \minted@drafttrue
55     \minted@cachefalse
56   \else
57     \fi
58 \fi
59 \ifthenelse{\boolean{minted@finalizcache}}%
60   {\ifthenelse{\boolean{minted@frozencache}}%
61     {\PackageError{minted}%
62       {Options "finalizcache" and "frozencache" are not compatible}%
63       {Options "finalizcache" and "frozencache" are not compatible}}%
64   {}}%
65 {}
66 \ifthenelse{\boolean{minted@cache}}%
67   {\ifthenelse{\boolean{minted@frozencache}}%
68     {}%
69   {\AtEndOfPackage{\ProvideDirectory{\minted@outputdir\minted@cachedir}}}}%
70 {}
```

### 8.3 Input, caching, and temp files

`\minted@input` We need a wrapper for `\input`. In most cases, `\input` failure will be due to attempts to use `\inputminted` with files that don't exist, but we also want to give

informative error messages when `outputdir` is needed or incompatible build tools are used.

```
71 \newcommand{\minted@input}[1]{%
72   \IfFileExists{#1}%
73   {\input{#1}}%
74   {\PackageError{minted}{Missing Pygments output; \string\inputminted\space
75     was^^Jprobably given a file that does not exist--otherwise, you may need
76     ^^Jthe outputdir package option, or may be using an incompatible build
77     tool,^^Jor may be using frozencache with a missing file}%
78   {This could be caused by using -output-directory or -aux-directory
79     ^^Jwithout setting minted's outputdir, or by using a build tool that
80     ^^Jchanges paths in ways minted cannot detect,
81     ^^Jor using frozencache with a missing file.}}%
82 }
```

`\minted@infile` Define a default name for files of highlighted content that are brought in. Caching will redefine this. We start out with the default, non-caching value.

```
83 \newcommand{\minted@infile}{\minted@jobname.out.pyg}
```

We need a way to track the cache files that are created, and delete those that are not in use. This is accomplished by creating a comma-delimited list of cache files and saving this list to the `.aux` file so that it may be accessed on subsequent runs. During subsequent runs, this list is compared against the cache files that are actually used, and unused files are deleted. Cache file names are created with MD5 hashes of highlighting settings and file contents, with a `.pygtex` extension, so they never contain commas. Thus comma-delimiting the list of file names doesn't introduce a potential for errors.

`\minted@cachelist` This is a list of the current cache files.

```
84 \newcommand{\minted@cachelist}{}
```

`\minted@addcachefile` This adds a file to the list of cache files. It also creates a macro involving the hash, so that the current usage of the hash can be easily checked by seeing if the macro exists. The list of cache files must be created with built-in linebreaks, so that when it is written to the `.aux` file, it won't all be on one line and thereby risk buffer errors.

```
85 \newcommand{\minted@addcachefile}[1]{%
86   \expandafter\long\expandafter\gdef\expandafter\minted@cachelist\expandafter{%
87     \minted@cachelist,^^J%
88     \space\space#1}%
89   \expandafter\gdef\csname minted@cached@#1\endcsname{}%
90 }
```

`\minted@savecachelist` We need to be able to save the list of cache files to the `.aux` file, so that we can reload it on the next run.

```
91 \newcommand{\minted@savecachelist}{%
92   \ifdefempty{\minted@cachelist}{}%
93     \immediate\write\@mainaux{%
94       \string\gdef\string\minted@oldcachelist\string{%
95         \minted@cachelist\string}}%
96   }%
97 }
```

`\minted@cleancache` Clean up old cache files that are no longer in use.

```
98 \newcommand{\minted@cleancache}{%
99   \ifcsname minted@oldcachelist\endcsname
100     \def\do##1{%
101       \ifthenelse{\equal{##1}{}}{ }{%
102         \ifcsname minted@cached@##1\endcsname\else
103           \DeleteFile[\minted@outputdir\minted@cachedir]{##1}%
104         \fi
105       }%
106     }%
107     \expandafter\docsvlist\expandafter{\minted@oldcachelist}%
108   \else
109     \fi
110 }
```

At the end of the document, save the list of cache files and clean the cache. If in draft mode, don't clean up the cache and save the old cache file list for next time. This allows draft mode to be switched on and off without requiring that all highlighted content be regenerated. The saving and cleaning operations may be called without conditionals, since their definitions already contain all necessary checks for their correct operation.

```
111 \ifthenelse{\boolean{minted@draft}}{%
112   {\AtEndDocument{%
113     \ifcsname minted@oldcachelist\endcsname
114       \StrSubstitute{\minted@oldcachelist}{,}{,^^J }[\minted@cachelist]
115       \minted@savecachelist
116     \fi}}%
117   {\ifthenelse{\boolean{minted@frozensave}}{%
118     {\AtEndDocument{%
119       \ifcsname minted@oldcachelist\endcsname
120         \StrSubstitute{\minted@oldcachelist}{,}{,^^J }[\minted@cachelist]
121         \minted@savecachelist
122       \fi}}%
123     {\AtEndDocument{%
124       \minted@savecachelist
125       \minted@cleancache}}}%
126   }
```



## 8.4 OS interaction

We need system-dependent macros for communicating with the “outside world.”

`\DeleteFile` Delete a file. Define conditionally in case an equivalent macro has already been defined.

```
126 \ifwindows
127 \providecommand{\DeleteFile}[2] [] {%
128   \ifthenelse{\equal{#1}{}}{%
129     {\IfFileExists{#2}{\ShellEscape{del #2}}{}}%
130     {\IfFileExists{#1/#2}{%
131       \StrSubstitute{#1}{/}{\@backslashchar}[\minted@windir]
132       \ShellEscape{del \minted@windir\@backslashchar #2}}{}}%
133 \else
134 \providecommand{\DeleteFile}[2] [] {%
135   \ifthenelse{\equal{#1}{}}{%
136     {\IfFileExists{#2}{\ShellEscape{rm #2}}{}}%
137     {\IfFileExists{#1/#2}{\ShellEscape{rm #1/#2}}{}}%
138 \fi
```

`\ProvideDirectory` We need to be able to create a directory, if it doesn't already exist. This is primarily for storing cached highlighted content.

```
139 \ifwindows
140 \newcommand{\ProvideDirectory}[1] {%
141   \StrSubstitute{#1}{/}{\@backslashchar}[\minted@windir]
142   \ShellEscape{if not exist \minted@windir\space mkdir \minted@windir}}
143 \else
144 \newcommand{\ProvideDirectory}[1] {%
145   \ShellEscape{mkdir -p #1}}
146 \fi
```

`\TestAppExists` Determine whether a given application exists.

Usage is a bit roundabout, but has been retained for backward compatibility. At some point, it may be worth replacing this with something using `\@input"<command>`". That would require MiKTeX users to `--enable-pipes`, however, which would make things a little more complicated. If Windows XP compatibility is ever no longer required, the `where` command could be used instead of the approach for Windows.

To test whether an application exists, use the following code:

```
\TestAppExists{appname}
\ifthenelse{\boolean{AppExists}}{app exists}{app doesn't exist}

147 \newboolean{AppExists}
```

```

148 \newread\minted@appexistsfile
149 \newcommand{\TestAppExists}[1]{%
150   \ifwindows

```

On Windows, we need to use path expansion and write the result to a file. If the application doesn't exist, the file will be empty (except for a newline); otherwise, it will contain the full path of the application.

```

151   \DeleteFile{\minted@jobname.aex}%
152   \ShellEscape{for \string^\@percentchar i in (#1.exe #1.bat #1.cmd)
153     do set > \minted@jobname.aex <nul: /p
154     x=\string^\@percentchar \string~$PATH:i>> \minted@jobname.aex}%
155   %$ <- balance syntax highlighting
156   \immediate\openin\minted@appexistsfile\minted@jobname.aex
157   \expandafter\def\expandafter\@tmp@cr\expandafter{\the\newlinechar}%
158   \newlinechar=-1\relax
159   \readline\minted@appexistsfile to \minted@apppathifexists
160   \newlinechar=\@tmp@cr
161   \ifthenelse{\equal{\minted@apppathifexists}{}}%
162     {\AppExistsfalse}%
163     {\AppExiststrue}%
164   \immediate\closein\minted@appexistsfile
165   \DeleteFile{\minted@jobname.aex}%
166   \else

```

On Unix-like systems, we do a straightforward which test and create a file upon success, whose existence we can then check.

```

167   \ShellEscape{which #1 && touch \minted@jobname.aex}%
168   \IfFileExists{\minted@jobname.aex}%
169     {\AppExiststrue
170       \DeleteFile{\minted@jobname.aex}}%
171     {\AppExistsfalse}%
172   \fi
173 }

```

## 8.5 Option processing

Option processing is somewhat involved, because we want to be able to define options at various levels of hierarchy: individual command/environment, language, global (document). And once those options are defined, we need to go through the hierarchy in a defined order of precedence to determine which option to apply. As if that wasn't complicated enough, some options need to be sent to Pygments, some need to be sent to fancyvrb, and some need to be processed within minted itself.

To begin with, we need macros for storing lists of options that will later be passed via the command line to Pygments (`optlistc1`). These are defined at the global

(`cl@g`), language (`cl@lang`), and command or environment (`cl@cmd`) levels, so that settings can be specified at various levels of hierarchy. The language macro is actually a placeholder. The current language will be tracked using `\minted@lang`. Each individual language will create a `\minted@optlistcl@lang⟨language⟩` macro. `\minted@optlistcl@lang` may be `\let` to this macro as convenient; otherwise, the general language macro merely serves as a placeholder.

The global- and language-level lists also have an `inline (i)` variant. This allows different settings to be applied in inline settings. An inline variant is not needed at the command/environment level, since at that level settings would not be present unless they were supposed to be applied.

```
\minted@optlistcl@g
```

```
174 \newcommand{\minted@optlistcl@g}{}
```

```
\minted@optlistcl@g@i
```

```
175 \newcommand{\minted@optlistcl@g@i}{}
```

```
\minted@lang
```

```
176 \let\minted@lang\@empty
```

```
\minted@optlistcl@lang
```

```
177 \newcommand{\minted@optlistcl@lang}{}
```

```
\minted@optlistcl@lang@i
```

```
178 \newcommand{\minted@optlistcl@lang@i}{}
```

```
\minted@optlistcl@cmd
```

```
179 \newcommand{\minted@optlistcl@cmd}{}
```

We also need macros for storing lists of options that will later be passed to `fancyvrb` (`optlistfv`). As before, these exist at the global (`fv@g`), language (`fv@lang`), and command or environment (`fv@cmd`) levels. `Pygments` accepts `fancyvrb` options, but in almost all cases, these options may be applied via `\fvset` rather than via running `Pygments`. This is significantly more efficient when caching is turned on, since it allows formatting changes to be applied without having to re-highlight the code.

```
\minted@optlistfv@g
```

```
180 \newcommand{\minted@optlistfv@g}{}
```

```

\minted@optlistfv@g@i
181 \newcommand{\minted@optlistfv@g@i}{}

\minted@optlistfv@lang
182 \newcommand{\minted@optlistfv@lang}{}

\minted@optlistfv@lang@i
183 \newcommand{\minted@optlistfv@lang@i}{}

\minted@optlistfv@cmd
184 \newcommand{\minted@optlistfv@cmd}{}

\minted@configlang We need a way to check whether a language has had all its option list macros
                    created. This generally occurs in a context where \minted@lang needs to be set.
                    So we create a macro that does both at once. If the language list macros do not
                    exist, we create them globally to simplify future operations.

185 \newcommand{\minted@configlang}[1]{%
186   \def\minted@lang{#1}%
187   \ifcsname minted@optlistcl@lang\minted@lang\endcsname\else
188     \expandafter\gdef\csname minted@optlistcl@lang\minted@lang\endcsname{}%
189   \fi
190   \ifcsname minted@optlistcl@lang\minted@lang @i\endcsname\else
191     \expandafter\gdef\csname minted@optlistcl@lang\minted@lang @i\endcsname{}%
192   \fi
193   \ifcsname minted@optlistfv@lang\minted@lang\endcsname\else
194     \expandafter\gdef\csname minted@optlistfv@lang\minted@lang\endcsname{}%
195   \fi
196   \ifcsname minted@optlistfv@lang\minted@lang @i\endcsname\else
197     \expandafter\gdef\csname minted@optlistfv@lang\minted@lang @i\endcsname{}%
198   \fi
199 }

```

We need a way to define options in bulk at the global, language, and command levels. How this is done will depend on the type of option. The keys created are grouped by level: `minted@opt@g`, `minted@opt@lang`, and `minted@opt@cmd`, plus inline variants. The language-level key groupings use `\minted@lang` internally, so we don't need to duplicate the internals for different languages. The key groupings are independent of whether a given option relates to `Pygments`, `fancyvrb`, etc. Organization by level is the only thing that is important here, since keys are applied in a hierarchical fashion. Key values are stored in macros of the form `\minted@opt@<level>:<key>`, so that they may be retrieved later. In practice, these key macros will generally not be used directly (hence the colon in the name). Rather, the hierarchy of macros will be traversed until an existing macro is found.

`\minted@def@optcl` Define a generic option that will be passed to the command line. Options are given in a `{key}{value}` format that is transformed into `key=value` and then passed to `pygmentize`. This allows `value` to be easily stored in a separate macro for later access. This is useful, for example, in separately accessing the value of `encoding` for performing `autogobble`.

If a `key` option is specified without `=value`, the default is assumed. Options are automatically created at all levels.

Options are added to the option lists in such a way that they will be detokenized. This is necessary since they will ultimately be used in `\write18`.

```

200 \newcommand{\minted@addto@optlistcl}[2]{%
201   \expandafter\def\expandafter#1\expandafter{#1%
202     \detokenize{#2}\space}}
203 \newcommand{\minted@addto@optlistcl@lang}[2]{%
204   \expandafter\let\expandafter\minted@tmp\csname #1\endcsname
205   \expandafter\def\expandafter\minted@tmp\expandafter{\minted@tmp%
206     \detokenize{#2}\space}%
207   \expandafter\let\csname #1\endcsname\minted@tmp}
208 \newcommand{\minted@def@optcl}[4] []{%
209   \ifthenelse{\equal{#1}{}}{%
210     {\define@key{\minted@opt@g}{#2}{%
211       \minted@addto@optlistcl{\minted@optlistcl@g}{#3=#4}%
212       \@namedef{\minted@opt@g:#2}{#4}}%
213     \define@key{\minted@opt@g@i}{#2}{%
214       \minted@addto@optlistcl{\minted@optlistcl@g@i}{#3=#4}%
215       \@namedef{\minted@opt@g@i:#2}{#4}}%
216     \define@key{\minted@opt@lang}{#2}{%
217       \minted@addto@optlistcl@lang{\minted@optlistcl@lang\minted@lang}{#3=#4}%
218       \@namedef{\minted@opt@lang\minted@lang:#2}{#4}}%
219     \define@key{\minted@opt@lang@i}{#2}{%
220       \minted@addto@optlistcl@lang{%
221         \minted@optlistcl@lang\minted@lang @i}{#3=#4}%
222       \@namedef{\minted@opt@lang\minted@lang @i:#2}{#4}}%
223     \define@key{\minted@opt@cmd}{#2}{%
224       \minted@addto@optlistcl{\minted@optlistcl@cmd}{#3=#4}%
225       \@namedef{\minted@opt@cmd:#2}{#4}}%
226   {\define@key{\minted@opt@g}{#2}[#1]{%
227     \minted@addto@optlistcl{\minted@optlistcl@g}{#3=#4}%
228     \@namedef{\minted@opt@g:#2}{#4}}%
229     \define@key{\minted@opt@g@i}{#2}[#1]{%
230       \minted@addto@optlistcl{\minted@optlistcl@g@i}{#3=#4}%
231       \@namedef{\minted@opt@g@i:#2}{#4}}%
232     \define@key{\minted@opt@lang}{#2}[#1]{%
233       \minted@addto@optlistcl@lang{\minted@optlistcl@lang\minted@lang}{#3=#4}%
234       \@namedef{\minted@opt@lang\minted@lang:#2}{#4}}%
235     \define@key{\minted@opt@lang@i}{#2}[#1]{%
236       \minted@addto@optlistcl@lang{%
237         \minted@optlistcl@lang\minted@lang @i}{#3=#4}%

```

```

238     \@namedef{minted@opt@lang\minted@lang @i:#2}{#4}}%
239     \define@key{minted@opt@cmd}{#2}[#1]{%
240     \minted@addto@optlistcl{\minted@optlistcl@cmd}{#3=#4}%
241     \@namedef{minted@opt@cmd:#2}{#4}}}%
242 }

```

This covers the typical options that must be passed to Pygments. But some, particularly `escapeinside`, need more work. Since their arguments may contain escaped characters, expansion rather than detokenization is needed. Getting expansion to work as desired in a `\write18` context requires the redefinition of some characters.

`\minted@escchars` We need to define versions of common escaped characters that will work correctly under expansion for use in `\write18`.

```

243 \edef\minted@hashchar{\string#}
244 \edef\minted@dollarchar{\string$}
245 \edef\minted@ampchar{\string&}
246 \edef\minted@underscorechar{\string_}
247 \edef\minted@tildechar{\string~}
248 \edef\minted@leftsquarebracket{\string[]}
249 \edef\minted@rightsquarebracket{\string]}
250 \newcommand{\minted@escchars}{%
251   \let#\minted@hashchar
252   \let%\minted@percentchar
253   \let{\minted@charlb
254   \let}\minted@charrb
255   \let$\minted@dollarchar
256   \let&\minted@ampchar
257   \let_\minted@underscorechar
258   \let\minted@backslashchar
259   \let~\minted@tildechar
260   \let~\minted@tildechar
261   \let[\minted@leftsquarebracket
262   \let]\minted@rightsquarebracket
263 } %$ <- highlighting

```

`\minted@def@optcl@e` Now to define options that are expanded.

```

264 \newcommand{\minted@addto@optlistcl@e}[2]{%
265   \begingroup
266   \minted@escchars
267   \xdef\minted@xtmp{#2}%
268   \endgroup
269   \expandafter\minted@addto@optlistcl@e@i\expandafter{\minted@xtmp}{#1}}
270 \def\minted@addto@optlistcl@e@i#1#2{%
271   \expandafter\def\expandafter#2\expandafter{#2#1\space}}
272 \newcommand{\minted@addto@optlistcl@lang@e}[2]{%
273   \begingroup

```

```

274 \minted@escchars
275 \xdef\minted@xtmp{#2}%
276 \endgroup
277 \expandafter\minted@addto@optlistcl@lang@e@i\expandafter{\minted@xtmp}{#1}}
278 \def\minted@addto@optlistcl@lang@e@i#1#2{%
279 \expandafter\let\expandafter\minted@tmp\csname #2\endcsname
280 \expandafter\def\expandafter\minted@tmp\expandafter{\minted@tmp#1\space}%
281 \expandafter\let\csname #2\endcsname\minted@tmp}
282 \newcommand{\minted@def@optcl@e}[4][{}]{%
283 \ifthenelse{\equal{#1}{}}{%
284   {\define@key{\minted@opt@g}{#2}{%
285     \minted@addto@optlistcl@e{\minted@optlistcl@g}{#3=#4}%
286     \@namedef{\minted@opt@g:#2}{#4}}%
287   \define@key{\minted@opt@g@i}{#2}{%
288     \minted@addto@optlistcl@e{\minted@optlistcl@g@i}{#3=#4}%
289     \@namedef{\minted@opt@g@i:#2}{#4}}%
290   \define@key{\minted@opt@lang}{#2}{%
291     \minted@addto@optlistcl@lang@e{\minted@optlistcl@lang\minted@lang}{#3=#4}%
292     \@namedef{\minted@opt@lang\minted@lang:#2}{#4}}%
293   \define@key{\minted@opt@lang@i}{#2}{%
294     \minted@addto@optlistcl@lang@e{%
295       \minted@optlistcl@lang\minted@lang @i}{#3=#4}%
296     \@namedef{\minted@opt@lang\minted@lang @i:#2}{#4}}%
297   \define@key{\minted@opt@cmd}{#2}{%
298     \minted@addto@optlistcl@e{\minted@optlistcl@cmd}{#3=#4}%
299     \@namedef{\minted@opt@cmd:#2}{#4}}%
300   {\define@key{\minted@opt@g}{#2}[#1]{%
301     \minted@addto@optlistcl@e{\minted@optlistcl@g}{#3=#4}%
302     \@namedef{\minted@opt@g:#2}{#4}}%
303   \define@key{\minted@opt@g@i}{#2}[#1]{%
304     \minted@addto@optlistcl@e{\minted@optlistcl@g@i}{#3=#4}%
305     \@namedef{\minted@opt@g@i:#2}{#4}}%
306   \define@key{\minted@opt@lang}{#2}[#1]{%
307     \minted@addto@optlistcl@lang@e{\minted@optlistcl@lang\minted@lang}{#3=#4}%
308     \@namedef{\minted@opt@lang\minted@lang:#2}{#4}}%
309   \define@key{\minted@opt@lang@i}{#2}[#1]{%
310     \minted@addto@optlistcl@lang@e{%
311       \minted@optlistcl@lang\minted@lang @i}{#3=#4}%
312     \@namedef{\minted@opt@lang\minted@lang @i:#2}{#4}}%
313   \define@key{\minted@opt@cmd}{#2}[#1]{%
314     \minted@addto@optlistcl@e{\minted@optlistcl@cmd}{#3=#4}%
315     \@namedef{\minted@opt@cmd:#2}{#4}}%
316 }

```

`\minted@def@optcl@switch` Define a switch or boolean option that is passed to Pygments, which is true when no value is specified.

```

317 \newcommand{\minted@def@optcl@switch}[2]{%
318   \define@booleankey{\minted@opt@g}{#1}%
319   {\minted@addto@optlistcl{\minted@optlistcl@g}{#2=True}%

```

```

320     \@namedef{minted@opt@g:#1}{true}}
321     {\minted@addto@optlistcl{\minted@optlistcl@g}{#2=False}}%
322     \@namedef{minted@opt@g:#1}{false}}
323 \define@booleankey{minted@opt@g@i}{#1}%
324     {\minted@addto@optlistcl{\minted@optlistcl@g@i}{#2=True}}%
325     \@namedef{minted@opt@g@i:#1}{true}}
326     {\minted@addto@optlistcl{\minted@optlistcl@g@i}{#2=False}}%
327     \@namedef{minted@opt@g@i:#1}{false}}
328 \define@booleankey{minted@opt@lang}{#1}%
329     {\minted@addto@optlistcl@lang{minted@optlistcl@lang\minted@lang}{#2=True}}%
330     \@namedef{minted@opt@lang\minted@lang:#1}{true}}
331     {\minted@addto@optlistcl@lang{minted@optlistcl@lang\minted@lang}{#2=False}}%
332     \@namedef{minted@opt@lang\minted@lang:#1}{false}}
333 \define@booleankey{minted@opt@lang@i}{#1}%
334     {\minted@addto@optlistcl@lang{minted@optlistcl@lang\minted@lang @i}{#2=True}}%
335     \@namedef{minted@opt@lang\minted@lang @i:#1}{true}}
336     {\minted@addto@optlistcl@lang{minted@optlistcl@lang\minted@lang @i}{#2=False}}%
337     \@namedef{minted@opt@lang\minted@lang @i:#1}{false}}
338 \define@booleankey{minted@opt@cmd}{#1}%
339     {\minted@addto@optlistcl{\minted@optlistcl@cmd}{#2=True}}%
340     \@namedef{minted@opt@cmd:#1}{true}}
341     {\minted@addto@optlistcl{\minted@optlistcl@cmd}{#2=False}}%
342     \@namedef{minted@opt@cmd:#1}{false}}
343 }

```

Now that all the machinery for Pygments options is in place, we can move on to fancyvrb options.

`\minted@def@optfv` Define fancyvrb options. The `#1={##1}` is needed because any braces enclosing the argument (`##1`) will be stripped during the initial capture, and they need to be reinserted before fancyvrb gets the argument and sends it through another keyval processing step. If there were no braces initially, adding them here doesn't hurt, since they are just stripped off again during processing.

```

344 \newcommand{\minted@def@optfv}[1]{%
345   \define@key{minted@opt@g}{#1}{%
346     \expandafter\def\expandafter\minted@optlistfv@g\expandafter{%
347       \minted@optlistfv@g#1={##1},}%
348     \@namedef{minted@opt@g:#1}{##1}}
349   \define@key{minted@opt@g@i}{#1}{%
350     \expandafter\def\expandafter\minted@optlistfv@g@i\expandafter{%
351       \minted@optlistfv@g@i#1={##1},}%
352     \@namedef{minted@opt@g@i:#1}{##1}}
353   \define@key{minted@opt@lang}{#1}{%
354     \expandafter\let\expandafter\minted@tmp%
355     \csname minted@optlistfv@lang\minted@lang\endcsname
356     \expandafter\def\expandafter\minted@tmp\expandafter{%
357       \minted@tmp#1={##1},}%
358     \expandafter\let\csname minted@optlistfv@lang\minted@lang\endcsname%

```



```

359     \minted@tmp
360     \@namedef{minted@opt@lang\minted@lang:#1}{##1}}
361 \define@key{minted@opt@lang@i}{#1}{%
362   \expandafter\let\expandafter\minted@tmp%
363   \csname minted@optlistfv@lang\minted@lang @i\endcsname
364   \expandafter\def\expandafter\minted@tmp\expandafter{%
365     \minted@tmp#1=##1},}%
366 \expandafter\let\csname minted@optlistfv@lang\minted@lang @i\endcsname%
367   \minted@tmp
368 \@namedef{minted@opt@lang\minted@lang @i:#1}{##1}}
369 \define@key{minted@opt@cmd}{#1}{%
370   \expandafter\def\expandafter\minted@optlistfv@cmd\expandafter{%
371     \minted@optlistfv@cmd#1=##1},}%
372 \@namedef{minted@opt@cmd:#1}{##1}}
373 }

```

`\minted@def@optfv@switch` Define fancyvrb boolean options.

```

374 \newcommand{\minted@def@optfv@switch}[1]{%
375   \define@booleankey{minted@opt@g}{#1}%
376   {\expandafter\def\expandafter\minted@optlistfv@g\expandafter{%
377     \minted@optlistfv@g#1=true},}%
378   \@namedef{minted@opt@g:#1}{true}}%
379   {\expandafter\def\expandafter\minted@optlistfv@g\expandafter{%
380     \minted@optlistfv@g#1=false},}%
381   \@namedef{minted@opt@g:#1}{false}}%
382 \define@booleankey{minted@opt@g@i}{#1}%
383   {\expandafter\def\expandafter\minted@optlistfv@g@i\expandafter{%
384     \minted@optlistfv@g@i#1=true},}%
385   \@namedef{minted@opt@g@i:#1}{true}}%
386   {\expandafter\def\expandafter\minted@optlistfv@g@i\expandafter{%
387     \minted@optlistfv@g@i#1=false},}%
388   \@namedef{minted@opt@g@i:#1}{false}}%
389 \define@booleankey{minted@opt@lang}{#1}%
390   {\expandafter\let\expandafter\minted@tmp%
391     \csname minted@optlistfv@lang\minted@lang\endcsname
392     \expandafter\def\expandafter\minted@tmp\expandafter{%
393       \minted@tmp#1=true},}%
394     \expandafter\let\csname minted@optlistfv@lang\minted@lang\endcsname%
395       \minted@tmp
396     \@namedef{minted@opt@lang\minted@lang:#1}{true}}%
397   {\expandafter\let\expandafter\minted@tmp%
398     \csname minted@optlistfv@lang\minted@lang\endcsname
399     \expandafter\def\expandafter\minted@tmp\expandafter{%
400       \minted@tmp#1=false},}%
401     \expandafter\let\csname minted@optlistfv@lang\minted@lang\endcsname%
402       \minted@tmp
403     \@namedef{minted@opt@lang\minted@lang:#1}{false}}%
404 \define@booleankey{minted@opt@lang@i}{#1}%
405   {\expandafter\let\expandafter\minted@tmp%

```

```

406     \csname minted@optlistfv@lang\minted@lang @i\endcsname
407     \expandafter\def\expandafter\minted@tmp\expandafter{%
408       \minted@tmp#1=true,}%
409     \expandafter\let\csname minted@optlistfv@lang\minted@lang @i\endcsname%
410       \minted@tmp
411     \@namedef{minted@opt@lang\minted@lang @i:#1}{true}}%
412   {\expandafter\let\expandafter\minted@tmp%
413     \csname minted@optlistfv@lang\minted@lang @i\endcsname
414     \expandafter\def\expandafter\minted@tmp\expandafter{%
415       \minted@tmp#1=false,}%
416     \expandafter\let\csname minted@optlistfv@lang\minted@lang @i\endcsname%
417       \minted@tmp
418     \@namedef{minted@opt@lang\minted@lang @i:#1}{false}}%
419   \define@booleankey{minted@opt@cmd}{#1}%
420   {\expandafter\def\expandafter\minted@optlistfv@cmd\expandafter{%
421     \minted@optlistfv@cmd#1=true,}%
422     \@namedef{minted@opt@cmd:#1}{true}}%
423   {\expandafter\def\expandafter\minted@optlistfv@cmd\expandafter{%
424     \minted@optlistfv@cmd#1=false,}%
425     \@namedef{minted@opt@cmd:#1}{false}}%
426 }

```

`minted@isinline` In resolving value precedence when actually using values, we need a way to determine whether we are in an inline context. This is accomplished via a boolean that is set at the beginning of inline commands.

```
427 \newboolean{minted@isinline}
```

`\minted@fvset` We will need a way to actually use the lists of stored fancyvrb options later on.

```

428 \newcommand{\minted@fvset}{%
429   \expandafter\fvset\expandafter{\minted@optlistfv@g}%
430   \expandafter\let\expandafter\minted@tmp%
431   \csname minted@optlistfv@lang\minted@lang\endcsname
432   \expandafter\fvset\expandafter{\minted@tmp}%
433   \ifthenelse{\boolean{minted@isinline}}%
434     {\expandafter\fvset\expandafter{\minted@optlistfv@g@i}%
435     \expandafter\let\expandafter\minted@tmp%
436     \csname minted@optlistfv@lang\minted@lang @i\endcsname
437     \expandafter\fvset\expandafter{\minted@tmp}}%
438   {}%
439   \expandafter\fvset\expandafter{\minted@optlistfv@cmd}%
440 }

```

We need a way to define `minted`-specific options at multiple levels of hierarchy, as well as a way to retrieve these options. As with previous types of options, values are stored in macros of the form `\minted@opt@<level>:<key>`, since they are not meant to be accessed directly.

The order of precedence is `cmd`, `lang@i`, `g@i`, `lang`, `g`. A value specified at the command or environment level should override other settings. In its absence, a value specified for an inline command should override other settings, if we are indeed in an inline context. Otherwise, language settings take precedence over global settings.

Before actually creating the option-definition macro, we need a few helper macros.

`\minted@def@opt` Finally, on to the actual option definitions for minted-specific options.

Usage: `\minted@def@opt` [*initial global value*] {*key name*}

```

441 \newcommand{\minted@def@opt}[2] []{%
442   \define@key{minted@opt@g}{#2}{%
443     \@namedef{minted@opt@g:#2}{##1}}
444   \define@key{minted@opt@g@i}{#2}{%
445     \@namedef{minted@opt@g@i:#2}{##1}}
446   \define@key{minted@opt@lang}{#2}{%
447     \@namedef{minted@opt@lang\minted@lang:#2}{##1}}
448   \define@key{minted@opt@lang@i}{#2}{%
449     \@namedef{minted@opt@lang\minted@lang @i:#2}{##1}}
450   \define@key{minted@opt@cmd}{#2}{%
451     \@namedef{minted@opt@cmd:#2}{##1}}
452   \ifstrempy{#1}{-}{\@namedef{minted@opt@g:#2}{#1}}%
453 }

```

`\minted@def@opt@detok` Same as `\minted@def@opt`, except wraps argument in `\detokenize`.

```

454 \newcommand{\minted@def@opt@detok}[2] []{%
455   \define@key{minted@opt@g}{#2}{%
456     \@namedef{minted@opt@g:#2}{\detokenize{##1}}}
457   \define@key{minted@opt@g@i}{#2}{%
458     \@namedef{minted@opt@g@i:#2}{\detokenize{##1}}}
459   \define@key{minted@opt@lang}{#2}{%
460     \@namedef{minted@opt@lang\minted@lang:#2}{\detokenize{##1}}}
461   \define@key{minted@opt@lang@i}{#2}{%
462     \@namedef{minted@opt@lang\minted@lang @i:#2}{\detokenize{##1}}}
463   \define@key{minted@opt@cmd}{#2}{%
464     \@namedef{minted@opt@cmd:#2}{\detokenize{##1}}}
465   \ifstrempy{#1}{-}{\@namedef{minted@opt@g:#2}{\detokenize{#1}}}%
466 }

```

`\minted@generate@PYGdef` Generate Pygments style definition with `pygmentize` if a cached version does not exist. Load the style definition into a global macro of the form

```
\csname minted@PYGdef@<style>\endcsname
```

to allow styles to be defined later. Styles are not defined globally to avoid naming issues with style names that involve punctuation characters and numbers. Rather,

styles are redefined upon every use (within groups), and all styles use macros with a `\PYG` prefix.

Takes a single argument that is the detokenized style name. Getting the detokenized style name here requires expansion (`\edef`) in an earlier macro (currently `\minted@defstyle`) to convert `\minted@get@opt{style}{default}` into detokenized text. The `style` value is always wrapped in `\detokenize` when it is set, so expansion automatically detokenizes. Detokenization can be important depending on active characters. Expansion is important because the style name may be used with caching, so we need the current value retrieved by `\minted@get@opt`, not the value at the end of the document when cache data is written to the `.aux` file.

Certain catcodes are required when loading Pygments style definitions from file.

- At sign `@` would be handled by the `\makeatletter` within the Pygments style definition if the style was brought in via `\input`, but `\makeatletter` doesn't affect tokenization with the `catchfile` approach.
- Percent `%` may not have its normal meaning within a `.dtx` file.
- Backtick ``` is made active by some `babel` package options, such as `magyar`.

`\endlinechar` also requires special handling to avoid introducing unwanted spaces.

The `\ifx\PYG\relax` tests detect outdated style definitions from `minted <2.6` and replace them when possible, and also detect missing styles. Before `minted 2.6`, style macros used a `\PYG<style>` prefix and were defined globally. Starting with `2.6`, styles are redefined upon every use (within groups), and all styles use macros with a `\PYG` prefix. This allows more robust treatment of style names that involve punctuation characters and numbers.

```
467 \newcommand{\minted@generate@PYGdef}[1]{%
468   \ifthenelse{\boolean{minted@cache}}{%
469     {\def\minted@pygstylepath@load{\minted@outputdir\minted@cachedir/#1.pygstyle}%
470      \minted@addcachefile{#1.pygstyle}}%
471     {\def\minted@pygstylepath@load{\minted@outputdir\minted@jobname.out.pyg}}%
472   \ifwindows
473     \StrSubstitute{\minted@pygstylepath@load}%
474     {/}{\@backslashchar}[\minted@pygstylepath@save]%
475   \else
476     \let\minted@pygstylepath@save\minted@pygstylepath@load
477   \fi
478   \IfFileExists{\minted@pygstylepath@load}%
479   {}%
480   {\ifthenelse{\boolean{minted@frozenscache}}{%
481     {\PackageError{minted}%
482      {Missing style definition for #1 with frozenscache}%
483      {Missing style definition for #1 with frozenscache}}%
484     {}%
485     \ShellEscape%
```

```

486     \MintedPygmentize\space -S #1 -f latex -P commandprefix=PYG
487     > \minted@pygstylepath@save
488     }%
489   }%
490 \CatchFileDef{\minted@tmp@filecontents}%
491   {\minted@pygstylepath@load}{\catcode`@=11\catcode`\%=14\catcode``=12\endlinechar=-1}%
492 \begingroup
493 \let\PYG\relax
494 \minted@tmp@filecontents
495 \ifx\PYG\relax
496   \ifthenelse{\boolean{minted@frozenscache}}{%
497     {\PackageError{minted}%
498       {Outdated style definition for #1 with frozenscache}%
499       {Outdated style definition for #1 with frozenscache}}%
500   }%
501 \ShellEscape{%
502   \MintedPygmentize\space -S #1 -f latex -P commandprefix=PYG
503   > \minted@pygstylepath@save
504   }%
505 \CatchFileDef{\minted@tmp@filecontents}%
506   {\minted@pygstylepath@load}{\catcode`@=11\catcode`\%=14\catcode``=12\endlinechar=-1}%
507 \minted@tmp@filecontents
508 \ifx\PYG\relax
509   \PackageError{minted}%
510     {Cannot find Pygments style #1}%
511     {Cannot find Pygments style #1}%
512 \fi
513 \fi
514 \expandafter\global\expandafter\let\csname minted@PYGdef@#1\endcsname%
515   \minted@tmp@filecontents
516 \endgroup
517 }

```

`\minted@defstyle` Define Pygments style macros. These are defined locally rather than globally, and redefined upon every use. Patch single quote macro if needed.

```

518 \newcommand{\minted@defstyle}[1]{%
519   \edef\minted@style{#1}%
520   \ifcsname minted@PYGdef@\minted@style\endcsname\else
521     \expandafter\minted@generate@PYGdef\expandafter{\minted@style}%
522   \fi
523   \csname minted@PYGdef@\minted@style\endcsname
524   \minted@patch@PYGZsq
525 }
526 \ifthenelse{\boolean{minted@draft}}{\renewcommand{\minted@defstyle}[1]{}{}}{}

```

`\minted@patch@PYGZsq` The single quote macro from Pygments 1.6+ needs to be patched if the `upquote` package is in use. Patching is done when the default style is created. Patching is only attempted if the macro exists, so that there is a graceful fallback in the event

of a custom Pygments stylesheet.

```
527 \newcommand{\minted@patch@PYGZsq}{%
528   \ifcsname PYGZsq\endcsname
529     \expandafter\ifdefstring\expandafter{\csname PYGZsq\endcsname}{\char`'}%
530     {\minted@patch@PYGZsq@i}%
531     {}%
532   \fi
533 }
534 \begingroup
535 \catcode`\'= \active
536 \gdef\minted@patch@PYGZsq@i{\gdef\PYGZsq{'}}
537 \endgroup
538 \ifthenelse{\boolean{minted@draft}}{\AtBeginDocument{\minted@patch@PYGZsq}}
```

`\minted@def@opt@switch` And we need a switch version.

It would be possible to create a special version of `\minted@get@opt` to work with these, but that would be redundant. During the key processing, any values other than `true` and `false` are filtered out. So when using `\minted@get@opt` later, we know that that part has already been taken care of, and we can just use something like `\ifthenelse{\equal{\minted@get@opt{<opt>}{<default>}}{true}}{...}{...}`. Of course, there is the possibility that a default value has not been set, but `\minted@def@opt@switch` sets a global default of `false` to avoid this. And as usual, Pygments values shouldn't be used without considering whether `\minted@get@opt` needs a fallback value.

```
539 \newcommand{\minted@def@opt@switch}[2][false]{%
540   \define@booleankey{minted@opt@g}{#2}%
541   {\@namedef{minted@opt@g:#2}{true}}%
542   {\@namedef{minted@opt@g:#2}{false}}
543   \define@booleankey{minted@opt@g@i}{#2}%
544   {\@namedef{minted@opt@g@i:#2}{true}}%
545   {\@namedef{minted@opt@g@i:#2}{false}}
546   \define@booleankey{minted@opt@lang}{#2}%
547   {\@namedef{minted@opt@lang\minted@lang:#2}{true}}%
548   {\@namedef{minted@opt@lang\minted@lang:#2}{false}}
549   \define@booleankey{minted@opt@lang@i}{#2}%
550   {\@namedef{minted@opt@lang\minted@lang @i:#2}{true}}%
551   {\@namedef{minted@opt@lang\minted@lang @i:#2}{false}}
552   \define@booleankey{minted@opt@cmd}{#2}%
553   {\@namedef{minted@opt@cmd:#2}{true}}%
554   {\@namedef{minted@opt@cmd:#2}{false}}%
555   \@namedef{minted@opt@g:#2}{#1}%
556 }
```

`\minted@get@opt` We need a way to traverse the hierarchy of values for a given key and return the current value that has precedence. In doing this, we need to specify a default value to use if no value is found. When working with minted-specific values, there should

generally be a default value; in those cases, an empty default may be supplied. But the macro should also work with Pygments settings, which are stored in macros of the same form and will sometimes need to be accessed (for example, `encoding`). In the Pygments case, there may very well be no default values on the  $\text{\LaTeX}$  side, because we are falling back on Pygments' own built-in defaults. There is no need to duplicate those when very few Pygments values are ever needed; it is simpler to specify the default fallback when accessing the macro value.

From a programming perspective, the default argument value needs to be mandatory, so that `\minted@get@opt` can be fully expandable. This significantly simplifies accessing options.

```

557 \def\minted@get@opt#1#2{%
558   \ifcsname minted@opt@cmd:#1\endcsname
559     \csname minted@opt@cmd:#1\endcsname
560   \else
561     \ifminted@isinline
562       \ifcsname minted@opt@lang\minted@lang @i:#1\endcsname
563         \csname minted@opt@lang\minted@lang @i:#1\endcsname
564       \else
565         \ifcsname minted@opt@g@i:#1\endcsname
566           \csname minted@opt@g@i:#1\endcsname
567         \else
568           \ifcsname minted@opt@lang\minted@lang:#1\endcsname
569             \csname minted@opt@lang\minted@lang:#1\endcsname
570           \else
571             \ifcsname minted@opt@g:#1\endcsname
572               \csname minted@opt@g:#1\endcsname
573             \else
574               #2%
575             \fi
576           \fi
577         \fi
578       \fi
579     \else
580       \ifcsname minted@opt@lang\minted@lang:#1\endcsname
581         \csname minted@opt@lang\minted@lang:#1\endcsname
582       \else
583         \ifcsname minted@opt@g:#1\endcsname
584           \csname minted@opt@g:#1\endcsname
585         \else
586           #2%
587         \fi
588       \fi
589     \fi
590   \fi
591 }%

```

Actual option definitions. Some of these must be defined conditionally depending

on whether we are in **draft** mode; in **draft** mode, we need to emulate Pygments functionality with L<sup>A</sup>T<sub>E</sub>X, particularly with `fancyvrb`, when possible. For example, gobbling must be performed by Pygments when **draft** is off, but when **draft** is on, `fancyvrb` can perform gobbling.

Lexers.

```

592 \minted@def@optcl{encoding}{-P encoding}{#1}
593 \minted@def@optcl{outencoding}{-P outencoding}{#1}
594 \minted@def@optcl@e{escapeinside}{-P "escapeinside}{#1"}
595 \minted@def@optcl@switch{stripnl}{-P stripnl}
596 \minted@def@optcl@switch{stripall}{-P stripall}
597 % Python console
598 \minted@def@optcl@switch{python3}{-P python3}
599 % PHP
600 \minted@def@optcl@switch{funcnamehighlighting}{-P funcnamehighlighting}
601 \minted@def@optcl@switch{startinline}{-P startinline}

```

Filters.

```

602 \ifthenelse{\boolean{minted@draft}}%
603   {\minted@def@optfv{gobble}}%
604   {\minted@def@optcl{gobble}{-F gobble:n}{#1}}
605 \minted@def@optcl{codetagify}{-F codetagify:codetags}{#1}
606 \minted@def@optcl{keywordcase}{-F keywordcase:case}{#1}

```

L<sup>A</sup>T<sub>E</sub>X formatter.

```

607 \minted@def@optcl@switch{texcl}{-P texcomments}
608 \minted@def@optcl@switch{texcomments}{-P texcomments}
609 \minted@def@optcl@switch{mathescape}{-P mathescape}
610 \minted@def@optfv@switch{linenos}
611 \minted@def@opt@detok{style}

```

`fancyvrb` and `fvextra` options.

```

612 \minted@def@optfv{frame}
613 \minted@def@optfv{framesep}
614 \minted@def@optfv{framerule}
615 \minted@def@optfv{rulecolor}
616 \minted@def@optfv{numbersep}
617 \minted@def@optfv{numbers}
618 \minted@def@optfv{firstnumber}
619 \minted@def@optfv{stepnumber}
620 \minted@def@optfv{firstline}
621 \minted@def@optfv{lastline}
622 \minted@def@optfv{baselinestretch}
623 \minted@def@optfv{xleftmargin}
624 \minted@def@optfv{xrightmargin}
625 \minted@def@optfv{fillcolor}
626 \minted@def@optfv{tabsize}

```



```

627 \minted@def@optfv{fontfamily}
628 \minted@def@optfv{fontsize}
629 \minted@def@optfv{fontshape}
630 \minted@def@optfv{fontseries}
631 \minted@def@optfv{formatcom}
632 \minted@def@optfv{label}
633 \minted@def@optfv{labelposition}
634 \minted@def@optfv{highlightlines}
635 \minted@def@optfv{highlightcolor}
636 \minted@def@optfv{space}
637 \minted@def@optfv{spacecolor}
638 \minted@def@optfv{tab}
639 \minted@def@optfv{tabcolor}
640 \minted@def@optfv{highlightcolor}
641 \minted@def@optfv@switch{beameroverlays}
642 \minted@def@optfv@switch{curlyquotes}
643 \minted@def@optfv@switch{numberfirstline}
644 \minted@def@optfv@switch{numberblanklines}
645 \minted@def@optfv@switch{stepnumberfromfirst}
646 \minted@def@optfv@switch{stepnumberoffsetvalues}
647 \minted@def@optfv@switch{showspaces}
648 \minted@def@optfv@switch{resetmargins}
649 \minted@def@optfv@switch{samepage}
650 \minted@def@optfv@switch{showtabs}
651 \minted@def@optfv@switch{obeytabs}
652 \minted@def@optfv@switch{breaklines}
653 \minted@def@optfv@switch{breakbytoken}
654 \minted@def@optfv@switch{breakbytokenanywhere}
655 \minted@def@optfv{breakindent}
656 \minted@def@optfv{breakindentnchars}
657 \minted@def@optfv@switch{breakautoindent}
658 \minted@def@optfv{breaksymbol}
659 \minted@def@optfv{breaksymbolsep}
660 \minted@def@optfv{breaksymbolsepnchars}
661 \minted@def@optfv{breaksymbolindent}
662 \minted@def@optfv{breaksymbolindentnchars}
663 \minted@def@optfv{breaksymbolleft}
664 \minted@def@optfv{breaksymbolsepleft}
665 \minted@def@optfv{breaksymbolsepleftnchars}
666 \minted@def@optfv{breaksymbolindentleft}
667 \minted@def@optfv{breaksymbolindentleftnchars}
668 \minted@def@optfv{breaksymbolright}
669 \minted@def@optfv{breaksymbolsepright}
670 \minted@def@optfv{breaksymbolseprightnchars}
671 \minted@def@optfv{breaksymbolindentright}
672 \minted@def@optfv{breaksymbolindentrightnchars}
673 \minted@def@optfv{breakbefore}
674 \minted@def@optfv{breakbeforesymbolpre}
675 \minted@def@optfv{breakbeforesymbolpost}
676 \minted@def@optfv@switch{breakbeforegroup}

```

```

677 \minted@def@optfv{breakafter}
678 \minted@def@optfv@switch{breakaftergroup}
679 \minted@def@optfv{breakaftersymbolpre}
680 \minted@def@optfv{breakaftersymbolpost}
681 \minted@def@optfv@switch{breakanywhere}
682 \minted@def@optfv{breakanywheresymbolpre}
683 \minted@def@optfv{breakanywheresymbolpost}
684 \minted@def@optfv{fontencoding}

```

Finally, options specific to minted.

`bgcolor`. The original, `minipage`- and `\colorbox`-based solution was replaced with a `framed`-based solution in version 2.2. A dedicated framing package will often be preferable.

```
685 \minted@def@opt{bgcolor}
```

`Autogobble`. We create an option that governs when Python's `textwrap.dedent()` is used to autogobble code.

```
686 \minted@def@opt@switch{autogobble}
```

`\minted@encoding` When working with encoding, we will need access to the current encoding. That may be done via `\minted@get@opt`, but it is more convenient to go ahead and define a shortcut with an appropriate default

```
687 \newcommand{\minted@encoding}{\minted@get@opt{encoding}{UTF8}}
```

## 8.6 Internal helpers

`minted@snugshade*` Define a custom version of `framed`'s `snugshade*` that takes a color as argument. This avoids the need to redefine `shadecolor`.

```

688 \newenvironment{minted@snugshade*}[1]{%
689   \def\FrameCommand##1{\hskip\@totalleftmargin
690     \colorbox{#1}{##1}}%
691   \hskip-\linewidth \hskip-\@totalleftmargin \hskip\columnwidth}%
692 \MakeFramed{\advance\hsize-\width
693   \@totalleftmargin\z@ \linewidth\hsize
694   \advance\labelsep\fbboxsep
695   \@setminipage}%
696 }{\par\unskip\@minipagefalse\endMakeFramed}

```

`\minted@bgbox` Define an environment that may be wrapped around a `minted` environment to assign a background color. This is retained as a holdover from version 1.0. In most cases, it is probably better to use a dedicated framing package, such as `tcolorbox` or `mdframed`.

First, we need to define a new save box.

```
697 \newsavebox{\minted@bgbox}
```

Now we can define the environment that applies a background color. Prior to `minted` 2.2, this involved a `minipage`. However, that approach was problematic because it did not allow linebreaks, would be pushed into the margin by immediately preceding text, and had very different whitespace separation from preceding and following text compared to no background color. In version 2.2, this was replaced with an approach based on `framed`. `\FV@NumberSep` is adjusted by `\fboxsep` to ensure that line numbers remain in the same location in the margin regardless of whether `bgcolor` is used.

```
698 \newenvironment{minted@colorbg}[1]{%
699   \setlength{\OuterFrameSep}{0pt}%
700   \let\minted@tmp\FV@NumberSep
701   \edef\FV@NumberSep{%
702     \the\numexpr\dimexpr\minted@tmp+\number\fboxsep\relax sp\relax}%
703   \medskip
704   \begin{minted@snugshade*}{#1}}
705 {\end{minted@snugshade*}%
706  \medskip\noindent}
```

`\minted@code` Create a file handle for saving code (and anything else that must be written to temp files).

```
707 \newwrite\minted@code
```

`\minted@savecode` Save code to be pygmentized to a file.

```
708 \newcommand{\minted@savecode}[1]{
709   \immediate\openout\minted@code\minted@jobname.pyg\relax
710   \immediate\write\minted@code{\expandafter\detokenize\expandafter{#1}}%
711   \immediate\closeout\minted@code}
```

`minted@FancyVerbLineTemp` At various points, we will need a temporary counter for storing and then restoring the value of `FancyVerbLine`. When using the `langlinenos` option, we need to store the current value of `FancyVerbLine`, then set `FancyVerbLine` to the current value of a language-specific counter, and finally restore `FancyVerbLine` to its initial value after the current chunk of code has been typeset. In patching `VerbatimOut`, we need to prevent `FancyVerbLine` from being incremented during the write process.

```
712 \newcounter{minted@FancyVerbLineTemp}
```

`\minted@FVB@VerbatimOut` We need a custom version of `fancyvrb`'s `\FVB@VerbatimOut` that supports Unicode (everything written to file is `\detokenized`). We also need to prevent the value of `FancyVerbLine` from being incorrectly incremented.

```

713 \newcommand{\minted@write@detok}[1]{%
714   \immediate\write\FV@OutFile{\detokenize{#1}}
715 \newcommand{\minted@FVB@VerbatimOut}[1]{%
716   \setcounter{minted@FancyVerbLineTemp}{\value{FancyVerbLine}}%
717   \@bsphack
718   \begingroup
719     \FV@UseKeyValues
720     \FV@DefineWhiteSpace
721     \def\FV@Space{\space}%
722     \FV@DefineTabOut
723     \let\FV@ProcessLine\minted@write@detok
724     \immediate\openout\FV@OutFile #1\relax
725     \let\FV@FontScanPrep\relax
726     \let\@noligs\relax
727     \FV@Scan}

```

`\minted@FVE@VerbatimOut` Likewise, we need a custom version of `\FVE@VerbatimOut` that completes the protection of `FancyVerbLine` from being incremented.

```

728 \newcommand{\minted@FVE@VerbatimOut}{%
729   \immediate\closeout\FV@OutFile\endgroup\@esphack
730   \setcounter{FancyVerbLine}{\value{minted@FancyVerbLineTemp}}%

```

`\MintedPygmentize` We need a way to customize the executable/script that is called to perform highlighting. Typically, we will want `pygmentize`. But advanced users might wish to use a custom Python script instead. The command is only defined if it does not exist. In general, the command should be `\renewcommanded` after the package is loaded, but this way, it will work if defined before `minted` is loaded.

```

731 \ifcsname MintedPygmentize\endcsname\else
732   \newcommand{\MintedPygmentize}{pygmentize}
733 \fi

```

`minted@pygmentizecounter` We need a counter to keep track of how many files have been pygmentized. This is primarily used with `finalizcache` for naming cache files sequentially in `listing<number>.pygtex` form.

```

734 \newcounter{minted@pygmentizecounter}

```

`\MintedPython` Python executable to be used for autogobble.

```

735 \ifwindows
736   \newcommand{\MintedPython}{python}
737 \else
738   \newcommand{\MintedPython}{python3}
739 \fi

```

`\minted@check@MintedPython` Check that `\MintedPython` is a valid executable before use. Swap `python` for `python3` and vice versa depending on what is available.

```
740 \newcommand{\minted@check@MintedPython}{%
741 \ifcsname minted@MintedPython@MintedPython\endcsname
742 \else
743 \let\minted@altpython\minted@undefined
744 \ifdefstring{\MintedPython}{python}{\def\minted@altpython{python3}}{}%
745 \ifdefstring{\MintedPython}{python3}{\def\minted@altpython{python}}{}%
746 \ifx\minted@altpython\minted@undefined\relax
747 \TestAppExists{\MintedPython}%
748 \ifAppExists
749 \expandafter\global\expandafter\let%
750 \csname minted@MintedPython@MintedPython\endcsname\relax
751 \else
752 \PackageError{minted}%
753 {Failed to find Python executable \MintedPython;
754 check Python installation (including PATH),
755 or redefine \string\MintedPython}%
756 {Failed to find Python executable \MintedPython;
757 check Python installation (including PATH),
758 or redefine \string\MintedPython}%
759 \fi
760 \else
761 \ifcsname minted@MintedPython@\minted@altpython\endcsname
762 \let\MintedPython\minted@altpython
763 \else
764 \TestAppExists{\MintedPython}%
765 \ifAppExists
766 \expandafter\global\expandafter\let%
767 \csname minted@MintedPython@MintedPython\endcsname\relax
768 \else
769 \TestAppExists{\minted@altpython}%
770 \ifAppExists
771 \expandafter\global\expandafter\let%
772 \csname minted@MintedPython@\minted@altpython\endcsname\relax
773 \let\MintedPython\minted@altpython
774 \else
775 \PackageError{minted}%
776 {Failed to find Python executables python or python3;
777 check Python installation (including PATH),
778 or redefine \string\MintedPython}%
779 {Failed to find Python executables python or python3;
780 check Python installation (including PATH),
781 or redefine \string\MintedPython}%
782 \fi
783 \fi
784 \fi
785 \fi
786 \fi
```

`\minted@pygmentize` Pygmentize a file (default: `\minted@outputdir\minted@jobname.pyg`) using the options provided.

Unfortunately, the logic for caching is a little complex due to operations that are OS- and engine-dependent.

The name of cached files is the result of concatenating the md5 of the code and the md5 of the command. This results in a filename that is longer than ideal (64 characters plus path and extension). Unfortunately, this is the only robust approach that is possible using the built-in pdfTeX hashing capabilities.<sup>6</sup> LuaTeX could do better, by hashing the command and code together. The Python script that provides XeTeX capabilities simply runs both the command and the code through a single sha1 hasher, but has the additional overhead of the `\write18` call and Python execution.

One potential concern is that caching should also keep track of the command from which code originates. What if identical code is highlighted with identical settings in both the `minted` environment and `\mintinline` command? In both cases, what is actually saved by Pygments is identical. The difference in final appearance is due to how the environment and command treat the Pygments output.

**This macro must always be checked carefully whenever it is modified.**

Under no circumstances should `#1` be written to or opened by Python in write mode. When `\inputminted` is used, `#1` will be an external file that is brought in for highlighting, so it must be left intact.

At the very beginning, a check is performed to make sure that style macros exist. This must be done before the highlighted content is generated, so that temp file names can be shared without accidental overwriting. Styles are generated here, rather than when a style is set, so that creating the style macros is done as late as possible in case a custom `pygmentize` is in use via `\MintedPygmentize`.

```

788 \newcommand{\minted@pygmentize}[2][\minted@outputdir\minted@jobname.pyg]{%
789   \minted@defstyle{\minted@get@opt{style}{default}}%
790   \stepcounter{minted@pygmentizecounter}%
791   \ifthenelse{\equal{\minted@get@opt{autogobble}{false}}{true}}%
792     {\def\minted@codefile{\minted@outputdir\minted@jobname.pyg}}%
793     {\def\minted@codefile{#1}}%
794   \ifthenelse{\boolean{minted@isinline}}%
795     {\def\minted@optlistcl@inlines{%
796       \minted@optlistcl@i
797       \curname minted@optlistcl@lang\minted@lang @i\endcurname}}%
798     {\let\minted@optlistcl@inlines\@empty}%
799   \def\minted@cmd{%

```

<sup>6</sup>It would be possible to use only the cache of the code, but that approach breaks down as soon as the code is used multiple times with different options. While that may seem unlikely in practice, it occurs in this documentation and may be expected to occur in other docs.

```

800 \ifminted@kpsewhich
801 \ifwindows
802 \detokenize{for /f "usebackq tokens=*" \space \@percentchar \detokenize{a in (`kpsewhich)}
803 \fi
804 \fi
805 \MintedPygmentize\space -l #2
806 -f latex -P commandprefix=PYG -F tokenmerge
807 \minted@optlistcl@g \csname minted@optlistcl@lang\minted@lang\endcsname
808 \minted@optlistcl@inlines
809 \minted@optlistcl@cmd -o \minted@outputdir\minted@infile\space
810 \ifminted@kpsewhich
811 \ifwindows
812 \@percentchar \detokenize{a}%
813 \else
814 \detokenize{`}kpsewhich \minted@codefile\space
815 \detokenize{||} \minted@codefile \detokenize{`}%
816 \fi
817 \else
818 \minted@codefile
819 \fi}%
820 % For debugging, uncomment: %%%
821 % \immediate\typeout{\minted@cmd}%
822 % %%%
823 \ifthenelse{\boolean{minted@cache}}%
824 {%
825 \ifminted@frozenscache
826 \else
827 \ifthenelse{\equal{\minted@get@opt{autogobble}{false}}{true}}%
828 {\edef\minted@hash{%
829 \pdf@filemdfivesum{#1}%
830 \pdf@mdfivesum{\minted@cmd\space%
831 autogobble(\the\numexpr\FancyVerbStartNum\relax-%
832 \the\numexpr\FancyVerbStopNum\relax)}}}%
833 {\edef\minted@hash{%
834 \pdf@filemdfivesum{#1}%
835 \pdf@mdfivesum{\minted@cmd}}}%
836 \edef\minted@infile{\minted@cachedir/\minted@hash.pygtex}%
837 \IfFileExists{\minted@infile}{}{%
838 \ifthenelse{\equal{\minted@get@opt{autogobble}{false}}{true}}{%
839 \minted@autogobble{#1}}{%
840 \ShellEscape{\minted@cmd}}}%
841 \fi
842 \ifthenelse{\boolean{minted@finalizcache}}%
843 {%
844 \edef\minted@cachefilename{listing\arabic{minted@pygmentizecounter}.pygtex}%
845 \edef\minted@actualinfile{\minted@cachedir/\minted@cachefilename}%
846 \ifwindows
847 \StrSubstitute{\minted@infile}{/}{\@backslashchar}[\minted@infile@windows]
848 \StrSubstitute{\minted@actualinfile}{/}{\@backslashchar}[\minted@actualinfile@windo
849 \ShellEscape{move /y \minted@outputdir\minted@infile@windows\space\minted@outputdir

```

```

850         \else
851             \ShellEscape{mv -f \minted@outputdir\minted@infile\space\minted@outputdir\minted@ac
852         \fi
853         \let\minted@infile\minted@actualinfile
854         \expandafter\minted@addcachefile\expandafter{\minted@cachefilename}%
855     }%
856     {\ifthenelse{\boolean{minted@frozenscache}}%
857     {%
858         \edef\minted@cachefilename{listing\arabic{minted@pygmentizecounter}.pygtex}%
859         \edef\minted@infile{\minted@cachedir/\minted@cachefilename}%
860         \expandafter\minted@addcachefile\expandafter{\minted@cachefilename}}%
861     {\expandafter\minted@addcachefile\expandafter{\minted@hash.pygtex}}%
862     }%
863     \minted@inputpyg}%
864     {%
865     \ifthenelse{\equal{\minted@get@opt{autogobble}{false}}{true}}{%
866         \minted@autogobble{#1}}{%
867         \ShellEscape{\minted@cmd}%
868         \minted@inputpyg}%
869     }

```

`\minted@autogobble` Remove common leading whitespace.

```

870 \def\minted@autogobble#1{%
871     \edef\minted@argone@esc{#1}%
872     \StrSubstitute{\minted@argone@esc}{\backslashchar}{\backslashchar\backslashchar}{\minted@a
873     \StrSubstitute{\minted@argone@esc}{"}{\backslashchar"}{\minted@argone@esc}%
874     \edef\minted@tmpfname@esc{\minted@outputdir\minted@jobname}%
875     \StrSubstitute{\minted@tmpfname@esc}{\backslashchar}{\backslashchar\backslashchar}{\minted
876     \StrSubstitute{\minted@tmpfname@esc}{"}{\backslashchar"}{\minted@tmpfname@esc}%
877     %Need a version of open() that supports encoding under Python 2
878     \minted@check@MintedPython
879     \edef\minted@autogobblecmd{%
880         \ifminted@kpsewhich
881             \ifwindows
882                 \detokenize{for /f "usebackq tokens=*" }{@percentchar\detokenize{a in (`kpsewhich} #1)\d
883             \fi
884         \fi
885         \MintedPython\detokenize{ -c "import sys; import os;
886         import textwrap;
887         from io import open;
888         fname = }%
889         \ifminted@kpsewhich
890             \detokenize{sys.argv[1];}\space
891         \else
892             \detokenize{os.path.expanduser(os.path.expandvars("\")\minted@argone@esc\detokenize{\})}
893         \fi
894         \detokenize{f = open(fname, "\r", encoding=\")\minted@encoding\detokenize{\}) if os.path.i
895         t = f.readlines() if f is not None else None;
896         t_opt = t if t is not None else [];}

```



```

897     f.close() if f is not None else None;
898     tmpfname = os.path.expanduser(os.path.expandvars("\}\minted@tmpfname@esc.pyg\detokenize{")
899     f = open(tmpfname, "w", encoding="\}\minted@encoding\detokenize{") if t is not None else
900     fvstartnum = }\the\numexpr\FancyVerbStartNum\detokenize{;
901     fvstopnum = }\the\numexpr\FancyVerbStopNum\detokenize{;
902     s = max(0, fvstartnum-1);
903     e = min(s, fvstopnum if fvstopnum > 0 else len(t_opt));
904     [f.write(textwrap.dedent("\".join(x)) for x in (t_opt[0:s], t_opt[s:e], t_opt[e:])) if x a
905     f.close() if t is not None else os.remove(tmpfname);"%
906     \ifminted@kpsewhich
907         \ifwindows
908             \space\@percentchar\detokenize{a}%
909         \else
910             \space\detokenize{`}\kpsewhich #1\space\detokenize{|}|} #1\detokenize{`}%
911         \fi
912     \fi
913 }%
914 \ShellEscape{\minted@autogobblecmd}%
915 }

```

`\minted@inputpyg` For increased clarity, the actual `\input` process is separated out into its own macro.

At the last possible moment, `\PYG` is `\let` to `\PYG<style>` and redefined to used appropriate line breaking via `\VerbatimPygments` from `fvextra`.

The `bgcolor` option needs to be dealt with in different ways depending on whether we are using `\mintinline`. It is simplest to apply this option here, so that the macro redefinitions may be local and thus do not need to be manually reset later.

```

916 \newcommand{\minted@inputpyg}{%
917   \VerbatimPygments{\PYG}{\PYG}%
918   \ifthenelse{\boolean{minted@isinline}}{%
919     {\ifthenelse{\equal{\minted@get@opt{breaklines}{false}}{true}}%
920       {\let\FV@BeginVBox\relax
921         \let\FV@endVBox\relax
922         \def\FV@BProcessLine##1{\FancyVerbFormatLine{##1}}%
923         \minted@inputpyg@inline}%
924       {\minted@inputpyg@inline}}%
925     {\minted@inputpyg@block}%
926   }
927 \def\minted@inputpyg@inline{%
928   \ifthenelse{\equal{\minted@get@opt{bgcolor}{}}{}}{%
929     {\minted@input{\minted@outputdir\minted@infile}}%
930     {\colorbox{\minted@get@opt{bgcolor}{}}{\minted@input{\minted@outputdir\minted@infile}}}%
931   }
932 }
933 \def\minted@inputpyg@block{%
934   \ifthenelse{\equal{\minted@get@opt{bgcolor}{}}{}}{%
935     {\minted@input{\minted@outputdir\minted@infile}}%
936     {\begin{minted@colorbg}{\minted@get@opt{bgcolor}{}}%

```

```

937 \minted@input{\minted@outputdir\minted@infile}%
938 \end{minted@colorbg}}

```

We need a way to have line counters on a per-language basis.

`\minted@langlinenoson`

```

939 \newcommand{\minted@langlinenoson}{%
940 \ifcsname c@minted@lang\minted@lang\endcsname\else
941 \newcounter{minted@lang\minted@lang}%
942 \fi
943 \setcounter{minted@FancyVerbLineTemp}{\value{FancyVerbLine}}%
944 \setcounter{FancyVerbLine}{\value{minted@lang\minted@lang}}%
945 }

```

`\minted@langlinenosoff`

```

946 \newcommand{\minted@langlinenosoff}{%
947 \setcounter{minted@lang\minted@lang}{\value{FancyVerbLine}}%
948 \setcounter{FancyVerbLine}{\value{minted@FancyVerbLineTemp}}%
949 }

```

Disable the language-specific settings if the package option isn't used.

```

950 \ifthenelse{\boolean{minted@langlinenos}}{ }{%
951 \let\minted@langlinenoson\relax
952 \let\minted@langlinenosoff\relax
953 }

```

## 8.7 Public API

`\setminted` Set global or language-level options.

```

954 \newcommand{\setminted}[2] []{%
955 \ifthenelse{\equal{#1}{}}%
956 {\setkeys{minted@opt@g}{#2}}%
957 {\minted@configlang{#1}%
958 \setkeys{minted@opt@lang}{#2}}

```

`\setmintedinline` Set global or language-level options, but only for inline (`\mintinline`) content. These settings will override the corresponding `\setminted` settings.

```

959 \newcommand{\setmintedinline}[2] []{%
960 \ifthenelse{\equal{#1}{}}%
961 {\setkeys{minted@opt@g@i}{#2}}%
962 {\minted@configlang{#1}%
963 \setkeys{minted@opt@lang@i}{#2}}

```

Now that the settings macros exist, we go ahead and create any needed defaults.

PHP should use `startinline` for `\mintinline`. Visible tabs should have a specified color so that they don't change colors when used to indent multiline strings or comments. Leading/trailing empty lines should be preserved by default.

```
964 \setmintedinline[php]{startinline=true}
965 \setminted{tabcolor=black}
966 \setminted{stripnl=false}
```

`\usemintedstyle` Set style. This is a holdover from version 1, since `\setminted` can now accomplish this, and a hierarchy of style settings are now possible.

```
967 \newcommand{\usemintedstyle}[2] [] {\setminted[#1]{style=#2}}
```

`\minted@defwhitespace@retok` The `\mint` and `\mintinline` commands need to be able to retokenize the code they collect, particularly in `draft` mode. Retokenization involves expansion combined with `\scantokens`, with active space and tab characters. The active characters need to expand to the appropriate `fancyvrb` macros, but the macros themselves should not be expanded. We need a macro that will accomplish the appropriate definitions.

```
968 \begingroup
969 \catcode`\ =\active
970 \catcode`\^^I=\active
971 \gdef\minted@defwhitespace@retok{\def {\noexpand\FV@Space}\def^^I{\noexpand\FV@Tab}}%
972 \endgroup
```

`\minted@writecmdcode` The `\mintinline` and `\mint` commands will need to write the code they capture to a temporary file for highlighting. It will be convenient to be able to accomplish this via a simple macro, since that makes it simpler to deal with any expansion of what is to be written. This isn't needed for the `minted` environment, because the (patched) `VerbatimOut` is used.

```
973 \newcommand{\minted@writecmdcode}[1]{%
974 \immediate\openout\minted@code\minted@jobname.pyg\relax
975 \immediate\write\minted@code{\detokenize{#1}}%
976 \immediate\closeout\minted@code}
```

`\mintinline` Define an inline command. This requires some catcode acrobatics. The typical verbatim methods are not used. Rather, a different approach is taken that is generally more robust when used within other commands (for example, when used in footnotes).

Pygments saves code wrapped in a `Verbatim` environment. Getting the inline command to work correctly require redefining `Verbatim` to be `BVerbatim` temporarily. This approach would break if `BVerbatim` were ever redefined elsewhere.

Everything needs to be within a `\begingroup... \endgroup` to prevent settings from escaping.

In the case of `draft` mode, the code is captured and retokenized. Then the internals of `fancyvrb` are used to emulate `SaveVerbatim`, so that `\BUseVerbatim` may be employed.

The `FancyVerbLine` counter is altered somehow within `\minted@pygmentize`, so we protect against this.

```

977 \newrobustcmd{\mintinline}[2] []{%
978   \begingroup
979   \setboolean{minted@isinline}{true}%
980   \minted@configlang{#2}%
981   \setkeys{minted@opt@cmd}{#1}%
982   \minted@fvset
983   \begingroup
984   \let\do\@makeother\dospecials
985   \catcode`\{=1
986   \catcode`\}=2
987   \catcode`\^^I=\active
988   \@ifnextchar\bgroup
989     {\minted@inline@iii}%
990     {\catcode`\{=12\catcode`\}=12
991       \minted@inline@i}}
992 \def\minted@inline@i#1{%
993   \endgroup
994   \def\minted@inline@ii##1#1{%
995     \minted@inline@iii{##1}}%
996   \begingroup
997   \let\do\@makeother\dospecials
998   \catcode`\^^I=\active
999   \minted@inline@ii}
1000 \ifthenelse{\boolean{minted@draft}}%
1001   {\newcommand{\minted@inline@iii}[1]{%
1002     \endgroup
1003     \begingroup
1004     \minted@defwhitespace@retok
1005     \everyeof{\noexpand}%
1006     \endlinechar-1\relax
1007     \let\do\@makeother\dospecials
1008     \catcode`\ =\active
1009     \catcode`\^^I=\active
1010     \xdef\minted@tmp{\scantokens{#1}}%
1011     \endgroup
1012     \let\FV@Line\minted@tmp
1013     \def\FV@SV\minted@tmp{%
1014       \FV@Gobble
1015       \expandafter\FV@ProcessLine\expandafter{\FV@Line}}%
1016     \ifthenelse{\equal{\minted@get@opt{breaklines}{false}}{true}}%

```

```

1017     {\let\FV@BeginVBox\relax
1018      \let\FV@EndVBox\relax
1019      \def\FV@BProcessLine##1{\FancyVerbFormatLine{##1}}%
1020      \UseVerbatim{minted@tmp}}%
1021     {\BUseVerbatim{minted@tmp}}%
1022     \endgroup}}%
1023 \newcommand{\minted@inline@iii}[1]{%
1024   \endgroup
1025   \minted@writecmdcode{#1}%
1026   \RecustomVerbatimEnvironment{Verbatim}{BVerbatim}{}%
1027   \setcounter{minted@FancyVerbLineTemp}{\value{FancyVerbLine}}%
1028   \minted@pygmentize{\minted@lang}%
1029   \setcounter{FancyVerbLine}{\value{minted@FancyVerbLineTemp}}%
1030   \endgroup}

```

`\mint` Highlight a small piece of verbatim code (a single line).

The draft version digs into a good deal of `fancyvrb` internals. We want to employ `\UseVerbatim`, and this requires assembling a macro equivalent to what `SaveVerbatim` would have created. Actually, this is superior to what `SaveVerbatim` would yield, because line numbering is handled correctly.

```

1031 \newrobustcmd{\mint}[2][ ]{%
1032   \begingroup
1033   \minted@configlang{#2}%
1034   \setkeys{minted@opt@cmd}{#1}%
1035   \minted@fvset
1036   \begingroup
1037   \let\do\@makeother\dospecials
1038   \catcode`\{=1
1039   \catcode`\}=2
1040   \catcode`\^I=\active
1041   \@ifnextchar\bgroup
1042     {\mint@iii}%
1043     {\catcode`\{=12\catcode`\}=12
1044      \mint@i}}
1045 \def\mint@i#1{%
1046   \endgroup
1047   \def\mint@ii##1#1{%
1048     \mint@iii{##1}}%
1049   \begingroup
1050   \let\do\@makeother\dospecials
1051   \catcode`\^I=\active
1052   \mint@ii}
1053 \ifthenelse{\boolean{minted@draft}}%
1054   {\newcommand{\mint@iii}[1]{%
1055     \endgroup
1056     \begingroup
1057     \minted@defwhitespace@retok
1058     \everyeof{\noexpand}%

```

```

1059 \endlinechar-1\relax
1060 \let\do\@makeother\dospecials
1061 \catcode`\ =\active
1062 \catcode`\^^I=\active
1063 \xdef\minted@tmp{\scantokens{#1}}%
1064 \endgroup
1065 \let\FV@Line\minted@tmp
1066 \def\FV@SV@minted@tmp{%
1067   \FV@CodeLineNo=1\FV@StepLineNo
1068   \FV@Gobble
1069   \expandafter\FV@ProcessLine\expandafter{\FV@Line}}%
1070 \minted@langlinenoson
1071 \UseVerbatim{minted@tmp}%
1072 \minted@langlinenosoff
1073 \endgroup}}%
1074 {\newcommand{\mint@iii}[1]{%
1075   \endgroup
1076   \minted@writecmdcode{#1}%
1077   \minted@langlinenoson
1078   \minted@pygmentize{\minted@lang}%
1079   \minted@langlinenosoff
1080   \endgroup}}

```

`minted` Highlight a longer piece of code inside a verbatim environment.

```

1081 \ifthenelse{\boolean{minted@draft}}%
1082 {\newenvironment{minted}[2][
1083   {\VerbatimEnvironment
1084     \minted@configlang{#2}%
1085     \setkeys{minted@opt@cmd}{#1}%
1086     \minted@fvset
1087     \minted@langlinenoson
1088     \begin{Verbatim}}%
1089   {\end{Verbatim}}%
1090   \minted@langlinenosoff}}%
1091 {\newenvironment{minted}[2][
1092   {\VerbatimEnvironment
1093     \let\FVB@VerbatimOut\minted@FVB@VerbatimOut
1094     \let\FVE@VerbatimOut\minted@FVE@VerbatimOut
1095     \minted@configlang{#2}%
1096     \setkeys{minted@opt@cmd}{#1}%
1097     \minted@fvset
1098     \begin{VerbatimOut}[codes={\catcode`\^^I=12},firstline,lastline]{\minted@jobname.pyg}}%
1099   {\end{VerbatimOut}}%
1100   \minted@langlinenoson
1101   \minted@pygmentize{\minted@lang}%
1102   \minted@langlinenosoff}}

```

`\inputminted` Highlight an external source file.

```
1103 \ifthenelse{\boolean{minted@draft}}{%
1104   {\newcommand{\inputminted}[3] [] {%
1105     \begingroup
1106     \minted@configlang{#2}%
1107     \setkeys{minted@opt@cmd}{#1}%
1108     \minted@fvset
1109     \VerbatimInput{#3}%
1110     \endgroup}}%
1111   {\newcommand{\inputminted}[3] [] {%
1112     \begingroup
1113     \minted@configlang{#2}%
1114     \setkeys{minted@opt@cmd}{#1}%
1115     \minted@fvset
1116     \minted@pygmentize[#3]{#2}%
1117     \endgroup}}
```

## 8.8 Command shortcuts

We allow the user to define shortcuts for the highlighting commands.

`\newminted` Define a new language-specific alias for the `minted` environment.

```
1118 \newcommand{\newminted}[3] [] {
```

First, we look whether a custom environment name was given as the first optional argument. If that's not the case, construct it from the language name (append "code").

```
1119   \ifthenelse{\equal{#1}{}}
1120     {\def\minted@envname{#2code}}
1121     {\def\minted@envname{#1}}
```

Now, we define two environments. The first takes no further arguments. The second, starred version, takes an extra argument that specifies option overrides.

```
1122   \newenvironment{\minted@envname}
1123     {\VerbatimEnvironment
1124     \begin{minted}[#3]{#2}}
1125     {\end{minted}}
1126   \newenvironment{\minted@envname *}[1]
1127     {\VerbatimEnvironment\begin{minted}[#3,##1]{#2}}
1128     {\end{minted}}}
```

`\newmint` Define a new language-specific alias for the `\mint` short form.

```
1129 \newcommand{\newmint}[3] [] {
```

Same as with `\newminted`, look whether an explicit name is provided. If not, take the language name as command name.

```
1130 \ifthenelse{\equal{#1}{}}
1131   {\def\minted@shortname{#2}}
1132   {\def\minted@shortname{#1}}
```

And define the macro.

```
1133 \expandafter\newcommand\csname\minted@shortname\endcsname[2] []{
1134   \mint[#3,##1]{#2}##2}}
```

`\newmintedfile` Define a new language-specific alias for `\inputminted`.

```
1135 \newcommand{\newmintedfile}[3] []{
```

Here, the default macro name (if none is provided) appends “file” to the language name.

```
1136 \ifthenelse{\equal{#1}{}}
1137   {\def\minted@shortname{#2file}}
1138   {\def\minted@shortname{#1}}
```

...and define the macro.

```
1139 \expandafter\newcommand\csname\minted@shortname\endcsname[2] []{
1140   \inputminted[#3,##1]{#2}{##2}}
```

`\newmintinline` Define an alias for `\mintinline`.

As is usual with inline commands, a little catcode trickery must be employed.

```
1141 \newcommand{\newmintinline}[3] []{%
1142   \ifthenelse{\equal{#1}{}}%
1143     {\def\minted@shortname{#2inline}}%
1144     {\def\minted@shortname{#1}}%
1145   \expandafter\newrobustcmd\csname\minted@shortname\endcsname{%
1146     \begingroup
1147     \let\do\@makeother\dospecials
1148     \catcode`\{=1
1149     \catcode`\}=2
1150     \@ifnextchar[{\endgroup\minted@inliner[#3][#2]}%
1151     {\endgroup\minted@inliner[#3][#2] []}%
1152     \def\minted@inliner[##1][##2][##3]{\mintinline[##1,##3]{##2}}%
1153   }
```



## 8.9 Float support

`listing` Define a new floating environment to use for floated listings. This is defined conditionally based on the `newfloat` package option.

```
1154 \ifthenelse{\boolean{minted@newfloat}}%  
1155   {\@ifundefined{minted@float@within}%  
1156     {\DeclareFloatingEnvironment[fileext=lol,placement=tbp]{listing}}%  
1157     {\def\minted@tmp#1{%  
1158       \DeclareFloatingEnvironment[fileext=lol,placement=tbp, within=#1]{listing}}%  
1159       \expandafter\minted@tmp\expandafter{\minted@float@within}}}%  
1160   {\@ifundefined{minted@float@within}%  
1161     {\newfloat{listing}{tbp}{lol}}%  
1162     {\newfloat{listing}{tbp}{lol}[\minted@float@within]}}
```

The following macros only apply when `listing` is created with the `float` package. When `listing` is created with `newfloat`, its properties should be modified using `newfloat`'s `\SetupFloatingEnvironment`.

```
1163 \ifminted@newfloat\else
```

`\listingcaption` The name that is displayed before each individual listings caption and its number. The macro `\listingscaption` can be redefined by the user.

```
1164 \newcommand{\listingscaption}{Listing}
```

The following definition should not be changed by the user.

```
1165 \floatname{listing}{\listingscaption}
```

`\listoflistingscaption` The caption that is displayed for the list of listings.

```
1166 \newcommand{\listoflistingscaption}{List of Listings}
```

`\listoflistings` Used to produce a list of listings (like `\listoffigures` etc.). This may well clash with other packages (for example, `listings`) but we choose to ignore this since these two packages shouldn't be used together in the first place.

```
1167 \providecommand{\listoflistings}{\listof{listing}{\listoflistingscaption}}
```

Again, the preceding macros only apply when `float` is used to create listings, so we need to end the conditional.

```
1168 \fi
```

## 8.10 Epilogue

Check whether LaTeX was invoked with `-shell-escape` option, set the default style, and make sure `pygmentize` exists. Checking for `pygmentize` must wait until the end of the preamble, in case it is specified via `\MintedPygmentize` (which would typically be after the package is loaded).

```
1169 \AtEndOfPackage{%
1170   \ifthenelse{\boolean{minted@draft}}{%
1171     {}%
1172     {%
1173       \ifthenelse{\boolean{minted@frozenscache}}{}{%
1174         \ifnum\pdf@shellescape=1\relax\else
1175           \PackageError{minted}%
1176             {You must invoke LaTeX with the
1177               -shell-escape flag}%
1178             {Pass the -shell-escape flag to LaTeX. Refer to the minted.sty
1179               documentation for more information.}%
1180           \fi}%
1181       }%
1182   }
1183 \AtEndPreamble{%
1184   \ifthenelse{\boolean{minted@draft}}{%
1185     {}%
1186     {%
1187       \ifthenelse{\boolean{minted@frozenscache}}{}{%
1188         \TestAppExists{\MintedPygmentize}%
1189         \ifAppExists\else
1190           \PackageError{minted}%
1191             {You must have `pygmentize' installed
1192               to use this package}%
1193             {Refer to the installation instructions in the minted
1194               documentation for more information.}%
1195         \fi}%
1196     }%
1197   }
```

## 8.11 Final cleanup

Clean up temp files. What actually needs to be done depends on caching and engine.

```
1198 \AfterEndDocument{%
1199   \ifthenelse{\boolean{minted@draft}}{%
1200     {}%
1201     {\ifthenelse{\boolean{minted@frozenscache}}{%
1202       {}
1203       {\ifx\XeTeXinterchartoks\minted@undefined
```

```

1204     \else
1205         \DeleteFile[\minted@outputdir]{\minted@jobname.mintedcmd}%
1206         \DeleteFile[\minted@outputdir]{\minted@jobname.mintedmd5}%
1207     \fi
1208     \DeleteFile[\minted@outputdir]{\minted@jobname.pyg}%
1209     \DeleteFile[\minted@outputdir]{\minted@jobname.out.pyg}%
1210 }%
1211 }%
1212 }

```

## 9 Implementation of compatibility package

minted version 2 is designed to be completely compatible with version 1.7. All of the same options and commands still exist. As far as most users are concerned, the only difference should be the new commands and options.

However, minted 2 does require some additional packages compared to minted 1.7. More importantly, since minted 2 has almost completely new internal code, user code that accessed the internals of 1.7 will generally not work with 2.0, at least not without some modification. For these reasons, a copy of minted 1.7 is supplied as the package `minted1`. This is intended *only* for compatibility cases when using the current version is too inconvenient.

The code in `minted1` is an exact copy of minted version 1.7, except for two things: (1) the package has been renamed, and (2) code has been added that allows `minted1` to act as (impersonate) `minted`, so that it can cooperate with other packages that require `minted` to be loaded.<sup>7</sup> When `minted1` is used, it must be loaded *before* any other packages that would require `minted`.

All modifications to the original `minted` 1.7 source are indicated with comments. All original code that has been replaced has been commented out rather than deleted. Any future modifications of `minted1` should *only* be for the purpose of allowing it to serve better as a drop-in compatibility substitute for the current release of `minted`.

```

1 \NeedsTeXFormat{LaTeX2e}
2 %%% Begin minted1 modification
3 %\ProvidesPackage{minted}[2011/09/17 v1.7 Yet another Pygments shim for LaTeX]
4 \ProvidesPackage{minted1}[2015/01/31 v1.0 minted 1.7 compatibility package]
5 %%% End minted1 modification
6 \RequirePackage{keyval}
7 \RequirePackage{fancyvrb}
8 \RequirePackage{xcolor}
9 \RequirePackage{float}
10 \RequirePackage{ifthen}

```

---

<sup>7</sup>The approach used for doing this is described at <http://tex.stackexchange.com/a/39418/10742>.

```

11 %%% Begin minted1 modification
12 \newboolean{mintedone@mintedloaded}
13 \@ifpackageloaded{minted}%
14   {\setboolean{mintedone@mintedloaded}{true}%
15   \PackageError{minted1}{The package "minted1" may not be loaded after
16     ^^J"minted" has already been loaded--load "minted1" only for "minted"
17     ^^Jversion 1.7 compatibility}%
18   {Load "minted1" only when "minted" version 1.7 compatibility is required}}%
19   {}
20 \ifmintedone@mintedloaded\else
21 \@namedef{ver@minted.sty}{2011/09/17 v1.7 Yet another Pygments shim for LaTeX}
22 \expandafter\let\expandafter\minted@tmp\csname opt@minted1.sty\endcsname
23 \expandafter\let\csname opt@minted.sty\endcsname\minted@tmp
24 \let\minted@tmp\relax
25 %%% End minted1 modification
26 \RequirePackage{calc}
27 \RequirePackage{ifplatform}
28 \DeclareOption{chapter}{\def\minted@float@within{chapter}}
29 \DeclareOption{section}{\def\minted@float@within{section}}
30 \ProcessOptions\relax
31 \ifwindows
32   \providecommand\DeleteFile[1]{\immediate\write18{del #1}}
33 \else
34   \providecommand\DeleteFile[1]{\immediate\write18{rm #1}}
35 \fi
36 \newboolean{AppExists}
37 \newcommand\TestAppExists[1]{
38   \ifwindows
39     \DeleteFile{\jobname.aex}
40     \immediate\write18{for \string^\@percentchar i in (#1.exe #1.bat #1.cmd)
41       do set >\jobname.aex <nul: /p x=\string^\@percentchar \string~$PATH:i>>\jobname.aex} %$
42     \newread\@appexistsfile
43     \immediate\openin\@appexistsfile\jobname.aex
44     \expandafter\def\expandafter\@tmp@cr\expandafter{\the\endlinechar}
45     \endlinechar=-1\relax
46     \readline\@appexistsfile to \@apppathifexists
47     \endlinechar=\@tmp@cr
48     \ifthenelse{\equal{\@apppathifexists}{}}
49       {\AppExistsfalse}
50       {\AppExiststrue}
51     \immediate\closein\@appexistsfile
52     \DeleteFile{\jobname.aex}
53 \immediate\typeout{file deleted}
54   \else
55     \immediate\write18{which #1 && touch \jobname.aex}
56     \IfFileExists{\jobname.aex}
57       {\AppExiststrue}
58       \DeleteFile{\jobname.aex}}
59     {\AppExistsfalse}
60 \fi}

```

```

61 \newcommand\minted@resetoptions{}
62 \newcommand\minted@defopt[1]{
63   \expandafter\def\expandafter\minted@resetoptions\expandafter{%
64     \minted@resetoptions
65     \@namedef{minted@opt@#1}{}}
66 \newcommand\minted@opt[1]{
67   \expandafter\detokenize%
68   \expandafter\expandafter\expandafter{\csname minted@opt@#1\endcsname}}
69 \newcommand\minted@define@opt[3][]{
70   \minted@defopt{#2}
71   \ifthenelse{\equal{#1}{}}{
72     \define@key{minted@opt}{#2}{\@namedef{minted@opt@#2}{#3}}
73     {\define@key{minted@opt}{#2}[#1]{\@namedef{minted@opt@#2}{#3}}}
74 \newcommand\minted@define@switch[3][]{
75   \minted@defopt{#2}
76   \define@booleankey{minted@opt}{#2}
77   {\@namedef{minted@opt@#2}{#3}}
78   {\@namedef{minted@opt@#2}{#1}}
79 \minted@defopt{extra}
80 \newcommand\minted@define@extra[1]{
81   \define@key{minted@opt}{#1}{
82     \expandafter\def\expandafter\minted@opt@extra\expandafter{%
83       \minted@opt@extra,#1=#1}}
84 \newcommand\minted@define@extra@switch[1]{
85   \define@booleankey{minted@opt}{#1}
86   {\expandafter\def\expandafter\minted@opt@extra\expandafter{%
87     \minted@opt@extra,#1}}
88   {\expandafter\def\expandafter\minted@opt@extra\expandafter{%
89     \minted@opt@extra,#1=false}}}
90 \minted@define@switch{texcl}{-P texcomments}
91 \minted@define@switch{mathescape}{-P mathescape}
92 \minted@define@switch{linenos}{-P linenos}
93 \minted@define@switch{startinline}{-P startinline}
94 \minted@define@switch[-P funcnamehighlighting=False]{%
95   {funcnamehighlighting}{-P funcnamehighlighting}
96 \minted@define@opt{gobble}{-F gobble:n=#1}
97 \minted@define@opt{bgcolor}{#1}
98 \minted@define@extra{frame}
99 \minted@define@extra{framesep}
100 \minted@define@extra{framerule}
101 \minted@define@extra{rulecolor}
102 \minted@define@extra{numbersep}
103 \minted@define@extra{firstnumber}
104 \minted@define@extra{stepnumber}
105 \minted@define@extra{firstline}
106 \minted@define@extra{lastline}
107 \minted@define@extra{baselinestretch}
108 \minted@define@extra{xleftmargin}
109 \minted@define@extra{xrightmargin}
110 \minted@define@extra{fillcolor}

```

```

111 \minted@define@extra{tabsize}
112 \minted@define@extra{fontfamily}
113 \minted@define@extra{fontsize}
114 \minted@define@extra{fontshape}
115 \minted@define@extra{fontseries}
116 \minted@define@extra{formatcom}
117 \minted@define@extra{label}
118 \minted@define@extra@switch{numberblanklines}
119 \minted@define@extra@switch{showspaces}
120 \minted@define@extra@switch{resetmargins}
121 \minted@define@extra@switch{samepage}
122 \minted@define@extra@switch{showtabs}
123 \minted@define@extra@switch{obeytabs}
124 \newsavebox{\minted@bgbox}
125 \newenvironment{minted@colorbg}[1]{
126   \def\minted@bgcol{#1}
127   \noindent
128   \begin{lrbox}{\minted@bgbox}
129   \begin{minipage}{\linewidth-2\fbboxsep}
130   {\end{minipage}
131   \end{lrbox}}%
132   \colorbox{\minted@bgcol}{\usebox{\minted@bgbox}}
133 \newwrite\minted@code
134 \newcommand\minted@savemode[1]{
135   \immediate\openout\minted@code\jobname.pyg
136   \immediate\write\minted@code{#1}
137   \immediate\closeout\minted@code}
138 \newcommand\minted@pygmentize[2][\jobname.pyg]{
139   \def\minted@cmd{pygmentize -l #2 -f latex -F tokenmerge
140     \minted@opt{gobble} \minted@opt{texcl} \minted@opt{mathescape}
141     \minted@opt{startinline} \minted@opt{funcnamehighlighting}
142     \minted@opt{linenos} -P "verboptions=\minted@opt{extra}"
143     -o \jobname.out.pyg #1}
144   \immediate\write18{\minted@cmd}
145   % For debugging, uncomment:
146   %\immediate\typeout{\minted@cmd}
147   \ifthenelse{\equal{\minted@opt@bgcolor}{}}{
148     {}
149     {\begin{minted@colorbg}{\minted@opt@bgcolor}}}
150   \input{\jobname.out.pyg}
151   \ifthenelse{\equal{\minted@opt@bgcolor}{}}{
152     {}
153     {\end{minted@colorbg}}}
154   \DeleteFile{\jobname.out.pyg}}
155 \newcommand\minted@usedefaultstyle{\usemintedstyle{default}}
156 \newcommand\usemintedstyle[1]{
157   \renewcommand\minted@usedefaultstyle{}
158   \immediate\write18{pygmentize -S #1 -f latex > \jobname.pyg}
159   \input{\jobname.pyg}}
160 \newcommand\mint[3][]{

```

```

161 \DefineShortVerb{#3}
162 \minted@resetoptions
163 \setkeys{minted@opt}{#1}
164 \SaveVerb[aftersave={
165   \UndefineShortVerb{#3}
166   \minted@savecode{\FV@SV@minted@verb}
167   \minted@pygmentize{#2}
168   \DeleteFile{\jobname.pyg}}]{minted@verb}#3}
169 \newcommand\minted@proglang[1]{
170 \newenvironment{minted}[2][
171   {\VerbatimEnvironment
172   \renewcommand{\minted@proglang}[1]{#2}
173   \minted@resetoptions
174   \setkeys{minted@opt}{#1}
175   \begin{VerbatimOut}[codes={\catcode\^^I=12}]{\jobname.pyg}}%
176   {\end{VerbatimOut}
177   \minted@pygmentize{\minted@proglang{}}
178   \DeleteFile{\jobname.pyg}}
179 \newcommand\inputminted[3][
180   \minted@resetoptions
181   \setkeys{minted@opt}{#1}
182   \minted@pygmentize[#3]{#2}}
183 \newcommand\newminted[3][
184   \ifthenelse{equal{#1}{}}
185     {\def\minted@envname{#2code}}
186     {\def\minted@envname{#1}}
187   \newenvironment{\minted@envname}
188     {\VerbatimEnvironment\begin{minted}[#3]{#2}}
189     {\end{minted}}
190   \newenvironment{\minted@envname *}[1]
191     {\VerbatimEnvironment\begin{minted}[#3,##1]{#2}}
192     {\end{minted}}}]
193 \newcommand\newmint[3][
194   \ifthenelse{equal{#1}{}}
195     {\def\minted@shortname{#2}}
196     {\def\minted@shortname{#1}}
197   \expandafter\newcommand\csname\minted@shortname\endcsname[2][
198     \mint[#3,##1]{#2}##2}}
199 \newcommand\newmintedfile[3][
200   \ifthenelse{equal{#1}{}}
201     {\def\minted@shortname{#2file}}
202     {\def\minted@shortname{#1}}
203   \expandafter\newcommand\csname\minted@shortname\endcsname[2][
204     \inputminted[#3,##1]{#2}##2}}
205 \@ifundefined{minted@float@within}
206   {\newfloat{listing}{h}{lol}}
207   {\newfloat{listing}{h}{lol}[\minted@float@within]}
208 \newcommand\listingscaption{Listing}
209 \floatname{listing}{\listingscaption}
210 \newcommand\listoflistingscaption{List of listings}

```

```

211 \providecommand\listoflistings{\listof{listing}{\listoflistingscaption}}
212 \AtBeginDocument{
213   \minted@usedefaultstyle}
214 \AtEndOfPackage{
215   \ifnum\pdf@shellescape=1\relax\else
216     \PackageError{minted}
217       {You must invoke LaTeX with the
218         -shell-escape flag}
219       {Pass the -shell-escape flag to LaTeX. Refer to the minted.sty
220         documentation for more information.}\fi
221   \TestAppExists{pygmentize}
222   \ifAppExists\else
223     \PackageError{minted}
224       {You must have `pygmentize' installed
225         to use this package}
226       {Refer to the installation instructions in the minted
227         documentation for more information.}
228   \fi}
229 %%%% Begin minted1 modification
230 \fi
231 %%%% End minted1 modification

```