

# Package ‘ICODS’

January 20, 2025

**Type** Package

**Title** Data Analysis for ODS and Case-Cohort Designs with Interval-Censoring

**Version** 1.1

**Date** 2022-06-05

**Author** Shannon T. Holloway, Qingning Zhou, Jianwen Cai, Haibo Zhou

**Maintainer** Shannon T. Holloway <shannon.t.holloway@gmail.com>

**Description** Sieve semiparametric likelihood methods for analyzing interval-censored failure time data from an outcome-dependent sampling (ODS) design and from a case-cohort design.  
Zhou, Q., Cai, J., and Zhou, H. (2018) <[doi:10.1111/biom.12744](https://doi.org/10.1111/biom.12744)>;  
Zhou, Q., Zhou, H., and Cai, J. (2017) <[doi:10.1093/biomet/asw067](https://doi.org/10.1093/biomet/asw067)>.

**License** GPL-2

**Depends** methods, stats, MASS

**NeedsCompilation** no

**Repository** CRAN

**Encoding** UTF-8

**RoxygenNote** 6.1.1

**Collate** 'myOptim.R' 'minObj.R' 'baseInfo.R' 'CaseCohort\_Obj.R'  
'CaseCohort\_gr.R' 'CaseCohort\_fn.R' 'class\_ICODS.R'  
'CaseCohort\_class.R' 'bernstein.R' 'CaseCohortIC.R'  
'CaseCohort\_data.R' 'ODSDesign\_Obj.R' 'ODSDesign\_class.R'  
'ODSDesignIC.R' 'ODSDesign\_data.R' 'ODSDesign\_fn.R'  
'ODSDesign\_gr.R' 'testInputData.R'

**Date/Publication** 2022-06-06 23:10:36 UTC

## Contents

CaseCohortIC . . . . .	2
ccData . . . . .	4
estimate . . . . .	5

minAIC . . . . .	6
mVal . . . . .	7
odsData . . . . .	8
ODSDesignIC . . . . .	9
optimObj . . . . .	11
summary . . . . .	12

<b>Index</b>	<b>14</b>
--------------	-----------

---

CaseCohortIC	<i>Case-Cohort Studies with Interval-Censored Failure Time Data</i>
--------------	---

---

### Description

Provides a sieve semiparametric likelihood approach under the proportional hazards model for analyzing data from a case-cohort design with failure times subject to interval-censoring. The likelihood function is constructed using inverse probability weighting, and the sieves are built with Bernstein polynomials. A weighted bootstrap procedure is implemented for variance estimation.

### Usage

```
CaseCohortIC(U, V, del1, del2, xi, z, sp, mVal, B, beta = NULL,
             maxit = 10L, verbose = TRUE, ...)
```

### Arguments

U	numeric vector (n); examination time. See Details for further information.
V	numeric vector (n); examination time. See Details for further information.
del1	integer vector (n); indicator of a left-censored observation $I(T \leq U)$ . See Details for further information.
del2	integer vector (n); indicator of an interval-censored observation $I(U < T \leq V)$ . See Details for further information.
xi	integer vector (n); indicating membership of the case-cohort sample.
z	matrix (nxp); covariates.
sp	numeric (1); sampling probability $0 < sp < 1$ .
mVal	integer vector (m); one or more options for the degree of the Bernstein polynomials. If more than one option provided, the value resulting in the lowest AIC is selected. The results returned are for only that m-value.
B	integer (1); number of bootstrap samples used to calculate the variance estimate.
beta	numeric vector (p); initial values for beta. If NULL, initial guess set to 0.5 for each of the p parameters.
maxit	integer(1); maximum number of calls to optimization method.
verbose	logical; TRUE generates progress screen prints.
...	optional inputs to "control" of function optim().

## Details

The implementation uses `stats::optim()` to minimize the likelihood. The hard-coded method is "BFGS". Users are able to make changes to the 'control' input of `optim()` by passing named inputs through the ellipses. If a call to `optim()` returns `convergence = 1`, i.e., `optim()` reached its internal maximum number of iterations before convergence was attained, the software automatically repeats the call to `optim()` with input variable `par` set to the last parameter values. This procedure is repeated at most `maxit` times.

Input parameters `U`, `V`, `del1`, and `del2` are defined as follows. Suppose there are `K` follow-up examinations at times  $TE = (T_1, T_2, \dots, T_K)$ , and the failure time is denoted as `TF`. For left-censored data, the failure occurs prior to the first follow-up examination ( $TF < T_1$ ); therefore, define `U = T_1`, `V = tau`, and  $(del1, del2) = (1, 0)$ . For right-censored data, the failure has not yet occurred at the last follow-up examination ( $TF > T_K$ ); therefore, define `U = 0`, `V = T_K`, and  $(del1, del2) = (0, 0)$ . For interval-censored data, the failure occurs between two follow-up examinations, e.g.  $T_2 < TF < T_3$ ; therefore, define `U` and `V` to be the two consecutive follow-up examination times bracketing the failure time `TF` and  $(del1, del2) = (0, 1)$ .

## Value

an object of class `CaseCohort` (inheriting from `ICODS`) containing

<code>optim</code>	a list of the results returned by <code>optim()</code> .
<code>beta</code>	the estimated beta parameters.
<code>se</code>	the standard error of the estimated beta parameters.
<code>pValue</code>	the p-value of the estimated beta parameters.
<code>m</code>	the selected degree of the Bernstein polynomials.
<code>AIC</code>	the AIC value for the selected degree of the Bernstein polynomials.

## References

Zhou, Q., Zhou, H., and Cai, J. (2017). Case-cohort studies with interval-censored failure time data. *Biometrika*, 104(1): 17–29. <doi:10.1093/biomet/asw067>

## Examples

```
data(ccData)

result <- CaseCohortIC(U = ccData$U,
                      V = ccData$V,
                      del1 = ccData$del1,
                      del2 = ccData$del2,
                      xi = ccData$xi,
                      z = ccData$z,
                      sp = 0.2,
                      mVal = 1L,
                      B = 10L,
                      beta = NULL,
                      maxit = 10L,
                      verbose = TRUE)
```

```

print(result)
mVal(result)
estimate(result)
optimObj(result)
minAIC(result)
summary(result)

```

---

ccData

*Toy Example for Case-Cohort Design with Interval-Censored Data*


---

### Description

This data set gives a simple toy example of case-cohort design with interval-censored data. It was generated following the simulation study used to illustrate the method in the original manuscript referenced below. This dataset is not meaningful and is intended for demonstration purposes only.

### Usage

```
data(ccData)
```

### Format

A data.frame containing 500 observations with 6 columns:

**U** examination time.

**V** examination time.

**del1** indicator of a left-censored observation  $I(T \leq U)$ .

**del2** indicator of an interval-censored observation  $I(U < T \leq V)$ .

**xi** indicating membership of the case-cohort sample.

**z** covariates.

See Details for further information.

### Details

The data can be understood as follow. There are  $K$  follow-up examinations at times  $TE = (T_1, T_2, \dots, T_K)$ , and the failure time is denoted as  $TF$ . For left-censored data, the failure occurred prior to the first follow-up examination ( $TF < T_1$ ); therefore,  $U = T_1$ ,  $V = \text{tau}$ , and  $(\text{del1}, \text{del2}) = (1, 0)$ . For right-censored data, the failure had not yet occurred at the last follow-up examination ( $TF > T_K$ ); therefore,  $U = 0$ ,  $V = T_K$ , and  $(\text{del1}, \text{del2}) = (0, 0)$ . For interval-censored data, the failure occurred between two follow-up examinations, e.g.  $T_2 < TF < T_3$ ; therefore,  $U$  and  $V$  to be the two consecutive follow-up examination times bracketing the failure time  $TF$  and  $(\text{del1}, \text{del2}) = (0, 1)$ .

### References

Zhou, Q., Zhou, H., and Cai, J. (2017). Case-cohort studies with interval-censored failure time data. *Biometrika*, 104(1): 17–29. <doi:10.1093/biomet/asw067>

---

estimate	<i>Retrieve the Estimated Beta Parameters</i>
----------	---

---

**Description**

Retrieves the estimated beta parameters for the m value that minimizes the AIC.

**Usage**

```
estimate(object, ...)
```

**Arguments**

object	An object of class ICODS
...	ignored

**Value**

A matrix containing the estimated parameter value, the standard error, and the p-value.

**Examples**

```
data(odsData)

resultODS <- ODSDesignIC(U = odsData$U,
  V = odsData$V,
  del1 = odsData$del1,
  del2 = odsData$del2,
  z = odsData$z,
  mVal = 1L,
  ind = odsData$ind,
  a1 = 0.43,
  a2 = 0.45,
  beta = NULL,
  maxit = 10L,
  verbose = TRUE)

estimate(resultODS)

data(ccData)

resultCC <- CaseCohortIC(U = ccData$U,
  V = ccData$V,
  del1 = ccData$del1,
  del2 = ccData$del2,
  xi = ccData$xi,
  z = ccData$z,
  sp = 0.2,
  mVal = 1L,
```

```

      B = 10L,
      beta = NULL,
      maxit = 10L,
      verbose = TRUE)

estimate(resultCC)

```

---

minAIC

*Retrieve the Minimum AIC*


---

### Description

Retrieves the minimum AIC.

### Usage

```
minAIC(object, ...)
```

### Arguments

object	An object of class ICODS
...	ignored

### Value

numeric

### Examples

```

data(odsData)

resultODS <- ODSDesignIC(U = odsData$U,
  V = odsData$V,
  del1 = odsData$del1,
  del2 = odsData$del2,
  z = odsData$z,
  mVal = 1L,
  ind = odsData$ind,
  a1 = 0.43,
  a2 = 0.45,
  beta = NULL,
  maxit = 10L,
  verbose = TRUE)

minAIC(resultODS)

data(ccData)

resultCC <- CaseCohortIC(U = ccData$U,

```

```

V = ccData$V,
del1 = ccData$del1,
del2 = ccData$del2,
xi = ccData$xi,
z = ccData$z,
sp = 0.2,
mVal = 1L,
B = 10L,
beta = NULL,
maxit = 10L,
verbose = TRUE)

minAIC(resultCC)

```

---

mVal *Retrieve Degree of Optimal Bernstein Polynomial*

---

### Description

Retrieves the degree of the Bernstein polynomial basis provided as input that minimizes the AIC.

### Usage

```
mVal(object, ...)
```

### Arguments

object	An object of class ICODS
...	ignored

### Value

an integer

### Examples

```

data(odsData)

resultODS <- ODSDesignIC(U = odsData$U,
V = odsData$V,
del1 = odsData$del1,
del2 = odsData$del2,
z = odsData$z,
mVal = 1L,
ind = odsData$ind,
a1 = 0.43,
a2 = 0.45,
beta = NULL,

```

```

                                maxit = 10L,
                                verbose = TRUE)

mVal(resultODS)

data(ccData)

resultCC <- CaseCohortIC(U = ccData$U,
                        V = ccData$V,
                        del1 = ccData$del1,
                        del2 = ccData$del2,
                        xi = ccData$xi,
                        z = ccData$z,
                        sp = 0.2,
                        mVal = 1L,
                        B = 10L,
                        beta = NULL,
                        maxit = 10L,
                        verbose = TRUE)

mVal(resultCC)

```

odsData

*Toy Example for ODS Design with Interval-Censored Data***Description**

This data set gives a simple toy example of ODS design with interval-censored data. It was generated following the simulation study used to illustrate the method in the original manuscript referenced below. This dataset is not meaningful and is intended for demonstration purposes only.

**Usage**

```
data(odsData)
```

**Format**

A data.frame containing 501 observations with 6 columns:

**U** examination time; see Details.

**V** examination time; see Details.

**del1** indicator of a left-censored observation  $I(T \leq U)$ .

**del2** indicator of an interval-censored observation  $I(U < T \leq V)$ .

**z** covariates.

**ind** indicating membership of the simple random sample (0), lower-tail supplemental sample (1), or upper-tail supplemental sample (2).



## Details

The data can be understood as follow. There are  $K$  follow-up examinations at times  $TE = (T_1, T_2, \dots, T_K)$ , and the failure time is denoted as  $TF$ . For left-censored data, the failure occurred prior to the first follow-up examination ( $TF < T_1$ ); therefore,  $U = T_1$ ,  $V = \tau$ , and  $(del1, del2) = (1, 0)$ . For right-censored data, the failure had not yet occurred at the last follow-up examination ( $TF > T_K$ ); therefore,  $U = 0$ ,  $V = T_K$ , and  $(del1, del2) = (0, 0)$ . For interval-censored data, the failure occurred between two follow-up examinations, e.g.  $T_2 < TF < T_3$ ; therefore,  $U$  and  $V$  to be the two consecutive follow-up examination times bracketing the failure time  $TF$  and  $(del1, del2) = (0, 1)$ .

## References

Zhou, Q., Cai, J., and Zhou, H. (2018). Outcome-dependent sampling with interval-censored failure time data. *Biometrics*, 74(1): 58–67. <doi:10.1111/biom.12744>

---

ODSDesignIC

*Outcome-Dependent Sampling with Interval-Censored Failure Time Data*

---

## Description

Provides an outcome-dependent sampling (ODS) design with interval-censored failure time data, where the observed sample is enriched by selectively including certain more informative failure subjects. The method is a sieve semiparametric maximum empirical likelihood approach for fitting the proportional hazards model to data from the interval-censoring ODS design.

## Usage

```
ODSDesignIC(U, V, del1, del2, z, mVal, ind, a1, a2, beta = NULL,
            maxit = 10L, verbose = TRUE, ...)
```

## Arguments

<code>U</code>	numeric vector (n); examination time. See Details for further information.
<code>V</code>	numeric vector (n); examination time. See Details for further information.
<code>del1</code>	integer vector (n); indicator of a left-censored observation $I(T \leq U)$ . See Details for further information.
<code>del2</code>	integer vector (n); indicator of an interval-censored observation $I(U < T \leq V)$ . See Details for further information.
<code>z</code>	matrix (n x p); covariates.
<code>mVal</code>	integer vector (m); one or more options for the degree of the Bernstein polynomials. If more than one option provided, the value resulting in the lowest AIC is selected. The results returned are for only that m-value.
<code>ind</code>	integer vector (n); indicating membership of the simple random sample (0), lower-tail supplemental sample (1), or upper-tail supplemental sample (2).
<code>a1</code>	numeric (1); lower cut-off point for selecting ODS sample ( $0 < a1 < a2 < \tau$ ).

a2	numeric (1); upper cut-off point for selecting ODS sample ( $0 < a1 < a2 < \tau$ ).
beta	numeric vector (p); initial values for beta. If NULL, initial guess set to 0.5 for each of the p parameters.
maxit	integer(1); maximum number of calls to optimization method.
verbose	logical; TRUE generates progress screen prints.
...	optional inputs to "control" of function optim().

### Details

The implementation uses `stats::optim()` to minimize the likelihood. The hard-coded method is "BFGS". Users are able to make changes to the 'control' input of `optim()` by passing named inputs through the ellipses. If a call to `optim()` returns `convergence = 1`, i.e., `optim()` reached its internal maximum number of iterations before convergence was attained, the software automatically repeats the call to `optim()` with input variable `par` set to the last parameter values. This procedure is repeated at most `maxit` times.

Input parameters `U`, `V`, `del1`, and `del2` are defined as follows. Suppose there are  $K$  follow-up examinations at times  $TE = (T1, T2, \dots, TK)$ , and the failure time is denoted as  $TF$ . For left-censored data, the failure occurred prior to the first follow-up examination ( $TF < T1$ ); therefore, define  $U = T1$ ,  $V = \tau$ , and  $(del1, del2) = (1, 0)$ . For right-censored data, the failure had not yet occurred at the last follow-up examination ( $TF > TK$ ); therefore, define  $U = 0$ ,  $V = TK$ , and  $(del1, del2) = (0, 0)$ . For interval-censored data, the failure occurred between two follow-up examinations, e.g.  $T2 < TF < T3$ ; therefore, define  $U$  and  $V$  to be the two consecutive follow-up examination times bracketing the failure time  $TF$  and  $(del1, del2) = (0, 1)$ .

### Value

an object of class `ODSDesign` (inheriting from `ICODS`) containing

<code>optim</code>	a list of the results returned by <code>optim()</code> .
<code>beta</code>	the estimated beta parameters.
<code>se</code>	the standard error of the estimated beta parameters.
<code>pValue</code>	the p-value of the estimated beta parameters.
<code>m</code>	the selected degree of the Bernstein polynomials.
<code>AIC</code>	the AIC value for the selected degree of the Bernstein polynomials.

### References

Zhou, Q., Cai, J., and Zhou, H. (2018). Outcome-dependent sampling with interval-censored failure time data. *Biometrics*, 74(1): 58–67. <doi:10.1111/biom.12744>

### Examples

```
data(odsData)

result <- ODSDesignIC(U = odsData$U,
                     V = odsData$V,
                     del1 = odsData$del1,
```

```

del2 = odsData$del2,
z = odsData$z,
mVal = 1L,
ind = odsData$ind,
a1 = 0.43,
a2 = 0.45,
beta = NULL,
maxit = 10L,
verbose = TRUE)

print(result)
mVal(result)
estimate(result)
optimObj(result)
minAIC(result)
summary(result)

```

---

optimObj

*Retrieve the Optimization Results*


---

### Description

Retrieves the final optimization results for the m value that minimizes the AIC.

### Usage

```
optimObj(object, ...)
```

### Arguments

object	An object of class ICODS
...	ignored

### Value

the value object returned by stats::optim()

### Examples

```

data(odsData)

resultODS <- ODSDesignIC(U = odsData$U,
  V = odsData$V,
  del1 = odsData$del1,
  del2 = odsData$del2,
  z = odsData$z,
  mVal = 1L,
  ind = odsData$ind,

```

```

      a1 = 0.43,
      a2 = 0.45,
      beta = NULL,
      maxit = 10L,
      verbose = TRUE)

optimObj(resultODS)

data(ccData)

resultCC <- CaseCohortIC(U = ccData$U,
                        V = ccData$V,
                        del1 = ccData$del1,
                        del2 = ccData$del2,
                        xi = ccData$xi,
                        z = ccData$z,
                        sp = 0.2,
                        mVal = 1L,
                        B = 10L,
                        beta = NULL,
                        maxit = 10L,
                        verbose = TRUE)

optimObj(resultCC)

```

---

summary

*Retrieve the Key Results*


---

### Description

Retrieves the estimated beta parameters for the m value that minimizes the AIC; the m value; and the AIC value.

### Arguments

object	An object of class ICODS
...	ignored

### Value

A list containing

par	A matrix containing the estimated parameter value, the standard error, and the p-value.
m	The selected m value.
AIC	The AIC.



# Index

## \* datasets

- ccData, 4
- odsData, 8

CaseCohortIC, 2  
ccData, 4

estimate, 5

minAIC, 6  
mVal, 7

odsData, 8  
ODSDesignIC, 9  
optimObj, 11

summary, 12